

## High Voltage High Current Feed-Through Terminal Blocks

---

The new High Voltage Generation of high current feed-through terminal blocks is specially designed for the requirements of drive technology and power electronics.

In addition to the already familiar simple assembly, the outstanding feature of these terminal blocks is a high nominal voltage of 1000 V. For the conductor cross section range up to 10 mm<sup>2</sup>, there are the horizontal feed-through terminal blocks, HDFK 10-HV and the vertical version, HDFKV 10-HV.

The HDFKV 10-TWIN-HV with a conductor connection on both sides is used to loop through intermediate circuit voltages.

In addition to this, the HV range is rounded off by the molded variant.

The HDFK...-VP-HV terminal blocks are specially designed for the requirements of potted devices, such as filter modules, for example. They are an ideal supplement to the HDFK range for the cross section range of up to 10 mm<sup>2</sup>.

The external parts of the molded high current feed-through terminal blocks is identical to those of the standard HV versions.

On the inside of the device, however, there is a sealing plate as well as a sponge rubber seal that prevents the molding compound from leaking out. The connection here is soldered.



# High Current Feed-Through Terminal Blocks HDFK 10-HV






| (IEC)<br>[mm <sup>2</sup> ] | rigid<br>solid | flexible<br>stranded | AWG  | I<br>[A] | U<br>[V] |
|-----------------------------|----------------|----------------------|------|----------|----------|
| Connection data             | 0.5-16         | 0.5-10               | 20-6 | 76       | 1000     |



## Technical data

**Feed-through terminal block**, for 1 - 4 mm thick housing panels, with internal and external screw connection

(1) **Insertion bridge**<sup>1)</sup>, fully insul., 2-pos.   
 fully insulated, 3-pos.   
 divisible, fully insulated, 10-pos. 

(2) **Screwdriver**,  
for actuating the tension spring 

(3) **Zack strip**, 10-section, white 

### Dimensions

#### Technical data in accordance with IEC/ DIN VDE

|   |                    |
|---|--------------------|
| Max. cross section with insertion bridge (solid/stranded) | [mm <sup>2</sup> ] |
| Rated surge voltage / contamination class                 | [kV] / -           |
| Surge voltage category / insulation material group        | - / -              |

#### Connection capacity

|   |                    |
|---|--------------------|
| Stranded with ferrule without / with plastic sleeve | [mm <sup>2</sup> ] |
|---|--------------------|

#### Multi-conductor connection (2 cond. with same cross section)

|  |                    |
|--|--------------------|
| Solid / Stranded                               | [mm <sup>2</sup> ] |
| Stranded with ferrule without plastic sleeve   | [mm <sup>2</sup> ] |
| Stranded with TWIN ferrule with plastic sleeve | [mm <sup>2</sup> ] |

**Stripping length** [mm]

#### Internal cylindrical gauge (IEC 60 947-1)

**Terminal sleeve: Thread / torque** - / [Nm]

#### Insulating material

Inflammability class in acc. with UL 94

#### Approval data (UL and CSA/CUL)

|   |                          |
|---|--------------------------|
| Nominal voltage / current / conductor sizes | UL: [V] / [A] / AWG      |
|   | CSA/CUL: [V] / [A] / AWG |

<sup>1)</sup> Finger-safe protection is not guaranteed when using the insertion bridge externally.

#### Note:


With the HDFK and HDFKV, the terminal space must be completely open when joining both terminal block halves.

The HDFK 10-HV can also be connected if turned by 180°.

| Type            | Order No.               | Pcs.<br>Pkt. |
|-----------------|-------------------------|--------------|
| HDFK 10-HV      | 07 09 86 4              | 50           |
| EB 2-10         | I <sub>max</sub> : 70 A | 100          |
| EB 3-10         |                         | 10           |
| EB 10-10        |                         | 10           |
| SZS 1,0 x 4,0   | 12 05 06 6              | 10           |
| ZB 10:UNPRINTED | 10 53 00 1              | 10           |

see dimensional drawing

|                     |
|---------------------|
| 10 / 10             |
| 6 / 3               |
| III / I             |
| 0.5 - 10 / 0.5 - 10 |
| 0.5 - 4 / 0.5 - 4   |
| 0.5 - 2.5           |
| 0.5 - 6             |
| 11                  |
| B 6                 |
| M 4 / 1.5 - 1.8     |
| PA                  |
| V0                  |
| 600 / 65 / 24 - 6   |
| 600 / 65 / 22 - 6   |



# High Current Feed-Through Terminal Blocks HDFKV 10-HV




| (IEC)<br>[mm <sup>2</sup> ] | rigid<br>solid | flexible<br>stranded | AWG  | I<br>[A] | U<br>[V] |
|-----------------------------|----------------|----------------------|------|----------|----------|
| Connection data             | 0.5-16         | 0.5-10               | 20-6 | 76       | 1000     |


## Technical data

**Feed-through terminal block**, for 1 - 4 mm thick housing panels, with internal and external screw connection

(1) **Insertion bridge**<sup>1)</sup>, fully insul., 2-pos. fully insulated, 3-pos. divisible, fully insulated, 10-pos.




(2) **Screwdriver**, for actuating the tension spring



(3) **Zack strip**, 10-section,

white



## Dimensions

### Technical data in accordance with IEC/ DIN VDE

|   |                    |         |
|---|--------------------|---------|
| Max. cross section with insertion bridge (solid/stranded) | [mm <sup>2</sup> ] | 10 / 10 |
| Rated surge voltage / contamination class                 | [kV] / -           | 6 / 3   |
| Surge voltage category / insulation material group        | - / -              | III / I |

### Connection capacity

|   |                    |                     |
|---|--------------------|---------------------|
| Stranded with ferrule without / with plastic sleeve | [mm <sup>2</sup> ] | 0.5 - 10 / 0.5 - 10 |
|---|--------------------|---------------------|

### Multi-conductor connection (2 cond. with same cross section)

|  |                    |                   |
|--|--------------------|-------------------|
| Solid / Stranded                               | [mm <sup>2</sup> ] | 0.5 - 4 / 0.5 - 4 |
| Stranded with ferrule without plastic sleeve   | [mm <sup>2</sup> ] | 0.5 - 2.5         |
| Stranded with TWIN ferrule with plastic sleeve | [mm <sup>2</sup> ] | 0.5 - 6           |

**Stripping length** [mm] 11

**Internal cylindrical gauge (IEC 60 947-1)** B 6

**Terminal sleeve: Thread / torque** M 4 / 1.5 - 1.8

### Insulating material

Inflammability class in acc. with UL 94 PA

### Approval data (UL and CSA/CUL)

Nominal voltage / current / conductor sizes UL/CUL: [V] / [A] / AWG 600 / 65 / 24 - 6


<sup>1)</sup> Finger-safe protection is not guaranteed when using the insertion bridge externally.

### Note:

With the HDFK and HDFKV, the terminal space must be completely open when joining both terminal block halves.


| Type            | Order No.               | Pcs.<br>Pkt. |
|-----------------|-------------------------|--------------|
| HDFKV 10-HV     | 07 17 23 8              | 50           |
| EB 2-10         | I <sub>max</sub> : 70 A | 100          |
| EB 3-10         |                         | 10           |
| EB 10-10        |                         | 10           |
| SZS 1,0 x 4,0   | 12 05 06 6              | 10           |
| ZB 10:UNPRINTED | 10 53 00 1              | 10           |

see dimensional drawing



# High Current Feed-Through Terminal Blocks



## HDFKV 10-TWIN-HV



| (IEC)<br>[mm <sup>2</sup> ] | rigid<br>solid | flexible<br>stranded | AWG  | I<br>[A] | U<br>[V] |
|-----------------------------|----------------|----------------------|------|----------|----------|
| Connection data             | 0.5-16         | 0.5-10               | 20-6 | 76*      | 1000     |

\* The max. load current must not be exceeded by the total current of all connected conductors.

### Technical data

|   |   |
|---|---|
| <b>Feed-through terminal block</b> , with internal and external screw connection, for 1 - 4 mm thick housing panels, external for vertical conductor connection |   |
| (1) <b>Insertion bridge</b> <sup>1)</sup> , fully insul., fully insulated,  | 2-pos.  |
| divisible, fully insulated,   | 3-pos.  |
|   | 10-pos.   |
| (2) <b>Screwdriver</b> , for actuating the tension spring   |        |
| (3) <b>Zack strip</b> , 10-section,   | white  |

### Dimensions

#### Technical data in accordance with IEC/ DIN VDE

|   |                    |
|---|--------------------|
| Max. cross section with insertion bridge (solid/stranded) | [mm <sup>2</sup> ] |
| Rated surge voltage / contamination class                 | [kV] / -           |
| Surge voltage category / insulation material group        | - / -              |

#### Connection capacity

|   |                    |
|---|--------------------|
| Stranded with ferrule without / with plastic sleeve | [mm <sup>2</sup> ] |
|---|--------------------|

#### Multi-conductor connection (2 cond. with same cross section)

|  |                    |
|--|--------------------|
| Solid / Stranded                               | [mm <sup>2</sup> ] |
| Stranded with ferrule without plastic sleeve   | [mm <sup>2</sup> ] |
| Stranded with TWIN ferrule with plastic sleeve | [mm <sup>2</sup> ] |

|                         |      |
|-------------------------|------|
| <b>Stripping length</b> | [mm] |
|-------------------------|------|

#### Internal cylindrical gauge (IEC 60 947-1)

|   |          |
|---|----------|
| <b>Terminal sleeve: Thread / torque</b> | - / [Nm] |
|---|----------|

#### Insulating material

Inflammability class in acc. with UL 94

#### Approval data (UL and CSA/CUL)

|   |                         |
|---|-------------------------|
| Nominal voltage / current / conductor sizes | UL/CUL: [V] / [A] / AWG |
|---|-------------------------|

<sup>1)</sup> Finger-safe protection is not guaranteed when using the insertion bridge externally.


#### Note:

With the HDFK and HDFKV, the terminal space must be completely open when joining both terminal block halves.

| Type                    | Order No.         | Pcs.<br>Pkt. |
|-------------------------|-------------------|--------------|
| <b>HDFKV 10-TWIN-HV</b> | <b>07 17 24 1</b> | <b>50</b>    |
| <b>EB 2-10</b>          | <b>02 03 15 3</b> | <b>100</b>   |
| <b>EB 3-10</b>          | <b>02 03 32 8</b> | <b>10</b>    |
| <b>EB 10-10</b>         | <b>02 03 13 7</b> | <b>10</b>    |
| <b>SZS 1,0 x 4,0</b>    | <b>12 05 06 6</b> | <b>10</b>    |
| <b>ZB 10:UNPRINTED</b>  | <b>10 53 00 1</b> | <b>10</b>    |

see dimensional drawing

|  |                     |
|--|---------------------|
|  | 10 / 10             |
|  | 6 / 3               |
|  | III / I             |
|  | 0.5 - 10 / 0.5 - 10 |
|  | 0.5 - 4 / 0.5 - 4   |
|  | 0.5 - 2.5           |
|  | 0.5 - 6             |
|  | 11                  |
|  | B 6                 |
|  | M 4 / 1.5 - 1.8     |
|  | PA                  |
|  | V0                  |
|  | 600 / 65 / 24 - 6   |



# High Current Feed-Through Terminal Blocks




## HDFK 10-VP-HV



| (IEC)<br>[mm <sup>2</sup> ] | rigid<br>solid | flexible<br>stranded | AWG  | I<br>[A] | U<br>[V] |
|-----------------------------|----------------|----------------------|------|----------|----------|
| Connection data             | 0.5-16         | 0.5-10               | 20-6 | 76       | 1000     |

### Technical data

**Molded feed-through terminal block**, for 1 - 4 mm thick housing panels, with external screw connection, with solder connection and sealing plate inside

(1) **Insertion bridge**<sup>1)</sup>, fully insul., 2-pos.   
 fully insulated, 3-pos.   
 divisible, fully insulated, 10-pos. 

(2) **Screwdriver**, for actuating the tension spring 

(3) **Zack strip**, 10-section, white 

### Dimensions

#### Technical data in accordance with IEC/ DIN VDE

|   |                    |
|---|--------------------|
| Max. cross section with insertion bridge (solid/stranded) | [mm <sup>2</sup> ] |
| Rated surge voltage / contamination class                 | [kV] / -           |
| Surge voltage category / insulation material group        | - / -              |

#### Connection capacity

|   |                    |
|---|--------------------|
| Stranded with ferrule without / with plastic sleeve | [mm <sup>2</sup> ] |
|---|--------------------|

#### Multi-conductor connection (2 cond. with same cross section)

|  |                    |
|--|--------------------|
| Solid / Stranded                               | [mm <sup>2</sup> ] |
| Stranded with ferrule without plastic sleeve   | [mm <sup>2</sup> ] |
| Stranded with TWIN ferrule with plastic sleeve | [mm <sup>2</sup> ] |

**Stripping length** [mm]

**Internal cylindrical gauge (IEC 60 947-1)**

**Terminal sleeve: Thread / torque** - / [Nm]

#### Insulating material


Inflammability class in acc. with UL 94

<sup>1)</sup> Finger-safe protection is not guaranteed when using the insertion bridge externally.

| Type                   | Order No.                             | Pcs.<br>Pkt. |
|------------------------|---------------------------------------|--------------|
| <b>HDFK 10-VP-HV</b>   | <b>07 17 39 3</b>                     | <b>50</b>    |
| <b>EB 2-10</b>         | $I_{max}$ : 70 A<br><b>02 03 15 3</b> | <b>100</b>   |
| <b>EB 3-10</b>         | 70 A<br><b>02 03 32 8</b>             | <b>10</b>    |
| <b>EB 10-10</b>        | 70 A<br><b>02 03 13 7</b>             | <b>10</b>    |
| <b>SZS 1,0 x 4,0</b>   | <b>12 05 06 6</b>                     | <b>10</b>    |
| <b>ZB 10:UNPRINTED</b> | <b>10 53 00 1</b>                     | <b>10</b>    |

see dimensional drawing

|                     |
|---------------------|
| 10 / 10             |
| 6 / 3               |
| III / I             |
| 0.5 - 10 / 0.5 - 10 |
| 0.5 - 4 / 0.5 - 4   |
| 0.5 - 2.5           |
| 0.5 - 6             |
| 11                  |
| B 6                 |
| M 4 / 1.5 - 1.8     |
| PA                  |
| V0                  |



# High Current Feed-Through Terminal Blocks


## HDFKV 10-VP-HV



| (IEC)<br>[mm <sup>2</sup> ] | rigid<br>solid | flexible<br>stranded | AWG  | I<br>[A] | U<br>[V] |
|-----------------------------|----------------|----------------------|------|----------|----------|
| Connection data             | 0.5-16         | 0.5-10               | 20-6 | 76       | 1000     |

### Technical data

**Molded Feed-through terminal block**, for 1 - 4 mm thick housing panels, with external screw connection, with solder connection and sealing plate inside

(1) **Insertion bridge**<sup>1)</sup>, fully insul., 2-pos.   
 fully insulated, 3-pos.  
 divisible, fully insulated, 10-pos.

(2) **Screwdriver**,  
for actuating the tension spring 

(3) **Zack strip**, 10-section, white 

### Dimensions

#### Technical data in accordance with IEC/ DIN VDE

|   |                    |
|---|--------------------|
| Max. cross section with insertion bridge (solid/stranded) | [mm <sup>2</sup> ] |
| Rated surge voltage / contamination class                 | [kV] / -           |
| Surge voltage category / insulation material group        | - / -              |

#### Connection capacity

|   |                    |
|---|--------------------|
| Stranded with ferrule without / with plastic sleeve | [mm <sup>2</sup> ] |
|---|--------------------|

#### Multi-conductor connection (2 cond. with same cross section)

|  |                    |
|--|--------------------|
| Solid / Stranded                               | [mm <sup>2</sup> ] |
| Stranded with ferrule without plastic sleeve   | [mm <sup>2</sup> ] |
| Stranded with TWIN ferrule with plastic sleeve | [mm <sup>2</sup> ] |

**Stripping length** [mm]

#### Internal cylindrical gauge (IEC 60 947-1)

**Terminal sleeve: Thread / torque** - / [Nm]

#### Insulating material

Inflammability class in acc. with UL 94

#### Approval data (UL and CSA/CUL)


Nominal voltage / current / conductor sizes UL/CUL: [V] / [A] / AWG

<sup>1)</sup> Finger-safe protection is not guaranteed when using the insertion bridge externally.

| Type            | Order No.               | Pcs.<br>Pkt. |
|-----------------|-------------------------|--------------|
| HDFKV 10-VP-HV  | 07 17 25 4              | 50           |
| EB 2-10         | I <sub>max</sub> : 70 A | 100          |
| EB 3-10         |                         | 10           |
| EB 10-10        |                         | 10           |
| SZS 1,0 x 4,0   | 12 05 06 6              | 10           |
| ZB 10:UNPRINTED | 10 53 00 1              | 10           |

see dimensional drawing

|                     |
|---------------------|
| 10 / 10             |
| 6 / 3               |
| III / I             |
| 0.5 - 10 / 0.5 - 10 |
| 0.5 - 4 / 0.5 - 4   |
| 0.5 - 2.5           |
| 0.5 - 6             |
| 11                  |
| B 6                 |
| M 4 / 1.5 - 1.8     |
| PA                  |
| V0                  |
| 600 / 65 / 24 - 6   |



## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9