

# Plastic Infrared Emitting Diode

## OP290 Series



### Features:

- Choice of narrow or wide irradiance pattern
- Choice of power ranges
- Choice of T-1¾, TO-18 or T-46 package
- Higher power output than GaAs at equivalent LEDs

### Description:

Each device in this series, is a gallium aluminum arsenide infrared Light Emitting Diode (LED) that is molded in an IR-transmissive package with a wavelength centered at 890 nm, which closely matches the spectral response of silicon phototransistors, except for OP298 (AA, AB, AC, AD), which has either an 850 nm or 875 nm center wavelength. For identification purposes, each LED anode lead is longer than the cathode lead. **Package T-1¾** devices include: **OP290, OP291, OP292, OP294, OP295, OP296, OP297, OP299 (A, B, C)** and **OP297FAB**, **Plastic Package TO-18 or TO-46** devices include: **OP293** and **OP298 (A, B, C, AA, AD)**.

Each **OP290, OP291** and **OP292** series come in three electrical parameters options A, B and C. The **OP290** series forward current is specified under pulse conditions up to 1.5 amps, the **OP291** series forward current is specified under pulse conditions up to 100 milliamps and the **OP292** series forward current is specified under pulse conditions up to 1 amp. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. The silver-copper lead frame offers excellent thermal characteristics.

Each **OP293** and **OP298** series come in three electrical parameter options A, B and C. The **OP293** series has an included emission angle of 60° while the **OP298** series has an included emission angle of 25°. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. These devices, which come in a variety of power ranges offering a low cost replacement for TO-18 or TO-46 hermetic packages.

Each **OP298** series come with a high irradiance output versions with four electrical parameter options AA, AB, AC and AD. These power options are in the range of **5X** greater than the A, B or C options. The **OP298** series has an included emission angle of 25°. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. These devices, which come in a variety of power ranges offering a low cost replacement for TO-18 or TO-46 hermetic packages.

**OP294** and **OP299** are designed for low-current or power-limited applications, such as battery supplies. They are similar to the **OP290** and **OP295**, but use a smaller chip that increases output efficiency at low current levels by increasing current density. Light output can be maximized with continuous (D.C.) forward current up to 100 mA or with pulsed forward current up to 750 mA. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead.

Each **OP295, OP296** and **OP297** series come in three electrical parameters options A, B and C. The **OP295** series forward current is specified under pulse conditions up to 5 amps, the **OP296** series forward current is specified under pulse conditions up to 2 amps and the **OP297** series forward current is specified under pulse conditions up to 1 amp. The Cathode Lead length is 0.06" (1.52 mm) shorter than the Anode Lead. The **OP297FAB** has a reversed polarity from the **OP297A, B**. The silver-copper lead frame offers excellent thermal characteristics.

*All of these devices are spectrally and mechanically matched to the OP593 and OP598 series phototransistors.*

Please refer to Application Bulletins 208 and 210 for additional design information and reliability (degradation) data.

### Applications:



RoHS

- Non-contact reflective object sensor
- Machine automation
- Door sensor
- Assembly line automation
- Machine safety
- Battery-operated applications
- End of travel sensor

### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


TT Electronics | OPTEK Technology  
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# Plastic Infrared Emitting Diode

## OP290 Series



### Part Number Guide — OP290 - OP299 Series



- 0, 5 — 5 amps
- 1, 6 — 2 amps
- 2, 7 — 1 amps
- 3, 8 — 200 milli-amps
- 4, 9 — 750 milli-amps

#### Electrical Specification Variations:

- A — Parameter A
- B — Parameter B
- C — Parameter C
- D — Parameter D
- AA — Parameter BA
- AB — Parameter BB
- AC — Parameter BC
- AD — Parameter BD



### T-1 $\frac{3}{4}$ Package OP290, OP291, OP292, OP294, OP295, OP296, OP297, OP299

#### Electrical Connection A, B, C, D

| Pin # | LED<br>X=0.060" (1.52 mm) |
|-------|---------------------------|
| 1     | Anode                     |
| 2     | Cathode                   |

#### Electrical Connection OP297AB

| Pin # | LED<br>X=0.060" (1.52 mm) |
|-------|---------------------------|
| 1     | Cathode                   |
| 2     | Anode                     |



### TO-18, TO-46 Package OP293 & OP298



#### Electrical Connection A, B, C, AA, AB, AC, AD

| Pin # | LED<br>X=0.060" (1.52 mm) |
|-------|---------------------------|
| 1     | Anode                     |
| 2     | Cathode                   |



#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

### Electrical Specifications

#### Absolute Maximum Ratings ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

|  |   |
|--|---|
| Storage and Operating Temperature Range  | -40° C to +100° C   |
| Reverse Voltage<br>OP290, OP292, OP294, OP295, OP297, OP299<br>OP291, OP293, OP296, OP298  | 5.0 V<br>2.0 V  |
| Continuous Forward Current<br>OP290, OP291, OP292<br>OP294, OP295, OP299<br>OP295, OP296, OP297  | 150 mA <sup>(1)</sup><br>100 mA <sup>(1)</sup><br>150 mA <sup>(1)</sup> |
| Continuous Forward Current, OP293, OP298<br>Free Air<br>Board Mounted<br>Full Heat Sink  | 100 mA<br>133 mA<br>200 mA  |
| Peak Forward Current<br>OP290, OP295 (25 µs pulse width)<br>OP291, OP296 (100 µs pulse width)<br>OP292, OP297 (100 µs pulse width)<br>OP293, OP298 (25 µs pulse width)<br>OP294, OP299 | 5.0 A<br>2.0 A<br>1.00 A<br>2.0 A<br>750 mA                             |

#### Notes:

- For OP290, OP291, OP292, OP295, OP296 and OP297, derate linearly 1.67 mA/° C above 25° C (free-air). When used with heat sink (see note 5), derate linearly 2.07 mA/° C above 65° C (normal use). For OP293 and OP298, when measured in free-air, derate power dissipation linearly 1.43 mW/° C above 25° C. For OP294 and OP299, derate linearly 1.80 mW/° C above 25° C.

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

### Electrical Specifications

#### Absolute Maximum Ratings ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

|   |  |
|---|--|
| Maximum Duty Cycle<br>OP290 (25 $\mu\text{s}$ pulse width @ 5 A)                              | 1.25% <sup>(1)</sup>                           |
| Lead Soldering Temperature [1/16 inch (1.6 mm) from case for 5 seconds with soldering iron]   | 260° C <sup>(2)</sup>                          |
| Power Dissipation, Free Air<br>OP290, OP291, OP292, OP295, OP296, OP297<br>OP293, OP298       | 333 mW <sup>(3)</sup><br>142 mW <sup>(3)</sup> |
| Power Dissipation, Board Mounted<br>OP290, OP291, OP292, op295, OP296, OP297<br>OP293, OP298  | 533 mW <sup>(4)</sup><br>200 mW <sup>(4)</sup> |
| Power Dissipation, Full Heat Sink<br>OP290, OP291, OP292, OP295, OP296, OP297<br>OP293, OP298 | 1.11 W <sup>(5)</sup><br>400 mW <sup>(5)</sup> |
| Power Dissipation<br>OP294, OP299   | 180 mW   |

#### Notes:

- For OP290, OP291, OP292, OP295, OP296 and OP297, refer to graph of Maximum Peak Pulse Current vs Pulse Width.
- For all OPs in this series, RMA flux is recommended. Duration can be extended to 10 second maximum when soldering. A maximum of 20 grams force may be applied to the leads when flow soldering.
- For OP290, OP291, OP292, OP295, OP296 and OP297, measured in free-air. Derate linearly 3.33 mW/° C above 25° C.
- For OP290, OP291 and OP292, mounted on 1/16" (1.6 mm) thick PCBoard with each lead soldered through 80 mil square lands 0.250" (6.35 mm) below flange of device. Derate linearly 5.33 mW/°C above 62.5°. For OP293 and OP298, mounted on 1/16" (1.60 mm) thick PCBoard with each lead soldered through 80 mil square lands 0.250" (6.35 mm) below flange of device. Derate power dissipation linearly 2.00 mW/°C above 25° C (normal use). For OP295, OP296 and OP297, mounted on 1/16" (1.6 mm) thick PCBoard with each lead soldered through 80 mil square lands 0.250" (6.35 mm) below flange of device. Derate linearly 5.33 mW/°C above 25° C.
- Immersed in silicone fluid to simulate infinite heat sink. For OP290, OP291 and OP292, derate linearly 11.1 mW/°C above 95°C. For OP293 and OP298, derate power dissipation linearly 2.50 mW/° C above 25° C. For OP295, OP296 and OP297, derate linearly 11.1 mW/° C above 25° C.

#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

### Electrical Specifications

Electrical Characteristics ( $T_A = 25^\circ \text{C}$  unless otherwise noted)

| SYMBOL             | PARAMETER                   | MIN  | TYP  | MAX  | UNITS   | TEST CONDITIONS   |
|--------------------|-----------------------------|------|------|------|---|---|
| <b>Input Diode</b> |                             |      |      |      |   |   |
| $E_{E(APT)}^{(2)}$ | Apertured Radiant Incidence |      |      |      |   |   |
|                    | OP290A                      | 210  | -    | -    |   | $I_F = 1.50 \text{ A}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |
|                    | OP290B                      | 180  | -    | 300  |   |   |
|                    | OP290C                      | 150  | -    | -    |   |   |
|                    | OP291A                      | 16   | -    | -    |   | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |
|                    | OP291C                      | 10   | -    | -    |   |   |
|                    | OP292A                      | 2.7  | -    | -    |   | $I_F = 20 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.    |
|                    | OP293A                      | 16   | -    | -    |   | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |
|                    | OP293B                      | 13   | 22   | 26   |   |   |
|                    | OP293C                      | 10   | -    | -    |   |   |
|                    | OP294                       | 0.50 | -    | 1.50 |   | $I_F = 5 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.200" (5.08mm) from the tip of the lens.    |
|                    | OP295A                      | 44   | -    | -    |   | $I_F = 1.50 \text{ A}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |
|                    | OP295B                      | 33   | -    | 77   |   |   |
| OP296A             | 3.6                         | -    | -    |      | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |   |
| OP296B             | 2.6                         | -    | 6.6  |      |   |   |
| OP297FAB           | 2.4                         | -    | -    |      | $I_F = 20 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens.  |   |
| OP297A             | 0.7                         | -    | -    |      |   |   |
| OP297B             | 0.5                         | 1.0  | 1.3  |      |   |   |
| OP298A             | 3.0                         | -    | -    |      | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>0.2" (5.08 mm) from the tip of the lens.   |   |
| OP298B             | 2.4                         | -    | 4.8  |      |   |   |
| OP298C             | 1.8                         | -    | -    |      |   |   |
| OP298AA            | 3.5                         | -    | -    |      | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |   |
| OP298AD            | 8.5                         | -    | -    |      |   |   |
| OP299              | 0.15                        | -    | 0.45 |      | $I_F = 100 \text{ mA}^{(1)(2)}$<br>Measured into a 0.250" [6.35mm] aperture<br>1.129" (28.7 mm) from the tip of the lens. |   |

Notes:

- Measurement is taken at the end of a single 100  $\mu\text{s}$  pulse. Heating due to increased pulse rate or pulse width will cause a decrease in reading.
- Measurement of the average apertured radiant energy incident upon a sensing area 0.250" (6.35 mm) in diameter perpendicular to and centered on the mechanical axis of the lens and the specified distance from the end of the device. On all models in this series,  $E_{E(APT)}$  is not necessarily uniform within the measured area.
- Measurement is taken at the end of a single 10 ms pulse. Heating due to increased pulse rate or pulse width will cause a decrease in reading.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

### Electrical Specifications

Electrical Characteristics ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

| SYMBOL                     | PARAMETER  | MIN | TYP   | MAX                 | UNITS                | TEST CONDITIONS  |
|----------------------------|--|-----|-------|---------------------|----------------------|--|
| <b>Input Diode</b>         |  |     |       |                     |                      |  |
| $V_F$                      | Forward Voltage <sup>(3)</sup>   |     |       |                     |                      |  |
|                            | OP290, OP295   | -   | -     | 4.00                | V                    | $I_F = 1.50\text{ A}$  |
|                            | OP291, OP296   | -   | -     | 2.00                |                      | $I_F = 100\text{ mA}$  |
|                            | OP292, OP297, OP297FAB   | -   | -     | 1.75                |                      | $I_F = 20\text{ mA}$   |
|                            | OP293, OP298 (A, B, C)   | -   | -     | 2.00                |                      | $I_F = 1.50\text{ A}$  |
|                            | OP298 (AA, AD)   | -   | -     | 2.00                |                      | $I_F = 100\text{ mA}$  |
| OP294, OP299               | -  | -   | 1.50  | $I_F = 5\text{ mA}$ |                      |  |
| $I_R$                      | Reverse Current <sup>(3)</sup>   |     |       |                     | $\mu\text{A}$        |  |
|                            | OP290, OP292   | -   | -     | 10                  |                      | $V_R = 5\text{ V}$   |
|                            | OP291, OP293, OP298 (A, B, C), OP296   | -   | -     | 100                 |                      | $V_R = 2\text{ V}$   |
|                            | OP298 (AA, AD)   | -   | -     | 100                 |                      | $V_R = 2\text{ V}$   |
|                            | OP294, OP299   | -   | -     | 10                  |                      | $V_R = 2\text{ V}$   |
|                            | OP295, OP297<br>OP297FAB   | -   | -     | 10<br>15            |                      | $V_R = 5\text{ V}$<br>$V_R = 5\text{ V}$                                   |
| $\lambda_P$                | Wavelength at Peak Emission  |     |       |                     | nm                   | $I_F = 10\text{ mA}$   |
|                            | OP290, OP291, OP292, OP293, OP294,<br>OP295, OP296, OP297, OP298 (A, B, C),<br>OP299 | -   | 890   | -                   |                      |  |
|                            | OP297FAB, OP298 (AA, AD)   | -   | 875   | -                   |                      |  |
| B                          | Spectral Bandwidth between Half Power Points   | -   | 80    | -                   | nm                   | $I_F = 10\text{ mA}$   |
| $\Delta\lambda_P/\Delta T$ | Spectral Shift with Temperature  | -   | +0.18 | -                   | nm/ $^\circ\text{C}$ | $I_F = \text{Constant}$  |
| $\theta_{HP}$              | Emission Angle at Half Power Points  |     |       |                     | Degree               | $I_F = 20\text{ mA}$   |
|                            | OP290, OP291, OP292, OP294   | -   | 50    | -                   |                      |  |
|                            | OP293  | -   | 60    | -                   |                      |  |
|                            | OP295, OP296, OP297, OP299   | -   | 20    | -                   |                      |  |
|                            | OP298  | -   | 25    | -                   |                      |  |
| $t_r$                      | Output Rise Time   | -   | 500   | -                   | ns                   | $I_{F(PK)}=100\text{ mA}$ , $PW=10\text{ }\mu\text{s}$ , and<br>D.C.=10.0% |
| $t_f$                      | Output Fall Time   | -   | 250   | -                   | ns                   |  |

Notes:

- Measurement is taken at the end of a single 100  $\mu\text{s}$  pulse. Heating due to increased pulse rate or pulse width will cause a decrease in reading.
- Measurement of the average apertured radiant energy incident upon a sensing area 0.250" (6.35 mm) in diameter perpendicular to and centered on the mechanical axis of the lens and the specified distance from the end of the device. On all models in this series,  $E_{E(APT)}$  is not necessarily uniform within the measured area.
- Measurement is taken at the end of a single 10 ms pulse. Heating due to increased pulse rate or pulse width will cause a decrease in reading.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
www.ttelectronics.com | sensors@ttelectronics.com

# Plastic Infrared Emitting Diode

## OP290 Series



### Performance

OP290, OP291, OP292, OP293, OP294, (A, C)

Forward Voltage vs Forward Current vs Temp.



Optical Power vs Forward Current vs Temperature



Distance vs Output Power vs Forward Current



Relative Radiant Intensity vs. Angular Displacement



**General Note**

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
 1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
[www.ttelectronics.com](http://www.ttelectronics.com) | [sensors@ttelectronics.com](mailto:sensors@ttelectronics.com)


# Plastic Infrared Emitting Diode

## OP290 Series



### Performance

OP295, OP296, OP297, OP298, OP299



**General Note**

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

TT Electronics | OPTEK Technology  
 1645 Wallace Drive, Carrollton, TX 75006 | Ph: +1 972 323 2200  
[www.ttelectronics.com](http://www.ttelectronics.com) | [sensors@ttelectronics.com](mailto:sensors@ttelectronics.com)



### Performance

#### OP290A/OP593 and OP295/OP598 - Coupling Characteristics



#### General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9