
ISOLATED DC/DC CONVERTERS

48 Vdc Input 1.2 Vdc - 12 Vdc / 8.33 A - 30 A Output, 1/8 Brick

bel POWER PRODUCTS

0RCY-85T Series RoHS Compliant Rev.B

- Isolated
- High Efficiency
- High Power Density
- Fixed Frequency (300 kHz)
- Low Cost
- Input Under Voltage Lockout
- Safety Approval to UL60950-1 (UL/cUL)
- Pre-Bias Start Up
- Output Over Voltage Shutdown
- OCP/SCP
- Over Temperature Protection
- Remote On/Off
- Output Voltage Trim
- Positive/Negative Remote Sense
- Basic Insulation
- Pin Length (option)



Description

The 0RCY-85T Series are isolated dc/dc converters that operate from a nominal 48 Vdc source. These units provide up to 100 W of output power. These units are designed to be highly efficient and cost-effective. Features include remote on/off, short circuit protection, over current protection, over temperature protection, input under voltage lockout, and output over voltage protection. These converters are provided in a compact, 1/8 brick industry standard package.

Part Selection

Output Voltage	Input Voltage	Max. Output Current	Max. Output Power	Typical Efficiency	Model Number Active High	Model Number Active Low
12.0 V	36 V - 75 V	8.33 A	100 W	91%	0RCY-85T120	0RCY-85T12L
5.0 V	36 V - 75 V	20 A	100 W	91%	0RCY-85T050	0RCY-85T05L
3.3 V	36 V - 75 V	25 A	85 W	90%	0RCY-85T033	0RCY-85T03L
2.5 V	36 V - 75 V	25 A	62.5 W	89%	0RCY-85T025	0RCY-85T02L
1.8 V	36 V - 75 V	25 A	45 W	88%	0RCY-85TV80	0RCY-85TV8L
1.5 V	36 V - 75 V	30 A	45 W	86%	0RCY-85TV50	0RCY-85TV5L
1.2 V	36 V - 75 V	30 A	36 W	84%	0RCY-85TV20	0RCY-85TV2L

Notes: 1.Change the last character to “M” to indicate 0.18’’ pin length and active low.
2. Add “G” suffix at the end of the model number to indicate Tray Packaging.
3. All part numbers above indicate RoHS 6. Change the second letter "R" to "7" for RoHS 5 part numbers.

Absolute Maximum Ratings

Parameter	Min	Typ	Max	Notes
Input Voltage (continuous)	-0.3 V	-	80 V	
Input Voltage Transient Protection	-	-	100 V	Operating for 100mS
Remote On/Off	-0.3 V	-	18 V	
I/O Isolation Voltage	-	-	2000 V	
Ambient Temperature	-40 °C	-	100 °C	
Storage Temperature	-55 °C	-	125 °C	

Input Specifications

Parameter	Min	Typ	Max	Notes
Input Voltage	36 V	48 V	75 V	
Input Current (full load)				
Vo=12.0 V	-	-	3.2 A	
Vo=5.0 V	-	-	3.2 A	
Vo=3.3 V	-	-	2.8 A	
Vo=2.5 V	-	-	2.2 A	
Vo=1.8 V	-	-	1.7 A	
Vo=1.5 V	-	-	1.7 A	
Vo=1.2 V	-	-	1.5 A	
Input Current (no load)				
Vo=12.0 V	-	65 mA	90 mA	
Vo=5.0 V	-	65 mA	90 mA	
Vo=3.3 V	-	60 mA	80 mA	
Vo=2.5 V	-	55 mA	75 mA	
Vo=1.8 V	-	50 mA	70 mA	
Vo=1.5 V	-	40 mA	60 mA	
Vo=1.2 V	-	35 mA	50 mA	
Remote Off Input Current		6 mA	12 mA	
Input Reflected Ripple Current (pk-pk)	-	12 mA	24 mA	Tested with simulated source impedance of 10 uH, 5 Hz to 20 MHz; use a 100 uF/100 V electrolytic capacitor with ESR = 1 ohm max. at 200 kHz at 25 °C.
Input Reflected Ripple Current (rms)	-	2 mA	4 mA	
I^2t Inrush Current Transient	-	0.01 A^2s	0.02 A^2s	
Turn-on Voltage Threshold	32 V	34 V	35 V	
Turn-off Voltage Threshold	30 V	32 V	33 V	

Output Specifications

Parameter	Min	Typ	Max	Notes
Output Voltage Set Point				
Vo=12.0 V	11.760 V	12.0 V	12.24 V	Vin=48 V, Io=50% full load, Ta=25 °C.
Vo=5.0 V	4.925 V	5.0 V	5.075 V	
Vo=3.3 V	3.250 V	3.3 V	3.350 V	
Vo=2.5 V	2.463 V	2.5 V	2.538 V	
Vo=1.8 V	1.773 V	1.8 V	1.827 V	
Vo=1.5 V	1.477 V	1.5 V	1.523 V	
Vo=1.2 V	1.182 V	1.2 V	1.218 V	
Line Regulation				
Vo=12.0 V-3.3 V	-	±2 mV	±5 mV	
Vo=1.2 V-2.5 V	-	±1 mV	±3 mV	
Load Regulation				
Vo=12.0 V	-	±8 mV	±16 mV	
Vo=5.0 V	-	±8 mV	±16 mV	
Vo=3.3 V	-	±6 mV	±12 mV	
Vo=2.5 V	-	±4 mV	±8 mV	
Vo=1.8 V	-	±3 mV	±6 mV	
Vo=1.5 V	-	±3 mV	±6 mV	
Vo=1.2 V	-	±2 mV	±4 mV	

Output Specifications (continued)

Parameter	Min	Typ	Max	Notes
Regulation Over Temperature (-40 °C to +85 °C)				
Vo=12.0 V	-	±50 mV	±75 mV	
Vo=5.0 V	-	±50 mV	±75 mV	
Vo=3.3 V	-	±20 mV	±40 mV	
Vo=2.5 V	-	±15 mV	±30 mV	
Vo=1.8 V	-	±15 mV	±30 mV	
Vo=1.5 V	-	±10 mV	±20 mV	
Vo=1.2 V	-	±10 mV	±20 mV	
Output Current				
Vo=12.0 V	0 A	-	8.33 A	
Vo=5.0 V	0 A	-	20 A	
Vo=3.3 V	0 A	-	25 A	
Vo=2.5 V	0 A	-	25 A	
Vo=1.8 V	0 A	-	25 A	
Vo=1.5 V	0 A	-	30 A	
Vo=1.2 V	0 A	-	30 A	
Current Limit Threshold				
Vo=12.0 V	10 A	13 A	16 A	
Vo=5.0 V	23 A	29 A	35 A	
Vo=3.3 V	30 A	36 A	42 A	
Vo=2.5 V	27 A	33 A	40 A	
Vo=1.8 V	27 A	33 A	40 A	
Vo=1.5 V	32 A	36 A	45 A	
Vo=1.2 V	32 A	36 A	45 A	
Short Circuit Surge Transient	-	3 A^2s	5 A^2s	
Ripple and Noise (rms)				Test conditions: 0-20 MHz BW, with a 1 uF ceramic capacitor and a 10 uF Tantalum capacitor at the output.
Vo=12.0 V	-	30 mV	50 mV	
Vo=5.0 V	-	25 mV	50 mV	
Vo=1.2 V-3.3 V	-	15 mV	30 mV	
Ripple and Noise (pk-pk)				
Vo=12.0 V	-	100 mV	150 mV	
Vo=5.0 V	-	80 mV	120 mV	
Vo=3.3 V	-	45 mV	90 mV	
Vo=1.2 V-2.5 V	-	40 mV	80 mV	
Turn on Time	-	-	30 mS	
Overshoot at Turn on	-	0%	5%	
Output Capacitance				
Vo=12.0 V	0 uF	-	1000 uF	
Vo=5.0 V	0 uF	-	10000 uF	
Vo=1.2 V- 3.3 V	0 uF	-	20000 uF	

Transient Response						
25% ~ 50% Max Load	Overshoot	Vo=12.0 V	-	300 mV	400 mV	Test conditions: di/dt = 0.1 A/uS, Vin=48 V, with a 1 uF ceramic capacitor and a 10 uF Tantalum capacitor at the output.
	Settling Time		-	200 uS	300 uS	
50% ~ 25% Max Load	Overshoot		-	300 mV	400 mV	
	Settling Time		-	200 uS	300 uS	
25% ~ 50% Max Load	Overshoot	Vo=5.0 V	-	200 mV	300 mV	
	Settling Time		-	200 uS	300 uS	
50% ~ 25% Max Load	Overshoot		-	200 mV	300 mV	
	Settling Time		-	200 uS	300 uS	
25% ~ 50% Max Load	Overshoot	Vo=3.3 V	-	150 mV	200 mV	
	Settling Time		-	200 uS	300 uS	
50% ~ 25% Max Load	Overshoot		-	150 mV	200 mV	
	Settling Time		-	200 uS	300 uS	

Output Specifications (continued)

Parameter			Min	Typ	Max	Notes
Transient Response						
25% ~ 50% Max Load	Overshoot	Vo=2.5 V	-	150 mV	200 mV	Test conditions: di/dt = 0.1 A/uS, Vin=48 V, with a 1 uF ceramic capacitor and a 10 uF Tantalum capacitor at the output.
	Settling Time		-	150 uS	200 uS	
50% ~ 25% Max Load	Overshoot		-	150 mV	200 mV	
	Settling Time		-	150 uS	200 uS	
25% ~ 50% Max Load	Overshoot	Vo=1.8 V	-	140 mV	170 mV	
	Settling Time		-	150 uS	200 uS	
50% ~ 25% Max Load	Overshoot		-	140 mV	170 mV	
	Settling Time		-	150 uS	200 uS	
25% ~ 50% Max Load	Overshoot	Vo=1.5 V	-	130 mV	150 mV	
	Settling Time		-	150 uS	200 uS	
50% ~ 25% Max Load	Overshoot		-	130 mV	150 mV	
	Settling Time		-	150 uS	200 uS	
25% ~ 50% Max Load	Overshoot	Vo=1.2 V	-	120 mV	140 mV	
	Settling Time		-	150 uS	200 uS	
50% ~ 25% Max Load	Overshoot		-	120 mV	140 mV	
	Settling Time		-	150 uS	200 uS	

Note: All specifications are typical at 25 °C unless otherwise stated.

General Specifications

Parameter	Min	Typ	Max	Notes
Efficiency				Vin=48V, Io=Io, max
Vo=12.0 V	88%	91%	-	
Vo=5.0 V	88%	91%	-	
Vo=3.3 V	87%	90%	-	
Vo=2.5 V	86%	89%	-	
Vo=1.8 V	85%	88%	-	
Vo=1.5 V	83%	86%	-	
Vo=1.2 V	81%	84%	-	
Switching Frequency	270 kHz	300 kHz	330 kHz	
Isolation capacitance	-	1500 pF	-	
Output Voltage Trim Range				The total voltage increased by trim and remote sense should not exceed 10%Vo.
Vo=1.5 V-12 V	80% Vo	-	110% Vo	
Vo=1.2 V	90% Vo	-	110% Vo	
Remote Sense	-	-	10%	
Over Temperature Protection	-	125 °C	-	
Over Voltage Protection	-	130% Vo	-	Vin=48V, full load, in hiccup mode.
Pre-bias Voltage				
Vo=5.0 V	-	-	4.0 V	
Vo=3.3 V	-	-	1.4 V	
Vo=2.5 V	-	-	2.0 V	
Vo=1.8 V	-	-	1.4 V	
Vo=1.5 V	-	-	1.2 V	
Vo=1.2 V	-	-	0.9 V	
MTBF	1,583,176 hours			Calculated Per Bell Core SR-332 (Vin=48 V, Vo=3.3 V, Io=20 A, T_a = 25 °C)
Dimensions				
Inches (L × W × H)	2.30 x 0.896 x 0.395			
Millimeters (L × W × H)	58.42 x 22.76 x 10.03			
Weight	-	27 g	-	

Note: All specifications are typical at 25 °C unless otherwise stated.


Control Specifications

Parameter		Min	Typ	Max	Notes
Remote On/Off					
Signal Low (Unit On)	Active Low	-0.3 V	-	0.8 V	0RCY-85TxxL. The remote on/off pin open, Unit off.
Signal High (Unit Off)		2.4 V	-	18 V	
Signal Low (Unit Off)	Active High	-0.3 V	-	0.8 V	0RCY-85Txx0. The remote on/off pin open, Unit on.
Signal High (Unit On)		2.4 V	-	18 V	
Current Sink		0 mA	-	0.75 mA	

Output Trim Equations


Equations for calculating the trim resistor are shown below. The Trim Down resistor should be connected between the Trim pin and Ground pin. The Trim Up resistor should be connected between the Trim pin and the Vout. Only one of the resistors should be used for any given application.

$$Rtrim-down = \frac{511}{|delta|} - 10.22[k\Omega]$$



Vo=1.5 V-12 V:

$$Rtrim-up = \frac{(100+delta)\cdot Vo\cdot 5.11-626}{1.225\cdot delta} - 10.22[k\Omega]$$



Vo=1.2 V:

$$Rtrim-up = \frac{(100+delta)\cdot Vo\cdot 5.11-313}{0.6125\cdot delta} - 10.22[k\Omega]$$


Notes:


$$delta = \frac{(Vo_req - Vo)}{Vo}\times 100[\%]$$


Vo_req=Desired (trimmed) output voltage [V]


Output voltage Vo=1.202 V for 1.2 V output; Vo=1.503 V for 1.5 V output; Vo=1.804 V for 1.8 V; Vo=2.505 V for 2.5 V output; Vo=3.308 V for 3.3 V output; Vo=5.000 V for 5.0 V; Vo=12.000 V for 12 V output


Efficiency Data



















Thermal Derating Curves


Vin=48V, with maximum junction temperature of semiconductors derated to 120 degree C.




Forced Airflow Direction




0RCY-85T12x




0RCY-85T05x



0RCY-85T03x




0RCY-85T02x




0RCY-85TV8x

Thermal Derating Curves (continued)




0RCY-85TV5x




0RCY-85TV2x

Thermal Reference




Note: T_{H1} and T_{H2} are hot spots which should not exceed 118 degree C.


Ripple and Noise Waveforms




Ripple and noise at max load 12 Vdc/8.33 A output




Ripple and noise at max load 5.0 Vdc/20 A output




Ripple and noise at max load 3.3 Vdc/25 A output



Ripple and noise at max load 2.5 Vdc/25 A output




Ripple and noise at max load 1.8 Vdc/25 A output



Ripple and noise at max load 1.5 Vdc/30 A output

.


Ripple and Noise Waveforms (continued)




Ripple and noise at max load 1.2 Vdc/30 A output

Note: Ripple and Noise at 48 V input, with a 1 uF ceramic capacitor and a 10 uF tantalum capacitor at the output, and Ta=25 deg C

Transient Response Waveforms




Transients 50% to 25% load 12 Vdc output




Transients 25% to 50% load 12 Vdc output


Transient Response Waveforms (continued)




Transients 50% to 25% load 5.0 Vdc output




Transients 25% to 50% load 5.0 Vdc output




Transients 50% to 25% load 3.3 Vdc output



Transients 25% to 50% load 3.3 Vdc output




Transients 50% to 25% load 2.5 Vdc output




Transients 25% to 50% load 2.5 Vdc output


Transient Response Waveforms (continued)




Transients 50% to 25% load 1.8 Vdc output




Transients 25% to 50% load 1.8 Vdc output




Transients 50% to 25% load 1.5 Vdc output



Transients 25% to 50% load 1.5 Vdc output



Transients 50% to 25% load 1.2 Vdc output




Transients 25% to 50% load 1.2 Vdc output


Note: Transient response at 48 V input, di/dt=0.1 A/uS, with external 10 uF tantalum cap and 1 uF ceramic cap at the output, Ta=25 deg C.


ISOLATED DC/DC CONVERTERS


48 Vdc Input 1.2 Vdc - 12 Vdc / 8.33 A - 30 A Output, 1/8 Brick

Mechanical Outline










BOTTOM VIEW



1,2,3,5,6,7 ø0.047 HOLE SIZE, ø0.08 min PAD SIZE
4,8 ø0.07 HOLE SIZE, ø0.10 min PAD SIZE

Pin Connections

Pin	Function	Pin Dia
1	Vin+	0.040”
2	Remote On/Off	0.040”
3	Vin-	0.040”
4	Vout-	0.062”
5	Sense-	0.040”
6	Trim	0.040”
7	Sense+	0.040”
8	Vout+	0.062”

RoHS Compliance

Complies with the European Directive 2002/95/EC, calling for the elimination of lead and other hazardous substances from electronic products.

©2009 Bel Fuse Inc. Specifications subject to change without notice. 052609

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F/ 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9