

### Is Now Part of



# ON Semiconductor®

# To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at <a href="www.onsemi.com">www.onsemi.com</a>. Please email any questions regarding the system integration to Fairchild <a href="general-regarding-numbers-n

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



February 2013

### FDMC8321L

### N-Channel Power Trench® MOSFET 40 V, 49 A, 2.5 m $\Omega$

#### **Features**

- Max  $r_{DS(on)} = 2.5 \text{ m}\Omega$  at  $V_{GS} = 10 \text{ V}$ ,  $I_D = 22 \text{ A}$
- Max  $r_{DS(on)}$  = 4.1 m $\Omega$  at  $V_{GS}$  = 4.5 V,  $I_D$  = 18 A

Top

- Advanced Package and Silicon combination for low r<sub>DS(on)</sub> and high efficiency
- Next Generation enhanced body diode technology, engineered for soft recovery
- 100% UIL tested
- RoHS Compliant



### **General Description**


This N-Channel MOSFET has been designed specifically to improve the overall efficiency and to minimize switch node ringing of DC/DC converters using either synchronous or convertional switching PWM contollers. It has been optimized for low gate charge, low  $r_{DS(on)}$ , fast switching speed body diode reverse recovery performance.

### **Applications**

- Synchronous rectifier
- Load switch/Orring
- Motor switch







Power 33

### **MOSFET Maximum Ratings** $T_A = 25$ °C unless otherwise noted

Symbol	Parameter			Ratings	Units
V <sub>DS</sub>	Drain to Source Voltage			40	V
V <sub>GS</sub>	Gate to Source Voltage			±20	V
	Drain Current -Continuous	T <sub>C</sub> = 25 °C		49	
I <sub>D</sub>	-Continuous	T <sub>A</sub> = 25 °C	(Note 1a)	22	Α
	-Pulsed			100	
E <sub>AS</sub>	Single Pulse Avalanche Energy		(Note 3)	86	mJ
В	Power Dissipation	T <sub>C</sub> = 25 °C		40	w
$P_{D}$	Power Dissipation	T <sub>A</sub> = 25 °C	(Note 1a)	2.3	VV
T <sub>J</sub> , T <sub>STG</sub>	Operating and Storage Junction Temperatur	e Range		-55 to +150	°C

#### **Thermal Characteristics**

$R_{\theta JC}$	Thermal Resistance, Junction to Case	(Note 1)	3.1	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	(Note 1a)	53	C/VV

#### **Package Marking and Ordering Information**

Device Marking	Device	Package	Reel Size	Tape Width	Quantity
FDMC8321L	FDMC8321L	Power33	13 "	12 mm	3000 units

## **Electrical Characteristics** $T_J = 25$ °C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Тур	Max	Units
Off Chara	cteristics					
$BV_{DSS}$	Drain to Source Breakdown Voltage	$I_D = 250 \mu A, V_{GS} = 0 V$	40			V
$\frac{\Delta BV_{DSS}}{\Delta T_{J}}$	Breakdown Voltage Temperature Coefficient	$I_D$ = 250 $\mu$ A, referenced to 25 °C		22		mV/°C
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> = 32 V, V <sub>GS</sub> = 0 V			1	μΑ
$I_{GSS}$	Gate to Source Leakage Current	$V_{GS} = \pm 20 \text{ V}, V_{DS} = 0 \text{ V}$			±100	nA

#### On Characteristics

$V_{GS(th)}$	Gate to Source Threshold Voltage	$V_{GS} = V_{DS}, I_D = 250 \mu A$	1	1.7	3	V
$\frac{\Delta V_{GS(th)}}{\Delta T_J}$	Gate to Source Threshold Voltage Temperature Coefficient	$I_D$ = 250 $\mu$ A, referenced to 25 °C		-5		mV/°C
		$V_{GS} = 10 \text{ V}, I_D = 22 \text{ A}$		1.9	2.5	
r <sub>DS(on)</sub>	Static Drain to Source On Resistance	$V_{GS} = 4.5 \text{ V}, I_D = 18 \text{ A}$		2.7	4.1	$m\Omega$
		$V_{GS} = 10 \text{ V}, I_D = 22 \text{ A}, T_J = 125 ^{\circ}\text{C}$		2.8	3.7	
9 <sub>FS</sub>	Forward Transconductance	$V_{DS} = 5 \text{ V}, I_{D} = 22 \text{ A}$		114		S

#### **Dynamic Characteristics**

C <sub>iss</sub>	Input Capacitance	V 20 V V 0 V		2930	3900	pF
C <sub>oss</sub>	Output Capacitance	$V_{DS} = 20 \text{ V}, V_{GS} = 0 \text{ V},$ f = 1  MHz		1000	1330	pF
C <sub>rss</sub>	Reverse Transfer Capacitance	1 - 1 101112		60	90	pF
$R_g$	Gate Resistance		0.1	0.7	2.5	Ω

### **Switching Characteristics**


t <sub>d(on)</sub>	Turn-On Delay Time		12	22	ns
t <sub>r</sub>	Rise Time	V <sub>DD</sub> = 20 V, I <sub>D</sub> = 22 A,	6.1	12	ns
t <sub>d(off)</sub>	Turn-Off Delay Time	$V_{GS} = 10 \text{ V}, R_{GEN} = 6 \Omega$	32	51	ns
t <sub>f</sub>	Fall Time		4.9	10	ns
$Q_{g(TOT)}$	Total Gate Charge at 10 V		44	61	nC
$Q_{g(TOT)}$	Total Gate Charge at 5 V	$V_{DD} = 20 \text{ V}, I_D = 22 \text{ A}$	21	32	nC
$Q_{gs}$	Total Gate Charge	$V_{DD} = 20 \text{ V}, I_D = 22 \text{ A}$	7.7		nC
$Q_{gd}$	Gate to Drain "Miller" Charge		5.8		nC

#### **Drain-Source Diode Characteristics**


V	/ob   Source to Drain Dioge Forward Voltage	$V_{GS} = 0 \text{ V}, I_{S} = 2 \text{ A}$	(Note 2)	0.69	1.2	\/
V SD		$V_{GS} = 0 \text{ V}, I_{S} = 22 \text{ A}$	(Note 2)	0.77	1.3	V
t <sub>rr</sub>	Reverse Recovery Time	I <sub>F</sub> = 22 A, di/dt = 100 A/μs		41	65	ns
Q <sub>rr</sub>	Reverse Recovery Charge			20	33	nC
			•			

Notes:

1. R<sub>BJA</sub> is determined with the device mounted on a 1 in<sup>2</sup> pad 2 oz copper pad on a 1.5 x 1.5 in. board of FR-4 material. R<sub>BJC</sub> is guaranteed by design while R<sub>BCA</sub> is determined by the user's board design.



53 °C/W when mounted on a 1 in<sup>2</sup> pad of 2 oz copper



125 °C/W when mounted on a minimum pad of 2 oz copper

<sup>2.</sup> Pulse Test: Pulse Width < 300  $\mu\text{s},$  Duty cycle < 2.0%.

<sup>3.</sup>Starting T  $_{J}$  = 25  $^{\circ}\text{C};$  N-ch: L = 0.3 mH, I  $_{AS}$  = 24 A, V  $_{DD}$  = 36 V, V  $_{GS}$  = 10 V.

### **Typical Characteristics** $T_J = 25$ °C unless otherwise noted




Figure 1. On Region Characteristics




Figure 3. Normalized On Resistance vs Junction Temperature




Figure 5. Transfer Characteristics




Figure 2. Normalized On-Resistance vs Drain Current and Gate Voltage




Figure 4. On-Resistance vs Gate to Source Voltage




Figure 6. Source to Drain Diode Forward Voltage vs Source Current

### **Typical Characteristics** $T_J = 25$ °C unless otherwise noted




Figure 7. Gate Charge Characteristics




Figure 9. Unclamped Inductive Switching Capability




Figure 11. Forward Bias Safe Operating Area




Figure 8. Capacitance vs Drain to Source Voltage




Figure 10. Maximum Continuous Drain Current vs Case Temperature




Figure 12. Single Pulse Maximum Power Dissipation

### **Typical Characteristics** $T_J = 25$ °C unless otherwise noted







Figure 13. Junction-to-Ambient Transient Thermal Response Curve

### **Dimensional Outline and Pad Layout**







PQFN08BREV1

NOTES: UNLESS OTHERWISE SPECIFIED

- A) PACKAGE STANDARD REFERENCE: JEDEC MO-240, ISSUE A, VAR. BA, DATED OCTOBER 2002.
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
- D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
- E) DRAWING FILE NAME: PQFN08BREV1





#### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

2Cool™ FPS™ AccuPower™ AX-CAP®\* F-PFS™ FRFET®

 $\mathsf{BitSiC}^{\mathsf{TM}}$ Global Power Resource<sup>SM</sup> Build it Now™ Green Bridge™

CorePLUS™ Green FPS™ CorePOWER™ Green FPS™ e-Series™

CROSSVOLT™  $Gmax^{TM}$ CTL™ GTO™ Current Transfer Logic™ IntelliMAX™ **DEUXPEED®** ISOPLANAR™

Dual Cool™ Marking Small Speakers Sound Louder

EcoSPARK® and Better™ MegaBuck™ EfficentMax™ ESBC™

MIČROCOUPLER™ MicroFET™

MicroPak™ MicroPak2™ Fairchild® MillerDrive™ Fairchild Semiconductor®  $Motion Max^{\mathsf{TM}}$ FACT Quiet Series™ mWSaver™ OptoHiT™

FAST® OPTOLOGIC® FastvCore™ **OPTOPLANAR®** FETBench™

 $(1)_{\mathbb{R}}$ PowerTrench<sup>®</sup> PowerXS™

Programmable Active Droop™

QS<sup>TM</sup> Quiet Series™ RapidConfigure™ тм

Saving our world, 1mW/W/kW at a time™

SignalWise™ SmartMax™ SMART START™

Solutions for Your Success™

STEALTH™ SuperFET® SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS<sup>®</sup> . SyncFET™

Sync-Lock™

SYSTEM ®' TinvBoost<sup>T</sup> TinyBuck™ TinyCalc™ TinyLogic® TINYOPTO™ TinyPower™ TinyPWM™ TinyWire™ TranSiC® TriFault Detect™ TRUECURRENT®\* μSerDes™

UHC® Ultra FRFET™ UniFET<sup>TI</sup> VCX™ VisualMax™

VoltagePlus™ XS™

\*Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

#### DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN. WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY
FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE
EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness

#### ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.Fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufactures of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed application, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handing and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address and warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### PRODUCT STATUS DEFINITIONS Definition of Terms

Datasheet Identification	Datasheet Identification Product Status Definition			
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary First Production		Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
No Identification Needed Full Production		Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		

Rev. 164

ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <a href="www.onsemi.com/site/pdt/Patent-Marking.pdf">www.onsemi.com/site/pdt/Patent-Marking.pdf</a>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and exp

#### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800-282-9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor: FDMC8321L

### **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

### http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru\_4 moschip.ru\_9