






LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
ES	00		A2	REV PER ECR-11-019166	21SEP2011	ML	SZ
			A3	CORRECT DRAWING VIEW	16MAR2012	OL	SZ
			A4	ADD HOLD DOWN ON SHEET 1	20MAR2012	OL	SZ
			A5	UPDATE	23MAR2012	OL	SZ




- 1 "AMP", PART NUMBER, AND DATECODE TO BE MARKED IN AREA SHOWN. PARTS UNDER 2.00[50.8] LONG MAY BE MARKED ON BOTH SIDES.
- 2 MATERIAL: HOUSING - GLASS FILLED HIGH TEMP THERMO PLASTIC,BLACK, UL94 V-0
SIGNAL CONTACT - COPPER ALLOY
POWER CONTACT - HIGH CONDUCTIVITY COPPER ALLOY
- 3 CONTACT PLATING: NOBLE METAL PLATING ON CONTACT FUNCTIONAL AREA OF POWER AND SIGNAL CONTACTS.
- 4 MECHANICAL CONNECTOR KEEP OUT ZONE.
- 5 DATUM AND BASIC DIMENSIONS ESTABLISHED BY CUSTOMER.
- 6 PCB - HOLE DIAMETERS ARE FINISHED HOLE SIZE.
- 7 PCB - .0453±.0010 DRILLED HOLES PLATED WITH .0003 MIN Sn OVER .001 TO .003 Cu PLATING TO ACHIEVE A .040 DIA HOLE.
- 8 VARIABLE DIMENSION PLEASE REFER TO TABLE
- 9 HOLD DOWN IS OPTIONAL AND PLEASE REFER TO TABLE FOR SPECIFIED PART NUMBERS ON FOLLOWING PAGES



SECTION Z-Z




3		3.740	3.600	3.390	3.500	2.625	0.170	3ACP+8P+24S	6450882-9
A1		3.790	3.650	3.440	3.550	2.700	.145	13P + 24S	6450882-7
A	.200	3.065	2.925	2.715	-	1.975	.145	10HDP + 24S	6450882-4
A1		3.740	3.600	3.390	3.500	2.625	0.170	3ACP+8P+24S	6450882-3
A1		3.740	3.600	3.390	3.500	2.625	0.170	3ACP+8P+24S	6450882-2
2		3.740	3.600	3.390	3.500	2.625	0.170	3ACP+8P+24S	6450882-1
	.250	1.565	1.425	1.215	1.325	.425	0.170	2P + 24S	6450882-8
	DIM S	DIM L	DIM V	DIM U	DIM D	DIM W	DIM K	DESCRIPTION	PART NUMBER






THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	ORANDO LI	19NOV2009	 TE Connectivity				
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK	SUNY ZHAO	19NOV2009					
DIMENSIONS: INCHES		APVD	STEVEN YAO	-	NAME RIGHT ANGLE RECEPTACLE AND SHORT END MODULAR MULTI-BEAM XLE				
		PRODUCT SPEC							
		108-2292							
		APPLICATION SPEC							
		114-13038							
		WEIGHT							
MATERIAL		SIZE					CAGE CODE	DRAWING NO	RESTRICTED TO
-		A1					100779	C6450882	-
		CUSTOMER DRAWING					SCALE 4:1		
							SHEET 1 OF 4		
					REV A6				




LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
ES	00	-	-	SEE SHEET 1	-	-	-

PART NUMBER	ROWS		SIGNAL						POWER		
			6	5	4	3	2	1	P2	P1	
6450882-8	D		D	D	D	D	D	D	RP	RS	
	C		C	C	C	C	C	C			
	B		B	B	B	B	B	B			
	A		A	A	A	A	A	A			
2P + 24S											




SCALE 3:1

PART NUMBER	ROWS		SIGNAL							POWER											
			6	5	4	3	2	1	P11	P10	P9	P8	P7	P6	P5	P4	P3	P2	P1		
6450882-1	D		D	D	D	D	D	D													
	C		C	C	C	C	C	C													
	B		B	B	B	B	B	B													
	A		A	A	A	A	A	A													
3ACP + 8P + 24S																					




PCB LAYOUT VIEW OF 6450882-1/2/3

PART NUMBER	ROWS		SIGNAL						POWER												
			6	5	4	3	2	1	P11	P10	P9	P8	P7	P6	P5	P4	P3	P2	P1		
6450882-2	D		D	D	D	D	D	D	RS	RS	RS	RS	RP	RS	RS	RS	RS	RS	RS		
	C		C	C	C	C	C	C													
	B		B	B	B	B	B	B													
	A		A	A	A	A	A	A													
3ACP + 8P + 24S																					




PART NUMBER	ROWS		SIGNAL						POWER												
			6	5	4	3	2	1	P11	P10	P9	P8	P7	P6	P5	P4	P3	P2	P1		
6450882-3	D		D	D	D	D	D	D	RS	RS	RS	RS	RS	RS	RS	RP	RS	RS	RS		
	C		C	C	C	C	C	C													
	B		B	B	B	B	B	B													
	A		A	A	A	A	A	A													
3ACP + 8P + 24S																					




HOLD DOWN	HD
STD PRESS FIT SIGNAL CONTACT, .119 TAIL LENGTH, ROW D	D
STD PRESS FIT SIGNAL CONTACT, .119 TAIL LENGTH, ROW C	C
STD PRESS FIT SIGNAL CONTACT, .119 TAIL LENGTH, ROW B	B
STD PRESS FIT SIGNAL CONTACT, .119 TAIL LENGTH, ROW A	A
MFBL PRESS FIT POWER CONTACT, .119 TAIL LENGTH	RP
STD PRESS FIT POWER CONTACT, .119 TAIL LENGTH	RS
DESCRIPTION	
IDENTIFIER	

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN: ORANDO L1 19NOV2009	NAME	
DIMENSIONS:		CHK: SUNY ZHAO 19NOV2009	RIGHT ANGLE RECEPTACLE AND SHORT END MODUAL MULTI-BEAM XLE	
INCHES		APVD: STEVEN YAO	SIZE	
		PRODUCT SPEC	CAGE CODE	
		108-2292	DRAWING NO	
		APPLICATION SPEC	RESTRICTED TO	
		114-13038	A100779	
		ANGLES	C=6450882	
		FINISH	REV	
		WEIGHT	A6	
		CUSTOMER DRAWING	SCALE 4:1	
			SHEET 2 OF 4	

PART NUMBER	ROWS		SIGNAL							POWER										
			6	5	4	3	2	1	P10	P9	P8	P7	P6	P5	P4	P3	P2	P1		
6450882-4	D		D	D	D	D	D	D	RS	RS	RS	RS	RS	RS	RS	RP	RS	RS		
	C		C	C	C	C	C													
	B		B	B	B	B	B													
	A		A	A	A	A	A													
10HDP + 24S																				

4805 (3/11)



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9