

PRINTING RIBBONS AND INKS TECHNICAL DATASHEET

TTDS-257 Revision 5, July 2015

Section 1, Contents

| SECTION | PAGE | SECTION DESCRIPTION | COLOUR AND TYPE |
|-----------|------------|---|---|
| Section 1 | Page 1 | CONTENTS | |
| Section 2 | Page 2 | 1966-RIBBONS, 2000P-4TT, T300-RIBBON-UV-SCE | BLACK THERMAL TRANSFER |
| Section 3 | Page 3 | TMS-XXX-RIBBON-XXX | BLACK THERMAL TRANSFER |
| Section 4 | Page 4 & 5 | TTB-XXXX/XXX | BLACK THERMAL TRANSFER |
| Section 5 | Page 6 & 7 | 1330-XXXX-XX | BLACK THERMAL TRANSFER |
| Section 6 | Page 8 & 9 | WHITE & SILVER | WHITE & SILVER THERMAL TRANSFER |
| Section 7 | Page 10 | BTT-02 CARD PRINTER | BLUE, RED, BLACK AND WHITE THERMAL TRANSFER |
| Section 8 | Page 11 | DOT MATRIX | BLACK INK CARTRIDGES |

Section 2, BLACK 1966-RIBBONS, 2000P-4TT, T300-RIBBON-UV-SCE

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|---------------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| 1966-RIBBON | F55931-000 | 1 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 100mm (3.9 inches) | 25.4mm (1 inch) | Ink side out | Black |
| LBF-2000P-RIBBON-1966-MED | 6-1768383-4 | 1 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | Black |
| T200-RIBBON-1966 | D60849-000 | 1 year, when stored between -5°C (23°F) and 40° (104°F) | 74m (242 feet) | 110mm (4.3 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 2000P-RIBBON-4TT-MED | 893803-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 2000P-RIBBON-4TT-NAR | 277493-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 40mm (1.57 inches) | 25.4mm (1 inch) | Ink side out | Black |
| T300-UV-SCE-RIBBON | EC8932-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |

Section 3, BLACK TMS THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|-----------------------|-------------|---|---------------------|------------------------|----------------------|--------------|--------|
| TMS-RJS-RIBBON-4DSCE | 311292-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 450m (1476 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TMS-101-RIBBON-4DSCE | 505478-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| TMS-RJS-RIBBON-4RPSCE | 557721-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TMS-101-RIBBON-4RPSCE | 310109-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| TMS-RJS-RIBBON-4HT | 754073-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TMS-101-RIBBON-4HT | 746617-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |

Section 4, BLACK TTB THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|--|---------------------|------------------------|--------------------|--------------|--------|
| TTB-060SC/300 | 2-1768049-6 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-076SC/300 | 3-1768049-0 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 76mm (3 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-084SC/300 | C75514-000 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 84mm (3.3 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-110SC/300 | 3-1768049-6 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-128SC/450 | 4-1768049-1 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 450m (1476 feet) | 128mm (5.04 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TTB-170SC/450 | 4-1768049-7 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 450m (1476 feet) | 170mm (6.70 inches) | 25.4mm (1 inch) | Ink side out | Black |

Section 4, BLACK TTB THERMAL TRANSFER RIBBONS (Continued)

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|---------------------|-------------|--|---------------------|------------------------|--------------------|--------------|--------|
| TTB-110SC/300WH | 3-1768049-8 | 1 year, when stored between 5 (40°F) and 35°C (95°F) | 300m (984 feet) | 110mm (4.30 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-060SC/450AQ529 | 2-1768049-7 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 450m (1476 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-090SC/360-AQ529 | 3-1768049-4 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 360m (1181 feet) | 90mm (3.54 inches) | 25.4mm (1 inch) | Ink side in | Black |
| TTB-110SC/300AQ529S | 3-1768049-7 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TTB-114SC/360AQ529 | 4-1768049-0 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 360m (984 feet) | 114mm (4.48 inches) | 25.4mm (1 inch) | Ink side out | Black |
| TTB-166SC/360AQ529 | 8-1768402-6 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 360m (1181 feet) | 166mm (6.53 inches) | 25.4mm (1 inch) | Ink side out | Black |

Section 5, BLACK 1330 THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| 1330-0600-10 | 143060-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0600-T200 | C36369-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 1330-TTB-T200 | 1-1768384-8 | 1 year, when stored between 5°C (40°F) and 35°C (95°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 1330-3300-15 | 562492-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 165mm (6.5 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-10 | 980892-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.3 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-08 | 728382-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 80mm (3.15 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-06 | F31906-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 64mm (2.52 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-3300-101TT | C95590-000 | 3 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.3 inches) | 12.7mm (1/2 inch) | Ink side out | Black |

Section 5, BLACK 1330 THERMAL TRANSFER RIBBONS (Continued)

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| 1330-0607-10 | 742412-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0607-08 | 555080-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 80mm (3.15 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0607-T200 | E45478-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| 1330-0619-10 | 952888-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0619-08 | F65920-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 83mm (3.27 inches) | 25.4mm (1 inch) | Ink side out | Black |
| 1330-0619-T200 | C49013-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Black |

Section 6, WHITE and SILVER THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|---------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| T300-RIBBON-WH-4HT | 154739-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | White |
| T200-RIBBON-WH-4HT | 086961-000 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | White |
| T300-RIBBON-WH | 650784-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | White |
| T200-RIBBON-WH | 117366-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | White |
| 2000P-RIBBON-WH-MED | 094514-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | White |
| 2000P-RIBBON-WH-NAR | 530304-000 | 2 year, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 40mm (1.57 inches) | 25.4mm (1 inch) | Ink side out | White |

Section 6, WHITE and SILVER THERMAL TRANSFER RIBBONS (Continued)

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|----------------------|-------------|---|--------------------|------------------------|----------------------|--------------|--------|
| TMS-RJS-RIBBON-4AG | 124503-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 110mm (4.33 inches) | 25.4mm (1 inch) | Ink side out | Silver |
| TMS-101-RIBBON-4AG | 252557-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 74m (242 feet) | 110mm (4.33 inches) | 12.7mm (1/2 inch) | Ink side out | Silver |
| 2000P-RIBBON-4AG-MED | 351013-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 60mm (2.36 inches) | 25.4mm (1 inch) | Ink side out | Silver |
| 2000P-RIBBON-4AG-NAR | 346933-000 | 5 years, when stored between -5°C (23°F) and 40°C (104°F) | 300m (984 feet) | 40mm (1.57 inches) | 25.4mm (1 inch) | Ink side out | Silver |

Section 7, BTT-02 CARD PRINTER THERMAL TRANSFER RIBBONS

| Ribbon Description | Part number | Shelf life and storage conditions | Length | Width | Core size | Ink side | Colour |
|--------------------|-------------|---|--------------------|-----------------------|----------------------|--------------|--------|
| BBB-060BL/200 | 1-1768016-1 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | Blue |
| BBB-060RT/200 | 1-1768016-3 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | Red |
| BBB-060SC/200 | 1-1768016-4 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | Black |
| BBB-060WE/200 | 1-1768016-5 | 2 years, when stored between -5°C (23°F) and 40°C (104°F) | 200m (656 feet) | 60mm (2.36 inches) | 12.7mm (1/2 inch) | Ink side out | White |

Section 8, DOT MATRIX INK CARTRIDGES

| Ribbon Description | Part number | Shelf life and storage conditions | Colour |
|---------------------------|-------------|--|--------|
| LQ590-RIBBON | 1-2186029-1 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. | Black |
| TMS-SYSTEM-SIX-RIBBON-A | 310347-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| TMS-LQ590-RIBBON | CC3130-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Superseded for LQ590-RIBBON | Black |
| TMS-SYSTEM-SIX-RIBBON-B | 264327-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 1892BK04-RIBBON | D06106-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 1892BK03-HIGH-PERF-RIBBON | A72722-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 18910000-OKI380-RIBBON | 856832-000 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |
| 1330-0037-00 | 9-1198202-3 | 6 months When stored between 18°C (64°F) and 24°C (75°F) then 90 days after opening the inner packaging. Ink cartridge Obsolete | Black |

Printer Information

Print quality and print performance can only be guaranteed when specific TE printer and ribbons are used.

The current list of printers and ribbons can be found in TE document 411-121005 'Identification Printer Product Ribbon Matrix'. This document can be found in 'Access Our Tools':

<http://www.te.com/usa-en/utilities/access-product-tools-and-resources.html>

Software

WINTOTAL and PrintEasy label printing software, available from the Identification Printer Software page:

<http://www.te.com/usa-en/products/identification-labeling/printers-software/printing-software.html?tab=pgp-story>

Contact a TE representative for further information

te.com

TE Connectivity, TE Connectivity (logo) and Every Connection Counts are trademarks. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2014 TE Connectivity Ltd. family of companies All Rights Reserved.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9