


## 1588A Multi-Conductor - Category 5e Nonbonded-Pair Cable



For more Information  
please call

1-800-Belden1

**General Description:**

CAT5e (200MHz), 2-Pair, U/UTP-Unshielded, Riser-CMR, Premise Horizontal Cable, 24 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Ripcord, PVC Jacket

**Usage (Overall)**

Suitable Applications:

Premise Horizontal Cable, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU, Digital Video, RS-422

**Physical Characteristics (Overall)****Conductor**

AWG:

| # Pairs | AWG | Stranding | Conductor Material |
|---------|-----|-----------|--------------------|
| 2       | 24  | Solid     | BC - Bare Copper   |

Total Number of Conductors:

4

**Insulation**

Insulation Material:

| Insulation Material |
|---------------------|
| PO - Polyolefin     |

**Outer Shield**

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded            |

**Outer Jacket**

Outer Jacket Material:

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Diameter:

| Nom. Dia. (in.) |
|-----------------|
| 0.183           |

Outer Jacket Ripcord:

Yes

**Pair**

Pair Color Code Chart:

| Number | Color                        |
|--------|------------------------------|
| 1      | White/Blue Stripe & Blue     |
| 2      | White/Orange Stripe & Orange |

**Mechanical Characteristics (Overall)**

|                                   |                 |
|-----------------------------------|-----------------|
| Storage Temperature Range:        | -20°C To +75°C  |
| Installation Temperature Range:   | 0°C To +60°C    |
| Operating Temperature Range:      | -20°C To +75°C  |
| Bulk Cable Weight:                | 15 lbs/1000 ft. |
| Max. Recommended Pulling Tension: | 13 lbs.         |
| Min. Bend Radius/Minor Axis:      | 1 in.           |
| Min. Bend/Installation:           | 1.800 in.       |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                    |     |
|------------------------------------|-----|
| NEC/(UL) Specification:            | CMR |
| CEC/C(UL) Specification:           | CMR |
| EU Directive 2011/65/EU (ROHS II): | Yes |

## 1588A Multi-Conductor - Category 5e Nonbonded-Pair Cable

|                                       |                                                      |
|---------------------------------------|------------------------------------------------------|
| EU CE Mark:                           | Yes                                                  |
| EU Directive 2000/53/EC (ELV):        | Yes                                                  |
| EU Directive 2002/95/EC (RoHS):       | Yes                                                  |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004                                           |
| EU Directive 2002/96/EC (WEEE):       | Yes                                                  |
| EU Directive 2003/11/EC (BFR):        | Yes                                                  |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                                                  |
| MII Order #39 (China RoHS):           | Yes                                                  |
| Telecommunications Standards:         | Category 5e - TIA 568.C.2                            |
| Other Specification:                  | NEMA WC-63.1 Category 5e, UL verified to Category 5e |

## Flame Test

|                   |                       |
|-------------------|-----------------------|
| UL Flame Test:    | UL1666 Vertical Riser |
| C(UL) Flame Test: | FT4                   |
| IEEE Flame Test:  | 1202                  |

## Suitability

|                        |     |
|------------------------|-----|
| Suitability - Indoor:  | Yes |
| Suitability - Outdoor: | No  |
| Suitability - Aerial:  | No  |
| Suitability - Burial:  | No  |
| Sunlight Resistance:   | No  |

## Plenum/Non-Plenum

|                |       |
|----------------|-------|
| Plenum (Y/N):  | No    |
| Plenum Number: | 1590A |

## Electrical Characteristics (Overall)

## Nom. Mutual Capacitance:

Capacitance (pF/ft)

15

Maximum Capacitance Unbalance (pF/100 m): 330

## Nominal Velocity of Propagation:

VP (%)

70

## Maximum Delay:

Delay (ns/100 m)

538 @ 100MHz

## Max. Delay Skew:

Delay Skew (ns/100 m)

45

## Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)

9.38

## Max. Operating Voltage - UL:

Voltage

300 V RMS

## Maximum DCR Unbalanced:

DCR Unbalance @ 20°C (%)

5

## Electrical Characteristics-Premise (Overall)

## Premise Cable Electrical Table 1:

| Freq. (MHz) | Max. Attenuation (dB/100 m) | Min. NEXT (dB) | Min. PSNEXT (dB) | Min. ACR (dB) | Min. PSACR (dB) | Min RL (dB) | Min. SRL (dB) |
|-------------|-----------------------------|----------------|------------------|---------------|-----------------|-------------|---------------|
| 1           | 2.0                         | 65.3           | 62.3             | 63.0          | 60.3            | 20.0        | 23.0          |
| 4           | 4.1                         | 56.3           | 53.3             | 51.0          | 49.2            | 23.0        | 23.0          |
| 8           | 5.8                         | 51.8           | 48.8             | 46.0          | 43.0            | 24.5        | 24.5          |
| 10          | 6.5                         | 50.3           | 47.3             | 43.0          | 40.8            | 25.0        | 25.0          |
| 16          | 8.2                         | 47.3           | 44.3             | 39.0          | 36.0            | 25.0        | 25.0          |
| 20          | 9.3                         | 45.8           | 42.8             | 36.5          | 33.5            | 25.0        | 25.0          |

## 1588A Multi-Conductor - Category 5e Nonbonded-Pair Cable

|       |      |      |      |      |      |      |      |
|-------|------|------|------|------|------|------|------|
| 25    | 10.4 | 44.3 | 41.3 | 33.9 | 30.9 | 24.3 | 24.3 |
| 31.25 | 11.7 | 42.9 | 39.9 | 31.0 | 28.2 | 23.6 | 23.6 |
| 62.5  | 17.0 | 38.4 | 35.4 | 22.0 | 19.0 | 21.5 | 21.5 |
| 100   | 22.0 | 35.3 | 32.3 | 14.0 | 10.3 | 20.1 | 20.1 |
| 155   | 28.1 | 32.5 | 29.5 | 4.4  | 1.4  | 15.8 |      |
| 200   | 32.0 | 30.8 | 27.8 | 4.0  | 1.0  | 15.0 |      |

Premise Cable Electrical Table 2:

| Freq. (MHz) | Input (Unfitted) Imp. (Ohms) | Fitted Impedance | Min. ELFEXT (dB) | Min. PSELFEXT (dB) |
|-------------|------------------------------|------------------|------------------|--------------------|
| 1           | 100 ± 15                     | 100 ± 15         | 63.8             | 60.8               |
| 4           | 100 ± 15                     | 100 ± 15         | 51.7             | 48.7               |
| 8           | 100 ± 15                     | 100 ± 15         | 45.7             | 42.7               |
| 10          | 100 ± 15                     | 100 ± 15         | 43.8             | 40.8               |
| 16          | 100 ± 15                     | 100 ± 15         | 39.7             | 36.7               |
| 20          | 100 ± 15                     | 100 ± 15         | 37.7             | 34.7               |
| 25          | 100 ± 15                     | 100 ± 15         | 35.8             | 32.8               |
| 31.25       | 100 ± 15                     | 100 ± 15         | 33.9             | 30.9               |
| 62.5        | 100 ± 15                     | 100 ± 15         | 27.8             | 24.9               |
| 100         | 100 ± 15                     | 100 ± 15         | 23.8             | 20.8               |
| 155         | 100 ± 25                     | 100 ± 15         | 19.9             | 16.9               |
| 200         | 100 ± 25                     | 100 ± 15         | 17.7             | 14.7               |

## Notes (Overall)

**Notes:** Jacket sequentially marked at 2 ft. intervals. Third party verified to ANSI/TIA-568-C.2, Category 5e.

## Put Ups and Colors:

| Item #         | Putup    | Ship Weight | Color            | Notes | Item Desc                |
|----------------|----------|-------------|------------------|-------|--------------------------|
| 1588A F6HU1000 | 1,000 FT | 15.000 LB   | GRAY, DARK PEARL |       | CAT5E 2PR U/UTP CMR BOX  |
| 1588A F6H1000  | 1,000 FT | 15.000 LB   | GRAY, DARK PEARL | C     | CAT5E 2PR U/UTP CMR REEL |
| 1588A F6H1640  | 1,640 FT | 24.600 LB   | GRAY, DARK PEARL |       | CAT5E 2PR U/UTP CMR REEL |
| 1588A 006U1000 | 1,000 FT | 15.000 LB   | BLUE, LIGHT      |       | CAT5E 2PR U/UTP CMR BOX  |
| 1588A 006I1000 | 1,000 FT | 15.000 LB   | BLUE, LIGHT      | C     | CAT5E 2PR U/UTP CMR REEL |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 4    Revision Date: 08-06-2013

© 2017 Belden, Inc  
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9