Ultralow Offset Voltage Operational Amplifier

Data Sheet **OP07**

FEATURES

- Low V_{OS}: 75 µV maximum
- Low V_{OS} drift: 1.3 µV/°C maximum
- Ultrastable vs. time: 1.5 µV per month maximum
- Low noise: 0.6 µV p-p maximum
- Wide input voltage range: ±14 V typical
- Wide supply voltage range: ±3 V to ±18 V
- 125°C temperature-tested dice

APPLICATIONS

- Wireless base station control circuits
- Optical network control circuits
- Instrumentation
- Sensors and controls
  - Thermocouples
  - Resistor thermal detectors (RTDs)
  - Strain bridges
  - Shunt current measurements
- Precision filters

PIN CONFIGURATION



Figure 1.

GENERAL DESCRIPTION

The OP07 has very low input offset voltage (75 µV maximum for OP07E) that is obtained by trimming at the wafer stage. These low offset voltages generally eliminate any need for external nulling. The OP07 also features low input bias current (±4 nA for the OP07E) and high open-loop gain (200 V/mV for the OP07E). The low offset and high open-loop gain make the OP07 particularly useful for high gain instrumentation applications.

The wide input voltage range of ±13 V minimum combined with a high CMRR of 106 dB (OP07E) and high input impedance provide high accuracy in the noninverting circuit configuration. Excellent linearity and gain accuracy can be maintained even at high closed-loop gains. Stability of offsets and gain with time or variations in temperature is excellent. The accuracy and stability of the OP07, even at high gain, combined with the freedom from external nulling have made the OP07 an industry standard for instrumentation applications.

The OP07 is available in two standard performance grades. The OP07E is specified for operation over the 0°C to 70°C range, and the OP07C is specified over the −40°C to +85°C temperature range.

The OP07 is available in epoxy 8-lead PDIP and 8-lead narrow SOIC packages. For CERDIP and TO-99 packages and standard microcircuit drawing (SMD) versions, see the OP77.



1R2A AND R2B ARE ELECTRONICALLY ADJUSTED ON CHIP AT FACTORY FOR MINIMUM INPUT OFFSET VOLTAGE.

Figure 2. Simplified Schematic

Rev. G

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.
Tel: 781.329.4700 www.analog.com
Fax: 781.461.3113 ©2002-2011 Analog Devices, Inc. All rights reserved.

TABLE OF CONTENTS

Features 1
Applications 1
General Description 1
Pin Configuration 1
Revision History 2
Specifications 3
OP07E Electrical Characteristics 3
OP07C Electrical Characteristics 4
Absolute Maximum Ratings 6
Thermal Resistance 6
ESD Caution 6
Typical Performance Characteristics 7
Typical Applications 11
Applications Information 12
Outline Dimensions 13
Ordering Guide 14

REVISION HISTORY

10/11—Rev. F. to Rev G
Changes to Features Section 1

8/10—Rev. E. to Rev F
Changes to Ordering Guide 14

7/09—Rev. D. to Rev E
Changes to Figure 29 Caption 11
Changes to Ordering Guide 14

7/06—Rev. C. to Rev D
Changes to Features 1
Changes to General Description 1
Changes to Specifications Section 3
Changes to Table 4 6
Changes to Figure 6 and Figure 8 7
Changes to Figure 13 and Figure 14 8
Changes to Figure 20 9
Changes to Figure 21 to Figure 25 10
Changes to Figure 26 and Figure 30 11
Replaced Figure 28 11
Changes to Applications Information Section 12
Updated Outline Dimensions 13
Changes to Ordering Guide 14

8/03—Rev. B to Rev. C
Changes to OP07E Electrical Specifications 2
Changes to OP07C Electrical Specifications 3
Edits to Ordering Guide 5
Edits to Figure 6 9
Updated Outline Dimensions 11

3/03—Rev. A to Rev. B
Updated Package Titles ..... Universal
Updated Outline Dimensions 11

2/02—Rev. 0 to Rev. A
Edits to Features 1
Edits to Ordering Guide 1
Edits to Pin Connection Drawings 1
Edits to Absolute Maximum Ratings 2
Deleted Electrical Characteristics 2–3
Deleted OP07D Column from Electrical Characteristics 4–5
Edits to TPCs 7–9
Edits to High-Speed, Low V_{OS} Composite Amplifier 9

SPECIFICATIONS

OP07E ELECTRICAL CHARACTERISTICS

V_S = ±15 V, unless otherwise noted.

Table 1.

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
T_A = 25°C						
Input Offset Voltage[1]	V_{OS}			30	75	µV
Long-Term V_{OS} Stability[2]	V_{OS}/Time			0.3	1.5	µV/Month
Input Offset Current	I_{OS}			0.5	3.8	nA
Input Bias Current	I_B			±1.2	±4.0	nA
Input Noise Voltage	e_n p-p	0.1 Hz to 10 Hz[3]		0.35	0.6	µV p-p
Input Noise Voltage Density	e_n	f_O = 10 Hz		10.3	18.0	nV/√Hz
		f_O = 100 Hz[3]		10.0	13.0	nV/√Hz
		f_O = 1 kHz		9.6	11.0	nV/√Hz
Input Noise Current	I_n p-p			14	30	pA p-p
Input Noise Current Density	I_n	f_O = 10 Hz		0.32	0.80	pA/√Hz
		f_O = 100 Hz[3]		0.14	0.23	pA/√Hz
		f_O = 1 kHz		0.12	0.17	pA/√Hz
Input Resistance, Differential Mode[4]	R_{IN}		15	50		MΩ
Input Resistance, Common Mode	R_{INCM}			160		GΩ
Input Voltage Range	IVR		±13	±14		V
Common-Mode Rejection Ratio	CMRR	V_{CM} = ±13 V	106	123		dB
Power Supply Rejection Ratio	PSRR	V_S = ±3 V to ±18 V		5	20	µV/V
Large Signal Voltage Gain	A_{VO}	R_L ≥ 2 kΩ, V_O = ±10 V	200	500		V/mV
		R_L ≥ 500 Ω, V_O = ±0.5 V, V_S = ±3 V[4]	150	400		V/mV
0°C ≤ T_A ≤ 70°C						
Input Offset Voltage[1]	V_{OS}			45	130	µV
Voltage Drift Without External Trim[4]	TCV_{OS}			0.3	1.3	µV/°C
Voltage Drift with External Trim[3]	TCV_{OSN}	R_P = 20 kΩ		0.3	1.3	µV/°C
Input Offset Current	I_{OS}			0.9	5.3	nA
Input Offset Current Drift	TCI_{OS}			8	35	pA/°C
Input Bias Current	I_B			±1.5	±5.5	nA
Input Bias Current Drift	TCI_B			13	35	pA/°C
Input Voltage Range	IVR		±13	±13.5		V
Common-Mode Rejection Ratio	CMRR	V_{CM} = ±13 V	103	123		dB
Power Supply Rejection Ratio	PSRR	V_S = ±3 V to ±18 V		7	32	µV/V
Large Signal Voltage Gain	A_{VO}	R_L ≥ 2 kΩ, V_O = ±10 V	180	450		V/mV
OUTPUT CHARACTERISTICS						
T_A = 25°C						
Output Voltage Swing	V_O	R_L ≥ 10 kΩ	±12.5	±13.0		V
		R_L ≥ 2 kΩ	±12.0	±12.8		V
		R_L ≥ 1 kΩ	±10.5	±12.0		V
0°C ≤ T_A ≤ 70°C						
Output Voltage Swing	V_O	R_L ≥ 2 kΩ	±12	±12.6		V

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
DYNAMIC PERFORMANCE						
T_A = 25°C						
Slew Rate	SR	$R_L \geq 2$ kΩ[3]	0.1	0.3		V/µs
Closed-Loop Bandwidth	BW	$A_{VOL} = 1$[5]	0.4	0.6		MHz
Open-Loop Output Resistance	R_O	$V_O = 0$, $I_O = 0$		60		Ω
Power Consumption	P_d	$V_S = \pm 15$ V, No load		75	120	mW
		$V_S = \pm 3$ V, No load		4	6	mW
Offset Adjustment Range		R_P = 20 kΩ		±4		mV

[1] Input offset voltage measurements are performed by automated test equipment approximately 0.5 seconds after application of power.
[2] Long-term input offset voltage stability refers to the averaged trend time of V_{OS} vs. the time over extended periods after the first 30 days of operation. Excluding the initial hour of operation, changes in V_{OS} during the first 30 operating days are typically 2.5 µV. Refer to the Typical Performance Characteristics section. Parameter is sample tested.
[3] Sample tested.
[4] Guaranteed by design.
[5] Guaranteed but not tested.

OP07C ELECTRICAL CHARACTERISTICS

$V_S = \pm 15$ V, unless otherwise noted.

Table 2.

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
INPUT CHARACTERISTICS						
T_A = 25°C						
Input Offset Voltage[1]	V_{OS}			60	150	µV
Long-Term V_{OS} Stability[2]	V_{OS}/Time			0.4	2.0	µV/Month
Input Offset Current	I_{OS}			0.8	6.0	nA
Input Bias Current	I_B			±1.8	±7.0	nA
Input Noise Voltage	e_n p-p	0.1 Hz to 10 Hz[3]		0.38	0.65	µV p-p
Input Noise Voltage Density	e_n	f_O = 10 Hz		10.5	20.0	nV/√Hz
		f_O = 100 Hz[3]		10.2	13.5	nV/√Hz
		f_O = 1 kHz		9.8	11.5	nV/√Hz
Input Noise Current	I_n p-p			15	35	pA p-p
Input Noise Current Density	I_n	f_O = 10 Hz		0.35	0.90	pA/√Hz
		f_O = 100 Hz[3]		0.15	0.27	pA/√Hz
		f_O = 1 kHz		0.13	0.18	pA/√Hz
Input Resistance, Differential Mode[4]	R_{IN}		8	33		MΩ
Input Resistance, Common Mode	R_{INCM}			120		GΩ
Input Voltage Range	IVR		±13	±14		V
Common-Mode Rejection Ratio	CMRR	$V_{CM} = \pm 13$ V	100	120		dB
Power Supply Rejection Ratio	PSRR	$V_S = \pm 3$ V to ±18 V		7	32	µV/V
Large Signal Voltage Gain	A_{VO}	$R_L \geq 2$ kΩ, $V_O = \pm 10$ V	120	400		V/mV
		$R_L \geq 500$ Ω, $V_O = \pm 0.5$ V, $V_S = \pm 3$ V[4]	100	400		V/mV
−40°C ≤ T_A ≤ +85°C						
Input Offset Voltage[1]	V_{OS}			85	250	µV
Voltage Drift Without External Trim[4]	TCV_{OS}			0.5	1.8	µV/°C
Voltage Drift with External Trim[3]	TCV_{OSN}	R_P = 20 kΩ		0.4	1.6	µV/°C
Input Offset Current	I_{OS}			1.6	8.0	nA
Input Offset Current Drift	TCI_{OS}			12	50	pA/°C
Input Bias Current	I_B			±2.2	±9.0	nA
Input Bias Current Drift	TCI_B			18	50	pA/°C
Input Voltage Range	IVR		±13	±13.5		V
Common-Mode Rejection Ratio	CMRR	$V_{CM} = \pm 13$ V	97	120		dB
Power Supply Rejection Ratio	PSRR	$V_S = \pm 3$ V to ±18 V		10	51	µV/V
Large Signal Voltage Gain	A_{VO}	$R_L \geq 2$ kΩ, $V_O = \pm 10$ V	100	400		V/mV

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
OUTPUT CHARACTERISTICS						
T_A = 25°C						
Output Voltage Swing	V_O	$R_L \geq 10$ kΩ	±12.0	±13.0		V
		$R_L \geq 2$ kΩ	±11.5	±12.8		V
		$R_L \geq 1$ kΩ		±12.0		V
−40°C ≤ T_A ≤ +85°C						
Output Voltage Swing	V_O	$R_L \geq 2$ kΩ	±12	±12.6		V
DYNAMIC PERFORMANCE						
T_A = 25°C						
Slew Rate	SR	$R_L \geq 2$ kΩ[3]	0.1	0.3		V/µs
Closed-Loop Bandwidth	BW	$A_{VOL} = 1$[5]	0.4	0.6		MHz
Open-Loop Output Resistance	R_O	$V_O = 0$, $I_O = 0$		60		Ω
Power Consumption	P_d	V_S = ±15 V, No load		80	150	mW
		V_S = ±3 V, No load		4	8	mW
Offset Adjustment Range		R_P = 20 kΩ		±4		mV

[1] Input offset voltage measurements are performed by automated test equipment approximately 0.5 seconds after application of power.
[2] Long-term input offset voltage stability refers to the averaged trend time of V_{OS} vs. the time over extended periods after the first 30 days of operation. Excluding the initial hour of operation, changes in V_{OS} during the first 30 operating days are typically 2.5 µV. Refer to the Typical Performance Characteristics section. Parameter is sample tested.
[3] Sample tested.
[4] Guaranteed by design.
[5] Guaranteed but not tested.

ABSOLUTE MAXIMUM RATINGS

Table 3.

Parameter	Ratings
Supply Voltage (V_S)	±22 V
Input Voltage[1]	±22 V
Differential Input Voltage	±30 V
Output Short-Circuit Duration	Indefinite
Storage Temperature Range	
S and P Packages	−65°C to +125°C
Operating Temperature Range	
OP07E	0°C to 70°C
OP07C	−40°C to +85°C
Junction Temperature	150°C
Lead Temperature, Soldering (60 sec)	300°C

[1] For supply voltages less than ±22 V, the absolute maximum input voltage is equal to the supply voltage.

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only; functional operation of the device at these or any other conditions above those indicated in the operational section of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

THERMAL RESISTANCE

θ_{JA} is specified for the worst-case conditions, that is, a device soldered in a circuit board for surface-mount packages.

Table 4. Thermal Resistance

Package Type	θ_{JA}	θ_{JC}	Unit
8-Lead PDIP (P-Suffix)	103	43	°C/W
8-Lead SOIC_N (S-Suffix)	158	43	°C/W

ESD CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although this product features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 3. Open-Loop Gain vs. Temperature



Figure 4. Offset Voltage Change due to Thermal Shock



Figure 5. Warm-Up Drift



Figure 6. Maximum Error vs. Source Resistance



Figure 7. Maximum Error vs. Source Resistance



Figure 8. Input Bias Current vs. Differential Input Voltage



Figure 9. Input Bias Current vs. Temperature



Figure 10. Input Offset Current vs. Temperature



Figure 11. Low Frequency Noise



Figure 12. Total Input Noise Voltage vs. Frequency



Figure 13. Input Wideband Noise vs. Bandwidth, 0.1 Hz to Frequency Indicated



Figure 14. CMRR vs. Frequency



Figure 15. PSRR vs. Frequency



Figure 16. Open-Loop Gain vs. Power Supply Voltage



Figure 17. Open-Loop Frequency Response



Figure 18. Closed-Loop Frequency Response for Various Gain Configurations



Figure 19. Maximum Output Swing vs. Frequency



Figure 20. Maximum Output Voltage vs. Load Resistance



Figure 21. Power Consumption vs. Power Supply



Figure 22. Output Short-Circuit Current vs. Time



Figure 23. Untrimmed Offset Voltage vs. Temperature



Figure 24. Trimmed Offset Voltage vs. Temperature



Figure 25. Offset Voltage Drift vs. Time

TYPICAL APPLICATIONS



Figure 26. Typical Offset Voltage Test Circuit



Figure 29. Absolute Value Circuit



Figure 27. Typical Low Frequency Noise Circuit



Figure 30. High Speed, Low V_{OS} Composite Amplifier



Figure 28. Optional Offset Nulling Circuit



Figure 31. Adjustment-Free Precision Summing Amplifier



NOTES
1. PINOUT SHOWN FOR P PACKAGE

Figure 32. High Stability Thermocouple Amplifier



NOTES
1. PINOUT SHOWN FOR P PACKAGE

Figure 33. Precision Absolute-Value Circuit

APPLICATIONS INFORMATION

The OP07 provides stable operation with load capacitance of up to 500 pF and ±10 V swings; larger capacitances should be decoupled with a 50 Ω decoupling resistor.

Stray thermoelectric voltages generated by dissimilar metals at the contacts to the input terminals can degrade drift performance. Therefore, best operation is obtained when both input contacts are maintained at the same temperature, preferably close to the package temperature.

OUTLINE DIMENSIONS



COMPLIANT TO JEDEC STANDARDS MS-012-AA

CONTROLLING DIMENSIONS ARE IN MILLIMETERS; INCH DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF MILLIMETER EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN.

012407-A

Figure 34. 8-Lead Standard Small Outline Package [SOIC_N]
Narrow Body S-Suffix
(R-8)
Dimensions shown in millimeters and (inches)



COMPLIANT TO JEDEC STANDARDS MS-001

CONTROLLING DIMENSIONS ARE IN INCHES; MILLIMETER DIMENSIONS (IN PARENTHESES) ARE ROUNDED-OFF INCH EQUIVALENTS FOR REFERENCE ONLY AND ARE NOT APPROPRIATE FOR USE IN DESIGN. CORNER LEADS MAY BE CONFIGURED AS WHOLE OR HALF LEADS.

070606-A

Figure 35. 8-Lead Plastic Dual-in-Line Package [PDIP]
P-Suffix
(N-8)
Dimensions shown in inches and (millimeters)

ORDERING GUIDE

Model[1]	Temperature Range	Package Description	Package Option
OP07EPZ	0°C to 70°C	8-Lead PDIP	N-8 (P-Suffix)
OP07CPZ	−40°C to +85°C	8-Lead PDIP	N-8 (P-Suffix)
OP07CSZ	−40°C to +85°C	8-Lead SOIC_N	R-8 (S-Suffix)
OP07CSZ-REEL	−40°C to +85°C	8-Lead SOIC_N	R-8 (S-Suffix)
OP07CSZ-REEL7	−40°C to +85°C	8-Lead SOIC_N	R-8 (S-Suffix)

[1] Z = RoHS Compliant Part.

NOTES

NOTES

©2002-2011 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners.
D00316-0-10/11(G)

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9