

ADAM-6150

ADAM-6151/6156

15-ch Isolated Digital I/O Real-time Ethernet Module

16-ch Isolated Digital Input/ Digital Output Real-time Ethernet Module



ADAM-6150

FCC CE RoHS COMPLIANT 2002/95/EC

Specifications

Digital Input

- Channels 8
- Dry Contact Logic level 0: open
Logic level 1: close to DGND
- Wet Contact Logic level 0: 0 ~ 3 V_{DC} or 0 ~ -3 V_{DC}
Logic level 1: 10 ~ 30 V_{DC} or -10 ~ -30 V_{DC}
(Dry/Wet Contact decided by switch)
- Input Impedance 5.2 k Ω (Wet Contact)
- Transition Time From logic level 0 to 1: 0.2 ms
From logic level 1 to 0: 0.2 ms

Digital Output

- Channels 7
- Output Voltage Range 8 ~ 35 V_{DC}
- Normal Output Current 100 mA (per channel)

Ordering Information

- ADAM-6150EI 15-ch Isolated DI/O EtherNet/IP Module



ADAM-6151/6156

FCC CE RoHS COMPLIANT 2002/95/EC

Specifications

Digital Input (ADAM-6151)

- Channels 16
- Dry Contact Logic level 0: open
Logic level 1: close to DGND
- Wet Contact Logic level 0: 0 ~ 3 V_{DC} or 0 ~ -3 V_{DC}
Logic level 1: 10 ~ 30 V_{DC} or -10 ~ -30 V_{DC}
(Dry/Wet Contact decided by switch)
- Input Impedance 5.2 k Ω (Wet Contact)
- Transition Time From logic level 0 to 1: 0.2 ms
From logic level 1 to 0: 0.2 ms

Digital Output (ADAM-6156)

- Channels 16
- Output Voltage Range 8 ~ 35 V_{DC}
- Normal Output Current 100 mA (per channel)

Ordering Information

- ADAM-6151EI 16-ch Isolated DI EtherNet/IP Module
- ADAM-6156EI 16-ch Isolated DO EtherNet/IP Module

Common Specifications

General

- LAN 10/100Base-T(X)
- Power Consumption ADAM-6150: 3 W @ 24 V_{DC}
ADAM-6151: 2.7 W @ 24 V_{DC}
ADAM-6156: 3.2 W @ 24 V_{DC}
- Connectors 2 x RJ-45 LAN, (Daisy Chain)
Plug-in screw terminal block (I/O and power)
- Watchdog System (1.6 second)
- Power Input 10 ~ 30 V_{DC}

Protection

- Over Voltage Protection ± 35 V_{DC}
- Isolation Protection 2,500 V_{DC}
- Power Reversal Protection

Environment

- Operating Temperature -10 ~ 70°C (14 ~ 158°F)
- Storage Temperature -20 ~ 80°C (-4 ~ 176°F)
- Operating Humidity 20 ~ 95% RH (non-condensing)
- Storage Humidity 0 ~ 95% RH (non-condensing)
0 ~ 95% RH (non-condensing)

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9