



# 8D Power Series

# 8D Power Series



## SOURIAU

The extreme environments interconnect specialist «from deep sea to deep space»

The company designs, manufactures and markets high performance interconnect solutions for severe environments from industrial broadband and universal ranges to complex system with integrated functions: filtering, high speed data transmission, hermetic seal, separation mechanism, remote handling, underwater mating, ...



Industrial



Aeronautical



Equipment & System

The dedicated end markets for SOURIAU's products are aeronautical, defense-space and industrial.



Railway  
Geophysics  
Manufacturing environment  
Instrumentation  
Automation & process  
Motosport



Civil & military aircraft  
Helicopter  
Weapon delivery system  
Avionics



Military marine  
Communications  
Satellites  
Launcher & missile

SOURIAU was established in 1917 and has been created by successive acquisitions of the industrial, aeronautical, defense and space activities of SOURIAU, JUPITER and BURNDY.

The Group's products are engineered and manufactured in the USA and Dominican Republic, Europe and Morocco, Japan and India, and sold by a worldwide sales and marketing organization, and in addition to SOURIAU's offices, a large network of licensed distributors and agents.

SOURIAU complies with most of national and international Quality Assurance Standards, production unit with ISO 14001

**Quality Certificate  
Management System**

**ISO 9001**

**Environment Certificate  
Management System**

**ISO 14001**

**Quality Certificate  
Management System**

**Aeronautic Industry : EN 9100**

# 8D Power Series



## Presentation

8D power series is a range extension of standard aeromil product line to adress high power supply in harsh environment for civil and military aeronautics market.

Thanks to its unique contact design (socket with a braid) these products can be used wherever very high power supply is required in environment where vibration and temperature are high.

Typical applications can be motor of electro hydraulic or electro mechanical actuators (located on Aircraft wings and tail or in the thrust reverser actuation sytem).

8D range features 6 different layouts in 4 shell sizes (composite or aluminum) with contacts from size 8 to size 4 enabling current rating up to 80 Amps.

## Contents

|                                         |    |
|-----------------------------------------|----|
| • Company profile .....                 | 2  |
| • Presentation .....                    | 3  |
| • Technical features and benefits ..... | 4  |
| • Ordering information .....            | 6  |
| • Layouts .....                         | 7  |
| • Dimensions .....                      | 8  |
| • Contacts and sealing boot .....       | 9  |
| • Tooling .....                         | 10 |


# 8D Power Series



## Technical features and benefits

### A unique contact design with a braid socket

- Enabling 20 contact points for a size 4 contact vs 2 or 3 for a standard socket,
- Allowing 20 % more intensity as compared to standard socket,
- Excellent vibration withstanding,
- Insure excellent crimping (crimping bucket can be heat treated to insure good plasticity without affecting the active part elasticity insured by the braid - added after heat treatment).




20 contact points on the pin for a #4 contact

Cut of a contact mated pair



### A versatile individual sealing on the cable

- Sealing on the cable done thanks to a sealing boot,
- Same connector can accommodate a wide range of cable diameter.



Longitudinal cut of a connector

### A contact technology integrated in well proven standard aeromil connectors

- Up to 260°C service temperature,
- Up to 60G vibration withstanding.



# 8D Power Series



## Description

- Quick screw coupling connector with removable crimp contact.
- Designed to be used in severe environments, fluid resistance, high shock and vibration.
- Shell available in, aluminium, composite, Stainless steel, Titanium & Bronze.
- Six layouts with different current rating.
- Consult us for power hermetic version.

## Applications

- Power supply in harsh environment:  
Electro Hydraulic actuator on Aircraft wings,  
Electro Mechanical actuator for Aircraft  
Thrust Reverser...

## Technical features

### Mechanical

- **Shell:** Aluminum alloy, Composite, Bronze, Stainless steel, Titanium.
- **Plating:**
  - Olive green cadmium (W/J),
  - Nickel (F/M/TF/S),
  - Without plating (X for composite, TT for titanium and JVS for Bronze),
  - Passivated (K).
- **Grommet and seal:** Silicon elastomer.
- **Insulator:** Thermoset.
- **Contact body:** Copper Alloy.
- **Contact retention:**
  - #4 = 200N
  - #8 = 111N.
- **Shock:** 300g during 3ms.
- **Endurance:** 500 mating / unmating operations.
- **Vibration:** As per MIL DTL 38999.

### Electrical

- **Dielectric withstanding:**  
Test voltage rating (Vrms).

| Service | Sea level | at 21 000 m |
|---------|-----------|-------------|
| M       | 1 300     | 800         |
| I       | 1 800     | 1 000       |

- **Insulation Resistance:**  
5000 MΩ under 500 Vdc.
- **Max current rating per contact:**
  - #4 = 80A
  - #8 = 45A.
- **Contact resistance:**
  - #4 = 2mΩ
  - #8 = 3mΩ.
- **Shielding:** As per MIL DTL 38999.
- **Electrical continuity:**
  - W = 2.5 mΩ,
  - F = 1mΩ,
  - J, M = 3 mΩ,
  - JVS = 5 mΩ.

### Environmental

- **Temperature range:**  
W, J, X, JVS = - 65°C +175°C,  
F, M, K, S, TT, TF = - 65°C +200°C.
- **Sealing:** As per MIL DTL 38999.
- **Damp Heat:** As per MIL DTL 38999.
- **Salt Spray:**  
W, TT, TF, K, JVS = 500 hours,  
F, S = 48 hours,  
J,M,X = 2000 hours.
- **Fire resistance:**  
As per EN 2591 - c 17 method A.
- **Resistance to fluid:**  
As per MIL DTL 38999.

# 8D Power Series



## Ordering information

|                                                                                                                                                                                                                                                                                                                                                        |    |   |   |    |   |    |   |   |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----|---|---|----|---|----|---|---|-----|
| Basic Series                                                                                                                                                                                                                                                                                                                                           | 8D | 0 | - | 11 | W | 80 | P | N | 251 |
| <b>Style:</b><br>0: Square flange receptacle<br>5: Plug with RFI shielding<br>7: Jam nut receptacle                                                                                                                                                                                                                                                    |    |   |   |    |   |    |   |   |     |
| <b>Type:</b> Crimp contact                                                                                                                                                                                                                                                                                                                             |    |   |   |    |   |    |   |   |     |
| <b>Shell size:</b> 11 - 17 - 21 - 25                                                                                                                                                                                                                                                                                                                   |    |   |   |    |   |    |   |   |     |
| <b>Plating (according shell material - see below):</b><br><b>Aluminum shell:</b><br>W: Olive green cadmium<br>F: Nickel<br><b>Composite shell:</b><br>J: Olive green cadmium<br>M: Nickel<br>X: Without plating<br><b>Stainless steel shell:</b><br>K: Corrosion resistant<br>S: Nickel<br><b>Titanium shell:</b><br>TT: Without plating<br>TF: Nickel |    |   |   |    |   |    |   |   |     |
| <b>Contact layouts:</b> See p.8                                                                                                                                                                                                                                                                                                                        |    |   |   |    |   |    |   |   |     |
| <b>Contact style:</b><br>P: Pin contact                      A: Male connector supplied without contact<br>S: Socket contact                    B: Female connector supplied without contact                                                                                                                                                           |    |   |   |    |   |    |   |   |     |
| <b>Orientation:</b> N - A - B - C - D - E                                                                                                                                                                                                                                                                                                              |    |   |   |    |   |    |   |   |     |
| <b>Specification:</b><br>251: To be added for some layouts to be supplied with power contacts (see page 8)                                                                                                                                                                                                                                             |    |   |   |    |   |    |   |   |     |

## Ordering information (Marine Bronze serie)

|                                                                                                                                                                                              |     |    |   |    |    |   |   |     |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|---|----|----|---|---|-----|
| Basic Series                                                                                                                                                                                 | JVS | 16 | A | 11 | 80 | P | N | 251 |
| <b>Style:</b><br>00: Square flange receptacle<br>07: Jam nut receptacle<br>16: Plug                                                                                                          |     |    |   |    |    |   |   |     |
| <b>Material:</b><br>A: Bronze shell material                                                                                                                                                 |     |    |   |    |    |   |   |     |
| <b>Shell size:</b> 11 - 17 - 21 - 25                                                                                                                                                         |     |    |   |    |    |   |   |     |
| <b>Contact layouts:</b> See p.8                                                                                                                                                              |     |    |   |    |    |   |   |     |
| <b>Contact style:</b><br>P: Pin contact                      A: Male connector supplied without contact<br>S: Socket contact                    B: Female connector supplied without contact |     |    |   |    |    |   |   |     |
| <b>Orientation:</b> N - A - B - C - D - E                                                                                                                                                    |     |    |   |    |    |   |   |     |
| <b>Specification:</b><br>251: To be added for some layouts to be supplied with power contacts (see page 8)                                                                                   |     |    |   |    |    |   |   |     |

# 8D Power Series



## Layouts

**11**

**80\***  
Spec 251



1#8

**17**

**02\***  
Spec 251



38#22  
1#8

**22\***  
Spec 251



2#12  
2#8


**75\***  
Spec 251



2#8

**19**


**18\***  
Spec 251



14#22  
4#8


**21**

**48**




4#8

**75\***  
Spec 251



4#8

**78\***  
Spec 251



17#22  
4#8


**25**

**07\***  
Spec 251




97#22  
2#8

**08\***  
Spec 251




8#8

**20\***  
Spec 251




10#20  
13#16  
4#12  
3#8

**41\***  
Spec 251




22#22  
3#20  
11#16  
2#12  
3#8

**44**



4#16  
4#4

**46\***  
Spec 251




40#20  
4#16  
2#8

\* For classes F, W, K, S only

# 8D Power Series




## Dimension plug type 5 - for all material




| Shell size | 11        | 17        | 21        | 25        |
|------------|-----------|-----------|-----------|-----------|
| A max      | 31        | 31        | 31        | 31        |
| B (thread) | M 15x1-6g | M 25x1-6g | M 31x1-6g | M 37x1-6g |
| C max      | 25.00     | 36.5      | 42.5      | 48.4      |

## Dimension receptacle type 0 - for all material



| Shell size   | 11        | 17        | 21        | 25        |
|--------------|-----------|-----------|-----------|-----------|
| A max        | 20.83     | 20.83     | 20.10     | 20.10     |
| B max        | 12.00     | 12.00     | 12.00     | 12.00     |
| C max        | 2.50      | 3.65      | 4.35      | 4.35      |
| D (thread)   | M 15x1-6g | M 25x1-6g | M 31x1-6g | M 37x1-6g |
| E $\pm 0.3$  | 26.20     | 33.30     | 39.70     | 46.00     |
| F            | 20.62     | 26.97     | 31.75     | 38.10     |
| G            | 18.26     | 24.61     | 29.36     | 34.93     |
| H $\pm 0.20$ | 3.25      | 3.25      | 3.25      | 3.91      |
| J $\pm 0.20$ | 4.93      | 4.93      | 4.93      | 6.15      |

## Dimension Jam nut type 7 - for all material (excepted composite)



| Shell size      | 11        | 17        | 21        | 25        |
|-----------------|-----------|-----------|-----------|-----------|
| A $+0.10 -0.15$ | 19.07     | 30.18     | 36.50     | 42.85     |
| B max           | 9.90      | 9.90      | 9.90      | 9.90      |
| C max           | 3.20      | 3.20      | 3.20      | 3.20      |
| D max           | 35.20     | 44.80     | 52.70     | 59.00     |
| E max           | 27.00     | 37.00     | 46.00     | 51.23     |
| F 0.4           | 31.80     | 41.30     | 49.20     | 55.60     |
| G (thread)      | M 15x1-6g | M 25x1-6g | M 31x1-6g | M 37x1-6g |

# 8D Power Series





## Contacts

Socket contact



Pin contact



| Contact size           | Contact type | Contact reference | Cable                                                               |                | Protection | Dimensions |      |
|------------------------|--------------|-------------------|---------------------------------------------------------------------|----------------|------------|------------|------|
|                        |              |                   | Cable size                                                          | Cable material |            | L          | D    |
| #4                     | Male         | 8599-7534         | #4-5 or 10-16mm <sup>2</sup> **<br>for cable 25mm <sup>2</sup> (#3) | Copper         | Au         | 9.70       | 5.74 |
|                        | Female       | 8599-7535         |                                                                     |                |            | 16.58      | 8.50 |
|                        | Male         | 8599-7598 900 *   |                                                                     |                |            | 9.70       | 5.74 |
|                        | Female       | 8599-7599 900 *   |                                                                     |                |            | 16.58      | 8.50 |
| #4 with reduced barrel | Male         | 8599-7528 900     | #6 or 10mm <sup>2</sup> **                                          | Copper         | Au         | 9.70       | 5.74 |
|                        | Female       | 8599-7529 900     |                                                                     |                |            | 16.58      | 8.50 |
| #8 JVS only            | Male         | 8599-7544         | #8 or 10 **                                                         | Copper         | Au         | 9.60       | 3.64 |
|                        | Female       | 8599-7541         |                                                                     |                |            | 16.00      | 7.30 |
| #8                     | Male         | 8599-7580         | #8 or 10 **                                                         | Copper         | Au         | 9.60       | 3.64 |
|                        | Female       | 8599-7581         |                                                                     |                |            | 16.00      | 7.30 |

\* Not included in connector P/N. Must be ordered separately.

\*\* To be used with crimping bucket reducer.

## Sealing boot and crimping bucket reducer



| Contact size | Cable size        | Cable material | Sealing boot reference |
|--------------|-------------------|----------------|------------------------|
| #4           | 16mm <sup>2</sup> | Copper         | 8599-4594              |
|              | 10mm <sup>2</sup> |                | 8599-4593              |
| #8           | #8                | Copper         | 8599-4542              |
|              | #10               |                | 8599-4547              |

| Contact size | Cable size        | Reducing sleeve reference |
|--------------|-------------------|---------------------------|
| #4           | 10mm <sup>2</sup> | 8400-2352A                |
| #8           | #10               | 8599-7545                 |

# 8D Power Series



## Tooling

| Contact size   | Contact type | Contact reference | Cable AWG                      | Crimping tool | Die set      | Locator      | Contact extraction tool (metallic) | Contact extraction tool (plastic) |
|----------------|--------------|-------------------|--------------------------------|---------------|--------------|--------------|------------------------------------|-----------------------------------|
| #4             | Male         | 8599-7534         | #4-5 or 10-16mm <sup>2</sup> * | M22520/23-01  | M22520/23-04 | M22520/23-11 | 8533-8175                          | M81969/14-07                      |
|                | Female       | 8599-7535         | #4-5 or 10-16mm <sup>2</sup> * | M22520/23-01  | M22520/23-04 | M22520/23-11 | 8533-8175                          | M81969/14-07                      |
| #8<br>JVS only | Male         | 8599-7544         | #8 or 10 *                     | M22520/23-01  | M22520/23-02 | 8599-9601    | 8660-197                           | M81969/14-12                      |
|                | Female       | 8599-7541         | #8 or 10 *                     | M22520/23-01  | M22520/23-02 | 8599-9601    | 8660-197                           | M81969/14-12                      |
| #8             | Male         | 8599-7580         | #8 or 10 *                     | M22520/23-01  | M22520/23-02 | 8599-9601    | 8660-197                           | M81969/14-12                      |
|                | Female       | 8599-7581         | #8 or 10 *                     | M22520/23-01  | M22520/23-02 | 8599-9601    | 8660-197                           | M81969/14-12                      |

Manual hand tool also existing for power contacts #8.

\* To be used with crimping bucket reductor.

### Automatic tool for contacts #4 & #8



Crimping tool (M22520/23-01)



Die set (M22520/23-02)



Locator (M22520/23-11)

### Manual hand tool for contacts #8




Crimping tool (M300 BT)




Locator (SP 593)


### Extraction tool



Metallic extraction tool  
for #4 (8533-8175)



Metallic extraction tool  
for #8 (8660-197)



[www.souriau.com](http://www.souriau.com)  
[contactmilaero@souriau.com](mailto:contactmilaero@souriau.com)



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9