
ANGELINA-XW

White version with ~91° wide beam



TECHNICAL SPECIFICATIONS:

Dimensions	Ø 82.0 mm
Height	31 mm
Fastening	socket
ROHS compliant	yes


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish	Coating
ANGELINA-XW	Reflector	HRPC	white		

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F13838_ANGELINA-XW » Box size: 480 x 280 x 300 mm	900	120	60	12.3

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.



INDEX	PART NO	DESCRIPTION	MATERIAL	COLOR
1		ANGELINA	Reflective PC	White

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:

DRAWING TITLE
ANGELINA series Reflector

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy."

SIZE A4 | PART NUMBER -

SCALE 1:1 | WEIGHT - | SHEET 1/1


PHOTOMETRIC DATA (MEASURED):

bridgelux

LED	V10 Gen7
FWHM	93.0°
Efficiency	89 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
F13671_ANGE-RZ-LENS
Bender Wirth: 434 Typ L1






bridgelux

LED	V13 Gen7
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213254-2 + OPTIC CLIP Z50 TYPE1 2213194-1







bridgelux

LED	V22 Gen6
FWHM	88.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2204-CT + 50-2100AN






bridgelux

LED	Vero SE 13
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C16402_CLAMP-VEROSE-13-18





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

bridgelux

LED	Vero SE 18
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C16402_CLAMP-VEROSE-13-18







bridgelux

LED	VERO18
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18







bridgelux

LED	VERO29
FWHM	91.0°
Efficiency	93 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13584_CLAMP-VERO29






bridgelux

LED	VERO29
FWHM	90.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13584_CLAMP-VERO29
F13671_ANGE-RZ-LENS





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

bridgelux

LED	Vesta TW 15mm DP
FWHM	92.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
- C13658_CLAMP-VERO13-18
- F13671_ANGE-RZ-LENS
- Bender Wirth: 482 Typ L2






bridgelux

LED	Vesta TW 15mm DP
FWHM	92.0°
Efficiency	96 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
- C13658_CLAMP-VERO13-18
- Bender Wirth: 482 Typ L2






bridgelux

LED	Vesta TW 18mm (31W) DP
FWHM	90.0°
Efficiency	90 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
- C13584_CLAMP-VERO29
- F13671_ANGE-RZ-LENS
- Bender Wirth: 483 Typ L3






bridgelux

LED	Vesta TW 18mm (31W) DP
FWHM	91.0°
Efficiency	96 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
- C13584_CLAMP-VERO29
- Bender Wirth: 483 Typ L3





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

bridgelux

LED	Vesta TW 22mm DP
FWHM	90.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
- C13584_CLAMP-VERO29
- F13671_ANGE-RZ-LENS
- Bender Wirth: 494 Typ L3






bridgelux

LED	Vesta TW 22mm DP
FWHM	90.0°
Efficiency	96 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
- C13584_CLAMP-VERO29
- Bender Wirth: 494 Typ L3






CITIZEN

LED	CLL02x/CLU02x (LES10)
FWHM	94.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13658_CLAMP-VERO13-18
- Bender Wirth: 434 Typ L1







CITIZEN

LED	CLL03x/CLU03x
FWHM	91.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- TE: 2213254-2 + OPTIC CLIP Z50 TYPE1 2213194-1






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CITIZEN

LED	CLL03x/CLU03x
FWHM	89.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- IDEAL: 50-2103CT + 50-2100AN






CITIZEN

LED	CLL03x/CLU03x
FWHM	91.0°
Efficiency	92 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C16791_CLAMP-Z45-A
- F13671_ANGE-RZ-LENS
- TE: 2325807-3






CITIZEN

LED	CLL03x/CLU03x
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C16791_CLAMP-Z45-A
- TE: 2325807-3






CITIZEN

LED	CLL04x/CLU04x
FWHM	88.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13584_CLAMP-VERO29
- Bender Wirth: 431 Typ L3






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CITIZEN

LED	CLL04x/CLU04x
FWHM	88.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2204-CT + 50-2100AN







CITIZEN

LED	CLU700/701/702
FWHM	95.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 434 Typ L1






CITIZEN

LED	CLU720/721
FWHM	89.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2103CT + 50-2100AN







CITIZEN

LED	CLU720/721
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213254-2 + OPTIC CLIP Z50 TYPE1 2213194-1






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CITIZEN

LED	CLU730/731
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2204-CT + 50-2100AN






CREE

LED	CMA1840
FWHM	93.0°
Efficiency	97 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C14123_CLAMP-CXA15-18






CREE

LED	CMA2550
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C14036_CLAMP_CXA25-30






CREE

LED	CMA3090
FWHM	90.0°
Efficiency	97 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C14036_CLAMP_CXA25-30





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CREE

LED	CMT14xx
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 434 Typ L1






CREE

LED	CMT19xx
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 477 Typ L1






CREE

LED	CMT28xx
FWHM	89.0°
Efficiency	96 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13584_CLAMP-VERO29
Bender Wirth: 471 Typ L3






CREE

LED	CXA/B 15xx
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C14123_CLAMP-CXA15-18





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CREE

LED	CXA/B 15xx
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 441 Typ L1







CREE

LED	CXA/B 1816 & CXA/B 1820 & CXA 1850
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 437 Typ L1






CREE

LED	CXA/B 1816 & CXA/B 1820 & CXA 1850
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213401-2 + OPTIC CLIP Z50 TYPE1 2213194-1







CREE

LED	CXA/B 1816 & CXA/B 1820 & CXA 1850
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C14123_CLAMP-CXA15-18





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

CREE

LED	CXA/B 30xx
FWHM	91.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C14036_CLAMP_CXA25-30







CREE

LED	CXA/B 3590
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2303CR + 50-2300AN






EVERLIGHT

LED	CHI3030 19W
FWHM	88.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
C13584_CLAMP-VERO29
F13671_ANGE-RZ-LENS
Bender Wirth: 468 Typ L3



EVERLIGHT

LED	CHI3030 29W
FWHM	89.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13584_CLAMP-VERO29
F13671_ANGE-RZ-LENS
Bender Wirth: 468 Typ L3




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON CoB 1202/1203
FWHM	95.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 438 Typ L1






LUMILEDS

LED	LUXEON CoB 1204HD
FWHM	92.0°
Efficiency	96 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213382-2 + OPTIC CLIP Z50 TYPE1 2213194-1






LUMILEDS

LED	LUXEON CoB 1205HD
FWHM	92.0°
Efficiency	96 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213382-2 + OPTIC CLIP Z50 TYPE1 2213194-1







LUMILEDS

LED	LUXEON CoB 1208
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON CoB 1211
FWHM	91.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13584_CLAMP-VERO29
Bender Wirth: 431 Typ L3






LUMILEDS

LED	LUXEON CoB 1211
FWHM	89.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2204-CT + 50-2100AN







LUMILEDS

LED	LUXEON CoB 1216/1812
FWHM	88.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2204-CT + 50-2100AN






LUMILEDS

LED	LUXEON K12
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213134-2 + OPTIC CLIP Z50 TYPE1 2213194-1




LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMILEDS

LED	LUXEON K16
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
BJB: 47.319.2070






LUMINUS

LED	CDM-14 (Dim-To-Warm)
FWHM	94.0°
Efficiency	90 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
F13671_ANGE-RZ-LENS
Bender Wirth: 491 Typ L2






LUMINUS

LED	CDM-14 (Dim-To-Warm)
FWHM	94.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 491 Typ L2






LUMINUS

LED	CDM-18 (Dim-To-Warm)
FWHM	93.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
F13671_ANGE-RZ-LENS
Bender Wirth: 491 Typ L2





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMINUS

LED	CDM-18 (Dim-To-Warm)
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13658_CLAMP-VERO13-18
- Bender Wirth: 491 Typ L2






LUMINUS

LED	CDM-9 (Dim-To-Warm)
FWHM	95.0°
Efficiency	89 %
Peak intensity	0.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13658_CLAMP-VERO13-18
- F13671_ANGE-RZ-LENS
- Bender Wirth: 490 Typ L1






LUMINUS

LED	CDM-9 (Dim-To-Warm)
FWHM	95.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13658_CLAMP-VERO13-18
- Bender Wirth: 490 Typ L1






LUMINUS

LED	CTM-14 (Tunable White)
FWHM	94.0°
Efficiency	88 %
Peak intensity	0.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13584_CLAMP-VERO29
- F13671_ANGE-RZ-LENS
- Bender Wirth: 442 Typ L3






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LUMINUS

LED	CTM-14 (Tunable White)
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13584_CLAMP-VERO29
- Bender Wirth: 442 Typ L3







LUMINUS

LED	CTM-22 (Tunable White)
FWHM	92.0°
Efficiency	88 %
Peak intensity	0.4 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13584_CLAMP-VERO29
- F13671_ANGE-RZ-LENS
- Bender Wirth: 494 Typ L3






LUMINUS

LED	CTM-22 (Tunable White)
FWHM	93.0°
Efficiency	93 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13584_CLAMP-VERO29
- Bender Wirth: 494 Typ L3







LUMINUS

LED	CxM-14 (19x19)
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- TE: 2213254-2 + OPTIC CLIP Z50 TYPE1 2213194-1





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	COB J-Type
FWHM	89.0°
Efficiency	90 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F13671_ANGE-RZ-LENS
IDEAL: 50-2103NC + 50-2100AN







NICHIA

LED	COB J-Type
FWHM	93.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 463 Typ L2







NICHIA

LED	COB J-Type
FWHM	88.0°
Efficiency	92 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2103NC + 50-2100AN







NICHIA

LED	COB L-Type (LES 11)
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 438 Typ L1





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	COB L-Type (LES 11)
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2100NC + 50-2100AN







NICHIA

LED	COB L-Type (LES 11)
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
Molex: 180580-0005






NICHIA

LED	COB L-Type (LES 11)
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213382-2 + OPTIC CLIP Z50 TYPE1 2213194-1






NICHIA

LED	NVCWJ024Z-V1MT: COB J-Type Tunable White
FWHM	94.0°
Efficiency	89 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
F13671_ANGE-RZ-LENS
Bender Wirth: 498 Typ L2





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

NICHIA

LED	NVCWJ024Z-V1MT: COB J-Type Tunable White
FWHM	94.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 498 Typ L2






OSRAM

LED	PrevaLED Core AC (LEP-2000)
FWHM	89.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1






OSRAM

LED	PrevaLED Core AC (LEP-800)
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1






OSRAM

LED	PrevaLED Core G7 L15 H1
FWHM	90.0°
Efficiency	92 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C16685_CLAMP-PRV-A
F13671_ANGE-RZ-LENS





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

OSRAM

LED	PrevaLED Core G7 L15 H1
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C16685_CLAMP-PRV-A






OSRAM

LED	PrevaLED Core Z4 LES19
FWHM	90.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1







OSRAM

LED	PrevaLED Core Z4 LES19
FWHM	90.0°
Efficiency	90 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F13671_ANGE-RZ-LENS
TE: OPTIC CLIP Z50 TYPE1 2213194-1






OSRAM
Opto Semiconductors

LED	Soleriq S13
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213401-2 + OPTIC CLIP Z50 TYPE1 2213194-1





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED	Soleriq S13
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 437 Typ L1






OSRAM
Opto Semiconductors

LED	Soleriq S13 19x19
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213254-2 + OPTIC CLIP Z50 TYPE1 2213194-1






OSRAM
Opto Semiconductors

LED	Soleriq S13 19x19
FWHM	91.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2103CT + 50-2100AN







OSRAM
Opto Semiconductors

LED	Soleriq S19
FWHM	90.0°
Efficiency	93 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13584_CLAMP-VERO29
Bender Wirth: 462 Typ L3






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

OSRAM
Opto Semiconductors

LED	Soleriq S19
FWHM	91.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213407-2 + OPTIC CLIP Z50 TYPE1 2213194-1







PHILIPS

LED	Fortimo SLM L09 + SLM holder
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1







PHILIPS

LED	Fortimo SLM L13 + SLM holder
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1






PHILIPS

LED	Fortimo SLM L13 CoB
FWHM	91.0°
Efficiency	88 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F13671_ANGE-RZ-LENS
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

PHILIPS

LED	Fortimo SLM L13 CoB
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1







PHILIPS

LED	Fortimo SLM L15 + SLM holder
FWHM	91.0°
Efficiency	92 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1






PHILIPS

LED	Fortimo SLM L15 + SLM holder
FWHM	91.0°
Efficiency	89 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F13671_ANGE-RZ-LENS
TE: OPTIC CLIP Z50 TYPE1 2213194-1






PHILIPS

LED	Fortimo SLM L15 CoB
FWHM	91.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

PHILIPS

LED	Fortimo SLM L15 CoB
FWHM	91.0°
Efficiency	89 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- F13671_ANGE-RZ-LENS
- TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1







PHILIPS

LED	Fortimo SLM L19 + SLM holder
FWHM	90.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- TE: OPTIC CLIP Z50 TYPE1 2213194-1







SAMSUNG

LED	LC026B / 033B / 040B
FWHM	91.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
- C13658_CLAMP-VERO13-18
- Bender Wirth: 450 Typ L2






SAMSUNG

LED	LC035T (Tunable white)
FWHM	90.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
- C13584_CLAMP-VERO29
- F13671_ANGE-RZ-LENS
- Bender Wirth: 502 Typ L3





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

SAMSUNG

LED	LC035T (Tunable white)
FWHM	91.0°
Efficiency	96 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	Tunable White

Required components:
C13584_CLAMP-VERO29
Bender Wirth: 502 Typ L3






SAMSUNG

LED	LC040C
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213382-2 + OPTIC CLIP Z50 TYPE1 2213194-1






SEOUL SEMICONDUCTOR

LED	AC Zhaga COB
FWHM	93.0°
Efficiency	91 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F13671_ANGE-RZ-LENS






SEOUL SEMICONDUCTOR

LED	MJT COB LES 14.5
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213254-2 + OPTIC CLIP Z50 TYPE1 2213194-1





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

SEOUL SEMICONDUCTOR

LED	MJT COB LES 22
FWHM	89.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13584_CLAMP-VERO29
Bender Wirth: 431 Typ L3







SHARP

LED	Mega Zenigata (GW6DME)
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1






SHARP

LED	Mega Zenigata (GW6DME)
FWHM	92.0°
Efficiency	92 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
F13671_ANGE-RZ-LENS
TE: 2213130-2 + OPTIC CLIP Z50 TYPE1 2213194-1







VS LIGHTING SOLUTIONS

LED	WU-M-464
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1





LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.


PHOTOMETRIC DATA (MEASURED):

LIGHTING SOLUTIONS

LED	WU-M-484
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1







LIGHTING SOLUTIONS

LED	WU-M-485
FWHM	93.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1






LIGHTING SOLUTIONS

LED	WU-M-486
FWHM	92.0°
Efficiency	94 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
TE: OPTIC CLIP Z50 TYPE1 2213194-1






LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

bridgelux

LED	V10 Gen7
FWHM	93.0°
Efficiency	92 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 486 Typ L1



bridgelux

LED	V13 Gen7
FWHM	86.0°
Efficiency	92 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White


Required components:
IDEAL: 50-2103CT + 50-2100AN



bridgelux

LED	V22 Gen7
FWHM	82.0°
Efficiency	94 %
Peak intensity	0.6 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
IDEAL: 50-2204-CT + 50-2100AN



LUMINUS

LED	CxM-9 (13.5x13.5)
FWHM	94.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:
C13658_CLAMP-VERO13-18
Bender Wirth: 434 Typ L1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

PHOTOMETRIC DATA (SIMULATED):

SEOUL SEMICONDUCTOR

LED	ZC12/18
FWHM	92.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

C13658_CLAMP-VERO13-18

Bender Wirth: 433 Typ L1

SEOUL SEMICONDUCTOR

LED	ZC4/6
FWHM	94.0°
Efficiency	95 %
Peak intensity	0.5 cd/lm
LEDs/each optic	1
Light colour	White

Required components:

C13658_CLAMP-VERO13-18

Bender Wirth: 434 Typ L1

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

Due to use of high power COB's with this product, special attention to proper thermal design is highly recommended. LEDiL has no liability for direct, indirect or consecutive damages arising from the LEDiL products being used outside of the recommended temperature range.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Salo, Finland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9