

# 40 Series

## Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard



Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

### FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

### SERIES SPECIFICATIONS

Series	Wattage	Ohms	Voltage
41	1.0	0.10-6K	150
42	2.0	0.10-8K	100
43	3.0	0.10-20K	200
45	5.0	0.10-70K	460
47	7.0	0.10-80K	670
40	10.0	0.10-150K	1000

Non-Inductive versions available. Insert "N" before tolerance code.  
Example: 42NJ27R

### CHARACTERISTICS

<b>Coating</b>	Conformal silicone-ceramic.
<b>Core</b>	Ceramic.
<b>Terminals</b>	Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu
<b>Derating</b>	Linearly from 100% @ +25°C to 0% @ +275°C.
<b>Tolerance</b>	±5% (J type), ±1% (F type) (other tolerances available).
<b>Power rating</b>	Based on 25°C free air rating
<b>Overload</b>	Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.
<b>Temperature coefficient</b>	Under 1Ω: ±90 ppm/°C; 1Ω to 9.99Ω: ±50 ppm/°C; 10Ω and over: ±20 ppm/°C
<b>Operating temp. range</b>	-55°C to 275°C

### DIMENSIONS

(in./mm max.)



Series	Wattage	Length	Diam.	Lead ga.
41	1.0	0.437 / 11.1	0.125 / 3.2	24
42	2.0	0.406 / 10.3	0.219 / 5.6	20
43	3.0	0.593 / 15.1	0.219 / 5.6	20
45	5.0	0.937 / 23.8	0.343 / 8.7	18
47	7.0	1.280 / 32.5	0.343 / 8.7	18
40	10.0	1.900 / 48.3	0.406 / 10.3	18

(continued)

# 40 Series

## Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard


### ORDERING INFORMATION

#### Standard part numbers

Ohmic value	Wattage and Tolerance		Ohmic value	Wattage and Tolerance		Ohmic value	Wattage and Tolerance				
	1% Tolerance	5% Tolerance		1% Tolerance	5% Tolerance		1% Tolerance	5% Tolerance			
Part No. Prefix > Suffix >	1	3	1	2	3	Part No. Prefix > Suffix >	1	2	3	5	10
0.1 —R10	✓	✓	✓	✓	✓	68 —68R	✓	✓	✓	✓	✓
0.15 —R15	✓	✓	✓	✓	✓	75 —75R	✓	✓	✓	✓	✓
0.2 —R20	✓	✓	✓	✓	✓	82 —82R	✱	✓	✓	✓	✓
0.25 —R25	✓	✓	✓	✓	✓	100 —100	✓	✓	✓	✓	✓
0.3 —R30	✓	✓	✓	✓	✓	120 —120	✱	✓	✓	✓	✓
0.33 —R33	✓	✓	✓	✓	✓	125 —125	✓	✱	✓	✓	✓
0.4 —R40	✓	✓	✓	✓	✓	150 —150	✓	✓	✓	✱	✓
0.5 —R50	✓	✓	✓	✓	✓	180 —180	✓	✓	✓	✱	✓
0.75 —R75	✓	✱	✓	✓	✓	200 —200	✓	✓	✓	✓	✓
1 —1R0	✓	✓	✓	✓	✓	220 —220	✓	✓	✓	✱	✓
1.5 —1R5	✓	✓	✓	✓	✓	225 —225	✱	✱	✓	✓	✓
2 —2R0	✓	✓	✓	✓	✓	250 —250	✓	✓	✓	✓	✓
2.2 —2R2	✓	✓	✓	✓	✓	270 —270	✓	✓	✓	✱	✓
3 —3R0	✓	✓	✱	✓	✓	300 —300	✓	✓	✓	✓	✓
4 —4R0	✓	✓	✓	✓	✓	330 —330	✓	✱	✓	✓	✓
5 —5R0	✓	✓	✓	✓	✓	350 —350	✱	✓	✓	✓	✓
7.5 —7R5	✓	✓	✓	✓	✓	390 —390	✱	✓	✓	✓	✓
10 —10R	✓	✓	✓	✓	✓	400 —400	✓	✓	✓	✱	✓
12 —12R	✱	✓	✓	✓	✓	450 —450	✱	✓	✓	✓	✓
15 —15R	✓	✓	✓	✓	✓	470 —470	✓	✓	✓	✓	✓
18 —18R	✱	✓	✱	✓	✓	500 —500	✓	✓	✓	✓	✓
20 —20R	✓	✓	✓	✓	✓	560 —560	✓	✓	✓	✓	✓
22 —22R	✓	✓	✓	✓	✓	600 —600	✓	✓	✓	✓	✓
25 —25R	✓	✓	✓	✓	✓	680 —680	✓	✓	✓	✓	✓
27 —27R	✱	✓	✓	✓	✓	750 —750	✓	✓	✓	✓	✓
30 —30R	✓	✓	✓	✓	✓	800 —800	✓	✓	✓	✓	✓
33 —33R	✓	✓	✓	✓	✓	820 —820	✓	✓	✓	✓	✓
35 —35R	✓	✓	✓	✓	✓	900 —900	✓	✓	✓	✓	✓
39 —39R	✓	✓	✓	✓	✓	1,000 —1K0	✓	✓	✓	✓	✓
40 —40R	✓	✓	✓	✓	✓	1,100 —1K1	✓	✓	✓	✓	✓
47 —47R	✓	✓	✓	✓	✓	1,200 —1K2	✓	✓	✓	✓	✓
50 —50R	✓	✓	✓	✓	✓	1,500 —1K5	✓	✓	✓	✓	✓
56 —56R	✓	✓	✓	✓	✓	1,800 —1K8	✓	✓	✓	✓	✓
62 —62R	✓	✓	✓	✓	✓	2,000 —2K0	✓	✓	✓	✓	✓

✓ = Standard values  
 ✱ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.



## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9