

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard



Ohmite 40 Series resistors are the most economical conformal silicone-ceramic coated resistors offered. These all-welded units are characterized by their low temperature coefficients and resistance to thermal shock, making them ideal for a wide range of electrical and electronic applications.

Units with 1% and 5% tolerances are identical in construction and electrical specifications. Durable but economical 40 Series resistors exceed industry requirements for quality.

FEATURES

- Economical
- Applications include commercial, industrial and communications equipment
- Stability under high temperature conditions
- All-welded construction
- RoHS compliant; add "E" suffix to part number to specify.

SERIES SPECIFICATIONS

Series	Wattage	Ohms	Voltage
41	1.0	0.10-6K	150
42	2.0	0.10-8K	100
43	3.0	0.10-20K	200
45	5.0	0.10-70K	460
47	7.0	0.10-80K	670
40	10.0	0.10-150K	1000

Non-Inductive versions available. Insert "N" before tolerance code.
Example: 42NJ27R

CHARACTERISTICS

Coating	Conformal silicone-ceramic.
Core	Ceramic.
Terminals	Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu
Derating	Linearly from 100% @ +25°C to 0% @ +275°C.
Tolerance	±5% (J type), ±1% (F type) (other tolerances available).
Power rating	Based on 25°C free air rating
Overload	Under 5 watts: 5 times rated wattage for 5 seconds. 5 watts and over: 10 times rated wattage for 5 seconds.
Temperature coefficient	Under 1Ω: ±90 ppm/°C; 1Ω to 9.99Ω: ±50 ppm/°C; 10Ω and over: ±20 ppm/°C
Operating temp. range	-55°C to 275°C

DIMENSIONS

(in./mm max.)



Series	Wattage	Length	Diam.	Lead ga.
41	1.0	0.437 / 11.1	0.125 / 3.2	24
42	2.0	0.406 / 10.3	0.219 / 5.6	20
43	3.0	0.593 / 15.1	0.219 / 5.6	20
45	5.0	0.937 / 23.8	0.343 / 8.7	18
47	7.0	1.280 / 32.5	0.343 / 8.7	18
40	10.0	1.900 / 48.3	0.406 / 10.3	18

(continued)

40 Series

Ohmicone® Silicone-Ceramic Conformal Axial Terminal Wirewound 1% and 5% Tolerance Standard

ORDERING INFORMATION

Standard part numbers

Ohmic value	Wattage and Tolerance		Wattage and Tolerance		Ohmic value	Wattage and Tolerance		Wattage and Tolerance		Ohmic value	Wattage and Tolerance		Wattage and Tolerance	
	Part No. Prefix > Suffix >	1% Tolerance	5% Tolerance	Part No. Prefix > Suffix >		1% Tolerance	5% Tolerance	Part No. Prefix > Suffix >	1% Tolerance		5% Tolerance	Part No. Prefix > Suffix >	1% Tolerance	5% Tolerance
0.1	R10	✓	✓	✓	68	68R	✓	✓	✓	2,200	2K2	✓	✓	
0.15	R15	✓	✓	✓	75	75R	✓	✓	✓	2,500	2K5	✓	✓	
0.2	R20	✓	✓	✓	82	82R	✱	✓	✓	2,700	2K7	✱	✓	
0.25	R25	✓	✓	✓	100	100	✓	✓	✓	3,000	3K0	✓	✓	
0.3	R30	✓	✓	✓	120	120	✱	✓	✓	3,300	3K3	✱	✓	
0.33	R33	✓	✓	✓	125	125	✓	✱	✓	3,500	3K5	✓	✓	
0.4	R40	✓	✓	✓	150	150	✓	✓	✱	3,900	3K9	✓	✓	
0.5	R50	✓	✓	✓	180	180	✓	✓	✱	4,000	4K0	✓	✓	
0.75	R75	✓	✱	✓	200	200	✓	✓	✓	4,500	4K5	✱	✓	
1	R10	✓	✓	✓	220	220	✓	✓	✱	4,700	4K7	✓	✓	
1.5	R15	✓	✓	✓	225	225	✱	✱	✓	5,000	5K0	✓	✓	
2	R20	✓	✓	✓	250	250	✓	✓	✓	6,000	6K0	✱	✓	
2.2	R22	✓	✓	✓	270	270	✓	✓	✱	6,800	6K8	✓	✓	
3	R30	✓	✓	✱	300	300	✓	✱	✓	7,000	7K0	✓	✱	
4	R40	✓	✓	✓	330	330	✓	✱	✓	7,500	7K5	✓	✓	
5	R50	✓	✓	✓	350	350	✱	✓	✱	8,000	8K0	✓	✱	
7.5	R75	✓	✓	✓	390	390	✱	✓	✓	9,000	9K0	✓	✱	
10	R10	✓	✓	✓	400	400	✓	✓	✓	10,000	10K	✓	✓	
12	R12	✱	✓	✓	450	450	✱	✓	✓	12,000	12K	✓	✓	
15	R15	✓	✓	✓	470	470	✓	✓	✓	13,000	13K	✓	✓	
18	R18	✱	✓	✓	500	500	✓	✓	✱	15,000	15K	✓	✓	
20	R20	✓	✓	✓	560	560	✓	✓	✓	17,000	17K	✓	✱	
22	R22	✓	✓	✱	600	600	✓	✓	✓	20,000	20K	✓	✓	
25	R25	✓	✓	✱	680	680	✓	✓	✱	22,000	22K	✓	✓	
27	R27	✱	✓	✓	750	750	✓	✓	✓	25,000	25K	✓	✓	
30	R30	✓	✓	✓	800	800	✓	✓	✱	30,000	30K	✓	✓	
33	R33	✓	✓	✓	820	820	✓	✓	✓	33,000	33K	✓	✓	
35	R35	✓	✱	✓	900	900	✓	✓	✱	35,000	35K	✓	✓	
39	R39	✓	✓	✱	1,000	1K0	✓	✓	✓	40,000	40K	✓	✓	
40	R40	✓	✓	✓	1,100	1K1	✓	✓	✓	50,000	50K	✓	✓	
47	R47	✓	✓	✱	1,200	1K2	✓	✓	✓					
50	R50	✓	✓	✓	1,500	1K5	✓	✓	✓					
56	R56	✓	✓	✓	1,800	1K8	✓	✓	✓					
62	R62	✓	✓	✓	2,000	2K0	✓	✓	✓					

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

✓ = Standard values
✱ = Non-standard values subject to minimum handling charge per item

40 Series Ohmicone® Silicone Ceramic Conformal Axial Term. Wirewound

Non-Inductive Winding optional (blank= std. winding)

RoHS Compliant

41NR10E-T — Tape & reel optional pc/reel:

Wattage	Tolerance	Resistance	
1 = 1W	F = 1%	R10 = 0.10Ω	41: 5000
2	J = 5%	1R0 = 1.0Ω	42: 1250
3		10R = 10.0Ω	43: 1250
5		250 = 250Ω	45: 1000
7		1K0 = 1,000Ω	47: 500
0 = 10W		4K5 = 4,500Ω	40: 500
		50K = 50,000Ω	

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9