BURR-BROWN®



ADS1286

12-Bit Micro Power Sampling ANALOG-TO-DIGITAL CONVERTER

FEATURES

- SERIAL INTERFACE
- GUARANTEED NO MISSING CODES
- 20kHz SAMPLING RATE
- LOW SUPPLY CURRENT: 250µA

APPLICATIONS

- REMOTE DATA ACQUISITION
- ISOLATED DATA ACQUISITION
- TRANSDUCER INTERFACE
- BATTERY OPERATED SYSTEMS

DESCRIPTION

The ADS1286 is a 12-bit, 20kHz analog-to-digital converter with a differential input and sample and hold amplifier and consumes only 250µA of supply current. The ADS1286 offers an SPI and SSI compatible serial interface for communications over a two or three wire interface. The combination of a serial two wire interface and micropower consumption makes the ADS1286 ideal for remote applications and for those requiring isolation.

The ADS1286 is available in a 8-pin plastic mini DIP and a 8-lead SOIC.



International Airport Industrial Park • Mailing Address: PO Box 11400, Tucson, AZ 85734 • Street Address: 6730 S. Tucson Blvd., Tucson, AZ 85706 • Tel: (520) 746-1111
Twx: 910-952-1111 • Internet: http://www.burr-brown.com/ • Cable: BBRCORP • Telex: 066-6491 • FAX: (520) 889-1510 • Immediate Product Info: (800) 548-6132

©1996 Burr-Brown Corporation

Printed in U.S.A. October, 1998

SPECIFICATIONS

At $T_A = T_{MIN}$ to T_{MAX}, $+V_{CC} = +5V$, $V_{REF} = +5V$, $f_{SAMPLE} = 12.5kHz$, , $f_{CLK} = 16 \bullet f_{SAMPLE}$, unless otherwise specified.

PARAMETER	CONDITIONS	ADS1286, ADS1286A			ADS1286K, ADS1286B			ADS1286C, ADS1286L			UNITS
		MIN	TYP	MAX	MIN	TYP	MAX	MIN	TYP	MAX	
ANALOG INPUT											
Full-Scale Input Range	+In – (–In)	0		V_{REF}	*		*	*		*	V
Absolute Input Voltage	+In	–0.2		V_{CC} +0.2	*		*	*		*	V
	–In	–0.2		+0.2	*		*	*		*	V
Capacitance			25			*			*		pF
Leakage Current			±1			*			*		µA
SYSTEM PERFORMANCE											
Resolution			12			*			*		Bits
No Missing Codes		12			*			*			Bits
Integral Linearity			±1	±2		*	*		±0.5	±1	LSB
Differential Linearity			±0.5	±1.0		*	±0.75		±0.25	±0.75	LSB
Offset Error			0.75	±3		*	*		*	*	LSB
Gain Error			±2	±8		*	*		*	*	LSB
Noise			50			*			*		µVrms
Power Supply Rejection			82			*			*		dB
SAMPLING DYNAMICS											
Conversion Time				12			*			*	Clk Cycles
Acquisition Time		1.5			*			*			Clk Cycles
Small Signal Bandwidth			500			*			*		kHz
DYNAMIC CHARACTERISTICS											
Total Harmonic Distortion	V_{IN} = 5.0Vp-p at 1kHz		–85			*			*		dB
	V_{IN} = 5.0Vp-p at 5kHz		–83			*			*		dB
SINAD	V_{IN} = 5.0Vp-p at 1kHz		72			*			*		dB
Spurious Free Dynamic Range	V_{IN} = 5.0Vp-p at 1kHz		90			*			*		dB
REFERENCE INPUT											
REF Input Range		1.25	2.5	V_{CC}+0.05V	*	*	*	*	*	*	V
Input Resistance	$\overline{CS}$ = V_{CC}		5000			*			*		MΩ
	$\overline{CS}$ = GND, f_{CLK} = 0Hz		5000			*			*		MΩ
Current Drain	$\overline{CS}$ = V_{CC}		0.01	2.5		*	*		*	*	µA
	$t_{CYC} \geq 640\mu s$, $f_{CLK} \leq 25kHz$		2.4	20		*	*		*	*	µA
	$t_{CYC} = 80\mu s$, $f_{CLK} = 200kHz$		2.4	20		*	*		*	*	µA
DIGITAL INPUT/OUTPUT											
Logic Family			CMOS			*			*		
Logic Levels:											
V_{IH}	I_{IH} = +5µA	3		$+V_{CC}$	*		*	*		*	V
V_{IL}	I_{IL} = +5µA	0.0		0.8	*		*	*		*	V
V_{OH}	I_{OH} = 250µA	3		$+V_{CC}$	*		*	*		*	V
V_{OL}	I_{OL} = 250µA	0.0		0.4	*		*	*		*	V
Data Format			Straight Binary			*			*		
POWER SUPPLY REQUIREMENTS											
Power Supply Voltage V_{CC}		+4.50	5	5.25	*	*	*	*	*	*	V
Quiescent Current, V_{ANA}	$t_{CYC} \geq 640\mu S$, $f_{CLK} \leq 25kHz$		200	400		*	*		*	*	µA
	$t_{CYC} = 90\mu S$, $f_{CLK} = 200kHz$		250	500		*	*		*	*	µA
Power Down	$\overline{CS}$ = V_{CC}			3			*			*	µA
TEMPERATURE RANGE											
Specified Performance	ADS1286, K, L	0		+70	*		*	*		*	°C
	ADS1286A, B, C	–40		+85	*		*	*		*	°C

* Specifications same as grade to the left.

TIMING CHARACTERISTICS

f_{CLK} = 200kHz, $T_A = T_{MIN}$ to T_{MAX}.

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNITS
t_{SMPL}	Analog Input Sample Time	See Operating Sequence	1.5		2.0	Clk Cycles
$t_{SMPL\ (MAX)}$	Maximum Sampling Frequency	ADS1286			20	kHz
t_{CONV}	Conversion Time	See Operating Sequence		12		Clk Cycles
t_{dDO}	Delay TIme, DCLOCK↓ to D_{OUT} Data Valid	See Test Circuits		85	150	ns
t_{dis}	Delay TIme, $\overline{CS}$↑ to D_{OUT} Hi-Z	See Test Circuits		25	50	ns
t_{en}	Delay TIme, DCLOCK↓ to D_{OUT} Enable	See Test Circuits		50	100	ns
t_{hDO}	Output Data Remains Valid After DCLOCK↓	C_{LOAD} = 100pF	15	30		ns
t_f	D_{OUT} Fall Time	See Test Circuits		70	100	ns
t_r	D_{OUT} Rise Time	See Test Circuits		60	100	ns
t_{CSD}	Delay Time, $\overline{CS}$↓ to DCLOCK↓	See Operating Sequence			0	ns
t_{SUCS}	Delay Time, $\overline{CS}$↓ to DCLOCK↑	See Operating Sequence	30			ns

ABSOLUTE MAXIMUM RATINGS[1]

$+V_{CC}$	+6V
Analog Input	–0.3V to ($+V_{CC}$ + 300mV)
Logic Input	–0.3V to ($+V_{CC}$ + 300mV)
Case Temperature	+100°C
Junction Temperature	+150°C
Storage Temperature	+125°C
External Reference Voltage	+5.5V

NOTE: (1) Stresses above these ratings may permanently damage the device.

PIN CONFIGURATION



8-Pin Mini PDIP
8-Lead SOIC

ELECTROSTATIC DISCHARGE SENSITIVITY

Electrostatic discharge can cause damage ranging from performance degradation to complete device failure. Burr-Brown Corporation recommends that all integrated circuits be handled and stored using appropriate ESD protection methods.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet published specifications.

PIN ASSIGNMENTS

PIN	NAME	DESCRIPTION
1	V_{REF}	Reference Input.
2	+In	Non Inverting Input.
3	–In	Inverting Input. Connect to ground or remote ground sense point.
4	GND	Ground.
5	$\overline{CS}$/SHDN	Chip Select when low, Shutdown Mode when high.
6	D_{OUT}	The serial output data word is comprised of 12 bits of data. In operation the data is valid on the falling edge of DCLOCK. The second clock pulse after the falling edge of $\overline{CS}$ enables the serial output. After one null bit the data is valid for the next 12 edges.
7	DCLOCK	Data Clock synchronizes the serial data transfer and determines conversion speed.
8	$+V_{CC}$	Power Supply.

PACKAGE/ORDERING INFORMATION

PRODUCT	INTEGRAL LINEARITY	TEMPERATURE RANGE	PACKAGE	PACKAGE DRAWING NUMBER[1]
ADS1286P	±2	0°C to +70°C	Plastic DIP	006
ADS1286PK	±2	0°C to +70°C	Plastic DIP	006
ADS1286PL	±1	0°C to +70°C	Plastic DIP	006
ADS1286U	±2	0°C to +70°C	SOIC	182
ADS1286UK	±2	0°C to +70°C	SOIC	182
ADS1286UL	±1	0°C to +70°C	SOIC	182
ADS1286PA	±2	–40°C to +85°C	Plastic DIP	006
ADS1286PB	±2	–40°C to +85°C	Plastic DIP	006
ADS1286PC	±1	–40°C to +85°C	Plastic DIP	006
ADS1286UA	±2	–40°C to +85°C	SOIC	182
ADS1286UB	±2	–40°C to +85°C	SOIC	182
ADS1286UC	±1	–40°C to +85°C	SOIC	182

NOTE: (1) For detailed drawing and dimension table, please see end of data sheet, or Appendix C of Burr-Brown IC Data Book.

The information provided herein is believed to be reliable; however, BURR-BROWN assumes no responsibility for inaccuracies or omissions. BURR-BROWN assumes no responsibility for the use of this information, and all use of such information shall be entirely at the user's own risk. Prices and specifications are subject to change without notice. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. BURR-BROWN does not authorize or warrant any BURR-BROWN product for use in life support devices and/or systems.

TYPICAL PERFORMANCE CURVES

At T_A = +25, V_{CC} = +5V, V_{REF} = +5V, f_{SAMPLE} = 12.5kHz, f_{CLK} = 16 • f_{SAMPLE}, unless otherwise specified.

REFERENCE CURRENT vs SAMPLE RATE



REFERENCE CURRENT vs TEMPERATURE



CHANGE IN OFFSET vs REFERENCE VOLTAGE



CHANGE IN OFFSET vs TEMPERATURE



CHANGE IN INTEGRAL LINEARITY AND DIFFERENTIAL LINEARITY vs REFERENCE VOLTAGE



CHANGE IN GAIN vs REFERENCE VOLTAGE



TYPICAL PERFORMANCE CURVES (CONT)

At T_A = +25, V_{CC} = +5V, V_{REF} = +5V, f_{SAMPLE} = 12.5kHz, f_{CLK} = 16 • f_{SAMPLE}, unless otherwise specified.

EFFECTIVE NUMBER OF BITS
vs REFERENCE VOLTAGE



DIFFERENTIAL LINEARITY ERROR vs CODE



SIGNAL-TO-(NOISE + DISTORTION)
vs FREQUENCY



SPURIOUS FREE DYNAMIC RANGE
AND SIGNAL-TO-NOISE RATIO vs FREQUENCY



SIGNAL-TO-(NOISE + DISTORTION) vs INPUT LEVEL



TOTAL HARMONIC DISTORTION vs FREQUENCY



TYPICAL PERFORMANCE CURVES (CONT)

At T_A = +25, V_{CC} = +5V, V_{REF} = +5V, f_{SAMPLE} = 12.5kHz, f_{CLK} = 16 • f_{SAMPLE}, unless otherwise specified.

4096 POINT FFT



PEAK-TO-PEAK NOISE vs REFERENCE VOLTAGE



POWER SUPPLY REJECTION vs RIPPLE FREQUENCY



CHANGE GAIN vs TEMPERATURE



POWER DOWN SUPPLY CURRENT
vs TEMPERATURE



SUPPLY CURRENT vs TEMPERATURE



TYPICAL PERFORMANCE CURVES (CONT)

At T_A = +25, V_{CC} = +5V, V_{REF} = +5V, f_{SAMPLE} = 12.5kHz, f_{CLK} = 16 • f_{SAMPLE}, unless otherwise specified.

INTEGRAL LINEARITY ERROR vs CODE



DIGITAL INPUT LINE THRESHOLD vs SUPPLY VOLTAGE



INPUT LEAKAGE CURRENT vs TEMPERATURE



TIMING DIAGRAMS AND TEST CIRCUITS



Load Circuit for t_{dDO}, t_r, and t_f



Voltage Waveforms for D_{OUT} Rise and Fall Times t_r, and t_f



Voltage Waveforms for D_{OUT} Delay Times, t_{dDO}



Load Circuit for t_{dis} and t_{den}



Voltage Waveforms for t_{dis}



Voltage Waveforms for t_{en}

NOTES: (1) Waveform 1 is for an output with internal conditions such that the output is HIGH unless disabled by the output control. (2) Waveform 2 is for an output with internal conditions such that the output is LOW unless disabled by the output control.



FIGURE 1. ADS1286 Operating Sequence.

SERIAL INTERFACE

The ADS1286 communicates with microprocessors and other external digital systems via a synchronous 3-wire serial interface. DCLOCK synchronizes the data transfer with each bit being transmitted on the falling DCLOCK edge and captured on the rising DCLOCK edge in the receiving system. A falling $\overline{CS}$ initiates data transfer as shown in Figure 1. After $\overline{CS}$ falls, the second DCLOCK pulse enables D_{OUT}. After one null bit, the A/D conversion result is output on the D_{OUT} line. Bringing $\overline{CS}$ high resets the ADS1286 for the next data exchange.

MICROPOWER OPERATION

With typical operating currents of 250µA and automatic shutdown between conversions, the ADS1286 achieves extremely low power consumption over a wide range of sample rates (see Figure 2). The auto-shutdown allows the supply current to drop with sample rate.

SHUTDOWN

The ADS1286 is equipped with automatic shutdown features. The device draws power when the $\overline{CS}$ pin is LOW and shuts down completely when the pin is HIGH. The bias circuit and comparator powers down and the reference input becomes high impedance at the end of each conversion leaving the DCLOCK running to clock out the LSB first data or zeroes. If the $\overline{CS}$ input is not running rail-to-rail, the input logic buffer will draw current. This current may be large compared to the typical supply current. To obtain the lowest supply current, bring the $\overline{CS}$ pin to ground when it is low and to supply voltage when it is high.



FIGURE 2. Automatic Power Shutdown Between Conversions Allows Power Consumption to Drop with Sample Rate.

MINIMIZING POWER DISSIPATION

In systems that have significant time between conversions, the lowest power drain will occur with the minimum $\overline{CS}$ LOW time. Bringing $\overline{CS}$ LOW, transferring data as quickly as possible, and then bringing it back HIGH will result in the lowest current drain. This minimizes the amount of time the device draws power. After a conversion the A/D automatically shuts down even if $\overline{CS}$ is held LOW. If the clock is left running to clock out LSB-data or zero, the logic will draw a small amount of current (see Figure 3).



FIGURE 3. Shutdown Current with $\overline{CS}$ HIGH is Lower than with $\overline{CS}$ LOW.

RC INPUT FILTERING

It is possible to filter the inputs with an RC network as shown in Figure 4. For large values of C_{FILTER} (e.g., 1µF), the capacitive input switching currents are averaged into a net DC current. Therefore, a filter should be chosen with a small resistor and large capacitor to prevent DC drops across the resistor. The magnitude of the DC current is approximately $I_{DC} = 20pF \times V_{IN}/t_{CYC}$ and is roughly proportional to V_{IN}. When running at the minimum cycle time of 64µs, the input current equals 1.56µA at V_{IN} = 5V. In this case, a filter resistor of 75Ω will cause 0.1LSB of full-scale error. If a larger filter resistor must be used, errors can be eliminated by increasing the cycle time.



FIGURE 4. RC Input Filtering.

REDUCED REFERENCE OPERATION

The effective resolution of the ADS1286 can be increased by reducing the input span of the converter. The ADS1286 exhibits good linearity and gain over a wide range of reference voltages (see Typical Performance Curves " Change in Linearity vs Reference Voltage" and "Change in Gain vs Reference Voltage"). However, care must be taken when operating at low values of V_{REF} because of the reduced LSB size and the resulting higher accuracy requirement placed on the converter. The following factors must be considered when operating at low V_{REF} values:

1. Offset
2. Noise

OFFSET WITH REDUCED V_{REF}

The offset of the ADS1286 has a larger effect on the output code. When the ADC is operated with reduced reference voltage. The offset (which is typically a fixed voltage) becomes a larger fraction of an LSB as the size of the LSB is reduced. The Typical Performance Curve "Change in Offset vs Reference Voltage" shows how offset in LSBs is related to reference voltage for a typical value of V_{OS}. For example, a V_{OS} of 122µV which is 0.1 LSB with a 5V reference becomes 0.5LSB with a 1V reference and 2.5LSBs with a 0.2V reference. If this offset is unacceptable, it can be corrected digitally by the receiving system or by offsetting the negative input of the ADS1286.

NOISE WITH REDUCED V_{REF}

The total input referred noise of the ADS1286 can be reduced to approximately 200µV peak-to-peak using a ground plane, good bypassing, good layout techniques and minimizing noise on the reference inputs. This noise is insignificant with a 5V reference but will become a larger fraction of an LSB as the size of the LSB is reduced.

For operation with a 5V reference, the 200µV noise is only 0.15LSB peak-to-peak. In this case, the ADS1286 noise will contribute virtually no uncertainty to the output code. However, for reduced references, the noise may become a significant fraction of an LSB and cause undesirable jitter in the output code. For example, with a 2.5V reference this same 200µV noise is 0.3LSB peak-to-peak. If the reference is further reduced to 1V, the 200µV noise becomes equal to 0.8LSBs and a stable code may be difficult to achieve. In this case averaging multiple readings may be necessary.



FIGURE 5. Thermocouple Application Using a MUX to Scale the Input Range of the ADS1286.



FIGURE 6. ADS1286 with RTD Sensor.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9