




**SERIES GP**

**SERIES TR**

## GP/ML/TR Design Features

Among the advances AGASTAT control relays offer over existing designs is a unique contact operating mechanism. An articulated arm assembly amplifies the movement of the solenoid core, allowing the use of a short stroke coil to produce an extremely wide contact gap. The long support arms used in conventional relays are eliminated. Both current capacity and shock/vibration tolerance are greatly increased, as well as life expectancy.

## Design/Construction

AGASTAT control relays are operated by a moving core electromagnet whose main gap is at the center of the coil. A shoe is fitted to the core which overlaps the yoke and further increases the magnetic attraction.

The coil itself is in the form of an elongated cylinder, which provides a low mean turn length and also assists heat dissipation. Since the maximum travel of the electromagnet does not provide optimum contacts movement, an ingenious amplifying device has been designed.

This consists of a W-shaped mechanism, shown in figure 1. When the center of the W is moved vertically the lower extremities move closer to each other as can be seen in the illustration. The center of the W mechanism is connected to the moving core of the electromagnet and the two lower points are connected to the moving contacts.

Two of these mechanisms are placed side-by-side to actuate the four contacts sets of the relay. The outer arms of the W mechanisms are leaf springs, manufactured from a flat piece of non-ferrous metal. These outer arms act as return springs for their corresponding contacts. This provides each contact with its own separate return spring, making the contacts independent.

The mechanical amplification of the motion of the electromagnet permits a greater distance between the contacts, while the high efficiency of the electromagnet provides a nominal contact force in excess of 100 grams on the normally open contacts.


All the contacts are positioned well away from the cover and are well ventilated and separated from each other by insulating walls.

The absence of metal-to-metal friction, the symmetrical design of the contact arrangement and the lack of heavy impacts provides a mechanical life of 100,000,000 operations.

For use in AC circuits, the relay is supplied with a built-in rectification circuit, thus retaining the high DC efficiency of the electromagnet. The current peak on energizing is also eliminated and consequently the relay can operate with a resistance in series (e.g. for high voltages or for drop-out by shorting the coil). The use of the rectification circuit offers still other advantages. The same model can operate at frequencies ranging from 40 to 400 cycles. Operation of the relay is crisp; even with a low AC voltage, there is a complete absence of hum and vibration.

The plastic dust cover has two windows through which the iron yoke protrudes to facilitate cooling and also to allow direct mounting arrangement of the relay irrespective of the terminals.

**Figure 1 – Illustration of Amplification**



**This diagram illustrates amplification obtained by the articulated operating mechanism.**

**NOTE: Seismic & radiation tested EGP, EML and ETR models are available. Consult factory for detailed information.**

Dimensions are shown for reference purposes only.

Dimensions are in inches over (millimeters) unless otherwise specified.

# GP/ML/TR series

## 10 Amp Control Relay Non-latching, Latching & Timing Versions

UL File E15631

CS File LR29186

Users should thoroughly review the technical data before selecting a product part number. It is recommended that users also seek out the pertinent approvals files of the agencies/laboratories and review them to ensure the product meets the requirements for a given application.

## Features

- Occupies very small panel space
- May be mounted singly, in continuous rows or in groups.
- Available with screw terminal molded socket.
- 4 SPDT contacts.
- Magnetic blowout device option increases DC current carrying ability approximately ten times for both N.O. and N.C. contacts. In both AC and DC operation, the addition of the device will normally double the contact life, due to reduced arcing.

## GP/ML Contact Data @ 25°C

**Arrangements:** 4 Form C (4PDT)

**Material:** Silver plated.

**Ratings:** See chart.


**Expected Life: Mechanical:** 100 million operations.

**Electrical:** See chart and graph.

## Contact Ratings and Expected Life

| Voltage | Current (Amps) | Power Factor or Time Constant | Number of Electrical Operations | Remarks                |
|---------|----------------|-------------------------------|---------------------------------|------------------------|
| 540 VAC | 3              | COS Ø = 0.5                   | 15,000                          | 2 contacts in series   |
| 380 VAC | 15             | Resistive                     | 10,000                          | 2 contacts in parallel |
| 380 VAC | 10             | Resistive                     | 200,000                         |                        |
| 380 VAC | 3 x 3.3        | COS Ø = 0.8                   | 200,000                         | 3hp motor              |
| 220 VAC | 20             | Resistive                     | 20,000                          | 2 contacts in parallel |
| 220 VAC | 15             | COS Ø = 0.5                   | 20,000                          | 2 contacts in parallel |
| 220 VAC | 10             | Resistive                     | 400,000                         |                        |
| 220 VAC | 3 x 6          | COS Ø = 0.8                   | 200,000                         | 3hp motor              |
| 220 VAC | 5              |                               | 1,500,000                       | Filament lamps         |
| 220 VAC | 5              | Resistive                     | 3,000,000                       |                        |
| 220 VAC | 2.5            | COS Ø = 0.25                  | 2,000,000                       |                        |
| 220 VAC | 2              | Resistive                     | 15,000,000                      |                        |
| 220 VAC | 1.25           | Resistive                     | 30,000,000                      |                        |
| 120 VDC | 1.5            | Resistive                     | 20,000,000                      | with blow-out device   |
| 48 VDC  | 10             | Resistive                     | 1,000,000                       |                        |

## Load Life Curve



Specifications and availability subject to change.

www.tycoelectronics.com  
Technical support:  
Refer to inside back cover.

## Initial Dielectric Strength

**Between non-connected terminals:** 2,000V rms, 60 Hz.  
**Between non-connected terminals & relay yoke:** 2,000V rms, 60 Hz.

## Initial Insulation Resistance

**Between non-connected terminals:**  $10^9$  ohms at 500VDC.  
**Between non-connected terminals & relay yoke:**  $10^9$  ohms at 500VDC.

## Coil Data

**Voltage:** 24, 120 & 220VAC, 60 Hz. Add series resistor for 380-440VDC;  
12, 24, 48, 125 & 250VDC.

**Duty Cycle:** Continuous.

**Nominal Coil Power:** 6VA for AC coils; 6W for DC coils.  
There is no surge current during operation.

## Coil Operating Voltage

|                                    | DC   |    |    |     |     | AC, 50/60Hz |     |     |
|------------------------------------|------|----|----|-----|-----|-------------|-----|-----|
| Nominal Coil Voltage               | 12   | 24 | 48 | 125 | 250 | 24          | 120 | 220 |
| Minimum Pick-up Voltage at 20°C    | 9    | 18 | 36 | 94  | 187 | 19          | 92  | 175 |
| Minimum Pick-up Voltage at 40°C    | 9.5  | 19 | 38 | 100 | 200 | 20          | 102 | 188 |
| Maximum voltage for continuous use | 13.5 | 27 | 53 | 143 | 275 | 27          | 137 | 245 |

For 380VAC – Use 6800 ohms 4 watt resistor in series with 220VAC relay.  
For 440VAC – Use 8200 ohms 6 watt resistor in series with 220VAC relay.

Drop-out voltage is between 10% and 40% of the nominal voltages for both DC and AC (For example: in a 120 VAC unit, drop-out will occur between 12 and 48 volts.) DC relays will function with unfiltered DC from a full-wave bridge rectifier.

## Operate Data @ 20°C

**Operate Time at Rated Voltage:** Between energizing and opening of normally closed contacts, less than 18 milliseconds on AC and less than 15 milliseconds on DC.

**Release Time:** Between energizing and closing of normally open contacts, less than 35 milliseconds on AC and less than 30 milliseconds on DC. Between de-energizing and opening of normally open contacts, less than 70 milliseconds on AC and less than 8 milliseconds on DC. Between de-energizing and closing of normally closed contacts, less than 85 milliseconds on AC and less than 25 milliseconds on DC.

## Environmental Data

**Operating Temperature Range:** 0°C to +60°C.

**Vibration:** Single axis fragility curve data are available on request at frequencies from 5 Hz. to 33 Hz.

**Shock:** The relay, when kept energized by means of one of its own contact sets, will withstand 40g shock load when operating on DC, and 150g shock load on AC.

## Mechanical Data

**Mounting Terminals:** 16 flat base pins. Screw terminal sockets are available.

**Wire Connection:** The 16 flat pins are arranged in four symmetrical rows of four pins; the pitch in both directions being .394". Connection may be made to the relay by soldering. Sockets are available with screw terminals.

The internal wiring of the relay is also symmetrical as shown in the adjacent figure, allowing the relay to be inserted into the socket in either of two positions. Terminals B2 and B3 are provided as extra connections for special applications.

**Weight:** 10.9 oz. (308g) approximately.

## Ordering Information

Typical Part No. ➤

**GP**

**I**

**N**

### 1. Basic Series:

GP = Non-latching Control Relay      ML = Magnetic Latching Control Relay

### 2. Coil Voltage:

A = 12VDC      G = 24VAC, 60 Hz.  
B = 24VDC      I = 120VAC, 60 Hz.  
C = 48VDC      J = 220VAC, 60 Hz.  
D = 125VDC  
F = 250VDC


### 3. Options:

N = Magnetic Blow-out Device  
Q = Light to indicate coil energization (GP only. 120VAC, 125VDC, 220VAC and 250VDC voltages only.)  
R = Internal diode to suppress coil de-energization transient. (GP only. When used on DC unit, relay release time increases to same value as AC unit).


**Our authorized distributors are more likely to maintain the following items in stock for immediate delivery..**

GPD  
GPDN

## Outline Dimensions



## Wiring Diagrams (Bottom Views)



# TR series

## 10 Amp Control Relay – Timing Version

### TR Features

- 8 timing ranges.
- 4 SPDT contacts.
- Magnetic blowout device option increases DC current carrying ability approximately ten times for both N.O. and N.C. contacts. In both AC and DC operation, the addition of the device will normally double the contact life, due to reduced arcing.

### TR Design/Construction

Couples an advanced electromechanical design with a field-proven solid-state timing network, an adaptation of the circuit used in the AGASTAT premium grade SSC Timer.

This unique circuit also eliminates the need for supplementary temperature-compensation components, affording unusual stability over a realistically broad operating temperature range. It also provides transient protection and protection against premature switching of the output contacts due to power interruption during timing.

### Timing Specifications

**Operating Mode:** On-Delay (Delay on energization).

**Timing Adjustment:** Internal fixed or internal potentiometer.

**Timing Ranges:**

|                |                |
|----------------|----------------|
| .15 to 3 sec.  | 4 to 120 sec.  |
| .55 to 15 sec. | 10 to 300 sec. |
| 1 to 30 sec.   | 1 to 30 min.   |
| 2 to 60 sec.   | 2 to 60 min.   |

**Accuracy:**

**Repeat:** ±2% as fixed temperature and voltage.

**Overall:** ±5% over combined rated extremes of temperature and voltage.

**Reset Time:** 75ms.

### Contact Data @ 25°C

**Arrangements:** 4 Form C (4PDT)

**Nominal Rating:** 10A @ 120VAC.

**Contact Pressure:**

**Between movable and normally closed contacts:** 30 g, typical.

**Between movable and normally open contacts:** 100 g, typical.


**Expected Life: Mechanical:** 100 million operations.

**Electrical:** See load/life graph.

### Initial Dielectric Strength

**Between terminals and case and between mutually-isolated contacts:** 2,000VAC.

### Load Life Curve



### Initial Insulation Resistance

**Between non-connected terminals:**  $10^9$  ohms at 500VDC.

**Between non-connected terminals & relay yoke:**  $10^9$  ohms at 500VDC.

### Coil Data

**Voltage:** 120VAC, 50-60 Hz.; 24 & 125VDC.

### Transient Protection

1,500 volt transient of less than 100 microseconds, or 1,000 volts or less.

### Environmental Data

**Operating Temperature Range:** 0°C to +50°C.

### Mechanical Data

**Mounting Terminals:** 16 flat base pins. Screw terminal sockets are available.

**Weight:** 11 oz. (311g) approximately.

### Ordering Information

Typical Part No. ➤

TR 1 4 B 1 A N

#### 1. Basic Series:

TR = Timing control relay

#### 2. Operation:

1 = On-delay

#### 3. Output:

4 = 4PDT (4 form C)

#### 4. Operating Voltage:

B = 24VDC D = 215VDC I = 120VAC, 50/60 Hz.

#### 5. Timing Adjustment:

1 = Internal fixed. 3 = Internal potentiometer.


#### 6. Timing Range:

A = .15 to 3 sec. C = 1 to 30 sec. E = 4 to 120 sec. I = 2 to 60 min.  
B = .55 to 15 sec. D = 2 to 60 sec. G = 10 to 300 sec. N = 1 to 30 min.

#### 7. Options:

N = Magnetic blow-out device.

### Wiring Diagram (Bottom View)



### Outline Dimensions


Same as GP/MR. See previous page.

**Our authorized distributors are more likely to maintain the following items in stock for immediate delivery..**

None at present.




## Accessories for GP/ML/TR series control relays

### Front connected sockets






**Cat. No. CR0001**  
With captive clamp terminals



**Cat. No. CR0002**  
With (#6) binding head screws




**Cat. No. CR0095**  
With (#6) screw terminals





**Cat. No. CR0067**  
With (#6) screw terminals





### Hold down (locking) springs




**Cat. No. CR0069**  
For socket: CR0067




**Cat. No. CR0070**  
For socket: CR0095




**Cat. No. CR0111**  
For sockets: CR0001 & CR0002



### Heavy-duty hold down (locking) straps




**\*Cat. No. CR0133**  
For socket: CR0001 & CR0002



**\*Cat. No. CR0155**  
For socket: CR0095


\* Catalog number includes strap, strap plate and necessary brackets.

### Magnetic blowout device



**Cat. No. CR0190**  
Reduces arcing on the relay contacts when they make or break contact, either upon energizing or de-energizing, resulting in less contact degradation. Extends the life of the contact.

### Extracting handle



**Cat. No. CR0179**  
Used to remove GP, ML and TR units from mounting bases.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## TE Connectivity:

[MLDN](#) [GPANR](#) [GPBN](#) [GPDQR](#) [GPVN](#) [GPCNC778](#) [TR14D3G](#) [TR14D3BN](#) [TR14I3C](#) [TR14D3DN](#) [MLI](#) [GPB](#)  
[GPC](#) [GPCN](#) [GPDN](#) [GPDNC756](#) [GPDR](#) [GPIQ](#) [GPFNC777](#)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9