



#### FEATURES

Small Size - Low Cost

#### APPLICATIONS

Filtering - Bypass - Coupling - Blocking

<b>Operating Temperature Range</b>		<b>-40°C to +85°C</b>										
<b>Capacitance Tolerance</b>		<b>+20% at 120 Hz, 20°C</b>										
<b>Surge voltage</b>	<b>WVDC</b>	<b>4</b>	<b>6.3</b>	<b>10</b>	<b>16</b>	<b>25</b>	<b>35</b>	<b>50</b>	<b>63</b>	<b>100</b>		
	<b>SVDC</b>	5.2	7.9	13	20	32	44	63	79	125		
<b>Dissipation Factor</b>	<b>WVDC</b>	<b>4</b>	<b>6.3</b>	<b>10</b>	<b>16</b>	<b>25</b>	<b>35</b>	<b>50</b>	<b>63</b>	<b>100</b>		
	<b>tan δ</b>	.35	.28	.24	.2	.16	.14	.12	.12	.1		
<b>Leakage current</b>		<b>2 Minutes</b>										
		.01CV or 3uA, Whichever is greater										
<b>Low temperature stability Impedance ratio (120 Hz)</b>	<b>Rated WVDC</b>		<b>4</b>	<b>6.3</b>	<b>10</b>	<b>16</b>	<b>25</b>	<b>35</b>	<b>50</b>	<b>63</b>	<b>100</b>	
	<b>-25°C to +20°C</b>	<b>D&lt;8</b>	7	4	3	2	2	2	2	2	2	
		<b>D≥8</b>	7	5	4	3	2	2	2	2	2	
	<b>-40°C to +20°C</b>	<b>D&lt;8</b>	15	8	6	4	4	3	3	3	3	
<b>D≥8</b>		15	10	8	6	4	3	3	3	3		
<b>Load Life</b>		<b>2000 hours at 85°C with rated WVDC and ripple current applied</b>										
		<b>Capacitance change</b>	≤20% of initial measured value									
		<b>Dissipation factor</b>	≤200% of maximum specified value									
		<b>Leakage current</b>	≤100% of maximum specified value									
<b>Shelf Life</b>		<b>1000 hours at 85°C with no voltage applied</b>										
		<b>Capacitance change</b>	≤20% of initial measured value									
		<b>Dissipation factor</b>	≤200% of maximum specified value									
		<b>Leakage current</b>	≤100% of maximum specified value									
<b>Resistance to soldering heat</b>		<b>Capacitors placed on a 250C hot plate for 30 seconds with their electrode terminations facing downward will fulfill the following conditions after being cooled to room temperature</b>										
		<b>Capacitance change</b>	≤10% of initial measured value									
		<b>Dissipation factor</b>	≤200% of maximum specified value									
		<b>Leakage current</b>	≤100% of maximum specified value									
<b>Ripple Current Multipliers</b>		<b>Frequency (Hz)</b>					<b>Temperature (°C)</b>					
		<b>50</b>	<b>120</b>	<b>400</b>	<b>1k</b>	<b>10k</b>	<b>100k</b>	<b>85</b>	<b>70</b>	<b>65</b>		
		0.7	1.0	1.17	1.36	1.5	1.5	1.0	1.35	1.35		



D	L	W±0.2	H±0.2	C±0.2	R	LL±0.2	S±0.2
4	5.4 +0.1/-0.2	4.3	4.3	5.0	0.5~0.8	1.8	1.0
5	5.4 +0.1/-0.2	5.3	5.3	6.0	0.5~0.8	2.1	1.4
6.3	5.4 +0.1/-0.2	6.6	6.6	7.3	0.5~0.8	2.4	2.2
6.3	5.8 +0.1/-0.2	6.6	6.6	7.3	0.5~0.8	2.4	2.2
6.3	7.7 +0.1/-0.2	6.6	6.6	7.3	0.5~0.8	2.4	2.2
8	6.2 +0.1/-0.2	8.3	8.3	9.0	0.7~1.0	2.4	3.2
8	10.2+0.1/-0.2	8.3	8.3	9.0	0.7~1.0	2.8	3.2
10	10.2+0.1/-0.2	10	10	11.0	0.7~1.0	3.2	4.6

# SML

+85°C Standard, 2000 hrs

WVDC	Capacitance (µF)	IC PART NUMBER	Maximum ESR (Ω) 120 Hz, +20°C	Maximum RMS Ripple Current (mA) 120 Hz, +85°C	Dims DxL (mm)
4	33	336SML004M	17.58	31	4x5.4
4	47	476SML004M	12.35	37	4x5.4
4	100	107SML004M	5.83	63	5x5.4
4	150	157SML004M	3.868	84	6.3x5.4
4	220	227SML004M	2.64	110	6.3x5.4
4	470	477SML004M	1.24	150	6.3x7.7
4	1000	108SML004MD8	0.58	300	8x10.5
6.3	22	226SML6R3M	21.1	31	4x5.4
6.3	47	476SML6R3MD4	9.877	40	4x5.4
6.3	47	476SML6R3M	9.877	52	5x5.4
6.3	68	686SML6R3M	6.826	50	5x5.4
6.3	100	107SML6R3M	4.642	54	5x5.4
6.3	220	227SML6R3M	2.11	91	6.3x5.8
6.3	330	337SML6R3M	1.407	188	6.3x7.7
6.3	330	337SML6R3MD8	1.407	190	8x6.2
6.3	470	477SML6R3M	0.9877	380	8x10.5
6.3	1000	108SML6R3M	0.464	370	8x10.5
6.3	1500	158SML6R3M	0.3095	750	10x10.5
10	33	336SML010MD4	12.057	34	4x5.4
10	33	336SML010M	12.057	48	5x5.4
10	150	157SML010M	2.653	88	6.3x5.4
10	220	227SML010M	1.8086	250	8x6.5
10	470	477SML010MD8	0.8466	390	8x10.5
10	1000	108SML010M	0.398	580	10x10.5
16	10	106SML016M	33.16	26	4x5.4
16	22	226SML016MD4	12.057	30	4x5.4
16	22	226SML016M	12.057	44	5x5.4
16	47	476SML016MD5	7.055	52	5x5.4
16	47	476SML016M	7.055	75	6.3x5.4
16	68	686SML016M	4.876	78	6.3x5.4
16	100	107SML016M	3.316	103	6.3x5.4
16	150	157SML016M	2.21	135	6.3x7.7
16	220	227SML016M	1.507	162	6.3x7.7
16	220	227SML016MD8	1.507	280	8x10.5
16	470	477SML016M	0.56	350	8x10.5
16	470	477SML016MD10	0.7055	330	10x10.5
25	22	226SML025MD5	12.06	38	5x5.4
25	33	336SML025MD5	8.038	46	5x5.4
25	33	336SML025M	8.038	67	6.3x5.4
25	47	476SML025M	5.644	70	6.3x5.4
25	100	107SML025M	2.653	145	8x6.2
25	220	227SML025MD8	1.206	230	8x10.5
25	220	227SML025M	1.206	250	10x7.7
25	330	337SML025M	0.7	270	8x10.5
25	330	337SML025MD10	0.7	340	10x10.5
25	470	477SML025M	0.49	430	10x10.5
35	4.7	475SML035M	49.38	20	4x5.4
35	10	106SML035MD4	23.21	24	4x5.4
35	10	106SML035M	23.21	34	5x5.4
35	22	226SML035M	10.55	59	6.3x5.4
35	33	336SML035M	7.033	65	6.3x5.4
35	47	476SML035M	4.938	70	6.3x5.8
35	47	476SML035MD8	4.938	105	8x6.2
35	100	107SML035M	2.321	132	6.3x7.7
35	150	157SML035MD8	1.547	220	8x10.5
35	220	227SML035M	0.9	270	8x10.5
35	220	227SML035MD10	0.9	310	10x10.5
35	330	337SML035M	0.703	360	10x10.5

# SML

+85°C Standard, 2000 hrs

WVDC	Capacitance (µF)	IC PART NUMBER	Maximum ESR (Ω) 120 Hz, +20°C	Maximum RMS Ripple Current (mA) 120 Hz, +85°C	Dims DxL (mm)
50	0.1	<a href="#">104SML050MD4</a>	1989.44	3.2	4x5.4
50	0.22	<a href="#">224SML050MD4</a>	904.29	4.7	4x5.4
50	0.33	<a href="#">334SML050MD4</a>	602.86	5.7	4x5.4
50	0.47	<a href="#">474SML050MD4</a>	423.28	6.8	4x5.4
50	1	<a href="#">105SML050MD4</a>	198.944	10	4x5.4
50	2.2	<a href="#">225SML050MD4</a>	90.429	15	4x5.4
50	3.3	<a href="#">335SML050M</a>	60.29	18	4x5.4
50	4.7	<a href="#">475SML050M</a>	42.33	24	4x5.4
50	4.7	<a href="#">475SML050MD5</a>	42.33	25	5x5.4
50	10	<a href="#">106SML050MD5</a>	19.894	41	5x5.4
50	10	<a href="#">106SML050M</a>	19.894	43	6.3x5.4
50	22	<a href="#">226SML050M</a>	9.043	71	6.3x5.4
50	33	<a href="#">336SML050M</a>	6.029	85	6.3x7.7
50	33	<a href="#">336SML050MD8</a>	6.029	95	8x6.2
50	47	<a href="#">476SML050M</a>	4.23	105	6.3x7.7
50	47	<a href="#">476SML050MD8</a>	4.23	140	8x10.5
50	100	<a href="#">107SML050M</a>	1.99	200	8x10.5
50	100	<a href="#">107SML050MD10</a>	1.99	250	10x10.5
50	220	<a href="#">227SML050M</a>	0.9043	320	10x10.5
63	10	<a href="#">106SML063M</a>	19.89	34	6.3x5.4
63	22	<a href="#">226SML063M</a>	9.04	70	6.3x7.7
63	22	<a href="#">226SML063MD8</a>	9.043	120	8x10.5
63	33	<a href="#">336SML063M</a>	6.03	117	8x10.5
63	47	<a href="#">476SML063M</a>	4.23	170	8x10.5
63	100	<a href="#">107SML063M</a>	1.99	280	10x10.5
100	3.3	<a href="#">335SML100M</a>	50.24	28	6.3x5.8
100	4.7	<a href="#">475SML100MD8</a>	3.53	60	8x10.5
100	10	<a href="#">106SML100M</a>	16.57	50	6.3x7.7
100	10	<a href="#">106SML100MD8</a>	16.579	85	8x10.5
100	22	<a href="#">226SML100M</a>	7.54	120	8x10.5
100	33	<a href="#">336SML100M</a>	5.02	100	8x10.5
100	47	<a href="#">476SML100M</a>	3.5274	130	10x10.5

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9