OptiMOS™2 Small-Signal-Transistor

Features

- Dual N-channel
- Enhancement mode
- Super Logic level (2.5V rated)
- Avalanche rated
- Qualified according to AEC Q101
- 100% lead-free; RoHS compliant
- Halogen-free according to IEC61249-2-21

AEC Qualified

RoHS

Halogen-Free

Product Summary

V_{DS}		20	V
$R_{DS(on),max}$	V_{GS}=4.5 V	350	mΩ
	V_{GS}=2.5 V	600	
I_D		0.95	A



PG-SOT-363



Type	Package	Tape and Reel Information	Marking	Lead Free	Packing
BSD235N	PG-SOT-363	H6327: 3000 pcs/ reel	X6s	Yes	Non dry

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter [1]	Symbol	Conditions	Value	Unit
Continuous drain current	I_D	T_A=25 °C	0.95	A
		T_A=70 °C	0.76	
Pulsed drain current	$I_{D,pulse}$	T_A=25 °C	3.8	
Avalanche energy, single pulse	E_{AS}	I_D=0.95 A, R_{GS}=16 Ω	1.6	mJ
Reverse diode dv/dt	dv/dt	I_D=0.95 A, V_{DS}=16 V, di/dt=200 A/µs, $T_{j,max}$=150 °C	6	kV/µs
Gate source voltage	V_{GS}		±12	V
Power dissipation	P_{tot}	T_A=25 °C	0.5	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	°C
ESD Class		JESD22-A114 -HBM	0 (<250V)	
Soldering Temperature			260 °C	
IEC climatic category; DIN IEC 68-1			55/150/56	

(1) Remark: only one of both transistors in operation.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - ambient	R_{thJA}	minimal footprint[2]	-	-	250	K/W
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=250 µA	20	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=1.6 µA	0.7	0.95	1.2	
Drain-source leakage current	I_{DSS}	V_{DS}=20 V, V_{GS}=0 V, T_j=25 °C	-	-	1	µA
		V_{DS}=20 V, V_{GS}=0 V, T_j=150 °C	-	-	100	
Gate-source leakage current	I_{GSS}	V_{GS}=12 V, V_{DS}=0 V	-	-	100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=2.5 V, I_D=0.29 A	-	415	600	mΩ
		V_{GS}=4.5 V, I_D=0.95 A	-	266	350	
Transconductance	g_{fs}	$\|V_{DS}\|>2\|I_D\|R_{DS(on)max}$, I_D=0.76 A		2	-	S

[2] Performed on 40 mm^2 FR4 PCB. The traces are 1mm wide, 70µm thick and 20mm long; they are present on both sides of the PCB

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=10 V, f=1 MHz	-	49	63	pF
Output capacitance	C_{oss}		-	23	32	
Reverse transfer capacitance	C_{rss}		-	3.2	-	
Turn-on delay time	$t_{d(on)}$	V_{DD}=10 V, V_{GS}=4.5 V, I_D=0.95 A, $R_{G,ext}$=6 Ω	-	3.8	-	ns
Rise time	t_r		-	3.6	-	
Turn-off delay time	$t_{d(off)}$		-	4.5	-	
Fall time	t_f		-	1.2	-	
Gate Charge Characteristics						
Gate to source charge	Q_{gs}	V_{DD}=10 V, I_D=0.95 A, V_{GS}=0 to 4.5 V	-	0.11	-	nC
Gate to drain charge	Q_{gd}		-	0.07	-	
Gate charge total	Q_g		-	0.32	-	
Gate plateau voltage	$V_{plateau}$		-	2.4	-	V
Reverse Diode						
Diode continous forward current	I_S	T_A=25 °C	-	-	0.5	A
Diode pulse current	$I_{S,pulse}$		-	-	3.8	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=0.95 A, T_j=25 °C	-	0.9	1.2	V
Reverse recovery time	t_{rr}	V_R=10 V, I_F=0.95 A, di_F/dt=100 A/µs	-	5.2	-	ns
Reverse recovery charge	Q_{rr}		-	0.97	-	nC

1 Power dissipation

$P_{tot}=f(T_A)$



2 Drain current

$I_D=f(T_A)$; $V_{GS}\geq 4.5$ V



3 Safe operating area

$I_D=f(V_{DS})$; $T_A=25$ °C; $D=0$

parameter: t_p



4 Max. transient thermal impedance

$Z_{thJA}=f(t_p)$

parameter: $D=t_p/T$



5 Typ. output characteristics

$I_D=f(V_{DS})$; $T_j=25$ °C

parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)}=f(I_D)$; $T_j=25$ °C

parameter: V_{GS}



7 Typ. transfer characteristics

$I_D=f(V_{GS})$; $|V_{DS}|>2|I_D|R_{DS(on)max}$



8 Typ. forward transconductance

$g_{fs}=f(I_D)$; $T_j=25$ °C



9 Drain-source on-state resistance

$R_{DS(on)}=f(T_j)$; $I_D=0.95$ A; $V_{GS}=4.5$ V



10 Typ. gate threshold voltage

$V_{GS(th)}=f(T_j)$; $V_{DS}=V_{GS}$; $I_D=1.6$ µA

parameter: I_D



11 Typ. capacitances

$C=f(V_{DS})$; $V_{GS}=0$ V; $f=1$ MHz; $T_j=25$°C



12 Forward characteristics of reverse diode

$I_F=f(V_{SD})$

parameter: T_j



13 Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=16 Ω

parameter: $T_{j(start)}$



14 Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=0.95 A pulsed

parameter: V_{DD}



15 Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=250 µA



16 Gate charge waveforms



SOT-363

Package Outline:



Footprint:



Packing:



Reflow soldering:



Note: For symmetric types there is no defined Pin 1 orientation in the reel.

Dimensions in mm

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9