



We Know Power *Inside and Out.*www.slpower.com



SL Power Electronics Corp is a subsidiary of SL Industries, Inc. (SLI), an AMEX and PHLX listed corporation. SL Power Electronics is a global manufacturer and marketer of AC/DC and DC/DC power supplies from 6 watts to more than 6000 watts. The Company develops, manufactures and markets two product brands:

ECONDOR

Leading the development of medical power supplies for more than 25 years, the Condor name

is a recognized brand for a broad range of internal, open-frame AC/DC and DC/DC switch-mode and linear power supplies. The Condor brand has broad appeal for a variety of markets including industrial, data communications and telecommunications. Condor products include a broad breadth of standard models as well as the opportunity to modify current power supplies or design 100% custom to meet specific customer requirements.



For more than 45 years, the Ault name has been the premier brand for external power supplies. The brand represents the most robust line available in external power from 6 watts to 180 watts. The product line includes its top selling switch-mode power supplies that are available in desktop or wall mount models, linear power supplies, transformers, battery chargers and mobile adapters. Ault products are sold across a

range of electronic market segments including medical, data communications and Power over Ethernet, computer/computer peripherals and industrial.

SL Power Electronics has more than 700 employees in five sales & engineering offices on three continents – North America, Europe and Asia. The headquarters for SL Power Electronics are in California with manufacturing locations in Mexico and China. SL Power Electronics ranks number one in providing medical OEMs with solutions that meet even the most stringent power requirements. Our standard products range from as low as 6 watts to as high as 6,000 watts with engineering expertise to modify existing designs or develop complete custom solutions.

SL Power Electronics is more than a leader in the design of commercial and medical power supplies; we are committed to staying in the forefront of environmental initiatives and technological advances that impact our customers' success. There are currently two initiatives of interest to existing and prospective customers:



As an ENERGY STAR partner, SL Power Electronics offers a line of external switch-mode power supplies from 10 to 60 watts for commercial and medical applications that comply with European

Union, US Environmental Protection Agency (EPA), and California Energy Commission (CEC) standards that include minimum efficiency levels in active mode and low energy consumption in no-load/stand-by mode.

SL Power Electronics, under the Ault brand name, was one of the first power supply companies in North America to be named an ENERGY STAR partner in 2005. Today, we have one of the most complete, energy-wise offerings of external power supplies.

RoHS – the RoHS directive stands for "the restriction of the use of certain hazardous substances in electrical and electronic equipment" (Directive 2002/95/EC). The directive banned the placement of new electrical and electronic equipment containing more than agreed levels of lead, cadmium, mercury and other flame-retardants on the EU market in certain sectors, and became effective on July 1, 2006. Some market sectors such as medical equipment do however currently have exemption from this directive.

The most popular product families within each of the Condor and Ault brands, where required, are fully compliant. Check with your SL Power Electronics representative for specific product compliance queries.

About SL Industries

SL Industries, Inc., through its four subsidiaries, designs, manufactures and markets power electronics, power motion and power protection equipment that are used in a variety of medical, aerospace, computer, datacom, industrial, telecom, transportation and utility applications. SL Industries' products are sold primarily to Original Equipment Manufacturers (OEMs) to increase operating safety, reliability and efficiency.

For more information on SL Industries and its subsidiaries, please visit **www.slindustries.com**

www.slpower.com



Power conversion products for OEMs in the global electronics marketplace

The frontrunners of Ault's external product offering are the switch-mode power supplies. This product category is the most popular due to wide range input, compact size and design versatility inherent in the switch-mode design.

In addition, the Ault brand includes a line of transformers, linear power supplies, DC mobile adapters for portable applications and battery chargers for lead acid, NiCad, NiMH and lithium ion topologies.

Listed below is a representative sampling of the external switch-mode power supplies available for medical applications. Check out **www.slpower.com** for more external power supplies for the medical market. If you don't find a standard power supply, keep in mind our global engineering expertise and the opportunity to develop modified or 100% custom solutions to meet even the most stringent requirements.

NEW PRODUCTS FROM THE AULT LINE



Interchangeable Blade Power Supplies

SL Power has introduced commercial and medical variants of the MW/PW170 and 172 series of products. All models have wide range input and capable of output power 6 to 19W, with output voltages ranging from 3 to 48Vdc. All models meet the requirements of the Energy Star programme.



MW172

Available in desktop and wall plug-in configurations, the MW172 series meets medical safety approvals and new efficiency and energy wise guidelines set forth by the California Energy Commission (CEC). The series is 10-19 watts with models available from 3V to 24V in single output. Wall plug-in configurations include North America/Japan, Euro and UK.



MW116

The MW116 is a 60-90 watt series available in desktop models from 5V to 48V. This power range is ideal for many of today's top medical applications including monitors, LCD displays, blood analyzers and oxygen concentrators.



Power over Ethernet Products

Power over Ethernet is designed to supply DC power to devices on the network infrastructure via existing CAT5 Ethernet cabling. SL Power is a market leader in POE power products with an ever expanding range of power supplies and line splitters meeting the requirements of IEEE 802.3AF.

AULT PRODUCT SELECTOR

Medical Switchmode

		Max	i/p	Desk-	Wall-					OUT	PUT CU	RRENT M	AX CONTI	NUOUS					
	o/p's	W	range	top	mount	3V	3.3V	5V	6V	7V	8V	9V	12V	13.5V	15V	16V	18V	24V	48V
MW117	1	12	100-240Vac	YES	YES		2A	2A		1.43A		1.1A	0.85A		0.7A		0.6A	0.45A	
MW128	1	32	100-240Vac	YES	YES		4A	4A		3.5A		3A	2.5A		2A		1.67A	1.33A	
MW125	1	40	100-240Vac	YES	YES	5A		5A		4.5A		4A	3A		2.5A		2.1A	1.67A	0.84A
MW160	1	48	100-240Vac	YES		5A		5A		5A		4.6A	3.5A		3A	2.8A	2.5A	2A	
MW136	1	60	100-250Vac	YES	YES								5A		4A		3.33A	2.5A	
MW116	1	90	100-240Vac	YES				12A	10A			7.8A	6.67A	6.15A	6A	5.6A	5A	3.75A	1.87A
MW132	1	101	100-240Vac	YES									8.15A		6.5A			4.21A	
MW122	1	120	100-240Vac	YES									10A					5A	
MW201	2	22.5	100-250Vac	YES				3A					0.8A						
MW301	2	22.5	100-259Vac	YES				3A					0.6/0.2A						

														energy STAR PARTNER
MW170	1	15	100-250Vac	YES	YES		2A	2A		1.15A	1.25A	1.0A		0.63A
MW172	1	19	100-240Vac	YES	YES	3.34A		3A		2A	1.5A	1.2A	1A	0.75A
MW173	1	32	100-250Vac	YES	YES		4A	4A	3.5A	3A	2.5A	2A	1.67A	1.33A
MW152	1	50	100-240Vac	YES				6A*		5A*	4.2A	3.33A	2.8A	2.0A
MW174	1	60	100-240Vac	YES							5A		3.33A	2.5A

^{*} Do not fully meet requirements on Energy Star

Commercial Switchmode

	o/p's	Max W	i/p range	Desk- top	Wall- mount	3V	3.3V	5V	6V	7V	8 V	9V	12V	13.5V	15V	16V	18V	24V	36V	48V
PW117	1	12	100-240Vac	YES	YES	2A		2A			1.28A	1.1A	0.85A		0.7A		06A	0.45A		0.25A
PW118	1	19	100-250Vac	YES	YES	3.34A		3A				2A	1.5A		1.2A		1A	0.75A		0.4A
PW128	1	32	100-250Vac	YES	YES		4A	4A	4A	3.5A		3A	2.5A		2A		1.67A	1.33A	0.84A	0.67A
PW125	1	40	100-250Vac	YES	YES		5A	5A		4.5A		4A	3.4A		2.5A		2.1A	1.67A		0.84A
PW160	1	48	100-250Vac	YES		5A		5A		5A		4.6A	3.5A		3A	2.8A	2.5A	2A		1A
PW130RA	1	20	100-250Vac	YES																0.42A
PW130RB	1	15.4	100-250Vac	YES																0.35A
PW136	1	60	100-250Vac	YES	YES		7A	6A		5.5A		5.5A	5A		4A		3.33A	2.5A		1.25A
PW116	1	90	100-250Vac	YES				12A	10A			7.8A	6.67A	6.15A	6A	5.6A	5A	3.75A		1.87A
PW132	1	101	100-240Vac	YES									8.15A		6.5A			4.21A		2.08A
PW122	1	120	100-240Vac	YES									10A					5A		2.5A
SW201	2	25	100-250Vac	YES				4A					1A							
PW300	3	50	100-250Vac	YES				5A					4/0.5A							
SW301	3	25	100-250Vac	YES				4A					1/0.6A							
SC300	3	25	100-250Vac	YES				4A					1/0.6A							
SC303	3	11	100-250Vac	YES				1A				0	.25/0.25/	4						



	Max W	i/p range	Desk- top	Wall- mount	3.3V	5V	6V	7V	8V	9V	12V	13.5V	15V	16V	18 V	24V	33V	48V
PW170 ITE	10-15W	100-250Vac	YES	YES	2A	2A				1.5A	1.25A		1A			0.63A		0.31A
PW148 ITE	15-19.2	100-250Vac	YES			3A				2A	1.5A		1.2A		1A	0.75A		0.4A
PW149 ITE	10-12	100-250Vac	YES							1.3A	1A		0.8A		0.67A	0.5A	0.36A	0.25A
PW152	48-50	100-250Vac	YES			6A*				5A*	4.2A		3.33A		2.8A	2A		1A*
PW173	27-32	100-250Vac	YES	YES	4A*	4A*				3A	2.5A		2A		1.67A	1.33A		0.67A
PW174	60-64.8	100-250Vac	YES			8A*				6A*	5A		4A		3.3A	2.7A		1.35A*

^{*} Do not fully meet requirements on Energy Star

Power over Ethernet

	Max W	i/p range	Desktop	5V	12V	24V	48V
PW180KA	20.2	100-250Vac	YES				0.42A
PW147RB	20						0.35A
Line Splitter							
LS15-05	10	48V		2A			
LS15-12	10.8				0.9A		
LS15-24	11.4					0.475A	

Mobile DC/DC Adaptors

	o/p's	Max W	i/p range	Desk- top	Wall- mount	15.1V	16.2V	18.2V	19.2V	20.2V	24.1V
TR7515	1	75	12-15.5Vdc	YES		4.77A					
TR7516	1	75	12-15.5Vdc	YES			4.63A				
TR7518	1	75	12-15.5Vdc	YES				4.12A			
TR7519	1	75	12-15.5Vdc	YES					3.91A		
TR7520	1	75	12-15.5Vdc	YES						3.71A	
TR7524	1	75	12-15.5Vdc	YES							3.11A

					15V	16V	18V	19V	20V	24V	
TR10015	1	100	10.6-16Vdc	YES	6.67A						
TR10016	1	100	10.6-16Vdc	YES		6.25A					
TR10018	1	100	10.6-16Vdc	YES			5.5A				
TR10019	1	100	10.6-16Vdc	YES				5.26A			
TR10020	1	100	10.6-16Vdc	YES					5A		
TR10024	1	100	10.6-16Vdc	YES						4.16A	
TR12015	1	120	10.6-16Vdc	YES	8A						
TR12016	1	120	10.6-16Vdc	YES		7.5A					
TR12018	1	120	10.6-16Vdc	YES	·		6.66A				
TR12019	1	120	10.6-16Vdc	YES				6.31A			
TR12020	1	120	10.6-16Vdc	YES					6A		
TR12024	1	120	10.6-16Vdc	YES						5A	

Battery Chargers

Nickel Metal Hydride

BCM NiMH Series	# Cells	Volts DC	Fast Charge Current A	
BCM-*306-150-00-21X	3-06	3-09	1.5	
BCM-*306-120-00-21X	3-06	3-09	1.2	
BCM-*306-100-00-21X	3-06	3-09	1	
BCM-*306-080-00-21X	3-06	3-09	0.8	
BCM-*306-060-00-21X	5-10	3-09	0.6	
BCM-*510-120-00-21X	5-10	5-15	1.2	
BCM-*510-100-00-21X	5-10	5-15	1	
BCM-*510-080-00-21X	5-10	5-15	0.8	
BCM-*510-060-00-21X	5-10	5-15	0.6	
BCM-*812-100-00-21X	8-12	8-18	1	
BCM-*812-080-00-21X	8-12	8-18	0.8	
BCM-*812-060-00-21X	8-12	8-18	0.6	

Nickel Cadmium

BCM NiCD Series	# Cells	Volts DC	Fast Charge Current A	
BCM-*306-150-00-21X	3-06	3-09	1.5	·
BCM-*306-120-00-21X	3-06	3-09	1.2	
BCM-*306-100-00-21X	3-06	3-09	1	
BCM-*306-080-00-21X	3-06	3-09	0.8	
BCM-*306-060-00-21X	5-10	3-09	0.6	
BCM-*510-120-00-21X	5-10	5-15	1.2	
BCM-*510-100-00-21X	5-10	5-15	1	
BCM-*510-080-00-21X	5-10	5-15	0.8	
BCM-*510-060-00-21X	5-10	5-15	0.6	
BCM-*812-100-00-21X	8-12	8-18	1	
BCM-*812-080-00-21X	8-12	8-18	0.8	
BCM-*812-060-00-21X	8-12	8-18	0.6	

Lithium Ion

BL600 Series	# Cells	Volts DC	Fast Charge Current A	Thermistor Required
BL600-*02-170-00-03X	2	8.4	1.7	no
BL600-*03-314-00-03X	3	12.6	1.4	no
BL600-*04-100-00-03X	4	16.8	1	no
BL600-*02-170-00-21X	2	8.4	1.7	yes
BL600-*03-314-00-21X	3	12.6	1.4	yes
BL600-*04-100-00-21X	4	16.8	1	yes

Lead Acid

BVL Series	Volts DC	Output Amps	Fast Charge Vdc	Float Charge Vdc	Max Watts
BVL061000003X	6	1	7.35	6.9	7.35
BVL062000003X	6	2			14.7
BVL120600003X	12	0.6	14.7	13.8	8.82
BVL121200003X	12	1.2			17.64
BVL240300003X	24	0.3	29.4	27.6	8.82
BVL240600003X	24	0.6			17.64

Linear External Power Supplies

Linear Unregulated	Input Volts	# of o/p	0/p Volts	0/p Power watts
UK	230Vdc	1	5 to 24Vdc	2 to 20W
Europe	230Vdc	1	3 to 24Vdc	2 to 20W
N America	120Vdc	1	3 to 24Vdc	0.3 to 24W
Japan	100Vdc	1	5 to 24Vdc	1.2 to 35W
Australia	240Vdc	1	3 to 24Vdc	1.2 to 14W

Linear Regulated	Input Volts	# of o/p	0/p Volts	0/p Power watts
UK	230Vdc	1	5 to 24Vdc	2.25 to 12W
Europe	230Vdc	1/2/3	5 to 24Vdc	2.25 to 12W
N America	120Vdc	1/3	5 to 24Vdc	2.65 to 12W
Japan	100Vdc	1	5 to 24Vdc	6 to 12W
Australia	240Vdc	1	5 to 24Vdc	6 to 12W



The world leader in medical OEM power supplies

For more than twenty five years, Condor has been the market leader in OEM power supplies for medical electronics, leading the industry in technological advances and providing specialized support for the challenges of the medical marketplace.

Condor currently produces more medically approved OEM power products for use in patient-connected applications than all of our competitors combined.

Power for industrial and instrumentation systems

Condor has many years of experience creating innovative power solutions for a variety of industrial and instrumentation applications. These systems often require unique outputs, have special size constraints, and may be used under demanding environmental conditions. The Condor line is versatile and robust by design so it is suitable for a broad range of applications including automated manufacturing systems, high-pressure liquid chromatography, gaming products, spectrometers and process control systems.

NEW PRODUCTS FROM THE CONDOR LINE



GSM11 Series

The GSM11 Series is an 11-watt universal input AC/DC power supply in an industry-leading small footprint. Wide range, Class II input. Six models available from 3.3V to 28V. Ideal for a broad range of medical applications including small single board computers, battery charging and operating small motors or pumps. Full safety agency and EN60601/EN60950-1 approvals.



GNT200 Series

The latest range of GNT products is the compact 200W (127 x 76 x 30mm) wide range input power supply. The products available with both medical and commercial agency approvals provide high efficiencies of typically 90% with a main channel output ranging from 12 to 48V and the possibility of a further two auxiliary outputs.



GNT400 Front End Series

The GNT400 provides 400 watts of DC output power in a compact $100 \times 178 \times 40 \text{mm}$ package. Approved for medical and commercial applications, the power supply has a 300 watts convection rating. There are four models available from 12V to 48V. MTBF of 300,000 hours minimum. The unit is available with optional secondary output channel and fan cover options.



GPMP/GPHP Series

The GPMP medical and GPHP commercial series are a family of universal input AC/DC power supplies with power factor correction (PFC) and up to 1000 watts of output power. This single output commercial series incorporates "hot-swap" capabilities and a handle. There are four models available in 24V, 28V, 36V and 48V outputs. The GPHP series may be placed in a CRA2-3 Rack which enables the user to have up to 6000W available.

CONDOR PRODUCT SELECTOR

Switchmode Power Supplies

Commercial Medical opps	Single Output			Max Pov		Input	pcb u channel		MAX CONTINUOUS CURRENT (AMPS)						
CSCUE	Commercial	Medical	o/p's	Conv (pk)	Forced	Voltage	enclosed	3.3V	5V	12V	15V	24V	28v	36 V	48V
GSNC28				. ,			р	2.2							
CSN/28		GSM15					р								
CECAMO	GSC20				24		р								
CECADO				()			р								
CLC-10		GNT30	1		30		р		6			1.25	1.07		0.63
PPC-40			1	40 (45)			р		7			1.7			
EPC41 GPM41			1	40 (45)			р	8	8	3.3	2.7	1.7	1.4		0.83
CLISSO CLIMSO 1 50 Gin 99-264 p 8 8 4.2 3.3 2.1 1.8 1.1			1	()			р	8	-						1.4
PPC55 PPM55			1				р		-						
GNT60			1	50 (60)			р								1.1
ELC65 GLM65 1 65 75 90-264 p 11 5.5 4.3 2.7 2.3 1.35	GPC55	GPM55	1	55 (70)		85-264	р	11	4.7	3.7	2.3	2	1.5		
SLC75 SLM75 1		GNT60	1	55		90-264	р			5	4.35	2.7			
GPC80 GPM80	GLC65	GLM65	1	65	75	90-264	р		11	5.5	4.3	2.7	2.3		1.35
SLC110 SLM110 1 75 110 99-264 p 9.1 7.3 4.6	GLC75	GLM75	1	75	110	90-264	р		19.6	9.1	7.3	4.6	4		
GPFC110	GPC80	GPM80	1	80	110	85-264	р		20	9.2	7.3	4.6	3.9		2.3
GPFM115	GLC110	GLM110	1	75	110	90-264	р			9.1	7.3	4.6			
GPC140	GPFC110		1	80	110	85-264	u		15	9.2	7.3	4.6	3.9		2.3
GD150 1 150 180 85-264 u 15 12 7.5 6.4 3.75 GPFC160 1 140 160 85-264 u 31.3 13.3 10.7 6.7 5.7 3.4 GPFC250 GPM225 1 200 225 85-264 u 40 19 15 9.4 8 GPFC250 GPM250 1 180 250 85-264 u 36 36 15 12 7.5 6.5 3.8 GNT400 GNT400 1 300 400 80-270 u 34 16.7 8.3 GNT400 GPMP600 1 600 (Internal fan) 85-264 e 25 21.5 17 GPHP700 GPMP700 1 700 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPM900 1 900 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPMP100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPMP100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPM100 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPM100 1 1000 (Internal fan) 85-264 e 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5		GPFM115	1	80	115	85-264	u	20	20	9.6	7.7	4.8			2.4
GPFC160	GPC140	GPM140	1	140	160	85-264	u		30	13.4	10.7	6.7	5.7		
GPC225 GPM255 1 200 225 85-264 u 40 40 19 15 9.4 8 GPC256 GPFM250 1 180 250 85-264 u 36 36 15 12 7.5 6.5 3.8 GNT400 GNT400 1 300 400 80-270 u 34 16.7 8.3 GPHP600 GPMP600 1 600 (Internal fan) 85-264 e 25 21.5 17 GPHP700 GPMP700 1 700 (Internal fan) 85-264 e 25 21.5 17 GPHP900 GPMP900 1 900 (Internal fan) 85-264 e 41.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 900 (Internal fan) 85-264 e 41.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 41.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 900 (Internal fan) 85-264 e 41.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 41.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 541.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 541.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 71.7** 35.7 27.7 20.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 8 81.2** 12.5** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 8 81.2** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 8 81.2** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 8 81.2** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 8 81.2** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 8 81.2** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 e 8 81.2** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 p 1.2** 12.5** 13.8 GPHP1000 GPMP900 1 1000 (Internal fan) 85-264 p 1.2** 12.5** 13.8 GENTAL REPARATION OF STATE AND STATE A		GLD150	1	150	180	85-264	u			15	12	7.5	6.4		3.75
GPFC250 GPFM250 1 180 250 85-264 u 36 36 15 12 7.5 6.5 3.8 GNT400 GNT400 1 300 400 80-270 u 34 16.7 8.3 GNT400 GPMP600 1 600 (Internal fan) 85-264 e 25 21.5 17 GPHP700 GPMP700 1 700 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP900 GPMP900 1 990 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP900 GPMP1000 1 1000 (Internal fan) 85-264 e 41.7** 35.7 27.7 20.8 Dual Output GCC110 GLM110 2 75 110 85-264 p +12V -12V +15V -15V +24V +5V Triple Output GSC25 GSM25 3 25 28 90-264 p +5V +12V -12V +5V +12V -12V +5V +12V -12V +5V +24V -12V GCC440 3 40 45) 90-264 p +3.3V +12V -12V +5V +12V -15V +5V +24V -12V GLC50 GPM40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 85-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50	GPFC160		1	140	160	85-264	u		31.3	13.3	10.7	6.7	5.7		3.4
GNT400 GNT400 1 300 400 80-270 u 34 16.7 8.3 GPHP600 GPMP600 1 600 (Internal fan) 85-264 e 25 21.5 17 GPHP700 GPMP700 1 700 (Internal fan) 85-264 e 25 21.5 17 GPHP700 GPMP700 1 900 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 180-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 180-264 e 41.7** 35.7 27.7 20.8 Dual Output GCC110 GLM110 2 75 110 85-264 p +12V -12V +15V -15V +24V +5V Triple Output GSC25 GSM25 3 25 28 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC40 GPM40 3 40 50 85-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC30 GPM80 4 80 110 85-264 p +3.3V +5 +12V -12V +5V +15V -15V +5V +24V -12V Quad Output GPC55 GPM80 4 80 110 85-264 p GPC500 GPM80 4 80 110 85-264 p GPC200 GPM30 4 100 125 85-264 u GPC200 GPM30 4 140 180 90-264 u GPC200 GPM30 4 140 180 90-264 u GPC200 GPM30 4 150 200 85-264 u	GPC225	GPM225	1	200	225	85-264	u		40	19	15	9.4	8		
GPHP600 GPMP600 1 600 (Internal fan) 85-264 e 25 21.5 17 GPHP700 GPMP700 1 700 (Internal fan) 85-264 e 14 GPHP900 GPMP900 1 900 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 85-264 e 41.7** 35.7 27.7 20.8 Dual Output GCC110 GLM110 2 75 110 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GSC25 GSM25 3 25 28 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GECA40 3 40 (45) 90-264 p +3.3V +12V -12V +5V +12V -5V +5V +12V -12V +5V +24V -12V GLC40 GPM40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 GLM50 3 50 60 85-264 p +3.3V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 3 50 60 85-264 p +3.3V +5 +12V -12V +5V +15V -15V +5V +5V +24V -12V GLC55 GLM65 3 65 75 90-264 p +3.3V +5 +12V -12V +5V +15V -15V +5V +5V +24V -12V GLC65 GLM65 4 55 70 85-264 p +3.3V +5 +12V -12V +5V +15V -15V +5V +5V +24V -12V GPC50 GPM80 4 80 110 85-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC60 GPM80 4 80 110 85-264 p Warious combinations of ±5, ±12, ±15, +24 and isolated outputs available. GPC125 GPM125 4 50/80 125 90-264 u Consult product data or local Sales Office for specific models.	GPFC250	GPFM250	1	180	250	85-264	u	36	36	15	12	7.5	6.5		3.8
GPHP700 GPMP700 1 700 (Internal fan) 85-264 e 37.5 32.1 25 18.8	GNT400	GNT400	1	300	400	80-270	u			34		16.7			8.3
GPHP900 GPMP900 1 900 (Internal fan) 85-264 e 37.5 32.1 25 18.8 GPHP1000 GPMP1000 1 1000 (Internal fan) 180-264 e 41.7** 35.7 27.7 20.8 Dual Output GLC110 GLM10 2 75 110 85-264 p +12V -12V +15V -15V +24V +5V Triple Output GSC25 GSM25 3 25 28 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V +5V +24V -12V GLC40 GPM40 3 40 (45) 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V +5V +24V -12V GRC40 GPM40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GLM50 3 50 60 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GLM50 3 65 75 90-264 p +5V +12V -12V +5V +15V -15V +5V +15V -15V +5V +24V -12V GRC50 GLM65 3 65 75 90-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GLM65 3 65 75 90-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GLM65 3 65 75 90-264 p +3.3V +5 +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GLM65 3 65 75 90-264 p +3.3V +5 +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GLM65 3 65 75 90-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GRM50 4 80 110 85-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GRM50 4 80 110 85-264 p GRC50 GRM50 4 80 110 85	GPHP600	GPMP600	1	600 (Inter	nal fan)	85-264	е					25	21.5	17	
GPHP1000 GPMP1000 1 1000 (Internal fam) 180-264 e 41.7** 35.7 27.7 20.8	GPHP700	GPMP700	1	700 (Inter	nal fan)	85-264	е								14
Dual Output	GPHP900	GPMP900	1	900 (Inter	nal fan)	85-264	е					37.5	32.1	25	18.8
GLC110 GLM110 2 75 110 85-264 p +12V -12V +15V -15V +24V +5V Triple Output GSC25 GSM25 3 25 28 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GECA40 3 40 (45) 90-264 p +3.3V +12V -12V +5V +12V -5V +5V +12V -12V +5V +24V -12V GLC40 GPM40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V Quad Output GPC55 GPM55 4 55 70 85-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC80 GPM80 4 80 110 85-264 p GPC80 GPM80 4 100 125 85-264 u GPC130 GPM130 4 100 125 85-264 u GPC200 GPM200 4 150 200 85-264 u GPC200 GPM20	GPHP1000	GPMP1000	1	1000 (Inter	nal fan)	180-264	е					41.7**	35.7	27.7	20.8
SC25 GSM25 3 25 28 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V	Dual Output														
GCC25 GSM25 3 25 28 90-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GECA40 3 40 (45) 90-264 p +3.3V +12V -12V +5V +12V -5V +5V +12V -12V +5V +24V -12V GLC40 GPM40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 3 50 60 85-264 p +5V +12V -12V +5V +15V -15V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +5V +12V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V -12V +5V +15V -15V +5V +24V -12V GPC50 GM30 4 55 70 85-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 GPM55 4 55 70 85-264 p GPC80 GPM80 4 80 110 85-264 p GPC80 GPM80 4 80 110 85-264 p GPC130 GPM130 4 100 125 85-264 u GPC130 GPM130 4 100 125 85-264 u GPC130 GPM200 4 150 200 85-264 u GPC200 GPM200 4 150 200 85-264 u GPC30 GPM300 4 150 200	GLC110	GLM110	2	75	110	85-264	р	+12V	-12V	+15V -1	5V	+24V +5V	'		
GECA40 3 40 (45) 90-264 p +3.3V +12V -12V +5V +12V -5V +5V +12V -12V +5V +24V -12V GLC40 GPM40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 3 50 60 85-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC50 GPM55 4 55 70 85-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC55 GPM55 4 75 110 90-264 p GRC30 GPM80 4 80 110 85-264 p Various combinations of ±5, ±12, ±15, +24 and isolated outputs available. GPC130 GPM130 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GRC200 GPM200 4 150 200 85-264 u GRC200 GPM200 4 150 200 85-264 u	Triple Output														
GLC40 GPM40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 3 50 60 85-264 p +5V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC65 GPM55 4 55 70 85-264 p GRC60 GPM80 4 80 110 85-264 p Various combinations of ±5, ±12, ±15, +24 and isolated outputs available. GPC130 GPM120 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GRC200 GPM200 4 150 200 85-264 u GRC200 GPM200 4 150 200	GSC25	GSM25	3	25	28	90-264	р	+5V -	⊦12V –12V	+5V +15	5V –15V	+5V +24V	-12V		
GPC40 3 40 50 85-264 p +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 3 50 60 85-264 p +5V +12V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GLC65 GLM75 4 55 70 85-264 p GLC75 GLM75 4 75 110 90-264 p GPC80 GPM80 4 80 110 85-264 p Various combinations of ±5, ±12, ±15, +24 and isolated outputs available. GPFC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GPC200 GPM200 4 150 200 85-264 u GPC200 GPM200 4 150 200 85-264 u	GECA40		3	40 (45)		90-264	р	+3.3\	/ +12V -12V	+5V +12	2V –5V	+5V +12V	-12V	+5V +24V -	-12V
GLC50 GLM50 3 50 60 90-264 p +3.3V +12V -12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GPC50 3 50 60 85-264 p +5V +12V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V GRC65 GPM55 4 55 70 85-264 p GLC75 GLM75 4 75 110 90-264 p GPC80 GPM80 4 80 110 85-264 p Various combinations of ±5, ±12, ±15, +24 and isolated outputs available. GPC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GLD140 4 140 180 90-264 u GPC200 GPM200 4 150 200 85-264 u	GLC40	GPM40	3	40	50	85-264	р	+5V -	⊦12V –12V	+5V +15	5V -15V	+5V +24V	-12V		
GPC50 3 50 60 85-264 p +5V +12V -12V GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V Quad Output GPC55 GPM55 4 55 70 85-264 p GLC75 GLM75 4 75 110 90-264 p GPC80 GPM80 4 80 110 85-264 p GPC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u GPC130 GPM130 4 140 180 90-264 u GPC200 GPM200 4 150 200 85-264 u GPC200 GPM200 4 150 200 85-264 u	GPC40		3	40	50	85-264	р	+5V -	⊦12V –12V	+5V +15	5V -15V	+5V +24V	-12V		
GLC65 GLM65 3 65 75 90-264 p +3.3V +5 +12V +5V +12V -12V +5V +15V -15V +5V +24V -12V Quad Output GPC55 GPM55 4 55 70 85-264 p GLC75 GLM75 4 75 110 90-264 p GPC80 GPM80 4 80 110 85-264 p GPC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u GPC130 GPM130 4 140 180 90-264 u GPC200 GPM200 4 150 200 85-264 u GPC200 GPM200 4 150 200 85-264 u	GLC50	GLM50	3	50	60	90-264	р	+3.3\	/ +12V -12V	+5V +12	2V -12V	+5V +15V	-15V	+5V +24V -	-12V
Quad Output GPC55 GPM55 4 55 70 85-264 p GLC75 GLM75 4 75 110 90-264 p GPC80 GPM80 4 80 110 85-264 p GPC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GPC200 GPM200 4 150 200 85-264 u	GPC50		3	50	60	85-264	р	+5V -	-12V –12V						
GPC55 GPM55 4 55 70 85-264 p GLC75 GLM75 4 75 110 90-264 p GPC80 GPM80 4 80 110 85-264 p GPFC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u GPC200 GPM200 4 150 200 85-264 u GPC200 GPM200 4 150 200 85-264 u	GLC65	GLM65	3	65	75	90-264	р	+3.3\	/ +5 +12V	+5V +12	2V -12V	+5V +15V	-15V	+5V +24V -	-12V
GLC75 GLM75 4 75 110 90-264 p GPC80 GPM80 4 80 110 85-264 p GPFC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u GPC200 GPM200 4 150 200 85-264 u GPC200 GPM200 4 150 200 85-264 u	Quad Output														
GPC80 GPM80 4 80 110 85-264 p Various combinations of ±5, ±12, ±15, +24 and isolated outputs available. GPFC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GPC200 GPM200 4 150 200 85-264 u	GPC55	GPM55	4	55	70	85-264	р								
GPFC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GLD140 4 140 180 90-264 u GPC200 GPM200 4 150 200 85-264 u	GLC75	GLM75	4	75	110	90-264	p								
GPFC125 GPFM125 4 50/80 125 90-264 u GPC130 GPM130 4 100 125 85-264 u Consult product data or local Sales Office for specific models. GLD140 4 140 180 90-264 u GPC200 GPM200 4 150 200 85-264 u	GPC80	GPM80	4	80	110	85-264		Variou	ıs combinatior	ns of ±5,	±12, ±15.	+24 and is	olated out	puts available	١.
GLD140 4 140 180 90-264 u GPC200 GPM200 4 150 200 85-264 u	GPFC125	GPFM125	4	50/80	125	90-264									
GPC200 GPM200 4 150 200 85-264 u	GPC130	GPM130	4	100	125	85-264	u	Consu	ılt product dat	a or local S	Sales Office	e for specific	models.		
GPC200 GPM200 4 150 200 85-264 u			4			90-264	u								
** Only available in medical version	GPC200	GPM200	4	150	200	85-264	u								
						*	* Only available in mor	lical version							

Linear Power Supplies

Linear Fower Supplies										
Single Output				MAX CONTINUO	US CURRENT (AMPS)	AT 50HZ INPUT				
Commercial	Medical	2V	5V	12V	15V ` ´	24V	28V	48V		
	ML			0.45	0.36	0.25				
HA		1.35	1.35	0.81	0.81	0.45	0.45			
НВ	MB	2.7*	2.7	1.53	1.35	1.08	0.9	0.45*		
HC	MC	5.4*	5.4	3.06	2.7	2.16	1.8	0.9*		
HN		8.1	8.1	4.59	4.05	3.24	2.7			
HD	MD	10.8*	10.8	6.12	5.4	4.32	3.6	2.7*		
HE		16.2	16.2	9.18	8.1	6.48	5.4	3.6		
F			22.5	14.4	14.4	10.8	5.4	5.4		
G			31.5							
Dual Output		5V 5V	5V 9 ~ 15V	5V 18 ~ 24V	+12V -12V	+15V -15V	+12 ~ 15V -12 ~ 15V	+18 ~ 24V —18 ~ 24V		
HAA	MAA	1.35* 1.35*	1.8 0.45	1.8 0.27			$0.9 \sim 0.72$ $0.9 \sim 0.72$	0.36 ~ 0.5* 0.36 ~ 0.5*		
HBB	MBB	2.7* 2.7*	2.7 1.08	2.7 0.72			1.53 ~ 1.35 1.53 ~ 1.35			
HCC	MCC	5.4* 5.4*	5.4 2.25	5.4 1.8			3.0 ~ 2.7 3.0 ~ 2.7			
HAD					0.36 0.36	0.36 0.36				
HDD							4.5 4.5			
	MLL				0.225 0.225	0.018 0.018				
Triple Output		5V	+12 ~ 15V	–12 ~ 15V						
	MTLL	4.5	0.09	0.09						
HTAA	MTAA	1.8	0.36	0.36						
HBAA	MBAA	2.7	0.9 ~ 0.72	0.9 ~ 0.72						
HCBB105		2.7	3.0 ~ 2.7	3.0 ~ 2.7						
HCAA	MCAA	5.4	0.9 ~ 0.72	0.9 ~ 0.72						
CP131		7.2	1.53 ~ 1.35	1.53 ~ 1.35						
HDBB		10.8	1.53 ~ 1.35	1.53 ~ 1.35						
HDCC		10.8	3.0 ~ 2.7	3.0 ~ 2.7						
HCBB75	MCBB75	5.4	1.5 ~ 1.35	1.5 ~ 1.35						

CUSTOM DESIGN







Tell us your power specifications and our design engineers will customize a solution.

Standard, Modified or Custom – our design engineers deliver solutions satisfying the most demanding requirements.

SL Power Electronics has sales and engineering teams in five offices on three continents to serve your power needs for internal or external switch-mode power supplies, linear power supplies, battery chargers or DC/DC mobile adapters.

Whether your device requires a specific voltage, rack mounting, unusual cabling or a special case design, SL Power's engineering teams can develop solutions to meet your unique requirements. They have the experience, knowledge and the creative talent to design power solutions using cutting edge technology and incorporating the latest components to optimize size, efficiency and performance.

OEMs often require special packaging requirements to meet stringent safety approval standards. SL Power Electronics has developed packaging to meet safety standards for power supplies exposed to water (IPX standard). Many market segments are interested in this unique design capability including medical, industrial and consumer OEMs.



With the growing popularity of portable products, SL Power Electronics' custom capabilities include designing power solutions that simplify the use of electronic devices at home, on vacation or while travelling worldwide for business.

SL Power Electronics is the choice of leading OEMs in commercial/ITE and medical device markets. Customers prefer to work with us because of our dedication to meeting their unique power requirements. We provide unparalleled experience at every critical stage of your project – design engineering expertise to modify an existing power supply or design a 100% custom solution; world-class manufacturing to ensure the processes are in place to replicate products to the most stringent requirements; and global sales and technical support to meet on-going needs.



UK: Crown Yealm House, Pathfields Business Park, South Molton, EX36 3LH, UK Tel: +44 (0)1769 579505 Fax: +44 (0)1769 579494 Email: euinfo@SLPower.com

USA: SL Power Electronics Corp, 6050 King Drive, Ventura, CA 93030 Tel: (+1) 805 486 4565 Germany: SL Power Electronics, Opelstrasse 2D, Moerfelden 64546 Tel +49 (0) 6105 297783

www.slpower.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

SL Power:
GPHP1000-48R

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

многоканальный

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru_4 moschip.ru_9