

S505H

5 mm x 20 mm 400 Vdc/500-600 Vac time-delay fuses



Applications

- Power supplies - adapters
- Desktops/notebooks
- TVs / Displays
- Set top boxes
- Lighting ballasts
- Battery chargers
- Printers
- Game systems
- Air conditioners

Product features

- 400 Vdc/500-600 Vac rating
- Time-delay, high breaking capacity
- 5 mm x 20 mm physical size
- Ceramic tube with plated end cap construction
- Designed to IEC 60127-2, Standard, Sheet 5
- RoHS Compliant, lead free and halogen free
- Optional axial leads available

| Electrical Characteristics | | | | | | | | |
|----------------------------|-------------------|-------------------|--------------------|-------|-----------------|-------|------------------|--------|
| Amps | 1.5I _n | 2.1I _n | 2.75I _n | | 4I _n | | 10I _n | |
| | Min min. | Max min. | Min ms | Max s | Min ms | Max s | Min ms | Max ms |
| <1A | >60 | <30 | >250 | <80 | >50 | <5 | >5 | <150 |
| 1A-3.15A | >60 | <30 | >750 | <80 | >95 | <5 | >10 | <150 |
| 4A-6.3A | >60 | <30 | >750 | <80 | >150 | <5 | >10 | <150 |
| 8A-10A | >30 | <30 | >750 | <80 | >150 | <5 | >10 | <150 |

Agency information

S505H-XXX-R (Ferrule)

- cURus approval: Guide JFHR2, File E56412 and Guide JFHR8, File E56412 (500 mA - 10 A)
- CCC Approval: 500 mA - 10 A, Cert. No.: 2010010207395946
- TUV Approval: 2 A - 10 A, Cert. No.: R50297821
- PSE Approval: 1 A - 5 A, Cert. No.: JET1641-31003-1017
6.3 A - 10 A, Cert. No.: JET1641-31003-2001

S505H-V-XXX-R (Axial Leads)

- PSE Approval: 1 A - 5 A, Cert. No.: JET1641-31003-1018;
6.3 A - 10 A, Cert. No.: JET1641-31003-2002
- cURus approval: Guide JFHR2, File E56412 and Guide JFHR8, File E56412 (500 mA - 10 A)
- CCC Approval: 500 mA - 10 A, Cert. No.: 2010010207395946

Specifications

| Catalog number | Voltage rating Vac | Max. voltage rating | | Interrupting rating (A) under max voltage | | | Typical DC cold resistance Ω ³ | Typical voltage drop (mV) ⁴ | Typical value I ² t (A ² s) ⁵ | Agency approvals | | | | |
|----------------|--------------------|---------------------|-----|---|-----------|---------|---|--|--|------------------|------------------|---------|--------------------|---|
| | | | | 250 Vac | Max Volts | 400 Vdc | | | | 250 Vac | | | | |
| | | AC | DC | | | | | | | TUV | CCC ⁶ | PSE/JET | cURus ² | |
| S505H-500-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.507 | 295 | 0.188 | | | | | x |
| S505H-800-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.237 | 189 | 0.632 | | | | | x |
| S505H-1-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.14 | 153 | 1.28 | | | | X | x |
| S505H-1.25-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.108 | 150 | 2.22 | | | | X | x |
| S505H-1.6-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.07 | 125 | 6.78 | | | | X | x |
| S505H-2-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.055 | 128 | 11.44 | X | X | X | X | x |
| S505H-2.5-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.04 | 126 | 24.23 | X | X | X | X | x |
| S505H-3.15-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.031 | 121 | 43.55 | X | X | X | X | x |
| S505H-4-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.019 | 90 | 38.45 | X | X | X | X | x |
| S505H-5-R | 250 | 600 | 400 | 1500 | 100 | 1500 | 0.015 | 89 | 71.3 | X | X | X | X | x |
| S505H-6.3-R | 250 | 500 | 400 | 1500 | 100 | 1500 | 0.011 | 80 | 111.4 | X | X | X | X | x |
| S505H-8-R | 250 | 500 | 400 | 1500 | 100 | 1500 | 0.007 | 76 | 228.2 | X | | | X | x |
| S505H-10-R | 250 | 500 | 400 | 1500 | 100 | 1500 | 0.006 | 72 | 349.5 | X | | | X | x |

1. Max. voltage rating: Base on the breaking capacity test according to UL.
 2. - Breaking capacity of 250 VAC/1500 A is tested by all agency approvals, test condition is 250 Vac, PF: 0.7-0.8.
 - Breaking capacity of Max. voltage is tested by UL, PF:1. (500 mA - 5 A @ 600Vac, 6.3 A - 10 A @ 500 Vac)
 - Breaking capacity test of DC is tested by UL under Capacitor Bank 4800 mF (for 400 V, 1500 A), 2400 mF (for 400 V, 500 A).

3. Cold resistance: measure at <10% rated current.
 4. Typical voltage drop: voltage drop is measured under ambient +20 °C with rated current
 5. Typical pre-arc I²t: Measured at 10I_n DC
 6. Does not apply to axial leaded versions.
 7. 600/500 Vac, 400 Vdc.



Powering Business Worldwide

Dimensions - mm



A (ref): 0.65 mm (0.5 A - 6.3 A), 0.80 mm (8 A-10 A)

Time-Current Curves



Construction



500-800mA



1-1.6 Amps



2 Amps & Above

1. Ceramic Tube
2. Wire Fuse Element
3. Plated Fuse Cap
4. Filler
5. Solder
6. Eyelet



Axial Leaded Versions

1. S505H-XXX-R
2. Axial Leaded Cap

Wave Soldering Parameters (axial lead only)

Note: These devices are NOT recommended for IR or convection reflow processes.



- Reservoir Temperature: +260°C ± 3°C
- Soldering Time: 10 seconds max.

Recommended Hand Solder Parameters

- Soldering Iron Tip Temperature: +350°C ± 5°C
- Heating Time: 5 seconds max.

Operating Temperature Range

- -55 °C to +125 °C (see temperature derating curve below for percentage of fuse rating per ambient temperature)

Temperature Derating Curve



| Packaging Code | |
|-----------------------|--|
| Packaging Code Prefix | Description |
| BK- | 100 fuses packed into a cardboard carton with flaps folded |
| BK1- | 1000 fuses packed into a poly bag |
| TR2- | 1500 axial leaded fuses on tape and reel |
| Option Code | |
| Option Code | Description |
| -V | Axial leads – copper tinned wire with nickel plated brass end caps |
| -R | RoHS compliant version |

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
 1000 Eaton Boulevard
 Cleveland, OH 44122
 United States
 Eaton.com/electronics

© 2019 Eaton
 All Rights Reserved
 Printed in USA
 Publication No. 4406 PCN19017M
 December 2019

Eaton is a registered trademark.
 All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.



Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9