

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AM3	REVISED PER ECO-11-004587	11MAR11	RK	HMR

1. FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7532.

2. SWITCH SHOWN IN OPEN POSITION.

3. ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLUE.

4. STAMPING WILL VARY ON 2 AND 3 POSITION SIDES DUE TO SPACE RESTRICTIONS.

5

.315 DIMENSION APPLIES AT TERMINAL TIPS.

TERMINALS ARE .300^{+.010}-.000 AT MOUNTING SURFACE.

6

STRIPPABLE TRANSPARENT SEAL, SEE FIG 1.

7	OBSOLETE	FIG 6	-----	1.08	10	6-435640-1	
			-----	.58	5	6-435640-0	
7	OBSOLETE	FIG 7	-----	.48	4	5-435640-9	
			-----	.88	8	5-435640-8	
			-----	.98	9	5-435640-7	
7	OBSOLETE	FIG 5	6	.68	6	5-435640-6	
				.58	5	5-435640-5	
				.48	4	5-435640-4	
		FIG 2	6	.88	8	5-435640-3	
	OBSOLETE	FIG 5	6	.88	8	5-435640-2	
				1.08	10	5-435640-1	
		FIG 3	6	.88	8	5-435640-0	
				.88	8	4-435640-9	
				.58	5	4-435640-8	
7	SUPSD BY 4-5435640-8	NONE	-----	1.08	10	4-435640-7	
				1.28	12	4-435640-3	
				1.08	10	4-435640-1	
				.98	9	4-435640-0	
				.88	8	3-435640-9	
				.78	7	3-435640-8	
				.68	6	3-435640-7	
				.58	5	3-435640-6	
				.48	4	3-435640-5	
				.38	3	3-435640-4	
				.28	2	3-435640-3	
	SUPSD BY 3-435668-3	FIG 4	-----	1.28	12	3-435640-2	
	SUPSD BY 2-435668-6 3-1589670-4		-----	.38	3	3-435640-0	
			-----	.28	2	2-435640-9	
		OBSOLETE	FIG 2	-----	.78	7	2-435640-2
				1.08	10	435640-7	
				.98	9	435640-6	
				.88	8	435640-5	
				.68	6	435640-4	
				.58	5	435640-3	
				.48	4	435640-2	
				.78	7	435640-1	
		TOP MARKING		A	NO OF POSN	PART NO.	

435640-4 SHOWN

TE Connectivity

SWITCH ASSY, DIP, TYPE C, 7100 SERIES, SPST, STANDARD

SIZEA2

CAGE CODE00779

DRAWING NOC=435640

RESTRICTED TO-

SCALE4:1

SHEET1 of 1

REVAM3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN15NOV89

CHK06MAR90

APVD06MAR90

PRODUCT SPEC

APPLICATION SPEC

WEIGHT-

CUSTOMER DRAWING

DIMENSIONS: INCHES

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± .005

4 PLC ± -

ANGLES ± -

FINISH

CONTACTS: PLATED .000030 MIN GOLD IN CONTACT AREA OVER .000050 MIN NICKEL

MATERIAL

HOUSING & ROCKERS: POLYESTER

CONTACTS: COPPER ALLOY

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AM3	REVISED PER ECO-11-004587	11MAR11	RK	HMR

1. FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7532.

2. SWITCH SHOWN IN OPEN POSITION.

3. ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLUE.

4. STAMPING WILL VARY ON 2 AND 3 POSITION SIDES DUE TO SPACE RESTRICTIONS.

5

.315 DIMENSION APPLIES AT TERMINAL TIPS.

TERMINALS ARE .300^{+.010}-.000 AT MOUNTING SURFACE.

6

STRIPPABLE TRANSPARENT SEAL, SEE FIG 1.

7	OBSOLETE	FIG 6	-----	1.08	10	6-435640-1	
			-----	.58	5	6-435640-0	
7	OBSOLETE	FIG 7	-----	.48	4	5-435640-9	
			-----	.88	8	5-435640-8	
			-----	.98	9	5-435640-7	
7	OBSOLETE	FIG 5	6	.68	6	5-435640-6	
				.58	5	5-435640-5	
				.48	4	5-435640-4	
		FIG 2	6	.88	8	5-435640-3	
	OBSOLETE	FIG 5	6	.88	8	5-435640-2	
				1.08	10	5-435640-1	
		FIG 3	6	.88	8	5-435640-0	
				.88	8	4-435640-9	
				.58	5	4-435640-8	
7	SUPSD BY 4-5435640-8	NONE	-----	1.08	10	4-435640-7	
				1.28	12	4-435640-3	
				1.08	10	4-435640-1	
				.98	9	4-435640-0	
				.88	8	3-435640-9	
				.78	7	3-435640-8	
				.68	6	3-435640-7	
				.58	5	3-435640-6	
				.48	4	3-435640-5	
				.38	3	3-435640-4	
				.28	2	3-435640-3	
	SUPSD BY 3-435668-3	FIG 4	-----	1.28	12	3-435640-2	
	SUPSD BY 2-435668-6 3-1589670-4		-----	.38	3	3-435640-0	
			-----	.28	2	2-435640-9	
		OBSOLETE	FIG 2	-----	.78	7	2-435640-2
				1.08	10	435640-7	
				.98	9	435640-6	
				.88	8	435640-5	
				.68	6	435640-4	
				.58	5	435640-3	
				.48	4	435640-2	
				.78	7	435640-1	
		TOP MARKING		A	NO OF POSN	PART NO.	

435640-4 SHOWN

TE Connectivity

SWITCH ASSY, DIP, TYPE C, 7100 SERIES, SPST, STANDARD

SIZEA2

CAGE CODE00779

DRAWING NOC=435640

RESTRICTED TO-

SCALE4:1

SHEET1 of 1

REVAM3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN15NOV89

CHK06MAR90

APVD06MAR90

PRODUCT SPEC

APPLICATION SPEC

WEIGHT-

CUSTOMER DRAWING

DIMENSIONS: INCHES

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± .005

4 PLC ± -

ANGLES ± -

FINISH

CONTACTS: PLATED .000030 MIN GOLD IN CONTACT AREA OVER .000050 MIN NICKEL

MATERIAL

HOUSING & ROCKERS: POLYESTER

CONTACTS: COPPER ALLOY

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AM3	REVISED PER ECO-11-004587	11MAR11	RK	HMR

1. FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7532.

2. SWITCH SHOWN IN OPEN POSITION.

3. ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLUE.

4. STAMPING WILL VARY ON 2 AND 3 POSITION SIDES DUE TO SPACE RESTRICTIONS.

5

.315 DIMENSION APPLIES AT TERMINAL TIPS.

TERMINALS ARE .300^{+.010}-.000 AT MOUNTING SURFACE.

6

STRIPPABLE TRANSPARENT SEAL, SEE FIG 1.

7	OBSOLETE	FIG 6	-----	1.08	10	6-435640-1	
			-----	.58	5	6-435640-0	
7	OBSOLETE	FIG 7	-----	.48	4	5-435640-9	
			-----	.88	8	5-435640-8	
			-----	.98	9	5-435640-7	
7	OBSOLETE	FIG 5	6	.68	6	5-435640-6	
				.58	5	5-435640-5	
				.48	4	5-435640-4	
		FIG 2	6	.88	8	5-435640-3	
	OBSOLETE	FIG 5	6	.88	8	5-435640-2	
				1.08	10	5-435640-1	
		FIG 3	6	.88	8	5-435640-0	
				.88	8	4-435640-9	
				.58	5	4-435640-8	
7	SUPSD BY 4-5435640-8	NONE	-----	1.08	10	4-435640-7	
				1.28	12	4-435640-3	
				1.08	10	4-435640-1	
				.98	9	4-435640-0	
				.88	8	3-435640-9	
				.78	7	3-435640-8	
				.68	6	3-435640-7	
				.58	5	3-435640-6	
				.48	4	3-435640-5	
				.38	3	3-435640-4	
				.28	2	3-435640-3	
	SUPSD BY 3-435668-3	FIG 4	-----	1.28	12	3-435640-2	
	SUPSD BY 2-435668-6 3-1589670-4		-----	.38	3	3-435640-0	
			-----	.28	2	2-435640-9	
		OBSOLETE	FIG 2	-----	.78	7	2-435640-2
				1.08	10	435640-7	
				.98	9	435640-6	
				.88	8	435640-5	
				.68	6	435640-4	
				.58	5	435640-3	
				.48	4	435640-2	
				.78	7	435640-1	
		TOP MARKING		A	NO OF POSN	PART NO.	

435640-4 SHOWN

TE Connectivity

SWITCH ASSY, DIP, TYPE C, 7100 SERIES, SPST, STANDARD

SIZEA2

CAGE CODE00779

DRAWING NOC=435640

RESTRICTED TO-

SCALE4:1

SHEET1 of 1

REVAM3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN15NOV89

CHK06MAR90

APVD06MAR90

PRODUCT SPEC

APPLICATION SPEC

WEIGHT-

CUSTOMER DRAWING

DIMENSIONS: INCHES

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± .005

4 PLC ± -

ANGLES ± -

FINISH

CONTACTS: PLATED .000030 MIN GOLD IN CONTACT AREA OVER .000050 MIN NICKEL

MATERIAL

HOUSING & ROCKERS: POLYESTER

CONTACTS: COPPER ALLOY

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AM3	REVISED PER ECO-11-004587	11MAR11	RK	HMR

1. FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7532.

2. SWITCH SHOWN IN OPEN POSITION.

3. ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLUE.

4. STAMPING WILL VARY ON 2 AND 3 POSITION SIDES DUE TO SPACE RESTRICTIONS.

5

.315 DIMENSION APPLIES AT TERMINAL TIPS.

TERMINALS ARE .300^{+.010}-.000 AT MOUNTING SURFACE.

6

STRIPPABLE TRANSPARENT SEAL, SEE FIG 1.

7	OBSOLETE	FIG 6	-----	1.08	10	6-435640-1	
			-----	.58	5	6-435640-0	
7	OBSOLETE	FIG 7	-----	.48	4	5-435640-9	
			-----	.88	8	5-435640-8	
			-----	.98	9	5-435640-7	
7	OBSOLETE	FIG 5	6	.68	6	5-435640-6	
				.58	5	5-435640-5	
				.48	4	5-435640-4	
		FIG 2	6	.88	8	5-435640-3	
	OBSOLETE	FIG 5	6	.88	8	5-435640-2	
				1.08	10	5-435640-1	
		FIG 3	6	.88	8	5-435640-0	
				.88	8	4-435640-9	
				.58	5	4-435640-8	
7	SUPSD BY 4-5435640-8	NONE	-----	1.08	10	4-435640-7	
				1.28	12	4-435640-3	
				1.08	10	4-435640-1	
				.98	9	4-435640-0	
				.88	8	3-435640-9	
				.78	7	3-435640-8	
				.68	6	3-435640-7	
				.58	5	3-435640-6	
				.48	4	3-435640-5	
				.38	3	3-435640-4	
				.28	2	3-435640-3	
	SUPSD BY 3-435668-3	FIG 4	-----	1.28	12	3-435640-2	
	SUPSD BY 2-435668-6 3-1589670-4		-----	.38	3	3-435640-0	
			-----	.28	2	2-435640-9	
		OBSOLETE	FIG 2	-----	.78	7	2-435640-2
				1.08	10	435640-7	
				.98	9	435640-6	
				.88	8	435640-5	
				.68	6	435640-4	
				.58	5	435640-3	
				.48	4	435640-2	
				.78	7	435640-1	
		TOP MARKING		A	NO OF POSN	PART NO.	

435640-4 SHOWN

TE Connectivity

SWITCH ASSY, DIP, TYPE C, 7100 SERIES, SPST, STANDARD

SIZEA2

CAGE CODE00779

DRAWING NOC=435640

RESTRICTED TO-

SCALE4:1

SHEET1 of 1

REVAM3

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN15NOV89

CHK06MAR90

APVD06MAR90

PRODUCT SPEC

APPLICATION SPEC

WEIGHT-

CUSTOMER DRAWING

DIMENSIONS: INCHES

0 PLC ± -

1 PLC ± -

2 PLC ± -

3 PLC ± .005

4 PLC ± -

ANGLES ± -

FINISH

CONTACTS: PLATED .000030 MIN GOLD IN CONTACT AREA OVER .000050 MIN NICKEL

MATERIAL

HOUSING & ROCKERS: POLYESTER

CONTACTS: COPPER ALLOY

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

© COPYRIGHT - By - ALL RIGHTS RESERVED.

LOCAD

DIST00

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	AM3	REVISED PER ECO-11-004587	11MAR11	RK	HMR

1. FOR ADDITIONAL SPECIFICATIONS SEE AMP PRODUCT SPEC 108-7532.

2. SWITCH SHOWN IN OPEN POSITION.

3. ALL CHARACTERS AND ROCKERS ARE WHITE, HOUSING IS BLUE.

4. STAMPING WILL VARY ON 2 AND 3 POSITION SIDES DUE TO SPACE RESTRICTIONS.

5

.315 DIMENSION APPLIES AT TERMINAL TIPS.

TERMINALS ARE .300^{+.010}-.000 AT MOUNTING SURFACE.

6

STRIPPABLE TRANSPARENT SEAL, SEE FIG 1.

7	OBSOLETE	FIG 6	-----	1.08	10	6-435640-1
			-----	.58	5	6-435640-0
7	OBSOLETE	FIG 7	-----	.48	4	5-435640-9
			-----	.88	8	5-435640-8
			-----	.98	9	5-435640-7
7	OBSOLETE	FIG 5	6	.68	6	5-435640-6
				.58	5	5-435640-5
				.48	4	5-435640-4
		FIG 2	6	.88	8	5-435640-3
	OBSOLETE	FIG 5	6	.88	8	5-435640-2
				1.08	10	5-435640-1
		FIG 3	6	.88	8	5-435640-0
				.88	8	4-435640-9
				.58	5	4-435640-8
7	SUPSD BY 4-5435640-8	NONE	-----	1.08	10	4-435640-7
				1.28	12	4-435640-3
				1.08	10	4-435640-1
				.98	9	4-435640-0
				.88	8	3-435640-9
				.78	7	3-435

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9