

CHIP NOISE FILTER NFZ18SM□□□SN10D REFERENCE SPECIFICATION

1. Scope

This reference specification applies to Chip Noise Filter NFZ18SM SN10 Series.

2. Part Numbering

NF 18 SM121 S Ν (ex) Product ID Structure Dimension Characteristics Typical Impedance Performance Category special Packaging Numbers $(L \times W)$ at 100MHz of speci- D:Taping fication *B: BULK Circuit


*B: Bulk packing also available

3. Rating

Operating Temperature Range
 Storage Temperature Range
 55°C to +125°C
 55°C to +125°C

Customer	MURATA	Impedance at 100 MHz		DC Resistance		Rated Current (mA)	
Part Number	Part Number	(Ω)	Tolerance	(Ω)	MAX.	85°C*1	125°C ^{*1}
	NFZ18SM121SN10D	120		0.11	0.14	1250	1100
	NFZ18SM251SN10D	250	±25%	0.15	0.19	1100	1000
	NFZ18SM501SN10D	500	±25%	0.20	0.25	950	850
	NFZ18SM701SN10D	700		0.23	0.29	800	800

(*1) As for the rated current, Rated Current derated as right figure depending on the operating temperature.



4. Testing Conditions


《Unless otherwise specified》 《In case of doubt》

Temperature : Ordinary Temperature / 15°C to 35°C Temperature : 20°C ± 2°C

Humidity : Ordinary Humidity / 25%(RH) to 85%(RH) Humidity : 60%(RH) to 70%(RH)

Atmospheric Pressure: 86kPa to 106kPa

5. Appearance and Dimensions



MURATA MFG.CO., LTD



6. Electrical Performance

No.	Item	Specification	Test Method
6.1	Impedance	Impedance shall meet item 3.	Measuring Equipment:
			Agilent 4991A or equivalent (50mV) Measuring Frequency: 100MHz
6.2	DC Resistance	DC Resistance shall meet item 3.	Measuring Equipment: Digital multi meter
			Digital multi meter (TR6846 or equivalent) a terminal 1— SW terminal 2
			DC resistance shall be measured after putting chip noise filter between the terminal 2 under the condition of opening between a and b. Every measurement the terminal 1 shall be shorted between a and b when changing noise filter.

7. Mechanical Performance

No.	Item	Specification	Test Method
7.1	Shear Test	Chip noise filter shall not be damaged after tested as follows.	Applied Direction CHIP NOISE FILTER
			Substrate F
			Force: 10N
			Hold Duration: 5s±1s
			Applied Direction: Parallel to PCB
7.2	Bending Test		Substrate: Glass-epoxy substrate
			(100mm×40mm×1.0mm) Solder: Reflow
			Pressure jig
			R230 \ F
			Deflection
			Speed of Applying Force: 0.5mm / s
			Deflection: 2mm
			Hold Duration: 30 s
7.3	Vibration		Oscillation Frequency:
			10Hz to 2000Hz to 10Hz for 20 min
			Total amplitude 3.0 mm or Acceleration amplitude 245m/s ² whichever is smaller.
			Testing Time:
			A period of 4h in each of 3 mutually
			perpendicular directions.
7.4	Drop		It shall be dropped on concrete or steel
			board.
			Method : free fall
			Height: 1m
			Total of 10 cycles



No.	Item	Specification	Test Method
7.5	Solderability	The wetting area of the electrode	Flux: Ethanol solution of rosin 25(wt)%
		shall be at least 90% covered with	(Immersed for 5s to 10s)
		new solder coating.	Solder: Sn-3.0Ag-0.5Cu
			Pre-Heating: 150°C±10°C / 60s to 90s
			Solder Temperature: 240°C±5°C
			Immersion Time: 3s±1s
7.6	Resistance to	Appearance: No damage	Flux: Ethanol solution of rosin 25(wt)%
	Soldering Heat	Impedance Change: within ±30%	(Immersed for 5s to 10s)
			Solder: Sn-3.0Ag-0.5Cu
			Pre-Heating: 150°C±10°C / 60s to 90s
			Solder Temperature: 270°C±5°C
			Immersion Time: 10s±1s
			Then measured after exposure in the room
			condition for 24h±2h.

8. Environmental Performance


It shall be soldered on the substrate.

No.	Item	Specification	Test Method
8.1	Heat Resistance	Appearance: No damage	Temperature: 125°C±2°C
		Impedance Change: within ±30%	Time: 1000h (+48h,-0h)
			Then measured after exposure in the room
			condition for 24h±2h.
8.2	Cold Resistance		Temperature: -55°C±2°C
			Time: 1000h (+48h,-0h)
			Then measured after exposure in the room
			condition for 24h±2h.
8.3	Humidity		Temperature: 40°C±2°C
			Humidity: 90%(RH) to 95%(RH)
			Time: 1000h (+48h,-0h)
			Then measured after exposure in the room
			condition for 24h±2h.
8.4	Temperature		1 cycle:
	Cycle		1 step: -55°C±2°C / 30 min±3 min
			2 step: Ordinary temp. / 10 min to 15 min
			3 step: 125°C±2°C / 30 min to 3 min
			4 step: Ordinary temp. / 10 min to15 min
			Total of 100cycles
			Then measured after exposure in the room
			condition for 24h±2h.



9. Specification of Packaging

9.1 Appearance and Dimensions of plastic tape (8mm-wide)



Dimension of the Cavity is measured at the bottom side.

9.2 Specification of Taping

(1) Packing quantity (standard quantity)

4,000 pcs / reel

(2) Packing Method

Products shall be packed in the cavity of base tape continuously and sealed by top tape And bottom tape.

(3) Sprocket hole

The sprocket holes are to the right as the tape is pulled toward the user.

(4) Spliced point

The base tape and top tape has no spliced point.

(5) Missing components number


Missing components number within 0.1% of the number per reel or 1 pc., whichever is greater, and are not continuous. The Specified quantity per reel is kept.

9.3 Pull Strength

Top tape	EN main
Bottom tape	5N min.


9.4 Peeling off force of cover tape

Speed of Peeling off	300mm / min	
Peeling off force	Plastic tape: 0.1N to 0.6N	
Feeling on loice	(minimum value is typical)	



9.5 Dimensions of Leader-tape, Trailer and Reel

There shall be leader-tape (top tape) and trailer-tape (empty tape) as follows.



MURATA MFG.CO., LTD

9.6 Marking for reel

Customer part number, MURATA part number, Inspection number (*1), RoHS marking (*2), Quantity etc · · ·

*1) < Expression of Inspection No.>

□□ <u>0000</u> <u>×××</u>

(1) Factory Code

(2) Date First digit

: Year / Last digit of year

: Month / Jan. to Sep. \rightarrow 1 to 9, Oct. to Dec. \rightarrow O, N, D Second digit

Third, Fourth digit: Day

(3) Serial No.

*2) <Expression of RoHS marking >

ROHS
$$-\underline{Y}(\underline{\Delta})$$


(1) RoHS regulation conformity parts.

(2) MURATA classification number

9.7 Marking for Outside package (corrugated paper box)

Customer name, Purchasing order number, Customer part number, MURATA part number, RoHS marking (*2), Quantity, etc · · ·

9.8 Specification of Outer Case



Outer Case Dimensions (mm)			Standard Reel Quantity
W	D	Н	in Outer Case (Reel)
186 186 93		93	5

* Above Outer Case size is typical. It depends on a quantity of an order

10. 🗥 Caution

Limitation of Applications

Please contact us before using our products for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property.


- (1) Aircraft equipment
- Aerospace equipment
- (3) Undersea equipment
- (4) Power plant control equipment
- (5) Medical equipment
- (6) Transportation equipment (vehicles, trains, ships, etc.)
- (7) Traffic signal equipment
- (8) Disaster prevention / crime prevention equipment
- (9) Data-processing equipment (10) Applications of similar complexity and /or reliability requirements to the applications listed in the above

11. Notice

This product is designed for solder mounting.

Please consult us in advance for applying other mounting method such as conductive adhesive.

11.1 Land pattern designing



Reted Current	a b	С	Land pad thickness and dimension d			
(A)	٦			18µm	35µm	70µm
0~1.25	0.7	1.8to2.0	0.7	0.7	0.7	0.7

(in mm)



11.2 Flux, Solder

·Use rosin-based flux.

Don't use highly acidic flux with halide content exceeding 0.2(wt) % (chlorine conversion value). Don't use water-soluble flux.

- Use Sn-3.0Ag-0.5Cu solder.
- •Standard thickness of solder paste: $100 \,\mu$ m to $200 \,\mu$ m.

11.3 Reflow soldering conditions


•Pre-heating should be in such a way that the temperature difference between solder and product surface is limited to 150°C max. Cooling into solvent after soldering also should be in such a way that the temperature difference is limited to 100°C max.

Insufficient pre-heating may cause cracks on the product, resulting in the deterioration of products quality.

•Standard soldering profile and the limit soldering profile is as follows.

The excessive limit soldering conditions may cause leaching of the electrode and/or resulting in the deterioration of product quality.

Soldering Profile for Lead Free solder



	Standard Profile	Limit Profile
Pre-heating	150°C∼180°C, 90s±30s	
Heating	above 220°C, 30s∼60s	above 230°C, 60s max.
Peak temperature	245°C±3°C	260°C, 10s
Cycle of reflow	2 times	2 times

11.4 Reworking with soldering iron


The following conditions must be strictly followed when using a soldering iron.

Pre-heating	150°C, 1 min
Tip temperature	350°C max.
Soldering iron output	80W max.
Tip diameter	ϕ 3mm max.
Soldering time	3(+1, -0)s
Time	2 times

Note :Do not directly touch the products with the tip of the soldering iron in order to prevent the crack on the ferrite material due to the thermal shock.

11.5 Solder Volume

- •Solder shall be used not to be exceeded the upper limits as shown below.
- •Accordingly increasing the solder volume, the mechanical stress to Chip is also increased. Exceeding solder volume may cause the failure of mechanical or electrical performance.






11.6 Product's location


The following shall be considered when designing and laying out P.C.B.'s.

(1) P.C.B. shall be designed so that products are not subject to the mechanical stress due to warping the board.



Products shall be located in the sideways direction (Length: a(b) to the mechanical stress.

(2) Products location on P.C.B. separation



Products (A, B, C, D) shall be located carefully so that products are not subject to the mechanical stress due to warping the board.

Because they may be subjected the mechanical stress in order of $A \cdot C \cdot B \cdot D$.

11.7 Cleaning Conditions

Products shall be cleaned on the following conditions.

- (1) Cleaning temperature shall be limited to 60°C max. (40°C max for IPA.)
- (2) Ultrasonic cleaning shall comply with the following conditions with avoiding the resonance phenomenon at the mounted products and P.C.B.

Power: 20 W / I max. Frequency: 28kHz to 40kHz Time: 5 min max.

- (3) Cleaner
 - 1. Alcohol type cleaner Isopropyl alcohol (IPA)
 - 2. Aqueous agent PINE ALPHA ST-100S
- (4) There shall be no residual flux and residual cleaner after cleaning. In the case of using aqueous agent, products shall be dried completely after rinse with de-ionized water in order to remove the cleaner.
- (5) Other cleaning Please contact us.

11.8 Resin coating

The impedance value may change and/or it may affect on the product's performance due to high cure-stress of resin to be used for coating/molding products. So please pay your careful attention when you select resin.

In prior to use, please make the reliability evaluation with the product mounted in your application set.

11.9 Caution for use


There is possibility that the impedance value change due to magnetism. Don't use a magnet or a pair of tweezers with magnetism when chip noise filters are handled. (The tip of the tweezers should be molded with resin or pottery.)


11.10 Handling of a substrate

After mounting products on a substrate, do not apply any stress to the product caused by bending or twisting to the substrate when cropping the substrate, inserting and removing a connector from the substrate or tightening screw to the substrate.

Excessive mechanical stress may cause cracking in the product.

Bending Twisting





Spec No. JENF243J-0007C-01



11.11 Storage and Handing Requirements

(1) Storage period

Use the products within 6 months after delivered. Solderability should be checked if this period is exceeded.

(2) Storage conditions

•Products should be stored in the warehouse on the following conditions.

Temperature : -10°C to 40°C

Humidity : 15% to 85% relative humidity No rapid change on temperature and humidity

Don't keep products in corrosive gases such as sulfur, chlorine gas or acid, or it may cause oxidization of electrode, resulting in poor solderability.

- Products should be stored on the palette for the prevention of the influence from humidity, dust and so on.
- Products should be stored in the warehouse without heat shock, vibration, direct sunlight and so on.
- •Products should be stored under the airtight packaged condition.

(3) Handling Condition

Care should be taken when transporting or handling product to avoid excessive vibration or mechanical shock.

12. /\ Note

- (1) Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
- (2) You are requested not to use our product deviating from the reference specifications.
- (3) The contents of this reference specification are subject to change without advance notice. Please approve our product specifications or transact the approval sheet for product specifications before ordering.

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru_4 moschip.ru_9