

# PVA Short Stroke Key Switches




A  
Pushbutton

## Features/Benefits

- **Compact design**
- **Short stroke to latch**
- **Wide variety of actuator heights**
- **Adapted for medium power applications**
- **RoHS compliant and compatible**

## Typical Applications

- **Automotive (air conditioning, lighting)**
- **Industrial**
- **Control panel**



## Construction

FUNCTION: Momentary, Push-Push  
CONTACT ARRANGEMENT:  
PVA1: 2 make contacts (DPST)  
PVA2: 2 change over contacts (DPDT)  
SWITCHING MODE: Non-shorting  
TERMINALS: PC pins<sup>1</sup>

## Mechanical

TOTAL TRAVEL / LATCHING TRAVEL:  
OA: 2,4 mm  
EE: 2,4 / 1,5 mm  
ELECTRICAL TRAVEL: 0.8 mm (1.1 for PVA2 OA H5)  
OPERATING FORCE: 1,2N; 1,7N; 3,5N

## Process

SOLDERABILITY:  
Wave soldering, compatible with lead free soldering profile  
Hand soldering, 350°C for 3 seconds

Note: Specifications listed above are for switches with standard options.  
For information on specific and custom switches, please contact technical support using the "Ask a Specialist" option on the PVA product web page.v

## Electrical

SWITCHING POWER MAX.: 3 W DC  
SWITCHING VOLTAGE MAX.: 32 V DC  
SWITCHING CURRENT MAX.: 100 mA DC\*  
DIELECTRIC STRENGTH (50 Hz / 1 min):  
1000 V between open contacts, PVA2: 750 V  
OPERATING LIFE:  
OA (momentary):  $\geq 1 \times 10^5$  operations  
EE (push-push):  $\geq 1 \times 10^5$  operations  
CONTACT RESISTANCE: Initial  $\leq 100 \text{ m}\Omega$   
INSULATION RESISTANCE:  $\geq 10^{10} \Omega$   
BOUNCE TIME:  $\leq 3 \text{ ms}$

## Environmental


OPERATING TEMPERATURE: -40°C to 85°C.<sup>2</sup>

- 1) "Snap-in" contacts on request, Version SNA with pins bent inside (standard)  
2) With button +70°C

## How To Order


Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box. **Some of the configurations may not be available or could require some development.**

### Switch



### Button

Buttons must be ordered separately.  
Shipped in bulk.



\*Compatible with H1 and H3 actuator models only.



24 may 19

Dimensions are shown: mm (inches)  
Specifications and dimensions subject to change




# PVA Short Stroke Key Switches



A

Pushbutton




SERIES



## PVA1 (DPST)



## PVA2 (DPDT)





## MECHANICAL FUNCTION





| OPTION CODE | FUNCTION  |
|-------------|-----------|
| OA          | Momentary |
| EE          | Push-Push |

OA



EE



# PVA Short Stroke Key Switches




A

Pushbutton


## TOTAL HEIGHT




**H1** 17,5 MM




**H2** 23 MM




**H3** 20,5 MM



**H4** 15 MM



**H5** 13 MM  
(MOMENTARY ONLY)



## OPERATING FORCE




**1.2N** PVA1 ONLY  
**1.7N** PVA2 ONLY  
**3.5N**


## TERMINATION



**SNA with PVA1**



**SNA with PVA2**




## BUTTONS




BUTTONS MUST BE ORDERED SEPARATELY. SHIPPED IN BULK.

**PE**



| OPTION CODE | COLOR |
|-------------|-------|
| <b>RD</b>   | Red   |
| <b>GY</b>   | Gray  |
| <b>BK</b>   | Black |
| <b>WH</b>   | White |

**PV**



## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9