





spec ref *				dr Louis Ng 2010/11/01		projection		mm		size A4		scale 11:10	
tolerance std ASME Y14.5 - TOLERANCES UNLESS OTHERWISE SPECIFIED				eng Nickor Zuo 2011/05/31						ecn no ELX-DG-003943-1			
				chr Alex Cao 2011/06/24						rel level Released			
				appr Pei-Ming Zheng 2011/06/27						product family GIG-Array			
surface ✓ - linear		0.X	±0.30			title 5mm RECEPTACLE ASSY. 200 SIG. POS. WITH NITROGEN BGA				dwg no 10097161		rev B	
		0.XX	±0.10										
		0.XXX	±0.05										
		angular		0°	±2°	www.fci.com		cat. no. *		Product - Customer Drw		sheet 1 of 5	




Copyright FCI.




spec ref *				dr	Louis Ng	2010/11/01	projection 	mm 	size	A4	scale	11:10
tolerance std ASME Y14.5 -	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Nickor Zuo	2011/05/31			ecn no	ELX-DG-003943-1		
				chr	Alex Cao	2011/06/24			rel level Released			
				appr	Pei-Ming Zheng	2011/06/27						product family GIG-Array
surface ✓ -	linear	0.X	±0.30		title 5mm RECEPTACLE ASSY. 200 SIG. POS. WITH NITROGEN BGA				dwg no 10097161	rev B		
		0.XX	±0.10									
		0.XXX	±0.05									
		angular	0°	±2°	www.fci.com	cat. no. *			Product - Customer Drw			sheet 2 of 5

PrintE File - REV C - 2009-06-09




RECEPTACLE INTERFACE DESCRIPTION


spec ref		*		dr	Louis Ng	2010/11/01	projection 	mm 	size	A4	scale	37:5
tolerance std ASME Y14.5 -	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Nickor Zuo	2011/05/31			ecn no	ELX-DG-003943-1		
				chr	Alex Cao	2011/06/24						
				appr	Pei-Ming Zheng	2011/06/27						
surface ✓ -	linear	0.X	±0.30		title 5mm RECEPTACLE ASSY. 200 SIG. POS. WITH NITROGEN BGA			dwg no	10097161		rev B	
		0.XX	±0.10									
		0.XXX	±0.05									
		angular	0°	±2°	www.fci.com	cat. no.	*	Product - Customer Drw		sheet 3 of 5		

ProjE File - REV C - 2009-06-09

FLAT AREA
FOR OPTIONAL
PICK-UP CAP
SCALE 2:1



DIM "A" REF.
MATED HEIGHT
AFTER REFLOW
SEE NOTE 3.





END VIEW OF MATED CONNECTORS
SCALE 2:1

DIM. "A"	PLUG ASSEMBLY P/N
15	55737
17	10026802
18	10060910
20	55738
25	55739
30	10054783

spec ref	*			dr	Louis Ng	2010/11/01	projection 	mm 	size	A4	scale	11:10	
tolerance std ASME Y14.5 -	TOLERANCES UNLESS OTHERWISE SPECIFIED			eng	Nickor Zuo	2011/05/31			ecn no	ELX-DG-003943-1			
				chr	Alex Cao	2011/06/24							
				appr	Pei-Ming Zheng	2011/06/27	product family		GIG-Array		rel level	Released	
surface ✓ -	linear	0.X	±0.30		title	5mm RECEPTACLE ASSY. 200 SIG. POS. WITH NITROGEN BGA			dwg no	10097161		rev	B
		0.XX	±0.10										
		0.XXX	±0.05										
		angular	0°	±2°	www.fci.com	cat. no.	*	Product - Customer Drw			sheet 4 of 5		



Copyright FCI.

1		2		3		4							
PRODUCT NUMBER		SOLDER BALL COMPOSITION		CONTACT PLATING PERFORMANCE LEVEL									
10097161-001		STANDARD (EUTECTIC)		PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-192, INCLUDING TELCORDIA CENTRAL OFFICE									
10097161-001LF		LEADFREE											
NOTES:													
① MATERIAL: HOUSING: LCP CONTACT: COPPER ALLOY PLATING (CONTACT): Au OVER Ni. UL RATING: 94 V-0 SOLDBALL: (SEE TABLE) EUTECTIC SnPb OR LEAD FREE 95.5 Sn/4Ag/0.5Cu. ② SOLDER BALLS WILL NOT BE PERFECT SPHERICAL SHAPE DUE TO REFLOW ATTACHMENT. ③ MATED HEIGHT EFFECTED BY CUSTOMERS' PCB PAD SIZE, PLATING, SOLDER REFLOW PROFILE & SOLDER PASTE. ④ CONTACTS IN ROWS A,C,E,G,J,K,M,P,R AND T ARE SINGLE BEAM CONTACTS, TYPICALLY USED AS GROUND PINS. (NOTE: CONTACTS IN ROWS J & K ARE TIED TOGETHER [COMMONED]) ⑤ CONTACTS IN ROWS B,D,F,H,L,N,Q AND S ARE DUAL BEAM CONTACTS, TYPICALLY USED AS SIGNAL PINS. ⑥ SPECIFIED POSITIONAL TOLERANCE DEFINES PAD TO PAD LOCATION WITHIN LAND PATTERN. POSITIONAL TOLERANCE OF LAND PATTERN TO FUDICIAL MARKS OR PCB DATUMS SHALL BE DEFINED BY CUSTOMER. FOR RECOMMENDED PRODUCT APPLICATION AND PCB DESIGN DETAILS, SEE DOC. NO. GS-20-016. ⑦ FOR PROPER APPLICATION FOLLOW FCI APPLICATION SPECIFICATION GS-20-033. LEAD FREE SOLDER BALLS WILL NOT SOLDER PROPERLY IN A LEADED SOLDER PROCESS DUE TO A HIGHER REFLOW TEMPERATURE. LEADFREE PRODUCT IS THEREFORE NOT BACKWARDS COMPATIBLE WITH LEADED OR SOME SOLDERING APPLICATIONS. REFERENCE FCI APPLICATION SPECIFICATION. ⑧ THIS PRODUCT MEETS THE EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008. PRODUCT MEETING THIS DIRECTIVE IS IDENTIFIED IN THE CODE NUMBER MARKED ON EACH PART BY HAVING AN "X" IN THE SEVENTH CHARACTER POSITION.													
spec ref		*		dr	Louis Ng	2010/11/01	projection 	mm 	size	A4	scale	1:10	
tolerance std	ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED		eng	Nickor Zuo	2011/05/31			ecn no	ELX-DG-003943-1			
				chr	Alex Cao	2011/06/24							
	-			appr	Pei-Ming Zheng	2011/06/27	product family	GIG-Array		rel level	Released		
surface		linear	0.X	±0.30		title	5mm RECEPTACLE ASSY. 200 SIG. POS. WITH NITROGEN BGA		dwg no	10097161		rev	B
			0.XX	±0.10									
			0.XXX	±0.05									
-		angular	0°	±2°	www.fci.com	cat. no.	*	Product - Customer Drw		sheet 5 of 5			

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9