

9907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

For more Information
please call

1-800-Belden1

**General Description:**

20 AWG stranded (19x32) .037" tinned copper conductor, foam polyethylene insulation, Duobond® II (100% coverage) plus an overall tinned copper braid shield (93% coverage), PVC jacket.

Usage (Overall)

Suitable Applications: Thin Ethernet

Physical Characteristics (Overall)**Conductor**

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	20	19x32	TC - Tinned Copper	.037

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
FHDPE - Foam High Density Polyethylene	.102

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Bonded Duofoil®	Tape	Bonded Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	93

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 0.185 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-40°C To +80°C
UL Temperature Rating:	60°C (UL AWM Style 1354)
Bulk Cable Weight:	23 lbs/1000 ft.
Max. Recommended Pulling Tension:	45 lbs.
Min. Bend Radius/Minor Axis:	2 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CL2, CM
CEC/C(UL) Specification:	CM
AWM Specification:	UL Style 1354 (30 V 60°C)
EU Directive 2011/65/EU (RoHS II):	Yes
IEEE Specification:	IEEE802.3 10Base2
Other Standards:	ISO8802.3 10Base2
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004

9907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Customer Part Number Reference Specification:	DEC Part No. 17-01248-00
RG Type:	58A/U

Flame Test

UL Flame Test:	UL1685 UL Loading
----------------	-------------------

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	82907, 89907

Electrical Characteristics (Overall)

Nom. Characteristic Impedance:

Impedance (Ohm)	Tolerance (Ohms)
50	+/- 2

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
25.4

Nominal Velocity of Propagation:

VP (%)
80

Nominal Delay:

Delay (ns/ft)
1.27

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
8.8

Maximum Loop Resistance:

Resistance (Ohm/1000 ft)
15.24

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
5.8

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1	.43
10	1.3
50	2.91
100	4.2
200	6.1
400	8.9
700	12.1
900	13.9
1000	14.8

Max. Operating Voltage - UL:

Voltage	Description
300 V RMS	
30 V RMS	UL AWM Style 1354

Notes (Overall)

Notes: Tape to bond at overlap area only. Tape is not designed to bond to dielectric core.

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
9907 E4XU1000	1,000 FT	24.000 LB	GRAY, LIGHT DEC		RG-58 TYPE COAX
9907 E4X1000	1,000 FT	25.000 LB	GRAY, LIGHT DEC	C	RG-58 TYPE COAX
9907 E4X1640	1,640 FT	41.000 LB	GRAY, LIGHT DEC	C	RG-58 TYPE COAX
9907 E4X2500	2,500 FT	62.500 LB	GRAY, LIGHT DEC	C	RG-58 TYPE COAX
9907 E4X3280	3,280 FT	82.000 LB	GRAY, LIGHT DEC	C	RG-58 TYPE COAX
9907 E4X500	500 FT	12.500 LB	GRAY, LIGHT DEC		RG-58 TYPE COAX

9907 Coax - Coaxial Cable - Thinnet 10Base2 Ethernet

9907 E4X5000	5,000 FT	125.000 LB	GRAY, LIGHT DEC		RG-58 TYPE COAX
--------------	----------	------------	-----------------	--	-----------------

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 09-25-2012

© 2014 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9