

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:

0528082270

Status:

Active

Overview:

Description:

1.00mm (.039") Pitch FFC/FPC Connector, SMT, Vertical, Non-ZIF Receptacle, 22 Circuits, Lead-free

EU RoHS

ELV and RoHS

Compliant

REACH SVHC

Contains SVHC: No

Halogen-Free

Status

Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

52808Series

Agency Certification

UL

E29179

General

Product Family

FFC/FPC Connectors

Series

52808

Overview

ffc_fpc_smt

Product Name

N/A

Physical

Circuits (Loaded)

22

Circuits (maximum)

22

Color - Resin

Natural

Contact Position

N/A

Durability (mating cycles max)

10

Entry Angle

N/A

Flammability

94V-0

Mated Height (in)

0.199 In

Mated Height (mm)

5.05 mm

Material - Metal

Phosphor Bronze

Material - Plating Mating

Tin-Bismuth

Material - Plating Termination

Tin-Bismuth

Material - Resin

High Temperature Thermoplastic

Number of Rows

1

Orientation

Vertical

PCB Locator

No

PCB Retention

None

Packaging Type

Embossed Tape on Reel

Pitch - Mating Interface (in)

0.039 In

Pitch - Mating Interface (mm)

1.00 mm

Pitch - Term. Interface (in)

0.039 In

Pitch - Term. Interface (mm)

1.00 mm

Plating min: Mating (µin)

40

Plating min: Mating (µm)

1

Plating min: Termination (µin)

40

Plating min: Termination (µm)

1

Polarized to PCB

No

Stackable

No

Surface Mount Compatible (SMC)

Yes

Temperature Range - Operating

-20°C to +80°C

Termination Interface: Style

Surface Mount

Wire/Cable Type

FFC/FPC

Electrical

Current - Maximum per Contact

0.5A

Voltage - Maximum

125V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Packaging Specification

SPK-52808-001

Product Specification

PS-52808-004, RPS-52808-039, RPS-52808-044,
RPS-52808-045, RPS-52808-047, RPS-52808-048,
RPS-52808-049
SD-52808-027, SD-52808-028

Sales Drawing

This document was generated on 06/05/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

F

E

D

C

B

A

F





E

D

C

B

A



33	31.05	29	52808-3019	30
32	30.05	28	-2919	29
31	29.05	27	-2819	28
30	28.05	26	-2719	27
29	27.05	25	-2619	26
28	26.05	24	-2519	25
27	25.05	23	-2419	24
26	24.05	22	-2319	23
25	23.05	21	-2219	22
24	22.05	20	-2119	21
23	21.05	19	-2019	20
22	20.05	18	-1919	19
21	19.05	17	-1819	18
20	18.05	16	-1719	17
19	17.05	15	-1619	16
18	16.05	14	-1519	15
17	15.05	13	-1419	14
16	14.05	12	-1319	13
15	13.05	11	-1219	12
14	12.05	10	-1119	11
13	11.05	9	-1019	10
12	10.05	8	-0919	9
11	9.05	7	-0819	8
10	8.05	6	-0719	7
9	7.05	5	-0619	6
8	6.05	4	-0519	5
7	5.05	3	52808-0419	4

注記 NOTES:

1. 使用材料 MATERIAL

ハウジング: PPS, UL94V-0

HOUSING: PPS, UL94V-0

ターミナル: リン青銅 ($t=0.25$)

TERMINAL: PHOSPHOR BRONZE

メッキ: ニッケル下地鍍ビスマスメッキ

PLATING: TIN-BISMUTH OVER NICKEL


△2 基準面 [E] からのソルダーテールの半田付け面のズレ量は、上方向に0.1MAX. 下方向0.15MAX. とする。

MISALIGNMENT OF SOLDER TAIL FROM [E]: UPPER DIRECTION 0.1 MAX., LOWER DIRECTION 0.15 MAX.

△3 偶数極に適用。
APPLY FOR EVEN CKT.

4. 本製品は52808-**-10の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 52808-**-10


REVISED EC NO: J2006-1497 DRWN: NABE1 CHKD: TOYODA APPR: NUKITA	DESCRIPTION 2005/11/04 2005/11/07 2005/11/11	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION	
		10 UNDER	± 0.2	DRAWN BY M. NABE1	DATE '04/02/19	TITLE 1.0 FFC CONN. NON ZIF SMT. ST. -LEAD FREE-			
		10 OVER 30 UNDER	± 0.25	CHECKED BY M. SASAO	DATE '04/02/19				
		30 OVER	± 0.3	APPROVED BY M. SASAO	DATE '04/02/19				
		ANGULAR ±3 °		MATERIAL NO.		DOCUMENT NO.		SHEET NO.	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-52808-027		1 OF 1		
A	REV	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							



打抜き方向は、導体側から補強板側を推奨いたします。
補強フィルム材質は、ポリイミドを推奨いたします。
接着剤は、熱硬化接着剤を推奨いたします。


RECOMMENDED MATERIAL :
STIFFENER FILM : POLYIMIDE
BONDING AGENT : TERMOSETTING BONDING AGENT

REVISED EC NO: J2006-1497 DWG: NABE1 CHKD: K TOYODA APPR: NUKITA	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE ---	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION		
		10 UNDER	± 0.2	M. NABE1	DATE '04/02/19	TITLE 1.0 FFC CONN. NON ZIF SMT. ST. -LEAD FREE-				
		10 OVER 30 UNDER	± 0.25	CHECKED BY M. SASAO	DATE '04/02/19					
		30 OVER	± 0.3	APPROVED BY M. SASAO	DATE '04/02/19	MOLEX MOLEX INCORPORATED				
		ANGULAR ±3 °		MATERIAL NO.		DOCUMENT NO.		SHEET NO.		
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE CHART		SD-52808-027		2 OF 2		
	REV	A	SIZE A3 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION							




NOTES

1. 製品詳細方法については図面 SD-52808-027 を参照下さい。
RE DETAILED DIMENSION, SEE SD-52808-027
2. 梱包数量: 10000個/リール
NUMBER OF CONNECTORS : 1000PCS/REEL
3. リーダーテープ長さ LEAD TAPE LENGTH




4. トッパテープの剥離強度: 0.1 ~ 1.3N (10 ~ 130gf) (剥離方向は下図参照)
- 尚、本規格値は出荷時に適用。(但し、輸送時に剥離が発生しないこと。)
- PEELING OFF FORCE OF TOP TAPE: 0.1 ~ 1.3N (10 ~ 130gf)
- (PEELING DIRECTION AS SHOWN IN FOLLOWING FIG.)
- THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT.
- PEEL OFF SHOULD NOT BE ALLOWED, DURING TRANSPORTATION.



5. 材料(MATERIAL)
キャリアテープ(CARRIER TAPE): ポリプロピレン(POLYPROPYLENE)
トップテープ(TOPTAPE): PET・PE・PEF
リール(REEL): ポリスチレン(PS) <リサイクル材を含む>
POLYSTYRENES) RECYCLE MATERIAL CONTAINED)
6. 本製品は52808-＊＊900の鉛フリー品である。
THIS PRODUCT IS LEAD FREE OF 52808-＊＊900


52808-***70	
MODEL NO.	
MOLEX-JAPAN CO.,LTD. (molex) 日本モリス株式会社	
REVISE ONLY ON CAD SYSTEM	
TITLE 名称	
1.0 FFC Conn NON ZIF	
SMT ST Embd'g PKg	
-LEAD FREE-	
DWG. NO.	(SHEET 1 OF 6) REV
SD-52808-028	0

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEKULAPLAN AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
 本図面は日本モレックス（株）の所有する情報を含むもので当社の許可なく複製を禁止する。
 EN-01C032IMXJ-32




SECTION-Y-Y

16mm幅キャリアテープ
16mm WIDTH CARRIER TAPE





引き出し方向
PULL OUT DIRECTION




SECTION-X-X
(SCALE:4-1)

52808-**-70		16		17.5	5.4	8.3	52808-0570	5
MODEL NO.		キャリアテープ幅 CARRIER TAPE WIDTH		C	(B)	(A)	MATERIAL NO.	極数 CKT.
		材料 MATERIAL		SHEET 1 OF 6 参照 REFER TO SHEET 1 OF 6		MOLEX-JAPAN CO.,LTD. モレックス株式会社		
		仕上げ FINISH		—#—		REVISE ONLY ON CAD SYSTEM		
		適用電線範囲 WIRE RANGE		—#—		TITLE 名称 I.O FFC CONN NON ZIF		
		挿入外径 INS. RANGE		—#—		SMT ST Embedd PKG		
		DRAWN BY 00/02/19 CHK'D BY 00/02/19 M.NABEI M.SASAO		尺 SCALE		—#—		
		DWC. NO. SD-52808-028		(SHEET 2 OF 6)		REV		
角 度 ANGLE		30°		30°				
30°以上 30°OFF		±0.2		±0.2				
10°以下 10°OFF		±0.25		±0.25				
10°以下 10°UNDER		±0.2		±0.2				
GENERAL TOLERANCES		記号 LTR		REVISION RECORD		DR-CHK. DATE		



SECT:Y-Y

引き出し方向
PULL OUT DIRECTION




SECT:X-X
(SCALE:4-1)



24mm幅キャリアテープ
24mm WIDTH CARRIER TAPE

52808-***70	24	25.5	10.4	13.3	52808-1070	10
			9.4	12.3	52808-0970	9
			8.4	11.3	52808-0870	8
			7.4	10.3	52808-0770	7
			6.4	9.3	52808-0670	6
MODEL NO.	キャリアテープ幅 CARRIER TAPE WIDTH	C	(B)	(A)	MATERIAL NO.	極数 CKT.

材料		SHEET 1 OF 6 参照		MATERIAL		SHEET 1 OF 6 参照	
仕上げ		FINISH		仕上げ		FINISH	
適用電線範囲		—#—		適用電線範囲		—#—	
絶縁外径		—#—		絶縁外径		—#—	
INS. RANGE		—#—		INS. RANGE		—#—	
DRAWN BY 04/02/19		CHK'D BY 04/02/19		DRAWN BY 04/02/19		CHK'D BY 04/02/19	
M.NABEI		M.SASAO		M.NABEI		M.SASAO	
APP'D BY 04/02/19		SCALE		APP'D BY 04/02/19		SCALE	
M.SASAO		—#—		M.SASAO		—#—	
DWG. NO.		(SHEET 3 OF 6)		DWG. NO.		(SHEET 3 OF 6)	
SD-52808-028		REV		SD-52808-028		REV	
0		0		0		0	



SECT:Y-Y



SECT:X-X
(SCALE:4-1)

32mm幅キャリアテープ
32mm WIDTH CARRIER TAPE

角度	ANGLE
30°以上	30°
10°以下	10°
未指定	未指定
10°以下	10°
未指定	未指定

記号	変更内容	DR-CHK.	DATE
0	新規作成 (12004-2528)	M.N.	M/W/2/9
1	変更内容	M.S.	M/S/2/9
2	変更内容	M.S.	M/S/2/9
3	変更内容	M.S.	M/S/2/9
4	変更内容	M.S.	M/S/2/9

MODEL NO.	キャリアテープ幅 CARRIER TAPE WIDTH	C	(B)	(A)	MATERIAL NO.	種数 CKT.
52808-**-70	32	33.5	15.4	18.3	52808-1570	15
			14.4	17.3	52808-1470	14
			13.4	16.3	52808-1370	13
			12.4	15.3	52808-1270	12
			11.4	14.3	52808-1170	11




材料
MATERIAL SHEET 1 OF 6 参照
REFER TO SHEET 1 OF 6

仕上げ
FINISH
適用電線範囲
WIRE RANGE
INS. RANGE

DRAWN BY M/W/2/9 CHK'D BY M/W/2/9
M.NABEI
M.SASAO

尺
SCALE
M.SASAO

DWG. NO. SD-52808-028 (SHEET 4 OF 6) REV 0



SECT:X-X
(SCALE:4-1)

SECT:Y-Y

引き出し方向
PULL OUT DIRECTION



NO.1 SIDE

44mm幅キヤリテータ
44mm WIDTH CARRIER TAPE

ACTIVE 0±0.2 1側 SIDE	44	45.5	28.4	31.3	52808-2870	28
			27.4	30.3	52808-2770	27
			26.4	29.3	52808-2670	26
			25.4	28.3	52808-2570	25
			24.4	27.3	52808-2470	24
			23.4	26.3	52808-2370	23
			22.4	25.3	52808-2270	22
			21.4	24.3	52808-2170	21
			20.4	23.3	52808-2070	20
			19.4	22.3	52808-1970	19
			18.4	21.3	52808-1870	18
			17.4	20.3	52808-1770	17
52808-1670	16.4	19.3	52808-1670	16		
MODEL NO.	CARRIER TAPE WIDTH	C	(B)	(A)	MATERIAL NO.	極数 C/T.

材料		SHEET 1 OF 6 参照		MOLEX-JAPAN CO.,L.TD.	
REFER TO SHEET 1 OF 6				MOLEX 日本モレックス株式会社	
仕上げ		—#—		REVISE ONLY ON CAD SYSTEM	
FINISH				TITLE 名称	
適用電線範囲		—#—		1.0 FFC Conn NON ZIF	
WIRE RANGE				SMT ST Embstd Pkg	
被覆外径		—#—		-LEAD FREE-	
INS. RANGE				DWG. NO. (SHEET 5 of 6) REV.	
DRAWN BY 04/02/19		CHK'D BY 04/02/19		SD-52208-028 0	
M.N.ABEL		M.SASAO			
RELEASED					
M.S		04/02/19			
DR.					
変更内容		DATE			
記号		日付			
LTR		CHK			
REVISION RECORD					
一般公差					
GENERAL TOLERANCES					
角度 ANGLE		±3°			
30 以上		±0.3			
10 以上 30 以下		±0.25			
10 以下		±0.2			
新規作成 (12/004-2528)					

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEKULAPLAN AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
 本図面は日本モルツナス（株）の所有する情報を含むもので当社の許可なく複製を禁止する。
 EN-01C0321MX-J-32



SECT:X-X
(SCALE:4-1)

SECT:Y-Y

56mm幅キヤリアテープ

56mm WIDTH CARRIER TAPE

	56	57.5	30.4	33.3	52808-3070	30
52808-**70			29.4	32.3	52808-2970	29
MODEL NO.	キヤリ子ノリ幅 CARRIER TAPE WIDTH	C	(B)	(A)	MATERIAL NO.	種数 CCT.

角度 ANGLE	30°	適用電線範圍 WIRE RANGE	—#—	1.0 STC Conn NON ZIF SMT ST Embstd Pkg -LEAD FREE- DWG. NO. (SHEET 6 OF 6) SD-52808-028 REV. 0
30 以上	0.3	被覆外径 INS. RANGE	—#—	
10 以上 30 UNDER	0.25	DRAWN BY 04/02/19	CHK'D BY 04/02/19	
10 UNDER	0.2	M.N. (M, NABE)	M.S. (M, SASAO)	
GENERAL TOLERANCES	0	新規作成 (12/004-2520) REL'D		
一般公差		變更內容 LTR	DR. DATE	
REVISION RECORD		CHK. DATE	APP'D BY 04/02/19	尺度 SCALE
			M, SASAO	—#—

引き出し方向
PULL OUT DIRECTION

4 累積ピッチ 40 ± 0.2
ACCUMULATIVE
PITCH 40 ± 0.2
回路番号 1 側
CKT.NO.1 SIDE

MOLEX-JAPAN CO.,LTD.
日本モレックス株式会社

TITLE 名称

1.0 FFC Conn NON ZIF
SMT ST Embstp Pkg
-LEAD FREE-

DWG. NO.	(SHEET 6 OF 6)	REV
SD-52808-028		0

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEKULAPLAN AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
 本図面は日本モルツクス（株）の所有する情報を含むもので当社の許可なく複製を禁止する。
 EN-01C0321MXJ-32

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9