

#### Is Now Part of



## ON Semiconductor®

## To learn more about ON Semiconductor, please visit our website at www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (\_), the underscore (\_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (\_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at <a href="www.onsemi.com">www.onsemi.com</a>. Please email any questions regarding the system integration to Fairchild <a href="general-regarding-numbers-n

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any EDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officer



October 2014

## FCD850N80Z / FCU850N80Z N-Channel SuperFET<sup>®</sup> II MOSFET

**800 V, 6 A, 850 m**Ω

#### **Features**


- Typ.  $R_{DS(on)} = 710 \text{ m}\Omega \text{ (Typ.)}$
- Ultra Low Gate Charge (Typ. Q<sub>g</sub> = 22 nC)
- Low E<sub>oss</sub> (Typ. 2.3 uJ @ 400V)
- Low Effective Output Capacitance (Typ. Coss(eff.) = 106 pF)
- · 100% Avalanche Tested
- RoHS Compliant
- · ESD Improved Capability


#### **Applications**


- · AC DC Power Supply
- · LED Lighting

#### Description

SuperFET® II MOSFET is Fairchild Semiconductor's brand-new high voltage super-junction (SJ) MOSFET family that is utilizing charge balance technology for outstanding low on-resistance and lower gate charge performance. This technology is tailored to minimize conduction loss, provide superior switching performance, dv/dt rate and higher avalanche energy. In addition, internal gate-source ESD diode allows to withstand over 2kV HBM surge stress.Consequently, SuperFET II MOSFET is very suitable for the switching power applications such as Audio, Laptop adapter, Lighting, ATX power and industrial power applications.







### $\textbf{Absolute Maximum Ratings} \ \texttt{T}_{\texttt{C}} = 25^{o} \texttt{Cunless otherwise noted}.$

Symbol		FCD850N80Z FCU850N80Z	Unit		
V <sub>DSS</sub>	Drain to Source Voltage			800	V
$V_{GSS}$	Cata to Source Voltage	- DC		±20	V
	Gate to Source Voltage	- AC	(f > 1 Hz)	±30	V
I <sub>D</sub>	Drain Current	- Continuous (T <sub>C</sub> = 25°C)		6	Α
	Drain Current	- Continuous (T <sub>C</sub> = 100°C)		3.8	_ A
I <sub>DM</sub>	Drain Current	- Pulsed	(Note 1)	18	Α
E <sub>AS</sub>	Single Pulsed Avalanche Energ	ЗУ	(Note 2)	114	mJ
I <sub>AR</sub>	Avalanche Current		(Note 1)	1.2	Α
E <sub>AR</sub>	Repetitive Avalanche Energy		(Note 1)	0.284	mJ
dv/dt	MOSFET dv/dt			100	V/ns
αν/αι	Peak Diode Recovery dv/dt		(Note 3)	20	V/IIS
D	Pawer Discinstian	(T <sub>C</sub> = 25°C)		75	W
$P_{D}$	Power Dissipation  - Derate Above 25°C			0.6	W/°C
T <sub>J</sub> , T <sub>STG</sub>	Operating and Storage Temperature Range			-55 to +150	°C
TL	Maximum Lead Temperature for	or Soldering, 1/8" from Case for 5 Se	econds	300	°C

#### **Thermal Characteristics**

Symbol	Parameter FCD850N80Z FCU850N80Z		Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case, Max.	1.65	°C/W
$R_{ hetaJA}$	Thermal Resistance, Junction to Ambient, Max.	100	*C/VV

## **Package Marking and Ordering Information**

Part Number	Top Mark	Package	Packing Method	Reel Size	Tape Width	Quantity
FCD850N80Z	FCD850N80Z	DPAK	Tape and Reel	330 mm	16 mm	2500 units
FCU850N80Z	FCU850N80Z	IPAK	Tube	NA	NA	75 units

## **Electrical Characteristics** $T_C = 25^{\circ}C$ unless otherwise noted.

Symbol	Parameter	Test Conditions	Min.	Тур.	Max.	Unit
Off Charac	cteristics					
BV <sub>DSS</sub>	Drain to Source Breakdown Voltage	$V_{GS} = 0 \text{ V, } I_D = 1 \text{ mA, } T_J = 25^{\circ}\text{C}$	800	-	-	V
ΔBV <sub>DSS</sub> / ΔT <sub>J</sub>	Breakdown Voltage Temperature Coefficient	I <sub>D</sub> = 1 mA, Referenced to 25°C	-	0.8	-	V/°C
1	Zoro Coto Voltago Drain Current	V <sub>DS</sub> = 800 V, V <sub>GS</sub> = 0 V	-	-	25	μА
I <sub>DSS</sub> Zero Gate Voltage Drain Current	$V_{DS} = 640 \text{ V}, V_{GS} = 0 \text{ V}, T_{C} = 125^{\circ}\text{C}$	-	-	250	μΑ	
I <sub>GSS</sub>	Gate to Body Leakage Current	$V_{GS} = \pm 20 \text{ V}, V_{DS} = 0 \text{ V}$	-	-	±10	μΑ

#### On Characteristics

V <sub>GS(th)</sub>	Gate Threshold Voltage	$V_{GS} = V_{DS}$ , $I_D = 0.6$ mA	2.5	-	4.5	V
R <sub>DS(on)</sub>	Static Drain to Source On Resistance	$V_{GS} = 10 \text{ V}, I_D = 3 \text{ A}$	1	710	850	$m\Omega$
9 <sub>FS</sub>	Forward Transconductance	$V_{DS} = 20 \text{ V}, I_{D} = 3 \text{ A}$	1	3.5	1	S

#### **Dynamic Characteristics**

C <sub>iss</sub>	Input Capacitance	V 400 V V 0 V	-\	990	1315	pF
C <sub>oss</sub>	Output Capacitance	V <sub>DS</sub> = 100 V, V <sub>GS</sub> = 0 V, f = 1 MHz	-	28	37	pF
C <sub>rss</sub>	Reverse Transfer Capacitance		-	0.74	-	pF
C <sub>oss</sub>	Output Capacitance	$V_{DS} = 480 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$	-	15	-	pF
C <sub>oss(eff.)</sub>	Effective Output Capacitance	$V_{DS} = 0 \text{ V to } 480 \text{ V}, V_{GS} = 0 \text{ V}$	-	106	-	pF
Q <sub>g(tot)</sub>	Total Gate Charge at 10V	V <sub>DS</sub> = 640 V, I <sub>D</sub> = 6 A,	-	22	29	nC
$Q_{gs}$	Gate to Source Gate Charge	V <sub>GS</sub> = 10 V	-	5	-	nC
$Q_{gd}$	Gate to Drain "Miller" Charge	(Note 4)	-	8.6	-	nC
ESR	Equivalent Series Resistance	f = 1 MHz	-	2.4	-	Ω

#### **Switching Characteristics**

t <sub>d(on)</sub>	Turn-On Delay Time		- /	16	42	ns
t <sub>r</sub>	Turn-On Rise Time	$V_{DD} = 400 \text{ V}, I_D = 6 \text{ A},$	-/	10	30	ns
t <sub>d(off)</sub>	Turn-Off Delay Time	$V_{GS} = 10 \text{ V}, R_g = 4.7 \Omega$	-	40	90	ns
t <sub>f</sub>	Turn-Off Fall Time	(Note 4)	_	4.5	19	ns

#### **Drain-Source Diode Characteristics**

I <sub>S</sub>	Maximum Continuous Drain to Source Diode Forward Current		-	-	6	Α
I <sub>SM</sub>	Maximum Pulsed Drain to Source Diode Forward Current			-	18	Α
$V_{SD}$	Drain to Source Diode Forward Voltage	V <sub>GS</sub> = 0 V, I <sub>SD</sub> = 6 A	-	-	1.2	V
t <sub>rr</sub>	Reverse Recovery Time	V <sub>GS</sub> = 0 V, I <sub>SD</sub> = 6 A,	-	318	-	ns
Q <sub>rr</sub>	Reverse Recovery Charge	$dI_F/dt = 100 A/\mu s$	-	4.5	-	μС

#### Notes

- 1. Repetitive rating: pulse width limited by maximum junction temperature.
- 2.  $I_{AS}$  = 1.2 A,  $V_{DD}$  = 50 V,  $R_G$  = 25  $\Omega$ , Starting  $T_J$  = 25°C
- 3.  $I_{SD} \le 6$  A, di/dt  $\le 200$  A/ $\mu$ s,  $V_{DD} \le BV_{DSS}$ , Starting  $T_J$  = 25°C
- 4. Essentially independent of operating temperature typical characteristics.

#### **Typical Performance Characteristics**

Figure 1. On-Region Characteristics




Figure 3. On-Resistance Variation vs.

Drain Current and Gate Voltage




Figure 5. Capacitance Characteristics




Figure 2. Transfer Characteristics




Figure 4. Body Diode Forward Voltage Variation vs. Source Current and Temperature





Figure 6. Gate Charge Characteristics



#### **Typical Performance Characteristics** (Continued)

Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 11. Eoss vs. Drain to Source Voltage




Figure 8. On-Resistance Variation vs. Temperature






Figure 10. Maximum Drain Current vs. Case Temperature



## **Typical Performance Characteristics** (Continued)

Figure 12. Transient Thermal Response Curve






Figure 13. Gate Charge Test Circuit & Waveform




Figure 14. Resistive Switching Test Circuit & Waveforms




Figure 15. Unclamped Inductive Switching Test Circuit & Waveforms






Figure 16. Peak Diode Recovery dv/dt Test Circuit & Waveforms






3 PLCS

- NOTES: UNLESS OTHERWISE SPECIFIED
  - ALL DIMENSIONS ARE IN MILLIMETERS.
  - B) THIS PACKAGE CONFORMS TO JEDEC, TO-251, ISSUE C, VARIATION AA, DATED SEP 1988.
    C) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.

  - DRAWING NUMBER AND REVISION: MKT-T0251A03REV2 D)





ON Semiconductor and in are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at <a href="www.onsemi.com/site/pdt/Patent-Marking.pdf">www.onsemi.com/site/pdt/Patent-Marking.pdf</a>. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and exp

#### **PUBLICATION ORDERING INFORMATION**

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor 19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com N. American Technical Support: 800-282-9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5817-1050

ON Semiconductor Website: www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

**ON Semiconductor:** 

FCU850N80Z

#### **ПОСТАВКА** ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

# Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

#### http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

#### Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru\_6 moschip.ru\_4 moschip.ru\_9