

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0465574245](#)
Status: **Active**
Description: 1.27mm (.050") by 1.27mm (.050") Pitch SEARAY* Slim Receptacle, 160 Circuits, 8.00mm (.236") Unmated Height, 4 Rows, With Pegs, Solder Charge™ Lead Free

Documents:
[3D Model](#) [Product Specification PS-45970-001 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification


CSA	LR19980
UL	E29179

General

Product Family	PCB Receptacles
Series	46557
Application	Board-to-Board
Product Name	SEARAY*

Physical

Circuits (Loaded)	160
Circuits (maximum)	160
Circuits Detail	160
Color - Resin	Black
Durability (mating cycles max)	100
Flammability	94V-0
Glow-Wire Compliant	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	No
Material - Metal	Copper Alloy
Material - Plating Mating	Gold, Nickel
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Rows	4
Orientation	Vertical
PC Tail Length (in)	0.086 In
PC Tail Length (mm)	2.18 mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.57 mm
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface (in)	0.050 In
Pitch - Mating Interface (mm)	1.27 mm
Pitch - Term. Interface (in)	0.050 In
Pitch - Term. Interface (mm)	1.27 mm
Plating min: Mating (µin)	30
Plating min: Mating (µm)	0.75
Plating min: Termination (µin)	100
Plating min: Termination (µm)	2.5
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Robotic Placement	Pick and Place Cap
Stackable	No
Surface Mount Compatible (SMC)	No



Series

image - Reference only

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[46557Series](#)

Mates With
[46556](#) Searay* Slim Plug Connector

Temperature Range - Operating

Termination Interface: Style

-55°C to +125°C

Through Hole

Electrical

Current - Maximum per Contact

Grounding to PCB

Voltage - Maximum

1A

No

240V AC

Solder Process Data

Duration at Max. Process Temperature (seconds)

Lead-free Process Capability

Max. Cycles at Max. Process Temperature

Process Temperature max. C

20

Reflow Capable (SMT only)

3

260

Material Info

Reference - Drawing Numbers

Product Specification

Sales Drawing

PS-45970-001

SD-46557-001

*SEARAY is a trademark of Samtec, Inc.

This document was generated on 04/14/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

6



5

4


3

2




1

ACROSS ALL
SOLDER CHARGESLEAD CODE
1 = TIN
2 = TIN/LEAD

DATE CODE



ROW 1 / CKT 1 ID

.050 TYP
TERMINAL PITCHUNMATED HEIGHT
DIM R +.002
-.004

POSITION	DIM M	
10	.782	.006
15	1.032	.006
20	1.282	.006
25	1.532	.006
30	1.782	.006
35	2.032	.006
40	2.282	.006
45	2.532	.009
50	2.782	.009

NOTES:

1. MATERIALS: HOUSING- LCP, UL94V-0, BLACK
CONTACTS- COPPER ALLOY
SOLDER CHARGE: SEE CHART
2. FINISH: ALL OPTIONS - SELECT GOLD IN CONTACT AREA: 30 MI MIN
OPTIONS 5.0: SELECT GOLD FLASH IN TAIL, 7 MI MIN
OPTIONS 6.0 THRU 8.0: SELECT TIN IN TAIL, 100 MI MIN
ALL OPTIONS - OVER NICKEL
3. PRODUCT SPECIFICATION: PS-45970-001
4. PACKAGING SPECIFICATION: PK-45970-002
5. MATES WITH SEARAY SLIM RECPT ASSY 46556
6. APPLICATION SPECIFICATION: AS-45970-001
7. COSMETIC SPECIFICATION: PS-45499-002 CLASS B
8. PART STATUS: CONTACT MOLEX

UPDATED NOTE 2

EC NO: UCP2010-2270

DRWN: TGREGORI 2010/03/05

CHKD: JCOMERC I 2007/05/21

APPR: JCOMERC I 2010/03/05

DESCRIPTION

REV

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .005
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---

ANGULAR ± ---°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONSDIMENSION STYLE
INCH ONLY

DRAWN BY	DATE
TGREGORI	2007/05/21
CHECKED BY	DATE
JCOMERC I	2007/05/21
APPROVED BY	DATE
JCOMERC I	2010/03/05

MATERIAL NO.

SEE CHART

SIZE
ASCALE
4:1DESIGN UNITS
INCH

TITLE

SEARAY SLIM
RECEPTACLE ASSEMBLY
.050 PITCH

MOLEX INCORPORATED

DOCUMENT NO.

SD-46557-001

SHEET NO.

1 OF 4

 THIRD ANGLE
PROJECTION

5

4



3

2

1


6
5
4
3
2
1

φ.050±.003 TYP 2
NON-PLT THRU HOLES



	MM	DIM R RECEPTACLE STACK HEIGHT				
		5.0	6.0	6.5	7.5	8.0
DIM P PLUG STACK HEIGHT	2.0	7.0	8.0	8.5	9.5	10.0
	3.0	8.0	9.0	9.5	10.5	11.0
	3.5	8.5	9.5	10.0	11.0	11.5
	2.5	7.5	8.5	9.0	10.0	10.5
	4.5	9.5	10.5	11.0	12.0	12.5
	5.0	10.0	11.0	11.5	12.5	13.0
	7.0	12.0	13.0	13.5	14.5	15.0

STACK HEIGHTS GIVEN IN MM FOR REF ONLY



SEE SHEET 1
EC NO: UCP2010-2270
DRWN: TGREGORI 2010/03/05
CHKD: JCOMERC I 2007/05/21
APPR: JCOMERC I 2010/03/05

DESCRIPTION
REV

GENERAL TOLERANCES
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± ---	± .005
2 PLACES	± ---	± ---
1 PLACE	± ---	± ---

ANGULAR ± ---°

DRAFT WHERE APPLICABLE
MUST REMAIN
WITHIN DIMENSIONS

DIMENSION STYLE
INCH ONLY

DRAWN BY	DATE
TGREGORI	2007/05/21
CHECKED BY	DATE
JCOMERC I	2007/05/21
APPROVED BY	DATE
JCOMERC I	2010/03/05

MATERIAL NO.

SEE CHART

SIZE
A

SCALE
4:1

DESIGN UNITS
INCH

THIRD ANGLE
PROJECTION

SEARAY SLIM
RECEPTACLE ASSEMBLY
.050 PITCH

MOLEX INCORPORATED

DOCUMENT NO.
SD-46557-001

SHEET NO.
2 OF 4

6		5		4		3		2		1																																																																																												
DIM R: (REF)		5.0 MM		6.0 MM		6.5 MM		7.5 MM		8.0 MM		STACK HEIGHTS GIVEN IN MM FOR REF ONLY																																																																																										
DIM R: HOUSING HEIGHT		.199		.238		.258		.297		.317																																																																																												
POSITIONS		MATERIAL NO		MATERIAL NO		MATERIAL NO		MATERIAL NO		MATERIAL NO																																																																																												
10		46557-1145		46557-1245		46557-1345		46557-1445		46557-1545																																																																																												
20		46557-2145		46557-2245		46557-2345		46557-2445		46557-2545																																																																																												
30		46557-3145		46557-3245		46557-3345		46557-3445		46557-3545																																																																																												
40		46557-4145		46557-4245		46557-4345		46557-4445		46557-4545																																																																																												
50		46557-5145		46557-5245		46557-5345		46557-5445		46557-5545																																																																																												
15		46557-6145		46557-6245		46557-6345		46557-6445		46557-6545																																																																																												
25		46557-7145		46557-7245		46557-7345		46557-7445		46557-7545																																																																																												
35		46557-8145		46557-8245		46557-8345		46557-8445		46557-8545																																																																																												
45		46557-9145		46557-9245		46557-9345		46557-9445		46557-9545																																																																																												
NOTES: 1. THIS SHEET CONTAINS THE FOLLOWING OPTIONS SOLDER CHARGE: TIN																																																																																																						
<table><tr><td rowspan="5">SEE SHEET 1 EC NO: UCP2010-2270 DRWN: TGREGORI 2010/03/05 CHKD: JCOMERCI 2007/05/21 APPR: JCOMERCI 2010/03/05</td><td rowspan="5">DESCRIPTION</td><td colspan="2">GENERAL TOLERANCES (UNLESS SPECIFIED)</td><td colspan="2">DIMENSION STYLE INCH ONLY</td><td>SCALE 1:1</td><td>DESIGN UNITS INCH</td><td colspan="2">THIRD ANGLE PROJECTION</td></tr><tr><td></td><td>mm</td><td>INCH</td><td>DRAWN BY TGREGORI</td><td>DATE 2007/05/21</td><td colspan="4" rowspan="3">TITLE SEARAY SLIM RECEPTACLE ASSEMBLY .050 PITCH</td></tr><tr><td>4 PLACES</td><td>± ---</td><td>± ---</td><td>CHECKED BY JCOMERCI</td><td>DATE 2007/05/21</td></tr><tr><td>3 PLACES</td><td>± ---</td><td>± .005</td><td>APPROVED BY JCOMERCI</td><td>DATE 2010/03/05</td></tr><tr><td>2 PLACES</td><td>± ---</td><td>± ---</td><td colspan="2">MATERIAL NO. SEE CHART</td><td colspan="2">DOCUMENT NO. SD-46557-001</td><td colspan="2">SHEET NO. 3 OF 4</td></tr><tr><td>1 PLACE</td><td>± ---</td><td>± ---</td><td colspan="10">THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</td></tr><tr><td colspan="2">ANGULAR ± ---°</td><td colspan="11"></td></tr><tr><td colspan="2">DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</td><td colspan="11"></td></tr><tr><td colspan="2">SIZE A</td><td colspan="11"></td></tr></table>													SEE SHEET 1 EC NO: UCP2010-2270 DRWN: TGREGORI 2010/03/05 CHKD: JCOMERCI 2007/05/21 APPR: JCOMERCI 2010/03/05	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH ONLY		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION			mm	INCH	DRAWN BY TGREGORI	DATE 2007/05/21	TITLE SEARAY SLIM RECEPTACLE ASSEMBLY .050 PITCH				4 PLACES	± ---	± ---	CHECKED BY JCOMERCI	DATE 2007/05/21	3 PLACES	± ---	± .005	APPROVED BY JCOMERCI	DATE 2010/03/05	2 PLACES	± ---	± ---	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-46557-001		SHEET NO. 3 OF 4		1 PLACE	± ---	± ---	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION										ANGULAR ± ---°													DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS													SIZE A												
SEE SHEET 1 EC NO: UCP2010-2270 DRWN: TGREGORI 2010/03/05 CHKD: JCOMERCI 2007/05/21 APPR: JCOMERCI 2010/03/05	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH ONLY		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION																																																																																														
			mm	INCH	DRAWN BY TGREGORI	DATE 2007/05/21	TITLE SEARAY SLIM RECEPTACLE ASSEMBLY .050 PITCH																																																																																															
		4 PLACES	± ---	± ---	CHECKED BY JCOMERCI	DATE 2007/05/21																																																																																																
		3 PLACES	± ---	± .005	APPROVED BY JCOMERCI	DATE 2010/03/05																																																																																																
		2 PLACES	± ---	± ---	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-46557-001		SHEET NO. 3 OF 4																																																																																													
1 PLACE	± ---	± ---	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																																																																																																			
ANGULAR ± ---°																																																																																																						
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS																																																																																																						
SIZE A																																																																																																						
tb_frame_A_P_AM_T Rev. E 2006/04/15		5		4		3		2		1																																																																																												

6		5		4		3		2		1																									
DIM R: (REF)		5.0 MM		6.0 MM		6.5 MM		7.5 MM		8.0 MM		STACK HEIGHTS GIVEN IN MM FOR REF ONLY																							
DIM R: HOUSING HEIGHT		.199		.238		.258		.297		.317																									
POSITIONS		MATERIAL NO		MATERIAL NO		MATERIAL NO		MATERIAL NO		MATERIAL NO																									
10		46557-1147		46557-1247		46557-1347		46557-1447		46557-1547																									
20		46557-2147		46557-2247		46557-2347		46557-2447		46557-2547																									
30		46557-3147		46557-3247		46557-3347		46557-3447		46557-3547																									
40		46557-4147		46557-4247		46557-4347		46557-4447		46557-4547																									
50		46557-5147		46557-5247		46557-5347		46557-5447		46557-5547																									
15		46557-6147		46557-6247		46557-6347		46557-6447		46557-6547																									
25		46557-7147		46557-7247		46557-7347		46557-7447		46557-7547																									
35		46557-8147		46557-8247		46557-8347		46557-8447		46557-8547																									
45		46557-9147		46557-9247		46557-9347		46557-9447		46557-9547																									
NOTES: 1. THIS SHEET CONTAINS THE FOLLOWING OPTIONS SOLDER CHARGE: TIN / LEAD																																			
												SEE SHEET 1 EC NO: UCP2010-2270 DRWN: TGREGORI CHKD: JCOMERCI APPR: JCOMERCI REV DESCRIPTION GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± .005 2 PLACES ± --- ± --- 1 PLACE ± --- ± --- ANGULAR ± ---° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DIMENSION STYLE INCH ONLY DRAWN BY DATE TGREGORI 2007/05/21 CHECKED BY DATE JCOMERCI 2007/05/21 APPROVED BY DATE JCOMERCI 2010/03/05 MATERIAL NO. SEE CHART SIZE A SCALE 1:1 DESIGN UNITS INCH THIRD ANGLE PROJECTION TITLE SEARAY SLIM RECEPTACLE ASSEMBLY .050 PITCH MOLEX INCORPORATED DOCUMENT NO. SD-46557-001 SHEET NO. 4 OF 4 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																							

tb_frame_A_P_AM_T

Rev. E 2006/04/15

5		4		3		2		1	
---	--	---	--	---	--	---	--	---	--

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9