

**HEX INVERTERS WITH SCHMITT TRIGGER INPUTS**
**NEW PRODUCT**
**Description**

The 74LV14A provides provides six independent Schmitt Trigger input inverters with standard push-pull outputs. The device is designed for operation with a power supply range of 2.0V to 5.5V.

The inputs are tolerant to 5.5V allowing this device to be used in a mixed voltage environment. The device is fully specified for partial power down applications using I<sub>OFF</sub>. The I<sub>OFF</sub> circuitry disables the output preventing damaging current backflow when the device is powered down.


The gates perform the Boolean function:

$$Y = \overline{A}$$

**Features**

- Wide Supply Voltage Range from 2.0V to 5.5V
- Sinks or sources 12mA at V<sub>CC</sub> = 4.5V
- CMOS low power consumption
- I<sub>OFF</sub> Supports Partial -Power Down Operation
- Inputs or Outputs accept up to 5.5V
- Inputs can be driven by 3.3V or 5V allowing for voltage translation applications.
- Schmitt Trigger Action at All Inputs
- ESD Protection Tested per JESD 22
  - Exceeds 200-V Machine Model (A115)
  - Exceeds 2000-V Human Body Model (A114)
  - Exceeds 1000-V Charged Device Model (C101)
- Latch-Up Exceeds 100mA per JESD 78, Class I
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

- Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
  2. See [http://www.diodes.com/quality/lead\\_free.html](http://www.diodes.com/quality/lead_free.html) for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

**Pin Assignments**

**Applications**


- General Purpose Logic
- Power Down Signal Isolation
- Wide array of products such as:
  - PCs, networking, notebooks, ultrabooks, netbooks
  - Computer peripherals, hard drives, CD/DVD ROM
  - TV, DVD, DVR, set top box

[Click here for ordering information, located at the end of datasheet](#)

### Pin Descriptions

| Pin Number | Pin Name | Description    |
|------------|----------|----------------|
| 1          | 1A       | Data Input     |
| 2          | 1Y       | Data Output    |
| 3          | 2A       | Data Input     |
| 4          | 2Y       | Data Output    |
| 5          | 3A       | Data Input     |
| 6          | 3Y       | Data Output    |
| 7          | GND      | Ground         |
| 8          | 4Y       | Data Output    |
| 9          | 4A       | Data Input     |
| 10         | 5Y       | Data Output    |
| 11         | 5A       | Data Input     |
| 12         | 6Y       | Data Output    |
| 13         | 6A       | Data Input     |
| 14         | VCC      | Supply Voltage |

### Logic Diagram



### Function Table

| Input | Output |
|-------|--------|
| A     | Y      |
| H     | L      |
| L     | H      |

### Absolute Maximum Ratings (Note 4) (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Symbol           | Description  | Rating       | Unit |
|------------------|--|--------------|------|
| ESD HBM          | Human Body Model ESD Protection  | 2            | kV   |
| ESD CDM          | Charged Device Model ESD Protection  | 1            | kV   |
| ESD MM           | Machine Model ESD Protection   | 200          | V    |
| V <sub>CC</sub>  | Supply Voltage Range   | -0.5 to +7.0 | V    |
| V <sub>I</sub>   | Input Voltage Range note 4   | -0.5 to +7.0 | V    |
| I <sub>IK</sub>  | Input Clamp Current V <sub>I</sub> < 0V                                    | -20          | mA   |
| I <sub>OK</sub>  | Output Clamp Current V <sub>O</sub> < 0V                                   | -50          | mA   |
| I <sub>O</sub>   | Continuous Output Current - 0.5V < V <sub>O</sub> < V <sub>CC</sub> + 0.5V | ±25          | mA   |
| I <sub>CC</sub>  | Continuous Current Through V <sub>CC</sub>                                 | 50           | mA   |
| I <sub>GND</sub> | Continuous Current Through GND   | -50          | mA   |
| T <sub>J</sub>   | Operating Junction Temperature   | -40 to +150  | °C   |
| T <sub>STG</sub> | Storage Temperature  | -65 to +150  | °C   |
| P <sub>TOT</sub> | Total Power Dissipation  | 500          | mW   |

Note: 4. Stresses beyond the absolute maximum may result in immediate failure or reduced reliability. These are stress values and device operation should be within recommend values.

**Recommended Operating Conditions** (Note 5) (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)

| Symbol   | Parameter                      | Conditions   | Min | Max      | Unit             |
|----------|--------------------------------|--------------|-----|----------|------------------|
| $V_{CC}$ | Supply Voltage                 | —            | 2.0 | 5.5      | V                |
| $V_I$    | Input Voltage                  | —            | 0   | 5.5      | V                |
| $V_O$    | Output Voltage                 | —            | 0   | $V_{CC}$ | V                |
| $I_{OH}$ | High-Level Output Current      | 2.0V         | —   | -50      | mA               |
|          |                                | 2.3V to 2.7V | —   | -2       | $\mu\text{A}$    |
|          |                                | 3.0V to 3.6V | —   | -6       | mA               |
|          |                                | 4.5V to 5.5V | —   | -12      | mA               |
| $I_{OL}$ | Low-Level Output Current       | 2.0V         | —   | 50       | $\mu\text{A}$    |
|          |                                | 2.3V to 2.7V | —   | 2        | mA               |
|          |                                | 3.0V to 3.6V | —   | 6        | mA               |
|          |                                | 4.5V to 5.5V | —   | 12       | mA               |
| $T_A$    | Operating Free-Air Temperature | —            | -40 | +125     | $^\circ\text{C}$ |

 Note: 5. Unused inputs should be held at  $V_{CC}$  or Ground.

**Electrical Characteristics** (@ $T_A = +25^\circ\text{C}$ , unless otherwise specified.)

| Symbol    | Parameter                        | Test Conditions                             | $V_{CC}$     | $T_A = -40^\circ\text{C to } +85^\circ\text{C}$ |         | $T_A = -40^\circ\text{C to } +125^\circ\text{C}$ |         | Unit          |
|-----------|----------------------------------|---|--------------|---|---------|--|---------|---------------|
|           |                                  |   |              | Min   | Max     | Min  | Max     |               |
| $V_{T+}$  | Positive Going Threshold         | —   | 2.5 V        | 1   | 1.75    | 1  | 1.75    | V             |
|           |                                  | —   | 3.3 V        | 1.31  | 2.31    | 1.31   | 2.31    |               |
|           |                                  | —   | 5.0 V        | 1.95  | 3.5     | 1.95   | 3.5     |               |
| $V_{T-}$  | Negative Going Threshold         | —   | 2.5 V        | 0.75  | 1.5     | 0.75   | 1.5     | —             |
|           |                                  | —   | 3.3 V        | 0.99  | 2.07    | 0.99   | 2.07    |               |
|           |                                  | —   | 5.0 V        | 1.5   | 3.05    | 1.5  | 3.05    |               |
| $V_H$     | Hysteresis ( $V_{T+} - V_{T-}$ ) | —   | 2.5 V        | 0.25  | 1       | 0.25   | 1       | V             |
|           |                                  | —   | 3.3 V        | 0.33  | 1.32    | 0.33   | 1.32    |               |
|           |                                  | —   | 5.0 V        | 0.5   | 2       | 0.5  | 2       |               |
| $V_{OH}$  | High-Level Output Voltage        | $I_{OH} = -50\mu\text{A}$                   | 2.0V to 5.5V | $V_{CC}-0.1$                                    | —       | $V_{CC}-0.1$                                     | —       | V             |
|           |                                  | $I_{OH} = -2\text{mA}$                      | 2.3V         | 2.0   | —       | 2.0  | —       |               |
|           |                                  | $I_{OH} = -6\text{mA}$                      | 3.0V         | 2.48  | —       | 2.48   | —       |               |
|           |                                  | $I_{OH} = -12\text{mA}$                     | 4.5V         | 3.8   | —       | 3.8  | —       |               |
| $V_{OL}$  | Low-Level Output Voltage         | $I_{OL} = 50\mu\text{A}$                    | 2.0V to 5.5V | —   | 0.1     | —  | 0.1     | V             |
|           |                                  | $I_{OL} = 2\text{mA}$                       | 2.3V         | —   | 0.4     | —  | 0.4     |               |
|           |                                  | $I_{OL} = 6\text{mA}$                       | 3.0V         | —   | 0.44    | —  | 0.44    |               |
|           |                                  | $I_{OL} = 12\text{mA}$                      | 4.5V         | —   | 0.55    | —  | 0.55    |               |
| $I_{OFF}$ | Power Down Leakage Current       | $V_I$ or $V_O = 0$ to 5.5V                  | 0V           | —   | 5       | —  | 5       | $\mu\text{A}$ |
| $I_I$     | Input Current                    | $V_I = \text{GND}$ or 5.5V                  | 0 to 5.5V    | —   | $\pm 1$ | —  | $\pm 1$ | $\mu\text{A}$ |
| $I_{CC}$  | Supply Current                   | $V_I = \text{GND}$ or $V_{CC}$<br>$I_O = 0$ | 5.5V         | —   | 20      | —  | 20      | $\mu\text{A}$ |

**Switching Characteristics**

| Symbol          | Parameter  | Test Conditions                   | V <sub>CC</sub> | T <sub>A</sub> = +25°C |      |      | -40°C to +85°C |      | -40°C to +125°C |      | Unit |
|-----------------|--|-----------------------------------|-----------------|------------------------|------|------|----------------|------|-----------------|------|------|
|                 |  |                                   |                 | Min                    | Typ. | Max  | Min            | Max  | Min             | Max  |      |
| t <sub>PD</sub> | Propagation Delay A <sub>N</sub> to Y <sub>N</sub> | Figure 1<br>C <sub>L</sub> = 15pF | 2.5V ± 0.2V     | —                      | 10.2 | 19.7 | 1              | 22   | 1               | 22   | ns   |
|                 |  |                                   | 3.3V ± 0.3V     | —                      | 7.3  | 12.8 | 1              | 15   | 1               | 15.9 |      |
|                 |  |                                   | 5.0V ± 0.5V     | —                      | 5.1  | 8.6  | 1              | 10   | 1               | 10   |      |
|                 |  | Figure 1<br>C <sub>L</sub> = 50pF | 2.5V ± 0.2V     | —                      | 13.3 | 24   | 1              | 27   | 1               | 27   | ns   |
|                 |  |                                   | 3.3V ± 0.3V     | —                      | 9.6  | 16.3 | 1              | 18.5 | 1               | 19.4 |      |
|                 |  |                                   | 5.0V ± 0.5V     | —                      | 6.7  | 10.6 | 1              | 12   | 1               | 12   |      |

**Operating Characteristics (@T<sub>A</sub> = +25°C, unless otherwise specified.)**

| Parameter       |  | Test Conditions                     | V <sub>CC</sub> | Typ | Unit |
|-----------------|--|-------------------------------------|-----------------|-----|------|
| C <sub>pd</sub> | Power Dissipation Capacitance per Gate | F = 10 MHz<br>C <sub>L</sub> = 50pF | 3.3V            | 8.8 | pF   |
|                 |  |                                     | 5.0V            | 9.6 |      |

**Noise Characteristics**

V<sub>CC</sub> = 3V, C<sub>L</sub> = 50pF T<sub>A</sub> = +25°C


| Symbol             | Parameter                                     | Min  | Typ  | Max  | Unit |
|--------------------|---|------|------|------|------|
| V <sub>OL(p)</sub> | Quiet output, maximum dynamic V <sub>OL</sub> | —    | 0.2  | 0.8  | V    |
| V <sub>OL(v)</sub> | Quiet output, minimum dynamic V <sub>OL</sub> | —    | -0.1 | -0.8 | V    |
| V <sub>OH(v)</sub> | Quiet output, minimum dynamic V <sub>OH</sub> | —    | 3.1  | —    | V    |
| V <sub>IH(D)</sub> | High Level dynamic input voltage              | 2.31 | —    | —    | V    |
| V <sub>IL(D)</sub> | Low Level dynamic input voltage               | —    | —    | 0.99 | V    |

**Package Characteristics**


| Symbol         | Parameter         | Test Conditions                           | V <sub>CC</sub> | Min | Typ | Max | Unit |
|----------------|-------------------|---|-----------------|-----|-----|-----|------|
| C <sub>i</sub> | Input Capacitance | V <sub>i</sub> = V <sub>CC</sub> – or GND | 2.0 to 5.5V     | —   | 3.3 | 10  | pF   |

**Parameter Measurement Information**


From Output Under Test



| $V_{CC}$     | Inputs   |             | $V_M$        | $C_L$        |
|--------------|----------|-------------|--------------|--------------|
|              | $V_I$    | $t_r / t_f$ |              |              |
| 2.0V to 5.5V | $V_{CC}$ | < 3ns       | $V_{CC} / 2$ | 15pF or 50pF |



**Voltage Waveform  
Pulse Duration**




**Voltage Waveform  
Propagation Delay Times  
Inverting and Non Inverting Outputs**

- Notes:
- A. Includes test lead and test apparatus capacitance.
  - B. All pulses are supplied at pulse repetition rate  $\leq 10$ MHz.
  - C. Inputs are measured separately one transition per measurement.
  - D.  $t_{PLH}$  and  $t_{PHL}$  are the same as  $t_{PD}$ .

**Figure 1 Load Circuit and Voltage Waveforms**

**Ordering Information**




| Part Number   | Package Code | Packaging (Note 6) | 13" Tape and Reel |                    |
|---------------|--------------|--------------------|-------------------|--------------------|
|               |              |                    | Quantity          | Part Number Suffix |
| 74LV14AS14-13 | S14          | SO-14              | 2500/Tape & Reel  | -13                |
| 74LV14AT14-13 | T14          | TSSOP-14           | 2500/Tape & Reel  | -13                |

Note: 6. The taping orientation and tape details can be found at <http://www.diodes.com/datasheets/ap02007.pdf>

**Marking Information**

(1) SO14, TSSOP14




| Part Number | Package  |
|-------------|----------|
| 74LV14AS14  | SO-14    |
| 74LV14AT14  | TSSOP-14 |

**Package Outline Dimensions** (All dimensions in mm.)


Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for latest version.

**Package Type: SO-14**



| SO-14                       |          |      |
|-----------------------------|----------|------|
| Dim                         | Min      | Max  |
| A                           | 1.47     | 1.73 |
| A1                          | 0.10     | 0.25 |
| A2                          | 1.45 Typ |      |
| B                           | 0.33     | 0.51 |
| D                           | 8.53     | 8.74 |
| E                           | 3.80     | 3.99 |
| e                           | 1.27 Typ |      |
| H                           | 5.80     | 6.20 |
| L                           | 0.38     | 1.27 |
| θ                           | 0°       | 8°   |
| <b>All Dimensions in mm</b> |          |      |

**Package Type: TSSOP-14**




| TSSOP-14                    |          |      |
|-----------------------------|----------|------|
| Dim                         | Min      | Max  |
| a1                          | 7° (4X)  |      |
| a2                          | 0°       | 8°   |
| A                           | 4.9      | 5.10 |
| B                           | 4.30     | 4.50 |
| C                           | —        | 1.2  |
| D                           | 0.8      | 1.05 |
| F                           | 1.00 Typ |      |
| F1                          | 0.45     | 0.75 |
| G                           | 0.65 Typ |      |
| K                           | 0.19     | 0.30 |
| L                           | 6.40 Typ |      |
| <b>All Dimensions in mm</b> |          |      |

### Suggested Pad Layout


Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.

Package Type: SO-14



| Dimensions | Value (in mm) |
|------------|---------------|
| X          | 0.60          |
| Y          | 1.50          |
| C1         | 5.4           |
| C2         | 1.27          |

Package Type: TSSOP-14



| Dimensions | Value (in mm) |
|------------|---------------|
| X          | 0.45          |
| Y          | 1.45          |
| C1         | 5.9           |
| C2         | 0.65          |



**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2013, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9