Heyco®-Tite Cast Aluminum Liquid Tight Cordgrips

Right Angle, NPT Hubs

The Ultimate in Liquid Tight Strain Relief Protection

- **Aluminum construction** provides excellent durability and performance for most **industrial applications**.
- For use in both indoor and outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture, and coolants.
- IP 67 rated.
- Protect cable from damage and pull-out and are used in conduit hubs or knock-outs at the point where the electrical cable is to be terminated.
- Unique design with a combination tightening surface that includes both a hex area and a knurled surface.
- Anti-friction washer allows for easier compression.
- DFARS Compliant



SUGGESTED CLEARANCE HOLE FOR NONTHREADED MOUNTING



CABLE DIA. RANGE Minimum in.	Minimum mm.	Maximum in.	Maximum mm.	PART NO. Cast Aluminum	THREAD SIZE	UL	PART DIMENSIONS A Clearance Hole Dia. in.	A mm.	B Max. O.A. Length in.	B mm.	C Thread Length in.	C mm.	D Wrenching Flat Size in.	D mm.
Sweep Design														
.125	3,2	.188	4,8	**M5230**										
.188	4,8	.250	6,4	**M5231**		UL								
.250	6,4	.312	7,9	**M5232**	NPT 3/8		.68	17,3	2.00	50,8	.44	11,2	.88	23,4
.312	7,9	.375	9,5	**M5233**										
.375	9,5	.438	11,1	**M5234**										
.125	3,2	.188	4,8	**M5235**										
.188	4,8	.250	6,4	**M5236**										
.250	6,4	.312	7,9	**M5237**		UL								
.312	7,9	.375	9,5	**M5238**	NPT 1/2		.88	22,3	2.39	60,7	.56	14,2	1.13	28,7
.375	9,5	.438	11,1	**M5239**										
.438	11,1	.500	12,7	**M5240**										
.500	12,7	.562	14,3	**M5241**										
.562	14,3	.625	15,9	**M5242**										
.438	11,1	.500	12,7	**M5243**										
.500	12,7	.562	14,3	**M5244**		UL								
.500	12,7	.625	15,9	**M5245**	NPT 3/4		1.09	27,7	2.88	73,2	.59	15,0	1.37	31,8
.562	14,3	.688	17,5	**M5246**										
.625	15,9	.750	19,1	**M5247**										
.688	17,5	.812	20,6	**M5248**										
.500	12,7	.562	14,3	**M5249**										
.500	12,7	.625	15,9	**M5250**										
.562	14,3	.688	17,5	**M5251**		UL								
.625	15,9	.750	19,1	**M5252**	NPT 1		1.38	35,0	3.13	79,5	.60	15,2	1.56	39,6
.688	17,5	.812	20,6	**M5253**										
.750	19,1	.875	22,2	**M5254**										
.812	20,6	.938	23,8	**M5255**										
.875	22,2	1.000	25,4	**M5256**										

O-ring not included - See pages 2-19 through 2-20 for Sealing Washers, Foam Washers & Thermoplastic O-rings.
Locknut not included - See page 3-48 for Metal Locknuts.

Quick Specs

Material		Aluminum with Neoprene Sealing Gland and Viton® O-Ring
Certifications	UL	Listed under Underwriters' Laboratories File E51579
	SA	Certified by Canadian Standard Association File 258093
Flammability Rating		94V-2
Temperature Range		-40°F (-40°C) to 250°F (121°C)
IP Rating		IP 67

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9