


Thick Film Resistor Networks, Dual-In-Line Small Outline Molded Dip 45 & 46 Schematics



FEATURES

- 0.110" [2.79] maximum seated height
- Rugged, molded case construction
- 0.050" [1.27] lead spacing
- Reduces total assembly costs
- Compatible with automatic surface mounting equipment
- Uniform performance characteristics
- Meets EIA PDP 100, SOGN-0003 outline dimensions
- Available in tube pack or tape and reel pack
- Lead (Pb)-free version is RoHS compliant



Available


RoHS*
COMPLIANT

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	CIRCUIT SCHEMATIC	RESISTOR CIRCUIT W AT 70 °C	PACKAGE POWER W AT 70 °C	TOLERANCE ± %	RESISTANCE VALUES Ω	OPERATING VOLTAGE VDC	TEMPERATURE COEFFICIENT ± ppm/°C
SOGC16	45	0.1	1.6	2	180, 270, 820	50 max	100
	46	0.1	1.6	2	330, 150, 330	50 max	100
SOGC20	45	0.1	2.0	2	180, 270, 820	50 max	100
	46	0.1	2.0	2	330, 150, 330	50 max	100

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	SOGC16	SOGC20
Package Power Rating: (Maximum at + 70°C)	W	1.6	2.0
TC Tracking: (- 55°C to + 125°C)	ppm/°C	± 50	
Voltage Coefficient of Resistance:	ppm/V	< 50 typical.	
Maximum Operating Voltage:	VDC	50	
Operating Temperature Range:	°C	- 55 to + 125	
Storage Temperature Range:	°C	- 55 to + 150	

MECHANICAL SPECIFICATIONS

Marking	Model number, schematic number, value, tolerance, pin 1 indicator, date code
Marking Resistance to Solvents	Permanency testing per MIL-STD-202, Method 215
Maximum Solder Reflow Temperature	+ 255 °C
Solderability	Per MIL-STD-202, Method 208E
Terminals	Copper alloy. Solder dipped terminal
Body:	Molded epoxy

GLOBAL PART NUMBER INFORMATION



New Global Part Numbering: SOGC1646DC (preferred part numbering format)

S	O	G	C	1	6	4	6	D	C			
GLOBAL MODEL		PIN COUNT		SCHEMATIC		PACKAGING			SPECIAL			
SOGC		16 20		45 = TTL/ECL Translator 46 = Signal Terminator		EJ = Lead Free, Tube EA = Lead Free, Tape & Reel DC = Tin/Lead, Tube RZ = Tin/Lead, Tape & Reel			Blank = Standard (Dash Number) (up to 3 digits) From 1-999 as applicable			


Historical Part Number example: SOGC1646 (will continue to be accepted)

SOGC	16	46	D02
HISTORICAL MODEL	PIN COUNT	SCHEMATIC	PACKAGING


* Pb containing terminations are not RoHS compliant, exemptions may apply

**DIMENSIONS** in inches [millimeters]**CIRCUIT APPLICATIONS****45 Schematic****TTL to ECL translator**

The SOGCxx45 network consists of resistors of 3 different values, internally divided into 6 or 8 identical three (3) resistor sections for TTL to ECL translation.

46 Schematic**SCSI-BUS signal terminator**

The SOGCxx46 network consists of resistors of 2 different values, internally divided into 7 or 9 identical three (3) resistor sections for SCSI-BUS terminator applications.

**PERFORMANCE**

TEST	MAX. ΔR (TYPICAL TEST LOTS)
Power Conditioning	± 0.50 % ΔR
Thermal Shock	± 0.50 % ΔR
Short Time Overload	± 0.25 % ΔR
Low Temperature Operation	± 0.25 % ΔR
Moisture Resistance	± 0.50 % ΔR
Resistance to Soldering Heat	± 0.25 % ΔR
Shock	± 0.25 % ΔR
Vibration	± 0.25 % ΔR
Load Life	± 0.50 % ΔR
Terminal Strength	± 0.25 % ΔR
Insulation Resistance	10 000 Megohm (minimum)
Dielectric Withstanding Voltage	No evidence of arcing or damage (200 V RMS for 1 minute)

* Test methods per MIL-STD-202



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9