

## Cascadable Amplifier 5 to 500 MHz

Rev. V4

### Features

- HIGH DYNAMIC RANGE: +116 dBm (1 MHz Band)
- HIGH OUTPUT POWER: +19 dBm (TYP.)
- HIGH THIRD ORDER I.P. + 34.0 dBm (TYP.)
- LOW NOISE: 4.0 dB (TYP.)

### Description


The A58 RF amplifier is a discrete thin film hybrid design, which incorporates the use of thin film manufacturing processes for accurate performance and high reliability. This single stage bipolar transistor feedback amplifier design displays impressive performance over a broadband frequency range. An active DC biasing network is used for temperature-stable performance, in addition to an RF Choke, used for power supply decoupling. Both TO-8 and Surface Mount packages are hermetically sealed, and MIL-STD-883 environmental screening is available.

### Ordering Information

| Part Number | Package           |
|-------------|-------------------|
| A58         | TO-8              |
| SMA58       | Surface Mount     |
| CA58 **     | SMA Connectorized |

\*\* The connectorized version is not RoHs compliant.

### Product Image



### Electrical Specifications: $Z_0 = 50\Omega$ , $V_{CC} = +15 V_{DC}$

| Parameter                          | Units | Typical       | Guaranteed    |                |
|------------------------------------|-------|---------------|---------------|----------------|
|                                    |       | 25°C          | 0° to 50°C    | -54° to +85°C* |
| Frequency                          | MHz   | 2-700         | 5-500         | 5-500          |
| Small Signal Gain (min)            | dB    | 11.5          | 10.5          | 10.0           |
| Gain Flatness (max)                | dB    | ±0.3          | ±0.7          | ±1.0           |
| Reverse Isolation                  | dB    | 16            |               |                |
| Noise Figure (max)                 | dB    | 4.0           | 5.0           | 5.5            |
| Power Output<br>@ 1 dB comp. (min) | dBm   | 19.0          | 18.0          | 17.5           |
| IP3                                | dBm   | +34           |               |                |
| IP2                                | dBm   | +48           |               |                |
| Second Order Harmonic IP           | dBm   | +54           |               |                |
| VSWR Input / Output (max)          |       | 1.5:1 / 1.5:1 | 1.9:1 / 1.9:1 | 2.0:1 / 2.0:1  |
| DC Current @ 15 Volts (max)        | mA    | 65            | 69            | 72             |

### Absolute Maximum Ratings

| Parameter                                 | Absolute Maximum |
|-------------------------------------------|------------------|
| Storage Temperature                       | -62°C to +125°C  |
| Case Temperature                          | +125°C           |
| DC Voltage                                | +17 V            |
| Continuous Input Power                    | 13 dBm           |
| Short Term Input power<br>(1 minute max.) | 50 mW            |
| Peak Power (3 µsec max.)                  | 0.5 W            |
| "S" Series Burn-In<br>Temperature (case)  | +125°C           |

### Thermal Data: $V_{CC} = +15 V_{DC}$


| Parameter                                        | Rating  |
|--------------------------------------------------|---------|
| Thermal Resistance $\theta_{jc}$                 | 75°C/W  |
| Transistor Power Dissipation $P_d$               | 0.651 W |
| Junction Temperature Rise<br>Above Case $T_{jc}$ | 49°C    |

1 \* Over temperature performance limits for part number CA58, guaranteed from 0°C to +50°C only.


## Cascadable Amplifier 5 to 500 MHz

Rev. V4


### Typical Performance Curves at +25°C




### Outline Drawing: TO-8 \*



### Outline Drawing: Surface Mount \*



### Outline Drawing: SMA Connectorized \*



M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9