



650V, 380mΩ, 8.5A N-Channel Enhancement Mode Super Junction Power MOSFET

Ordering Information

Part Number	Package Option
D3S380N65B-U	TO-220
D3S380N65E-U	TO-263

Description

+FET™ is an advanced Super Junction Power MOSFET offering excellent efficiency through low R_{DS-ON} and low gate charge. +FET™ is a rugged device with precision charge balance implementation designed for demanding uses such as enterprise power computing power supplies, motor control, lighting and other challenging power conversion applications.



Features

- LOW $R_{DS(ON)}$
- FAST SWITCHING
- HIGH E_{AS}
- REL TEST SPEC: JESD-22
- HTRB >3000 HRS

Benefits

- LOW CONDUCTION LOSSES
- HIGH EFFICIENCY
- EXCELLENT AVALANCHE PERFORMANCE

Table 1 Key Maximum Parameters

Parameter	Value	Unit
$V_{DSS} @ T_{jmax}$	710	V
$R_{DS(on)} max$	< 380	mΩ
$Q_g typ$	16	nC
$I_{Dmax} @ 25\text{ }^{\circ}\text{C}$	13.9	A

Applications

- POWER FACTOR CORRECTION
- SERVER POWER SUPPLIES
- TELECOM POWER SUPPLIES
- INVERTERS
- MOTOR CONTROL

Contents

Contents.....	2
1. Maximum Ratings	3
2. Thermal Characteristics	4
3. Electrical Characteristics	5
4. Package Outlines.....	7
5. Revision History	9
6. Resources.....	9
7. Patents, Copyrights and Trademarks.....	9
8. Legal Disclaimer	9

1. Maximum Ratings

Table 2 Maximum Ratings

@ T_j = 25 °C, unless otherwise specified

Parameter	Symbol	Values			Unit	Condition
		Min	Typ	Max		
Continuous drain current	I _D			5.4	A	T _C = 100°C
				8.5	A	T _C = 25°C
Pulsed drain current	I _{D, pulse}			34	A	T _C = 25°C
Avalanche energy, single pulse	E _{AS}			304	mJ	I _D = 3.5A; V _{DD} = 50V, V _{GS} = 10V, L=50mH, R _G =25 Ohms
Avalanche energy, repetitive	E _{AR}			0.456	mJ	I _D = 1.5; V _{DD} = 50V
Avalanche current, single pulse	I _{AS}			1.34	A	
MOSFET dv/dt ruggedness	dv/dt			50	V/ns	V _{DS} = 0...480V
Gate source voltage (static)	V _{GS}	-30		30	V	Static
Gate source voltage (dynamic)	V _{GS}	-30		30	V	AC (F>1Hz)
Power dissipation	P _{tot}			62	W	TO-220, TO-263, T _C = 25°C
Storage temperature	T _{stg}	-55		150	°C	
Operating junction temperature	T _j	-55		150	°C	
Mounting torque				60	N-cm	M3 and M3.5 screws
Continuous diode forward current	I _{SD}			8.5	A	T _C = 25°C
Diode pulse current	I _{S, pulse}			34	A	T _C = 25°C
Reverse diode dv/dt	dv/dt			15	V/ns	V _{DS} =0...480V, I _{SD} <=I _S , T _j = 25°C
Maximum diode commutation speed	di/dt			500	A/μs	V _{DS} =0...480V, I _{SD} <=I _S , T _j = 25°C

2. Thermal Characteristics

Table 3 Thermal Characteristics

Symbol	Parameter	Values				Unit
		TO-220	TO-220FP	TO-263	TO-247	
R_{th-jc}	Thermal resistance, junction-case	2.0	8.2	2.0	TBD	°C/W
R_{th-jA}	Thermal resistance, junction-ambient	65	65	65	TBD	°C/W
T_s	Soldering temperature, wave soldering only allowed at leads	260	260	260	TBD	°C

3. Electrical Characteristics

@ $T_j = 25^\circ\text{C}$, unless otherwise specified

Table 4 Static Characteristics

Parameter	Symbol	Values			Unit	Condition
		Min	Typ	Max		
Drain-source breakdown voltage	$V_{(BR)DSS}$	650			V	$I_D = 1\text{mA}$, $V_{GS} = 0\text{V}$
Gate threshold voltage	$V_{GS(TH)}$	2.3	3	3.7	V	$V_{DS} = V_{GS}$, $I_D = 47\mu\text{A}$
Zero gate voltage drain current	I_{DSS}			1	μA	$V_{DS} = 650\text{V}$, $T_C = 25^\circ\text{C}$, $V_{GS} = 0\text{V}$
				50		$V_{DS} = 650\text{V}$, $T_C = 125^\circ\text{C}$, $V_{GS} = 0\text{V}$
Gate-source leakage current	I_{GSS}			100	nA	$V_{GS} = \pm 30\text{V}$, $V_{DS} = 0\text{V}$
Drain-source on-state resistance	$R_{DS(on)}$		0.35	0.38	Ω	$V_{GS} = 10\text{V}$, $I_D = 4.3\text{A}$, $T_j = 25^\circ\text{C}$
			0.86		Ω	$V_{GS} = 10\text{V}$, $I_D = 4.3\text{A}$, $T_j = 150^\circ\text{C}$
Gate resistance***	R_G		1		Ω	

Table 5 Dynamic Characteristics

Parameter	Symbol	Values			Unit	Condition
		Min	Typ	Max		
Input capacitance	C_{iss}		777		pF	$V_{DS} = 100\text{V}$, $f = 1\text{MHz}$, $V_{GS} = 0\text{V}$
Output capacitance	C_{oss}		26.2		pF	
Reverse transfer capacitance	C_{rss}		7.4		pF	
Turn-on delay time	$t_{d(on)}$		10.5		ns	$V_{DD} = 400\text{V}$, $I_D = 4.3\text{A}$, $R_G = 1\Omega$, $V_{GS} = 10\text{V}$
Rise time	t_r		20		ns	
Turn-off delay time	$t_{d(off)}$		35		ns	
Fall time	t_f		21		ns	

Table 6 Gate Charge Characteristics

Parameter	Symbol	Values			Unit	Condition
		Min	Typ	Max		
Gate to source charge	Q_{gs}		3.1		nC	$V_{DD} = 480\text{V}$, $I_D = 4.3\text{A}$, $V_{GS} = 0$ to 10V
Gate to drain charge	Q_{gd}		5.8		nC	
Gate charge total	Q_g		15.4		nC	
Gate plateau voltage	$V_{plateau}$		5		V	


Table 7 Reverse Diode Characteristics

Parameter	Symbol	Values			Unit	Condition
		Min	Typ	Max		
Diode source-drain current	I_{SD}			8.5	A	
Diode forward voltage	V_{fd}		0.95	1.5	V	$I_{SD} = 8.5A$, $V_{GS} = 0V$, $T_J = 25^{\circ}C$
Reverse recovery time	t_{rr}		244		ns	$I_F = 8.5A$, $L = 5mH$ $di/dt = 100A/\mu S$ $V_{DD} = 60V$, $T_J = 25^{\circ}C$
Reverse recovery charge	Q_{rr}		3.1		μC	
Peak reverse recovery current	I_{rrm}		14.6		A	


4. Package Outlines

4a) TO-220

D3 Semiconductor TO-220-3L



D3 Semiconductor TO-263 (D2PAK)



5. Revision History

Revision	Release Date	Comments
1.0	1-November-2016	Preliminary Datasheet Release
1.1	1-July-2017	Updated tables and package information

6. Resources

www.d3semi.com

7. Patents, Copyrights and Trademarks

U.S. and Foreign Patents Pending.

The following are trademarks and service marks owned by D3 Semiconductor:

D3 Semiconductor[®], “Flying D” [®], +FET[™], Defining Precision Power[™].

All trademarks are property of their respective owners. © D3 Semiconductor 2016. All rights reserved

8. Legal Disclaimer

The information in this document is provided solely regarding D3 Semiconductor (“D3”) products. The information is not a guarantee of performance or characteristics. D3 Semiconductor reserves the right to modify, change, amend, improve or make corrections to this document, and its products, at any time and its sole discretion without prior written consent or notice. No license to any intellectual property rights is granted or implied under this document. D3 Semiconductor disclaims warranties and liabilities of any kind including non-infringement of intellectual property rights of any third party. D3 Semiconductor products may be used in applications such as automotive, military, aerospace, medical or other applications where failure or malfunction may result in personal injury, death or severe property or environmental damage only with express written approval from D3 Semiconductor. Sale of D3 Semiconductor products are subject to D3 Semiconductor’s standard terms and conditions. Products not purchased through D3 Semiconductor’s authorized distributors, agents or sales representatives are void of warranty.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9