




N- and P-Channel for Level Shift Load Switch


PRODUCT SUMMARY

	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)	Q _g (Typ.)
N-Channel	20	0.225 at V _{GS} = 4.5 V	1.5 ^a	1.1 nC
		0.270 at V _{GS} = 2.5 V	1.5 ^a	
		0.345 at V _{GS} = 1.8 V	1.5 ^a	
		0.960 at V _{GS} = 1.5 V	0.5	
P-Channel	- 12	0.057 at V _{GS} = - 4.5 V	- 4.5 ^a	5 nC
		0.077 at V _{GS} = - 2.5 V	- 4.5 ^a	
		0.115 at V _{GS} = - 1.8 V	- 4.5 ^a	
		0.200 at V _{GS} = - 1.5 V	- 1.5	

PowerPAK® SC-70-6 Dual



Marking Code



Ordering Information: SiA777EDJ-T1-GE3 (Lead (Pb)-free and Halogen-free)

FEATURES


- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFETs
- Typical ESD Protection: N-Channel 2800 V P-Channel 1900 V
- 100 % R_g Tested
- Compliant to RoHS Directive 2002/95/EC

APPLICATIONS

- Load Switch with Level Shift for Portable Devices
 - N-Channel for Level Shift Drive
 - P-Channel for Main Switch



RoHS
COMPLIANT
HALOGEN
FREE



ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter		Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage		V _{DS}	20	- 12	V
Gate-Source Voltage		V _{GS}	± 6	± 8	
Continuous Drain Current (T _J = 150 °C)	T _C = 25 °C	I _D	1.5 ^a	- 4.5 ^a	A
	T _C = 70 °C		1.5 ^a	- 4.5 ^a	
	T _A = 25 °C		1.5 ^{a, b, c}	- 4.5 ^{a, b, c}	
	T _A = 70 °C		1.5 ^{a, b, c}	- 3.9 ^{b, c}	
Pulsed Drain Current		I _{DM}	4	- 15	
Source Drain Current Diode Current	T _C = 25 °C	I _S	1.5 ^a	- 4.5 ^a	
	T _A = 25 °C		1.6 ^{b, c}	- 1.6 ^{b, c}	
Maximum Power Dissipation	T _C = 25 °C	P _D	5	7.8	W
	T _C = 70 °C		3.2	5	
	T _A = 25 °C		1.9 ^{b, c}	1.9 ^{b, c}	
	T _A = 70 °C		1.2 ^{b, c}	1.2 ^{b, c}	
Operating Junction and Storage Temperature Range		T _J , T _{stg}	- 55 to 150		°C
Soldering Recommendations (Peak Temperature) ^{d, e}			260		

THERMAL RESISTANCE RATINGS

Parameter	Symbol	N-Channel		P-Channel		Unit
		Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^{b, f}	R _{thJA}	52	65	52	65	°C/W
Maximum Junction-to-Case (Drain)	R _{thJC}	20	25	12.5	16	

Notes:

a. Package limited.

b. Surface mounted on 1" x 1" FR4 board.

c. t = 5 s.

d. See solder profile (www.vishay.com/ppg?73257). The PowerPAK SC-70 is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.

e. Rework Conditions: manual soldering with a soldering iron is not recommended for leadless components.

f. Maximum under steady state conditions for channel 1 and channel 2 is 110 °C/W.

SPECIFICATIONS T _J = 25 °C, unless otherwise noted							
Parameter	Symbol	Test Conditions		Min.	Typ.	Max.	Unit
Static							
Drain-Source Breakdown Voltage	V _{DS}	V _{GS} = 0 V, I _D = 250 μA	N-Ch	20			V
		V _{GS} = 0 V, I _D = - 250 μA	P-Ch	- 12			
V _{DS} Temperature Coefficient	ΔV _{DS} /T _J	I _D = 250 μA	N-Ch		21		mV/°C
		I _D = - 250 μA	P-Ch		- 3		
V _{GS(th)} Temperature Coefficient	ΔV _{GS(th)} /T _J	I _D = 250 μA	N-Ch		- 2.3		
		I _D = - 250 μA	P-Ch		2.3		
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	N-Ch	0.4		1.0	V
		V _{DS} = V _{GS} , I _D = - 250 μA	P-Ch	- 0.4		- 1	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ± 3 V	N-Ch			± 1	μA
		V _{DS} = 0 V, V _{GS} = ± 4.5 V	P-Ch			± 0.5	
		V _{DS} = 0 V, V _{GS} = ± 6 V	N-Ch			± 1	mA
		V _{DS} = 0 V, V _{GS} = ± 8 V	P-Ch			± 3	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V	N-Ch			1	μA
		V _{DS} = - 12 V, V _{GS} = 0 V	P-Ch			- 1	
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 55 °C	N-Ch			10	
		V _{DS} = - 12 V, V _{GS} = 0 V, T _J = 55 °C	P-Ch			- 10	
On-State Drain Current ^b	I _{D(on)}	V _{DS} ≥ 5 V, V _{GS} = 4.5 V	N-Ch	4			A
		V _{DS} ≤ - 5 V, V _{GS} = - 4.5 V	P-Ch	- 10			
Drain-Source On-State Resistance ^b	R _{DS(on)}	V _{GS} = 4.5 V, I _D = 1.6 A	N-Ch		0.183	0.225	Ω
		V _{GS} = - 4.5 V, I _D = - 3.8 A	P-Ch		0.047	0.057	
		V _{GS} = 2.5 V, I _D = 1.5 A	N-Ch		0.220	0.270	
		V _{GS} = - 2.5 V, I _D = - 3.3 A	P-Ch		0.063	0.077	
		V _{GS} = 1.8 V, I _D = 1.3 A	N-Ch		0.275	0.345	
		V _{GS} = - 1.8 V, I _D = 2.6 A	P-Ch		0.095	0.115	
		V _{GS} = 1.5 V, I _D = 0.3 A	N-Ch		0.320	0.960	
		V _{GS} = - 1.5 V, I _D = 1 A	P-Ch		0.125	0.200	
Forward Transconductance ^b	g _{fs}	V _{DS} = 10 V, I _D = 1.6 A	N-Ch		3.5		S
		V _{DS} = - 10 V, I _D = - 3.8 A	P-Ch		11		
Dynamic ^a							
Total Gate Charge	Q _g	V _{DS} = 10 V, V _{GS} = 5 V, I _D = 1.7 A	N-Ch		1.3	2.2	nC
		V _{DS} = - 6 V, V _{GS} = - 8 V, I _D = - 4.9 A	P-Ch		7.5	12	
		N-Channel V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 1.7 A	N-Ch		1.1	1.7	
P-Ch			5	8			
Gate-Source Charge	Q _{gs}	P-Channel V _{DS} = - 6 V, V _{GS} = - 4.5 V, I _D = - 4.9 A	N-Ch		0.2		
Gate-Drain Charge	Q _{gd}		P-Ch		0.6		
			N-Ch		0.1		
			P-Ch		1.8		
Gate Resistance	R _g	f = 1 MHz	N-Ch	40	200	400	Ω
			P-Ch	2	10	20	

Notes:

a. Guaranteed by design, not subject to production testing.

b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.



SPECIFICATIONS T _J = 25 °C, unless otherwise noted							
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit	
Dynamic ^a							
Turn-On Delay Time	t _{d(on)}	N-Channel V _{DD} = 10 V, R _L = 7.7 Ω I _D ≅ 1.3 A, V _{GEN} = 4.5 V, R _g = 1 Ω	N-Ch		20	30	ns
			P-Ch		20	30	
Rise Time	t _r		N-Ch		12	20	
			P-Ch		20	30	
Turn-Off Delay Time	t _{d(off)}	P-Channel V _{DD} = - 6 V, R _L = 1.5 Ω I _D ≅ - 3.9 A, V _{GEN} = - 4.5 V, R _g = 1 Ω	N-Ch		70	105	
			P-Ch		32	50	
Fall Time	t _f		N-Ch		20	30	
			P-Ch		16	25	
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I _S	T _C = 25 °C	N-Ch			1.5	A
			P-Ch			- 4.5	
Pulse Diode Forward Current ^a	I _{SM}		N-Ch			4	
			P-Ch			- 15	
Body Diode Voltage	V _{SD}	I _S = 1.3 A, V _{GS} = 0 V	N-Ch		0.9	1.2	V
		I _S = - 3.9 A, V _{GS} = 0 V	P-Ch		- 0.8	- 1.2	
Body Diode Reverse Recovery Time	t _{rr}	N-Channel I _F = 1.3 A, dI/dt = 100 A/μs, T _J = 25 °C	N-Ch		50	75	ns
			P-Ch		45	70	
Body Diode Reverse Recovery Charge	Q _{rr}		N-Ch		30	45	nC
			P-Ch		25	40	
Reverse Recovery Fall Time	t _a	P-Channel I _F = - 3.9 A, dI/dt = - 100 A/μs, T _J = 25 °C	N-Ch		15		ns
			P-Ch		15		
Reverse Recovery Rise Time	t _b		N-Ch		35		
			P-Ch		30		

Notes:







a. Guaranteed by design, not subject to production testing.







b. Pulse test; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

SiA777EDJ



Vishay Siliconix

**N-CHANNEL TYPICAL CHARACTERISTICS** $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted**Gate Current vs. Gate-to-Source Voltage****Gate Current vs. Gate-to-Source Voltage****Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current****Gate Charge**




N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$, unless otherwise noted

Normalized On-Resistance vs. Junction Temperature

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Single Pulse Power, Junction-to-Ambient

Threshold Voltage

Safe Operating Area, Junction-to-Ambient







SiA777EDJ







Vishay Siliconix




**N-CHANNEL TYPICAL CHARACTERISTICS** $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted

* The power dissipation P_D is based on $T_{J(max)} = 150\text{ }^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.




N-CHANNEL TYPICAL CHARACTERISTICS $T_A = 25\text{ }^{\circ}\text{C}$, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Case

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted**Gate Current vs. Gate-Source Voltage****Gate Current vs. Gate-Source Voltage****Output Characteristics****Transfer Characteristics****On-Resistance vs. Drain Current and Gate Voltage****Capacitance**


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified**Safe Operating Area, Junction-to-Ambient**


* The power dissipation P_D is based on $T_{J(max)} = 150\text{ }^\circ\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.


P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Case


Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg265371.




PowerPAK® SC70-6L



BACKSIDE VIEW OF SINGLE



BACKSIDE VIEW OF DUAL



- Notes:
1. All dimensions are in millimeters
 2. Package outline exclusive of mold flash and metal burr
 3. Package outline inclusive of plating

DIM	SINGLE PAD						DUAL PAD					
	MILLIMETERS			INCHES			MILLIMETERS			INCHES		
	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max	Min	Nom	Max
A	0.675	0.75	0.80	0.027	0.030	0.032	0.675	0.75	0.80	0.027	0.030	0.032
A1	0	-	0.05	0	-	0.002	0	-	0.05	0	-	0.002
b	0.23	0.30	0.38	0.009	0.012	0.015	0.23	0.30	0.38	0.009	0.012	0.015
C	0.15	0.20	0.25	0.006	0.008	0.010	0.15	0.20	0.25	0.006	0.008	0.010
D	1.98	2.05	2.15	0.078	0.081	0.085	1.98	2.05	2.15	0.078	0.081	0.085
D1	0.85	0.95	1.05	0.033	0.037	0.041	0.513	0.613	0.713	0.020	0.024	0.028
D2	0.135	0.235	0.335	0.005	0.009	0.013						
E	1.98	2.05	2.15	0.078	0.081	0.085	1.98	2.05	2.15	0.078	0.081	0.085
E1	1.40	1.50	1.60	0.055	0.059	0.063	0.85	0.95	1.05	0.033	0.037	0.041
E2	0.345	0.395	0.445	0.014	0.016	0.018						
E3	0.425	0.475	0.525	0.017	0.019	0.021						
e	0.65 BSC			0.026 BSC			0.65 BSC			0.026 BSC		
K	0.275 TYP			0.011 TYP			0.275 TYP			0.011 TYP		
K1	0.400 TYP			0.016 TYP			0.320 TYP			0.013 TYP		
K2	0.240 TYP			0.009 TYP			0.252 TYP			0.010 TYP		
K3	0.225 TYP			0.009 TYP								
K4	0.355 TYP			0.014 TYP								
L	0.175	0.275	0.375	0.007	0.011	0.015	0.175	0.275	0.375	0.007	0.011	0.015
T							0.05	0.10	0.15	0.002	0.004	0.006
ECN: C-07431 – Rev. C, 06-Aug-07 DWG: 5934												

RECOMMENDED PAD LAYOUT FOR PowerPAK® SC70-6L Dual



Dimensions in mm (inches)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9