

**ZXTN26070CV**

**70V NPN LOW SATURATION TRANSISTOR IN SOT-666**

**Features**

- $BV_{ce0} = 70V$ ,  $BV_{cbo} = 150V$
- $I_c$  Cont. 2A
- 5A Peak Pulse Current
- Extremely Low Equivalent On Resistance;  $R_{CE(sat)} = 130m\Omega$  at 1A
- **Lead, Halogen, and Antimony Free/RoHS Compliant (Note 1)**
- **“Green” Devices (Note 2)**

**Applications**


- DC-DC converter

**Mechanical Data**


- Case: SOT-666
- Case material: Molded Plastic. “Green” Molding Compound.
- UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Matte Tin Finish annealed over copper leadframe. Solderable per MIL-STD-202, Method 208
- Weight: 0.003 grams (Approximate)



Top View



Device Schematic




Pin Out Configuration

**Ordering Information** (Note 3)

Product	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
ZXTN26070CV-7	1Q6	7	8mm	3000

- Notes:
1. No purposefully added lead. Halogen and Antimony free: <900ppm bromine, <900ppm chlorine (<1500ppm total) and <1000ppm antimony compounds.
  2. Diodes Inc.'s “Green” Policy can be found on our website at <http://www.diodes.com>
  3. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**



1Q6 = Product Type Marking Code

**Maximum Ratings** @ $T_A = 25^\circ\text{C}$  unless otherwise specified


Characteristic	Symbol	Value	Unit
Collector-Base Voltage	$V_{CBO}$	150	V
Collector-Emitter Voltage	$V_{CEO}$	70	V
Emitter-Base Voltage	$V_{EBO}$	7	V
Continuous Collector Current	$I_C$	2	A
Peak Pulse Current	$I_{CM}$	5	A
Base Current	$I_B$	500	A

**Thermal Characteristics**


Characteristic	Symbol	Value	Unit
Power Dissipation at $T_A = 25^\circ\text{C}$ (Note 4)	$P_D$	0.6	W
Power Dissipation at $T_A = 25^\circ\text{C}$ (Note 5)	$P_D$	1	W
Thermal Resistance, Junction to Ambient (Note 4) @ $T_A = 25^\circ\text{C}$	$R_{\theta JA}$	208	$^\circ\text{C/W}$
Thermal Resistance, Junction to Ambient (Note 5) @ $T_A = 25^\circ\text{C}$	$R_{\theta JA}$	121	$^\circ\text{C/W}$
Thermal Resistance, Junction to Lead (Note 6)	$R_{\theta JL}$	37	$^\circ\text{C/W}$
Operating and Storage Temperature Range	$T_J, T_{STG}$	-55 to +150	$^\circ\text{C}$

- Notes:
4. For a device surface mounted minimum recommended pad layout, in still air conditions
  5. Mounted on 25mm X 25mm X 1.6mm FR4 PCB with high coverage of single sided 2 oz copper, in still air conditions.
  6. From Collector leads. Typical.


**Thermal Characteristics and Derating Information**




**Safe Operating Area**



**Derating Curve**



**Transient Thermal Impedance**









**Pulse Power Dissipation**

**Electrical Characteristics** @T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS</b>						
Collector-Base Breakdown Voltage	V <sub>(BR)CBO</sub>	150	190	–	V	I <sub>C</sub> = 100μA
Collector-Emitter Breakdown Voltage (Note 7)	V <sub>(BR)CEO</sub>	70	80	–	V	I <sub>C</sub> = 10mA
Emitter-Base Breakdown Voltage	V <sub>(BR)EBO</sub>	7	8.3	–	V	I <sub>E</sub> = 100μA
Collector Cutoff Current	I <sub>CBO</sub> , I <sub>CES</sub>	–	–	100	nA	V <sub>CB</sub> = 60V, V <sub>CES</sub> = 60V
Emitter Cutoff Current	I <sub>EBO</sub>	–	–	100	nA	V <sub>EB</sub> = 5.6V
<b>ON CHARACTERISTICS (Note 7)</b>						
DC Current Gain	h <sub>FE</sub>	190	320	–	–	I <sub>C</sub> = 10mA, V <sub>CE</sub> = 5V
		200	340	–		
		75	110	–		
Collector-Emitter Saturation Voltage	V <sub>CE(SAT)</sub>	–	22	30	V	I <sub>C</sub> = 0.1A, I <sub>B</sub> = 10mA
		–	110	150		I <sub>C</sub> = 0.5A, I <sub>B</sub> = 10mA
		–	147	200		I <sub>C</sub> = 1A, I <sub>B</sub> = 50mA
		–	135	165		I <sub>C</sub> = 1A, I <sub>B</sub> = 100mA
		–	265	330		I <sub>C</sub> = 2A, I <sub>B</sub> = 200mA
Base-Emitter Turn-On Voltage	V <sub>BE(ON)</sub>	–	0.85	1.0	V	I <sub>C</sub> = 1A, V <sub>CE</sub> = 2V
Base-Emitter Saturation Voltage	V <sub>BE(SAT)</sub>	–	0.90	1.1	V	I <sub>C</sub> = 1A, I <sub>B</sub> = 50mA
<b>SMALL SIGNAL CHARACTERISTICS</b>						
Output Capacitance	C <sub>obo</sub>	–	10	–	pF	V <sub>CB</sub> = 10V, f = 1MHz
Current Gain-Bandwidth Product	f <sub>T</sub>	–	200	–	MHz	V <sub>CE</sub> = 10V, I <sub>C</sub> = 50mA, f = 100MHz
<b>SWITCHING CHARACTERISTICS</b>						
Turn-On Time	t <sub>on</sub>	–	46	–	ns	V <sub>CE</sub> = 10V, I <sub>C</sub> = 0.5A
Turn-Off Time	t <sub>off</sub>	–	722	–	ns	I <sub>B1</sub> = -I <sub>B2</sub> = 25mA


Notes: 7. Measured under pulsed conditions. Pulse width = 300μs. Duty cycle ≤ 2%

**Typical Characteristics**




**ZXTN26070CV**

**Package Outline Dimensions**



SOT-666			
Dim	Min	Max	Typ
A	0.15	0.30	0.20
B	1.10	1.25	1.20
C	1.55	1.70	1.60
D	-	-	0.50
G	0.90	1.10	1.00
H	1.50	1.70	1.60
K	0.55	0.60	0.60
L	0.10	0.30	0.20
M	0.10	0.18	0.15
All Dimensions in mm			

**Suggested Pad Layout**



Dimensions	Value (in mm)
Z	2.2
G	1.2
X	0.375
Y	0.5
C1	1.7
C2	0.5

#### IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

#### LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2010, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9