

Aluminum Capacitors SMD (Chip), High Temperature





Fig.1 Component outline



QUICK REFERENCE DATA

DESCRIPTION	VALUE
Nominal case sizes (L x W x H in mm)	8 x 8 x 10 to 10 x 10 x 14
Rated capacitance range, C_R	10 to 680 μF
Tolerance on C_R	$\pm 20 \%$
Rated voltage range, U_R	6.3 to 63 V
Category temperature range	- 55 to + 125 °C
Endurance test at 125 °C	1000 hours
Useful life at 125 °C	1500 hours
Useful life at 40 °C; 1.8 x I_R applied	150 000 hours
Shelf life at 0 V, 125 °C	1000 hours
Based on sectional specification	IEC 60384-18/CECC 32300
Climatic category IEC 60068	55/125/56

FEATURES

- Polarized aluminum electrolytic capacitors, non-solid electrolyte, self healing
- SMD-version with base plate, reflow solderable
- High temperature, 1500 hours at 125 °C
- High capacitance values
- Charge and discharge proof, no peak current limitation
- Lead (Pb)-free
- ATTENTION: for maximum safe soldering conditions refer to fig.4

APPLICATIONS

- SMD technology, for high mounting density
- Industrial and professional applications
- Automotive, general industrial
- Smoothing, filtering, buffering

MARKING

- Rated capacitance (in μF)
- Rated voltage (in V)
- Date code, in accordance with IEC 60062
- Black mark or '–' sign indicating the cathode (the anode is identified by bevelled edges)
- Code indicating group number (H)

PACKAGING

- Supplied in blister tape on reel

SELECTION CHART FOR C_R , U_R AND RELEVANT NOMINAL CASE SIZES (L x W x H in mm)

C_R (μF)	U_R (V)						
	6.3	10	16	25	35	50	63
10	-	-	-	-	-	-	8 x 8 x 10
22	-	-	-	-	-	-	8 x 8 x 10
33	-	-	-	-	-	-	8 x 8 x 10
47	-	-	-	-	-	8 x 8 x 10	10 x 10 x 10
68	-	-	-	-	8 x 8 x 10	10 x 10 x 10	10 x 10 x 14
100	-	-	-	8 x 8 x 10	10 x 10 x 10	10 x 10 x 14	-
150	-	-	8 x 8 x 10	-	10 x 10 x 14	-	-
220	-	8 x 8 x 10	-	10 x 10 x 10	-	-	-
330	8 x 8 x 10	10 x 10 x 10	10 x 10 x 14	-	-	-	-
470	10 x 10 x 10	10 x 10 x 14	-	-	-	-	-
680	10 x 10 x 14	-	-	-	-	-	-

Table 1

DIMENSIONS in millimeters AND MASS									
NOMINAL CASE SIZE L x W x H	CASE CODE	L _{max.}	W _{max.}	H _{max.}	Ø D	B _{max.}	S	L _{1 max.}	MASS (g)
8 x 8 x 10	0810	8.5	8.5	10.5	8.0	1.0	3.1	9.9	≈ 1.0
10 x 10 x 10	1010	10.5	10.5	10.5	10.0	1.0	4.5	11.8	≈ 1.3
10 x 10 x 14	1014	10.5	10.5	14.3	10.0	1.0	4.5	11.8	≈ 1.5




Fig.2 Dimensional outline

Table 2

TAPE AND REEL DIMENSIONS in millimeters, PACKAGING QUANTITIES						
NOMINAL CASE SIZE L x W x H	CASE CODE	PITCH P ₁	TAPE WIDTH W	TAPE THICKNESS T ₂	REEL DIA.	PACKAGING QUANTITY PER REEL
8 x 8 x 10	0810	16	24	11.3	380	500
10 x 10 x 10	1010	16	24	11.3	380	500
10 x 10 x 14	1014	16	24	14.8	330	250

Note

1. Detailed tape dimensions see section "PACKAGING".

MOUNTING

The capacitors are designed for automatic placement on to printed-circuit boards.

Optimum dimensions of soldering pads depend amongst others on soldering method, mounting accuracy, print lay-out and/or adjacent components.

For recommended soldering pad dimensions, refer to Fig.3 and Table 3.

SOLDERING

Soldering conditions are defined by the curve, temperature versus time, where the temperature is that measured on the soldering pad during processing.

For maximum conditions refer to Fig.4.

Any temperature versus time curve which does not exceed the specified maximum curves may be applied.

Table 3

RECOMMENDED SOLDERING PAD DIMENSIONS in millimeters			
CASE CODE	a	b	c
0810	3.5	2.5	3.0
1010	4.3	2.5	4.0
1014	4.3	2.5	4.0




Fig. 3 Recommended solder pad dimensions

AS A GENERAL PRINCIPLE, TEMPERATURE AND DURATION SHALL BE THE **MINIMUM** NECESSARY REQUIRED TO ENSURE GOOD SOLDERING CONNECTIONS. HOWEVER, THE SPECIFIED MAXIMUM CURVES SHOULD NEVER BE EXCEEDED.




Fig. 4 Maximum temperature load during infrared reflow soldering measured on the soldering pad

Aluminum Capacitors
SMD (Chip), High Temperature

Vishay BCcomponents

ELECTRICAL DATA

SYMBOL	DESCRIPTION
C_R	rated capacitance at 100 Hz, tolerance $\pm 20\%$
I_R	rated RMS ripple current at 100 kHz, 125 °C
I_{L2}	max. leakage current after 2 minutes at U_R
$\tan \delta$	max. dissipation factor at 100 Hz
Z	max. impedance at 100 kHz

Note

Unless otherwise specified, all electrical values in Table 4 apply at
 $T_{amb} = 20\text{ °C}$, $P = 86$ to 106 kPa , $RH = 45$ to 75% .

ORDERING EXAMPLE

Electrolytic capacitor 140 CLH series

100 $\mu\text{F}/50\text{ V}$; $\pm 20\%$

Nominal case size:

10 x 10 x 14 mm; taped on reel

Ordering code: MAL214095102E3

Former 12NC: 2222 140 95102

Table 4

ELECTRICAL DATA AND ORDERING INFORMATION

U_R (V)	C_R (μF)	NOMINAL CASE SIZE L x W x H (mm)	I_R 100 kHz 125 °C (mA)	I_{L2} 2 min (μA)	$\tan \delta$	Z 100 kHz + 20 °C (Ω)	ORDERING CODE MAL2140.....
6.3	330	8 x 8 x 10	180	21	0.30	0.65	95303E3
	470	10 x 10 x 10	300	30	0.30	0.17	95301E3
	680	10 x 10 x 14	430	43	0.30	0.12	95302E3
10	220	8 x 8 x 10	180	22	0.26	0.65	95403E3
	330	10 x 10 x 10	300	33	0.26	0.17	95401E3
	470	10 x 10 x 14	430	47	0.26	0.12	95402E3
16	150	8 x 8 x 10	180	24	0.22	0.65	95502E3
	330	10 x 10 x 14	430	53	0.22	0.12	95501E3
25	100	8 x 8 x 10	180	25	0.18	0.65	95602E3
	220	10 x 10 x 10	300	55	0.18	0.19	95601E3
35	68	8 x 8 x 10	180	24	0.14	0.65	95003E3
	100	10 x 10 x 10	255	35	0.14	0.40	95001E3
	150	10 x 10 x 14	317	53	0.14	0.30	95002E3
50	47	8 x 8 x 10	145	24	0.12	1.00	95103E3
	68	10 x 10 x 10	205	34	0.12	0.56	95101E3
	100	10 x 10 x 14	255	50	0.12	0.42	95102E3
63	10	8 x 8 x 10	145	6.3	0.12	1.00	95805E3
	22	8 x 8 x 10	145	14	0.12	1.00	95803E3
	33	8 x 8 x 10	145	21	0.12	1.00	95804E3
	47	10 x 10 x 10	205	30	0.12	0.56	95801E3
	68	10 x 10 x 14	255	43	0.12	0.42	95802E3

ADDITIONAL ELECTRICAL DATA

PARAMETER	CONDITIONS	VALUE
Voltage		
Surge voltage for short periods	IEC 60384-18, subclause 4.14	$U_S \leq 1.15 \times U_R$
Reverse voltage for short periods	IEC 60384-18, subclause 4.16	$U_{rev} \leq 0.5\text{ V}$
Current		
Leakage current	after 2 minutes at U_R	$I_{L2} \leq 0.01 \times C_R \times U_R$
Inductance		
Equivalent series inductance (ESL)		typ. 16 nH
Resistance		
Equivalent series resistance (ESR) at 100 Hz	calculated from $\tan \delta_{max.}$ and C_R (see Table 4)	$ESR = \tan \delta / 2 \pi f C_R$


CAPACITANCE (C)

Fig.5 Typical multiplier of capacitance as a function of frequency of ambient temperature



DISSIPATION FACTOR ($\tan \delta$)Fig.6 Typical multiplier of dissipation factor ($\tan \delta$) as a function of ambient temperature**EQUIVALENT SERIES RESISTANCE (ESR)**

Fig.7 Typical multiplier of ESR as a function of frequency


IMPEDANCE (Z)

Fig.8 Typical multiplier of ESR as a function of frequency




Fig.9 Typical impedance as a function of frequency




Fig.10 Typical impedance as a function of frequency

RIPPLE CURRENT AND USEFUL LIFE




Table 5

MULTIPLIER OF RIPPLE CURRENT (I_R) AS A FUNCTION OF FREQUENCY			
FREQUENCY (Hz)	I_R MULTIPLIER		
	$U_R = 6.3 \text{ to } 25 \text{ V}$	$U_R = 35 \text{ and } 50 \text{ V}$	$U_R = 63 \text{ V}$
50	0.60	0.45	0.40
100	0.70	0.60	0.55
300	0.80	0.75	0.70
1000	0.85	0.85	0.85
3000	0.90	0.90	0.90
10 000	0.95	0.95	0.95
30 000	0.97	0.97	0.97
100 000	1.00	1.00	1.00

Table 6

TEST PROCEDURES AND REQUIREMENTS			
TEST		PROCEDURE (quick reference)	REQUIREMENTS
NAME OF TEST	REFERENCE		
Mounting	IEC 60384-18, subclause 4.3	shall be performed prior to tests mentioned below; reflow soldering; for maximum temperature load refer to chapter "Mounting"	$\Delta C/C: \pm 5 \%$ $\tan \delta \leq \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$
Endurance	IEC 60384-18/ CECC 32 300, subclause 4.15	$T_{\text{amb}} = 125 \text{ }^{\circ}\text{C}$; U_R applied; 1000 hours	$U_R = 6.3 \text{ V}$; $\Delta C/C: \pm 25 \%$ $U_R \geq 10 \text{ V}$; $\Delta C/C: \pm 20 \%$ $\tan \delta \leq 2 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$
Useful life	CECC 30301, subclause 1.8.1	$T_{\text{amb}} = 125 \text{ }^{\circ}\text{C}$; U_R and I_R applied; 1500 hours	$\Delta C/C: \pm 50 \%$ $\tan \delta \leq 3 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$ no short or open circuit total failure percentage: $\leq 1 \%$
Shelf life (storage at high temperature)	IEC 60384-18/ CECC 32 300, subclause 4.17	$T_{\text{amb}} = 125 \text{ }^{\circ}\text{C}$; no voltage applied; 1000 hours after test: U_R to be applied for 30 minutes, 24 to 48 hours before measurement	for requirements see 'Endurance test' above
Reverse voltage	IEC 60384-18/ CECC 32 300, subclause 4.16	$T_{\text{amb}} = 125 \text{ }^{\circ}\text{C}$: 125 hours at $U = -0.5 \text{ V}$, followed by 125 hours at U_R	$\Delta C/C: \pm 15 \%$ $\tan \delta \leq 1.5 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9