

448 Series Fuse



Agency Approvals

| Agency | Agency File Number | Ampere Range |
|--------|--------------------|--------------|
| | E10480 | 0.062A - 15A |
| | 29862 | 0.062A - 15A |
| | NBK030205-E10480A | 1A - 1.6A |
| | NBK030205-E10480B | 2A - 5A |
| | NBK101105-E184655 | 6.3A - 10A |

Electrical Characteristics for Series

| % of Ampere Rating | Ampere Rating | Opening Time |
|--------------------|---------------|------------------|
| 100% | 0.062A -15 | 4 hours, Minimum |
| 200% | 0.062A -10 | 5 sec., Maximum |
| | 12 -15 | 20 sec., Maximum |

Description

The lead-free Nano² SMF Fuse is a very small, square surface mount fuse that is RoHS compliant, Halogen Free and 100% lead-free. This product is fully compatible with lead-free solder alloys and higher temperature profiles associated with lead-free assembly.

Features

- RoHS compliant, Lead-free and Halogen Free
- Very fast-acting
- Small size
- Wide range of current rating available (0.062A to 15A)
- Wide operating temperature range
- UL Recognized to UL/CSA/NMX UL 248-1 and UL/CSA/NMX UL 248-14
- Conforms to DENAN's Appendix 3

Applications

- Notebook PC
- LCD/PDPTV
- LCD monitor
- LCD/PDP panel
- LCD backlight inverter
- Portable DVD player
- Power supply
- Networking
- PC server
- Cooling fan system
- Storage system
- Telecom system
- Wireless basestation
- White goods
- Game console
- Office Automation equipment
- Battery charging circuit protection
- Industrial equipment

Additional Information



Datasheet



Resources



Samples

Electrical Specifications by Item

| Ampere Rating (A) | Amp Code | Max Voltage Rating (V) | Interrupting Rating | Nominal Cold Resistance (Ohms) | Nominal Melting I ² t (A ² sec) | Agency Approvals | | |
|-------------------|----------|------------------------|--|--------------------------------|---|---|---|---|
| | | | | | |  |  |  |
| 0.062 | .062 | 125 | 50A @125VAC/ VDC 300A @32 VDC PSE: 100A @100VAC | 5.50 | 0.00023 | x | x | |
| 0.080 | .080 | 125 | | 4.42 | 0.00043 | x | x | |
| 0.100 | .100 | 125 | | 2.90 | 0.00082 | x | x | |
| 0.125 | .125 | 125 | | 2.58 | 0.00130 | x | x | |
| 0.160 | .160 | 125 | | 1.76 | 0.00280 | x | x | |
| 0.200 | .200 | 125 | | 1.65 | 0.00380 | x | x | |
| 0.250 | .250 | 125 | | 0.95 | 0.01520 | x | x | |
| 0.315 | .315 | 125 | | 0.7015 | 0.02650 | x | x | |
| 0.375 | .375 | 125 | | 0.6155 | 0.02400 | x | x | |
| 0.400 | .400 | 125 | | 0.4895 | 0.04160 | x | x | |
| 0.500 | .500 | 125 | | 0.3800 | 0.10000 | x | x | |
| 0.630 | .630 | 125 | | 0.3125 | 0.121 | x | x | |
| 0.750 | .750 | 125 | | 0.2290 | 0.206 | x | x | |
| 0.800 | .800 | 125 | | 0.1907 | 0.272 | x | x | |
| 1.00 | .001. | 125 | | 0.08630 | 0.441 | x | x | x |
| 1.25 | 1.25 | 125 | | 0.06619 | 0.900 | x | x | x |
| 1.50 | 01.5 | 125 | | 0.06514 | 0.900 | x | x | x |
| 1.60 | 01.6 | 125 | | 0.06261 | 1.122 | x | x | x |
| 2.00 | 002. | 125 | | 0.03529 | 0.812 | x | x | x |
| 2.50 | 02.5 | 125 | | 0.02934 | 1.156 | x | x | x |
| 3.00 | 003. | 125 | | 0.02445 | 1.720 | x | x | x |
| 3.15 | 3.15 | 125 | | 0.02300 | 1.810 | x | x | x |
| 3.50 | 03.5 | 125 | | 0.02100 | 2.300 | x | x | x |
| 4.00 | 004. | 125 | | 0.01577 | 3.970 | x | x | x |
| 5.00 | 005. | 125 | | 0.01531 | 4.490 | x | x | x |
| 6.30 | 06.3 | 125 | | 0.01044 | 12.10 | x | x | x |
| 7.00 | 007. | 125 | | 0.00900 | 13.92 | x | x | x |
| 8.00 | 008. | 125 | | 0.00780 | 18.33 | x | x | x |
| 10.00 | 010. | 125 | 35A @125 VAC 50A @125 VDC 300A @32 VDC PSE: 100A @100VAC | 0.00700 | 28.00 | x | x | x |
| 12.00 | 012. | 85 | 50A @65 VAC/ VDC | 0.00533 | 47.59 | x | x | |
| 15.00 | 015. | 85 | 300A @24 VDC 200A @85 VDC | 0.00394 | 78.4 | x | x | |

Notes:


- I²t calculated at 8ms.
- Resistance is measured at 10% of rated current, 25°C

Temperature Re-rating Curve



Note:
1. Rerating depicted in this curve is in addition to the standard derating of 25% for continuous operation.

Average Time Current Curves



Soldering Parameters

| | | |
|--|------------------------------------|-------------------------|
| Reflow Condition | | Pb - Free assembly |
| Pre Heat | - Temperature Min ($T_{s(min)}$) | 150°C |
| | - Temperature Max ($T_{s(max)}$) | 200°C |
| | - Time (Min to Max) (t_s) | 60 - 180 secs |
| Average ramp up rate (Liquidus Temp (T_L) to peak) | | 5°C/second max. |
| $T_{s(max)}$ to T_L - Ramp-up Rate | | 5°C/second max. |
| Reflow | - Temperature (T_L) (Liquidus) | 217°C |
| | - Temperature (t_L) | 60 - 150 seconds |
| Peak Temperature (T_p) | | 260 ^{+0/-5} °C |
| Time within 5°C of actual peak Temperature (t_p) | | 20 - 40 seconds |
| Ramp-down Rate | | 5°C/second max. |
| Time 25°C to peak Temperature (T_p) | | 8 minutes max. |
| Do not exceed | | 260°C |

Wave Soldering Parameters 260°C Peak Temperature, 10 seconds max.



Product Characteristics

| | |
|--|---|
| Materials | Body: Ceramic Terminations: Gold-plated Caps |
| Product Marking | Brand, Amperage Rating |
| Operating Temperature | -55°C to 125°C |
| Moisture Sensitivity Level | Level 1, J-STD-020 |
| Solderability | MIL-STD-202, Method 208 |
| Insulation Resistance (after Opening) | MIL-STD-202, Method 302, Test Condition A (10,000 ohms minimum) |


| | |
|-------------------------------------|---|
| Thermal Shock | MIL-STD-202, Method 107, Test Condition B, 5 cycles, -65°C to 125°C, 15 minutes @ each extreme |
| Mechanical Shock | MIL-STD-202, Method 213, Test I: Deenergized. 100G's pk amplitude, sawtooth wave 6ms duration, 3 cycles XYZ+xyz = 18 shocks |
| Vibration | MIL-STD-202, Method 201: 0.03" amplitude, 10-55 Hz in 1 min. 2hrs each XYZ=6hrs |
| Moisture Resistance | MIL-STD-202, Method 106, 10 cycles |
| Salt Spray | MIL-STD-202, Method 101, Test Condition B (48hrs) |
| Resistance to Soldering Heat | MIL-STD-202, Method 210, Test condition B (10 sec at 260°C) |

Dimensions



Recommended pad layout

Part Numbering System



***Example:**
1.5 amp product is 044801.5MR (1 amp product shown above).

Packaging

| Packaging Option | Packaging Specification | Quantity | Quantity & Packaging Code |
|--------------------|-----------------------------|----------|---------------------------|
| 12mm Tape and Reel | EIA RS-481-1 (IEC 600286-3) | 1000 | MR |

Disclaimer Notice - Littelfuse products are not designed for, and shall not be used for, any purpose (including, without limitation, automotive, military, aerospace, medical, life-saving, life-sustaining or nuclear facility applications, devices intended for surgical implant into the body, or any other application in which the failure or lack of desired operation of the product may result in personal injury, death, or property damage) other than those expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse documentation. The sale and use of Littelfuse products is subject to Littelfuse Terms and Conditions of Sale, unless otherwise agreed by Littelfuse. Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at www.littelfuse.com/disclaimer-electronics.

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9