

## 5.5kV E-Rated

Medium voltage fuses for feeder circuit, switchgear and transformer protection



### Description:

- E-Rated, current-limiting, medium voltage fuses for feeder circuit, switchgear and transformer protection.

### Features and benefits

- Current-limiting E-Rated medium voltage fuses are defined by their melting time-current characteristic that permit their electrical interchangeability with other fuses of the same E Rating.
- E-Rated fuses must have a defined current response time specified by ANSI C37.46. E-Rated fuse of 100 amps and below must melt in 300 seconds at an RMS current within the range of 200% to 240% of the fuse's nameplate current rating. E-Rated fuses greater than 100 amps must melt in 600 seconds at an RMS current within the range of 220% to 264% of the fuse's nameplate current rating.
- E-Rated fuses are physically dimensioned for easy installation in existing hardware.
- Current-limiting fuses provide positive interruption even on low fault currents. The fuse limits the magnitude of electromechanical stresses in the protected apparatus.
- Constructions available in ferrule, bolt-on and clip-lock, and specialty mount fuses for AMPGARD™ motor starters.
- Outdoor rating available on select catalog numbers (requires installation in a suitable enclosure).
- Open fuse indicator easily integrates into automation schemes and speeds troubleshooting by providing a positive visual indication of fuse operation.
- 50/60Hz operating frequency for worldwide application.
- Mountings are available in disconnect and non-disconnect versions with porcelain or glass polyester insulators.
- Live parts and end fittings available.

### Typical applications:

- Medium voltage transformer primary protection
- Medium voltage feeder circuit protection
- Medium voltage switches
- Medium voltage metal-enclosed switchgear



Powering Business Worldwide

## E-Rated medium voltage ferrule fuses

### Catalog symbols:

- General purpose:
  - 5CLE-\_E-D (10-25A)
  - 5CLE-\_E (10-1350A)
  - 5HLE-\_E (10-450A)
  - JCY-\_E (1-25A)
- Full range (per ANSI C37.40)
  - MV055F\_ (10-450A)

### Ratings\*:

- Volts
  - 5.5kV
- Amps
  - 1 to 1350A
- Interrupting ratings
  - 40 to 63kA RMS Sym

\* See catalog number tables for voltages, ampacities and interrupting ratings by catalog number.


### Agency information:

- E-Rated fuses meet the performance characteristics of ANSI C37.46
- UL® Listed, Guide JEEG, File E240398. See catalog numbers.

### Recommended fuseclips and holders:

CLE and HLE

### Dimensions (see catalog number tables for values)



|                                          |                           |                     |                                  |                  |              | Catalog number                                     |                              |                                           |                                      |
|------------------------------------------|---------------------------|---------------------|----------------------------------|------------------|--------------|----------------------------------------------------|------------------------------|-------------------------------------------|--------------------------------------|
|                                          |                           |                     |                                  |                  |              | Mounting<br>(including live parts, end fittings)** |                              | Live parts<br>(including<br>end fittings) | End fittings<br>(disconnect<br>only) |
| Amp rating                               | Fuse<br>mounting<br>type* | Voltage<br>BIL (kV) | Approximate dimensions - in (mm) |                  |              | Porcelain insulator                                | Glass-polyester<br>insulator |                                           |                                      |
|                                          |                           |                     | Diameter<br>A                    | Clip center<br>B | Length<br>C  |                                                    |                              |                                           |                                      |
| CLE                                      |                           |                     |                                  |                  |              |                                                    |                              |                                           |                                      |
| 10E-D-25E-D<br>30E-250E<br>Single barrel | Non-disconnect            | 60                  | 3.0 (76.2)                       | 14.0 (355.6)     | 17.9 (454.7) | 5CLE-PNM-D                                         | 5CLE-GNM-D                   | CLE-NL-D                                  | —                                    |
|                                          | Disconnect†               | 60                  |                                  |                  |              | 5CLE-PDM-D                                         | 5CLE-GDM-D                   | CLE-DL-D                                  | CLE-DF-D                             |
| 15E-25E<br>Single barrel                 | Non-disconnect            | 60                  | 2.0 (50.8)                       | 11.5 (292.1)     | 12.9 (327.7) | 5CLE-PNM-C                                         | 5CLE-GNM-C                   | CLE-NL-C                                  | —                                    |
|                                          | Disconnect†               | 60                  |                                  |                  |              | 5CLE-PDM-C                                         | 5CLE-GDM-C                   | CLE-DL-C                                  | CLE-DF-C                             |
| 300E-450E<br>Double barrel               | Non-disconnect            | 60                  | 3.0 (76.2)                       | 14.0 (355.6)     | 17.9 (454.7) | 5CLE-PNM-E                                         | 5CLE-GNM-E                   | CLE-NL-E                                  | —                                    |
|                                          | Disconnect†               | 60                  |                                  |                  |              | 5CLE-PDM-E                                         | 5CLE-GDM-E                   | CLE-DL-E                                  | CLE-DF-E                             |
| 600E and 750E<br>Double barrel           | Consult factory           | 60                  | 4.0 (101.6)                      | N/A              | N/A          | —                                                  | —                            | —                                         | —                                    |
| 1100E and 1350E<br>Four barrel           | Consult factory           | —                   | 4.0 (101.6)                      | N/A              | N/A          | —                                                  | —                            | —                                         | —                                    |
| HLE                                      |                           |                     |                                  |                  |              |                                                    |                              |                                           |                                      |
| 10E-D-250E<br>Single barrel              | Non-disconnect            | 60                  | 3.0 (76.2)                       | 12.0 (304.8)     | 15.9 (403.9) | 5HLE-PNM-D                                         | 5HLE-GNM-D                   | CLE-NL-D                                  | —                                    |
|                                          | Disconnect                | 60                  |                                  |                  |              | 5HLE-PDM-D                                         | 5HLE-GDM-D                   | CLE-DL-D                                  | CLE-DF-D                             |
| 300E-450E<br>Double barrel               | Non-disconnect            | 60                  | 3.0 (76.2)                       | 12.0 (304.8)     | 15.9 (403.9) | 5HLE-PNM-E                                         | 5HLE-GNM-E                   | CLE-NL-E                                  | —                                    |
|                                          | Disconnect                | 60                  |                                  |                  |              | 5HLE-PDM-E                                         | 5HLE-GDM-E                   | CLE-DL-E                                  | CLE-DF-E                             |

\* See page 12 for illustrations and dimensions

\*\* End fittings supplied only when required.

† Disconnect mountings provide a means for fuse extraction only. Do not use a disconnect mounting for load switching or fuse removal while energized.


CLE, HLE and JCY general purpose

| Amp rating | Dimensions - in (mm) |            |                | Interrupting<br>rating kA<br>(RMS Sym.) | Number of<br>barrels | Installation<br>location | Catalog number |
|------------|----------------------|------------|----------------|-----------------------------------------|----------------------|--------------------------|----------------|
|            | Length A             | Diameter B | Clip centers C |                                         |                      |                          |                |
| 1          | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-1E         |
| 2          | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-2E         |
| 3          | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-3E         |
| 5          | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-5E         |
| 7          | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-7E         |
| 10         | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-10E        |
| 10         | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-10E-D     |
| 10         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-10E       |
| 15         | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-15E        |
| 15         | 12.9 (328)           | 2 (51)     | 11.5 (292)     | 50                                      | 1                    | Indoor                   | 5CLE-15E*      |
| 15         | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-15E-D     |
| 15         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-15E       |
| 20         | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-20E        |
| 20         | 12.9 (328)           | 2 (51)     | 11.5 (292)     | 50                                      | 1                    | Indoor                   | 5CLE-20E*      |
| 20         | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-20E-D     |
| 20         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-20E       |
| 25         | 11.2 (284)           | 2 (51)     | 9 (229)        | 40                                      | 1                    | Indoor/outdoor           | JCY-25E        |
| 25         | 12.9 (328)           | 2 (51)     | 11.5 (292)     | 50                                      | 1                    | Indoor                   | 5CLE-25E*      |
| 25         | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-25E-D     |
| 25         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-25E       |
| 30         | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-30E       |
| 30         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-30E       |
| 40         | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 5CLE-40E†      |
| 40         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-40E†      |
| 50         | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 5CLE-50E†      |
| 50         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-50E†      |
| 65         | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 5CLE-65E†      |
| 65         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-65E†      |
| 80         | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 5CLE-80E†      |
| 80         | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-80E†      |
| 100        | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 5CLE-100E†     |
| 100        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-100E†     |
| 125        | 17.9 (455)           | 3 (76)     | 14 (356)       | 50                                      | 1                    | Indoor/outdoor           | 5CLE-125E†     |
| 125        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-125E†     |
| 150        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-150E†     |
| 150        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-150E†     |
| 175        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-175E†     |
| 175        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-175E†     |
| 200        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-200E†     |
| 200        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-200E†     |
| 250        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 1                    | Indoor/outdoor           | 5CLE-250E†     |
| 250        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 1                    | Indoor/outdoor           | 5HLE-250E†     |
| 300        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 2                    | Indoor/outdoor           | 5CLE-300E†     |
| 300        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 2                    | Indoor/outdoor           | 5HLE-300E†     |
| 350        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 2                    | Indoor/outdoor           | 5CLE-350E†     |
| 350        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 2                    | Indoor/outdoor           | 5HLE-350E†     |
| 400        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 2                    | Indoor/outdoor           | 5CLE-400E†     |
| 400        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 2                    | Indoor/outdoor           | 5HLE-400E†     |
| 450        | 17.9 (455)           | 3 (76)     | 14 (356)       | 63                                      | 2                    | Indoor/outdoor           | 5CLE-450E†     |
| 450        | 15.9 (404)           | 3 (76)     | 12 (305)       | 63                                      | 2                    | Indoor/outdoor           | 5HLE-450E†     |

\* Fuses conform to dimensional standards established by Westinghouse.

† UL Listed, Guide JEEG, File E240398.

5.5kV time-current curves — minimum melt for JCY\_E fuses



JCY-  
\_

5.5kV time-current curves — total clear for JCY-E fuses



JCY-

MV055 full range

| Amp rating | Dimensions - in (mm) |               |                   | Interrupting<br>rating kA<br>(RMS Sym.) | Number of<br>barrels | Installation<br>location | Catalog number |
|------------|----------------------|---------------|-------------------|-----------------------------------------|----------------------|--------------------------|----------------|
|            | Length<br>A          | Diameter<br>B | Clip centers<br>C |                                         |                      |                          |                |
| 5          | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX5E   |
| 7          | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX7E   |
| 10         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX10E  |
| 10         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX10E  |
| 15         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX15E  |
| 15         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX15E  |
| 20         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX20E  |
| 20         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX20E  |
| 25         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX25E  |
| 25         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX25E  |
| 30         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX30E  |
| 30         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX30E  |
| 40         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX40E  |
| 40         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX40E  |
| 50         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX50E  |
| 50         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX50E  |
| 65         | 15.7 (399)           | 2 (51)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1CAX65E  |
| 65         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX65E  |
| 80         | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX80E  |
| 100        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX100E |
| 125        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX125E |
| 150        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX150E |
| 175        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX175E |
| 200        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 1                    | Indoor                   | MV055F1DAX200E |
| 250        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 2                    | Indoor                   | MV055F2DAX250E |
| 300        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 2                    | Indoor                   | MV055F2DAX300E |
| 350        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 2                    | Indoor                   | MV055F2DAX350E |
| 400        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 2                    | Indoor                   | MV055F2DAX400E |
| 450        | 15.7 (399)           | 3 (76)        | 12 (305)          | 50                                      | 2                    | Indoor                   | MV055F2DAX450E |

Recommended MV055 fuseclips:

| Description                    | Fuse<br>diameter -<br>in (mm) | Figure | Clip dimensions - in (mm) |           |           |           |            |           |          | Catalog<br>number |
|--------------------------------|-------------------------------|--------|---------------------------|-----------|-----------|-----------|------------|-----------|----------|-------------------|
|                                |                               |        | A                         | B         | C         | D         | E          | F         | G        |                   |
| Enclosed fuseclip              | 2 (51)                        | 1      | 3.75 (95)                 | 1.98 (50) | 2.01 (51) | 1.19 (30) | 4.54 (115) | 1.51 (38) | 0.4 (10) | A3354710*         |
| Enclosed fuseclip              | 3 (76)                        | 1      | 4.14 (105)                | 2.45 (62) | 3.01 (76) | 1.19 (30) | 5.64 (143) | 1.51 (38) | 0.4 (10) | A3354730*         |
| Open fuseclip                  | 3 (76)                        | 2      | See dimensions drawing    |           |           |           |            |           |          | 1A0065            |
| Spring loaded open<br>fuseclip | 3 (76)                        | 3      | See dimensions drawing    |           |           |           |            |           |          | 9078A67G04        |

\*For single barrel applications only. Not sold in pairs.

Figure 1



Figure 2







Figure 3




**5.5kV time-current curves — minimum melt for MV055\_ 2 inch diameter fuses**




5.5kV time-current curves — total clear for MV055\_ 2 inch diameter fuses




**5.5kV time-current curves — minimum melt for MV055\_ 3 inch diameter fuses**



5.5kV time-current curves — total clear for MV055\_ 3 inch diameter fuses



5.5kV peak let-through for MV055\_ 2 and 3 inch diameter fuses



MV055\_ (2 and 3 inch diameter)

**CLE and HLE type mountings - in (mm)**

| Catalog number               | Hole centers  |           | Overall length | Hole Inset  | Hole centers | Contact height | Overall height | BIL kV |
|------------------------------|---------------|-----------|----------------|-------------|--------------|----------------|----------------|--------|
|                              | A             | B         |                |             |              |                |                |        |
| Disconnect single barrel†    |               |           |                |             |              |                |                |        |
| 5CLE-GDM-C                   | 12.74 (323.6) | 6 (152.4) | 25.5 (647.7)   | 0.75 (19)   | 1.75 (44.4)  | 4.5 (114.3)    | 9.75 (247.6)   | 60     |
| 5CLE-PDM-C                   | 12.74 (323.6) | 6 (152.4) | 25.5 (647.7)   | 0.75 (19)   | 1.75 (44.4)  | 4.5 (114.3)    | 9.75 (247.6)   | 60     |
| 5CLE-GDM-D                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 11.72 (297.7)  | 60     |
| 5CLE-PDM-D                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 11.72 (297.7)  | 60     |
| 5HLE-GDM-D                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 11.72 (297.7)  | 60     |
| 5HLE-PDM-D                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 11.72 (297.7)  | 60     |
| Disconnect double barrel†    |               |           |                |             |              |                |                |        |
| 5CLE-GDM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 15.28 (388.1)  | 60     |
| 5CLE-PDM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 15.28 (388.1)  | 60     |
| 5HLE-GDM-E                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 15.28 (388.1)  | 60     |
| 5HLE-PDM-E                   | 16.25 (412.8) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 15.28 (388.1)  | 60     |
| Non-disconnect single barrel |               |           |                |             |              |                |                |        |
| 5CLE-GNM-C                   | 12.75 (323.8) | 6 (152.4) | 22 (558.8)     | 0.75 (19)   | 1.75 (44.4)  | 4.5 (114.3)    | 7.25 (184.1)   | 60     |
| 5CLE-PNM-C                   | 12.75 (323.8) | 6 (152.4) | 22 (558.8)     | 0.75 (19)   | 1.75 (44.4)  | 4.5 (114.3)    | 7.25 (184.1)   | 60     |
| 5CLE-GNM-D                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 8.79 (223.3)   | 60     |
| 5CLE-PNM-D                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 8.79 (223.3)   | 60     |
| 5HLE-GNM-D                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 8.79 (223.3)   | 60     |
| 5HLE-PNM-D                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 8.79 (223.3)   | 60     |
| Non-disconnect double barrel |               |           |                |             |              |                |                |        |
| 5CLE-GNM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.42 (36.1)  | 4.5 (114.3)    | 12.48 (317)    | 60     |
| 5CLE-PNM-E                   | 15.24 (387.1) | 6 (152.4) | 25 (635)       | 0.62 (15.7) | 1.42 (36.1)  | 4.5 (114.3)    | 12.48 (317)    | 60     |
| 5HLE-GNM-E                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 12.48 (317)    | 60     |
| 5HLE-PNM-E                   | 16.25 (412.7) | 6 (152.4) | 23 (584.2)     | 0.62 (15.7) | 1.75 (44.4)  | 4.5 (114.3)    | 12.48 (317)    | 60     |

**CLE and HLE type disconnect mounting†**



**CLE and HLE type non-disconnect mounting**



† Disconnect mountings provide a means for fuse extraction only. Do not use a disconnect mounting for load switching or fuse removal while energized.

## E-Rated medium voltage specialty mount fuses

### Catalog symbols:

- \_AHLE-\_E (for Eaton AMPGARD motor starting assemblies)
- \_BHLE-\_E/\_BHCL-\_E (bolt-on version)
- \_HCL-\_E (clip-lock version)

### Ratings\*:

- Volts
  - 5.5kV
- Amps
  - 10 to 900A
- Interrupting ratings
  - 31 to 63kA RMS Sym

\* See catalog number tables for voltages, ampacities and interrupting ratings by catalog number.

### Agency information:


- E-Rated fuses meet the performance characteristics of ANSI C37.46

### Recommended live parts for clip-lock fuses


- Catalog number HCL-NL-1

### Dimensions - in (mm)


#### BHLE bolt-on



#### HCL clip-lock



#### CLE four barrel bolt-on



### AHLE for Eaton AMPGARD motor starting assemblies

| Amp rating | Interrupting rating kA (RMS Sym.) | Number of barrels | Catalog number |
|------------|-----------------------------------|-------------------|----------------|
| 10         | 63                                | 1                 | 5AHLE-10E      |
| 15         | 63                                | 1                 | 5AHLE-15E      |
| 20         | 63                                | 1                 | 5AHLE-20E      |
| 25         | 63                                | 1                 | 5AHLE-25E      |
| 30         | 63                                | 1                 | 5AHLE-30E      |
| 40         | 63                                | 1                 | 5AHLE-40E†     |
| 50         | 63                                | 1                 | 5AHLE-50E†     |
| 65         | 63                                | 1                 | 5AHLE-65E†     |
| 80         | 63                                | 1                 | 5AHLE-80E†     |
| 100        | 63                                | 1                 | 5AHLE-100E†    |
| 125        | 63                                | 1                 | 5AHLE-125E†    |
| 150        | 63                                | 1                 | 5AHLE-150E†    |
| 175        | 63                                | 1                 | 5AHLE-175E†    |
| 200        | 63                                | 1                 | 5AHLE-200E†    |
| 250        | 63                                | 1                 | 5AHLE-250E†    |
| 300        | 63                                | 2                 | 5AHLE-300E†    |
| 350        | 63                                | 2                 | 5AHLE-350E†    |
| 400        | 63                                | 2                 | 5AHLE-400E†    |
| 450        | 63                                | 2                 | 5AHLE-450E†    |

† UL Listed, Guide JEEG, File E240398.

### HCL clip-lock versions

| Amp rating | Dimensions - in (mm) |            |                | Interrupting<br>rating kA<br>(RMS Sym.) | Number of<br>barrels | Installation<br>location | Catalog<br>number |
|------------|----------------------|------------|----------------|-----------------------------------------|----------------------|--------------------------|-------------------|
|            | Overall length A     | Diameter B | Hole centers C |                                         |                      |                          |                   |
| 10         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-10E          |
| 15         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-15E          |
| 20         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-20E          |
| 25         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-25E          |
| 30         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-30E          |
| 40         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-40E†         |
| 50         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-50E†         |
| 65         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-65E†         |
| 80         | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-80E†         |
| 100        | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-100E†        |
| 125        | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-125E†        |
| 150        | 16.8 (427)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-150E†        |
| 200        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-200E†        |
| 250        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 1                    | Indoor                   | 5HCL-250E†        |
| 300        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 2                    | Indoor                   | 5HCL-300E†        |
| 400        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 2                    | Indoor                   | 5HCL-400E†        |
| 450        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 2                    | Indoor                   | 5HCL-450E†        |
| 500        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 2                    | Indoor                   | 5HCL-500E         |
| 600        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 2                    | Indoor                   | 5HCL-600E         |
| 750        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 3                    | Indoor                   | 5HCL-750E         |
| 900        | 22.8 (579)           | 3 (76)     | N/A            | 63                                      | 3                    | Indoor                   | 5HCL-900E         |


† UL Listed, Guide JEEG, File E240398.

**CLE, BHLE and BHCL bolt-on versions**

| Amp rating | Dimensions - in (mm) |               |                   | Interrupting<br>rating kA<br>(RMS Sym.) | Number of<br>barrels | Installation<br>location | Catalog<br>number |
|------------|----------------------|---------------|-------------------|-----------------------------------------|----------------------|--------------------------|-------------------|
|            | Overall length<br>A  | Diameter<br>B | Hole centers<br>C |                                         |                      |                          |                   |
| 10         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-10E         |
| 15         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-15E         |
| 20         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-20E         |
| 25         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-25E         |
| 30         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-30E         |
| 40         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-40E†        |
| 50         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-50E†        |
| 65         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-65E†        |
| 80         | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-80E†        |
| 100        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-100E†       |
| 125        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-125E†       |
| 150        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-150E†       |
| 175        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-175E†       |
| 200        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-200E†       |
| 200        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 1                    | Indoor                   | 5BHCL-200E        |
| 250        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 1                    | Indoor                   | 5BHLE-250E†       |
| 250        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 1                    | Indoor                   | 5BHCL-250E        |
| 300        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 2                    | Indoor                   | 5BHLE-300E†       |
| 300        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 2                    | Indoor                   | 5BHCL-300E        |
| 350        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 2                    | Indoor                   | 5BHLE-350E†       |
| 400        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 2                    | Indoor                   | 5BHLE-400E†       |
| 400        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 2                    | Indoor                   | 5BHCL-400E        |
| 450        | 19.2 (488)           | 3 (76)        | 17.9 (455)        | 63                                      | 2                    | Indoor                   | 5BHLE-450E†       |
| 450        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 2                    | Indoor                   | 5BHCL-450E        |
| 500        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 2                    | Indoor                   | 5BHCL-500E        |
| 600        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 2                    | Indoor                   | 5BHCL-600E        |
| 600        | 28.9 (734)           | 4 (102)       | 18.4 (467)        | 40                                      | 2                    | Indoor                   | 5CLE-600E         |
| 750        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 3                    | Indoor                   | 5BHCL-750E        |
| 750        | 28.9 (734)           | 4 (102)       | 18.4 (467)        | 40                                      | 2                    | Indoor                   | 5CLE-750E         |
| 900        | 25.1 (637)           | 3 (76)        | 23.7 (602)        | 63                                      | 3                    | Indoor                   | 5BHCL-900E        |
| 1100       | 19.8 (503)           | 4 (102)       | 18.4 (467)        | 31                                      | 4                    | Indoor                   | 5CLE-1100E        |
| 1350       | 19.8 (503)           | 4 (102)       | 18.4 (467)        | 31                                      | 4                    | Indoor                   | 5CLE-1350E        |

† UL Listed, Guide JEEG, File E240398.


5.5kV time-current curves — minimum melt for 5CLE- \_E and 5CLE- \_D



5CLE- \_

|                    |                    |                    |                    |
|--------------------|--------------------|--------------------|--------------------|
| Curve 70548501     | Curve 70545801     | Curve 70546001     | Curve 62908902     |
| April 16, 1999     | April 16, 1999     | April 20, 1999     | April 1999         |
| Reference # 563532 | Reference # 705458 | Reference # 705460 | Reference # 629089 |

5.5kV time-current curves — total clear for 5CLE-\_E and 5CLE\_-\_D



5CLE-\_

Curve 70548702  
April 16, 1999  
Reference # 563533

Curve 70545901  
April 20, 1999  
Reference # 705459

Curve 70546101  
April 20, 1999  
Reference # 705461

Curve 62908903  
April 1999  
Reference # 629089


5.5kV peak let-through for 5CLE- \_E and 5CLE- \_D



|                    |                    |                    |
|--------------------|--------------------|--------------------|
| Curve 70548701     | Curve 70547601     | Curve 62908904     |
| April 1999         | April 1999         | April 1999         |
| Reference # 705487 | Reference # 705476 | Reference # 629089 |

5CLE- \_

5.5kV time-current curves — minimum melt for 5HLE-\_E, 5AHLE-\_E and 5BHLE-\_E



5HLE-\_, 5BHLE-\_, 5AHLE-\_

Curve 70548507

April 16, 1999

Reference # 563532

Curve 70545805

April 16, 1999


Reference # 705458

Curve 70546005

April 20, 1999


Reference # 705460

5.5kV time-current curves — total clear for 5HLE- \_E, 5AHLE- \_E and 5BHLE- \_E



|                                                                                    |                                                        |                                                        |
|------------------------------------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|
| 5HLE-_, 5BHLE-_, 5AHLE-_<br>Curve 70548607<br>April 16, 1999<br>Reference # 563533 | Curve 70545905<br>April 20, 1999<br>Reference # 705459 | Curve 70546105<br>April 20, 1999<br>Reference # 705461 |
|------------------------------------------------------------------------------------|--------------------------------------------------------|--------------------------------------------------------|

5.5kV peak let-through for 5HLE-\_E, 5AHLE-\_E and 5BHLE-\_E



5HLE-\_, 5BHLE-\_, 5AHLE-\_

Curve 70548703

April 1999


Reference # 705487

Curve 70547603

April 1999

Reference # 705476


5.5kV time-current curves — minimum melt for 5HCL-E



5HCL-    

|                |                |                |                |
|----------------|----------------|----------------|----------------|
| Curve 70548505 | Curve 70545803 | Curve 70546003 | Curve 66703401 |
| Janaury 2001   | January 2001   | April 2001     | Janaury 2001   |

5.5kV time-current curves — total clear for 5HCL\_E




5HCL\_

Curve 70548605  
Janaury 2001

Curve 70545903  
Janaury 2001

Curve 70516103  
Janaury 2001

Curve 66703501  
Janaury 2001



5HCL-\_\_

Curve 70548702 January 2001  
Curve 70547602 January 2001  
Curve 66703701 January 2001

The only controlled copy of this data sheet is the electronic read-only version located on the Eaton network drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

**Eaton**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
Eaton.com

Bussmann Division  
114 Old State Road  
Ellisville, MO 63021  
United States  
Eaton.com/bussmannseries

© 2016 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. 10351 - BU-SB15151  
April 2016

Eaton, Bussmann and AMPGARD are valuable trademarks of Eaton in the US and other countries. You are not permitted to use the Eaton trademarks without prior written consent of Eaton.

For Eaton's Bussmann series product information, call 1-855-287-7626 or visit: [Eaton.com/bussmannseries](http://Eaton.com/bussmannseries)

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9