

**Balun transformers**  
**Wound SMD**  
**ATB series**



# ATB3225 type



## FEATURES

- The ATB3225 case size is L3.2×W2.5×H2.3mm.
- The case size is smaller than conventional Baluns.
- The frequency band width for ATB3225-75011CT is 5 to 200MHz, for ATB3225-75032CT is 5 to 100MHz, for ATB3225-75034CT is 1 to 100MHz, and for ATB3225-50011CT is 1 to 100MHz.
- Low insertion loss and good balance parameters.

## APPLICATION

- Cable modem

## PART NUMBER CONSTRUCTION

| ATB         | 3225                  | - | 750                     | 11                         | CT            | - | T               | 001           |
|-------------|-----------------------|---|-------------------------|----------------------------|---------------|---|-----------------|---------------|
| Series name | L×W×H dimensions (mm) |   | Impedance (Ω) at 100MHz | Impedance ratio            | Type          |   | Packaging style | Internal code |
|             | 3.2×2.5×2.3           |   | 750 75<br>500 50        | 11 1:1<br>32 3:2<br>34 3:4 | CT Center tap |   | T ø180mm reel   |               |

## CHARACTERISTICS SPECIFICATION TABLE

| DC resistance (Ω)max. | Impedance ratio | Frequency range (MHz) | Insertion loss (dB)max. | Return loss (dB)min. | Amplitude unbalance (dB)max. | Phase difference (deg.) | Part No.                             |
|-----------------------|-----------------|-----------------------|-------------------------|----------------------|------------------------------|-------------------------|--------------------------------------|
| 0.7                   | 1:1 (75Ω:75Ω)   | 5 to 65<br>5 to 200   | 0.8<br>1.5              | 15<br>10             | 0.1<br>0.5                   | 180±2<br>180±5          | <a href="#">ATB3225-75011CT-T001</a> |
| 0.7                   | 3:2 (75Ω:50Ω)   | 5 to 100              | 2                       | 5                    | 1                            | 180±10                  | <a href="#">ATB3225-75032CT-T001</a> |
| 0.7                   | 3:4 (75Ω:100Ω)  | 1 to 100              | 2                       | 5                    | 0.1                          | 180±10                  | <a href="#">ATB3225-75034CT-T000</a> |
| 0.7                   | 1:1 (50Ω: 50Ω)  | 1<br>100              | 0.8<br>1.5              | 15<br>10             | 0.1<br>0.5                   | 180±2<br>180±5          | <a href="#">ATB3225-50011CT-T000</a> |

\* Temperature derating was considered for the rated current.

### Measurement equipment

| Measurement item    | Product No. | Manufacturer          |
|---------------------|-------------|-----------------------|
| Insertion loss      | E5071B      | Keysight Technologies |
| Return loss         | E5071B      | Keysight Technologies |
| Amplitude unbalance | E5071B      | Keysight Technologies |
| Phase difference    | E5071B      | Keysight Technologies |

\* Equivalent measurement equipment may be used.




# ATB3225 type


## FREQUENCY CHARACTERISTICS

### ATB3225-75011CT-T001


#### INSERTION LOSS




#### RETURN LOSS



#### AMPLITUDE UNBALANCE




#### PHASE UNBALANCE




### ATB3225-75032CT-T001


#### INSERTION LOSS




#### RETURN LOSS



#### AMPLITUDE BALANCE



#### PHASE BALANCE




# ATB3225 type


## FREQUENCY CHARACTERISTICS

### ATB3225-75034CT-T000


#### INSERTION LOSS




#### RETURN LOSS



#### AMPLITUDE IMBALANCE




#### PHASE BALANCE




### ATB3225-50011CT-T000


#### INSERTION LOSS




#### RETURN LOSS



#### AMPLITUDE IMBALANCE




#### PHASE BALANCE




# ATB3225 type


## SHAPE & DIMENSIONS




## RECOMMENDED LAND PATTERN



## CIRCUIT DIAGRAM




## RECOMMENDED REFLOW PROFILE




## PACKAGING STYLE


### REEL DIMENSIONS



### TAPE DIMENSIONS



| Type    | A        | B        | K        |
|---------|----------|----------|----------|
| ATB3225 | 2.90±0.1 | 3.60±0.1 | 2.5±0.05 |



### PACKAGE QUANTITY

| Package quantity | 1000 pcs/reel |
|------------------|---------------|
|------------------|---------------|

### TEMPERATURE RANGE, INDIVIDUAL WEIGHT

| Operating temperature range | Storage temperature range* | Individual weight |
|-----------------------------|----------------------------|-------------------|
| -40 to +85°C                | -40 to +85°C               | 75 mg             |

\* The storage temperature range is for after the assembly.

## REMINDERS FOR USING THESE PRODUCTS

Before using these products, be sure to request the delivery specifications.

### SAFETY REMINDERS

Please pay sufficient attention to the warnings for safe designing when using this products.

#### REMINDERS

- The storage period is within 6 months. Be sure to follow the storage conditions (temperature: 5 to 40°C, humidity: 10 to 75% RH or less).  
If the storage period elapses, the soldering of the terminal electrodes may deteriorate.
- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Before soldering, be sure to preheat components.  
The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications.  
If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- When embedding a printed circuit board where a chip is mounted to a set, be sure that residual stress is not given to the chip due to the overall distortion of the printed circuit board and partial distortion such as at screw tightening portions.
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Carefully lay out the coil for the circuit board design of the non-magnetic shield type.  
A malfunction may occur due to magnetic interference.
- Use a wrist band to discharge static electricity in your body through the grounding wire.
- Do not expose the products to magnets or magnetic fields.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.  
The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.  
If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

When designing your equipment even for general-purpose applications, you are kindly requested to take into consideration securing protection circuit/device or providing backup circuits in your equipment.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9