



## Dual Common Cathode Schottky Rectifier


ITO-220AB



MBRF15xxCT


D<sup>2</sup>PAK (TO-263AB)


MBRB15xxCT


**RoHS**  
COMPLIANT

### FEATURES

- Power pack
- Guardring for overvoltage protection
- Low power loss, high efficiency
- Low forward voltage drop
- High forward surge capability
- High frequency operation
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C (for D<sup>2</sup>PAK (TO-263AB)) package
- Solder bath temperature 275 °C maximum, 10 s, per JESD 22-B106 (for ITO-220AB package)
- AEC-Q101 qualified
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

### DESIGN SUPPORT TOOLS


[click logo to get started](#)

### TYPICAL APPLICATIONS

For use in high frequency rectifier of switching mode power supplies, freewheeling diodes, DC/DC converters, or polarity protection application.

### MECHANICAL DATA

**Case:** ITO-220AB, D<sup>2</sup>PAK (TO-263AB)

Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS-compliant, commercial grade  
Base P/NHE3\_X - RoHS-compliant, AEC-Q101 qualified ("\_X" denotes revision code, e.g. A, B,...)

**Terminals:** matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

**Polarity:** as marked

**Mounting Torque:** 10 in-lbs maximum

| PRIMARY CHARACTERISTICS |                                          |
|-------------------------|------------------------------------------|
| $I_{F(AV)}$             | 2 x 7.5 A                                |
| $V_{RRM}$               | 45 V, 60 V                               |
| $I_{FSM}$               | 150 A                                    |
| $V_F$                   | 0.57 V, 0.65 V                           |
| $T_J$ max.              | 150 °C                                   |
| Package                 | ITO-220AB, D <sup>2</sup> PAK (TO-263AB) |
| Circuit configuration   | Common cathode                           |

| MAXIMUM RATINGS (T <sub>C</sub> = 25 °C unless otherwise noted)                              |                  |             |            |      |
|----------------------------------------------------------------------------------------------|------------------|-------------|------------|------|
| PARAMETER                                                                                    | SYMBOL           | MBRB1545CT  | MBRB1560CT | UNIT |
| Maximum repetitive peak reverse voltage                                                      | V <sub>RRM</sub> | 45          | 60         | V    |
| Working peak reverse voltage                                                                 | V <sub>RWM</sub> | 45          | 60         |      |
| Maximum DC blocking voltage                                                                  | V <sub>DC</sub>  | 45          | 60         |      |
| Maximum average forward rectified current at T <sub>C</sub> = 105 °C                         | total device     | 15          |            | A    |
|                                                                                              | per diode        | 7.5         |            |      |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load per diode | I <sub>FSM</sub> | 150         |            |      |
| Peak repetitive reverse surge current per diode at t <sub>p</sub> = 2.0 μs, 1 kHz            | I <sub>RRM</sub> | 1.0         | 0.5        |      |
| Voltage rate of change (rated V <sub>R</sub> )                                               | dV/dt            | 10 000      |            | V/μs |
| Operating junction temperature range                                                         | T <sub>J</sub>   | -65 to +150 |            | °C   |
| Storage temperature range                                                                    | T <sub>STG</sub> | -65 to +175 |            |      |
| Isolation voltage (ITO-220AB only) from terminal to heatsink t = 1 min                       | V <sub>AC</sub>  | 1500        |            | V    |



| ELECTRICAL CHARACTERISTICS ( $T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise noted) |             |                      |                                     |            |            |      |
|-----------------------------------------------------------------------------------------|-------------|----------------------|-------------------------------------|------------|------------|------|
| PARAMETER                                                                               | SYMBOL      | TEST CONDITIONS      |                                     | MBRF1545CT | MBRB1560CT | UNIT |
| Maximum instantaneous forward voltage per diode                                         | $V_F^{(1)}$ | $I_F = 7.5\text{ A}$ | $T_C = 25\text{ }^{\circ}\text{C}$  | -          | 0.75       | V    |
|                                                                                         |             | $I_F = 7.5\text{ A}$ | $T_C = 125\text{ }^{\circ}\text{C}$ | 0.57       | 0.65       |      |
|                                                                                         |             | $I_F = 15\text{ A}$  | $T_C = 25\text{ }^{\circ}\text{C}$  | 0.84       | -          |      |
|                                                                                         |             | $I_F = 15\text{ A}$  | $T_C = 125\text{ }^{\circ}\text{C}$ | 0.72       | -          |      |
| Maximum instantaneous reverse current at DC blocking voltage per diode                  | $I_R^{(2)}$ | Rated $V_R$          | $T_C = 25\text{ }^{\circ}\text{C}$  | 0.1        | 1.0        | mA   |
|                                                                                         |             |                      | $T_C = 125\text{ }^{\circ}\text{C}$ | 15         | 50         |      |

**Notes**(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle(2) Pulse test: pulse width  $\leq 40\text{ ms}$ 

| THERMAL CHARACTERISTICS ( $T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise noted) |                 |      |      |                      |
|--------------------------------------------------------------------------------------|-----------------|------|------|----------------------|
| PARAMETER                                                                            | SYMBOL          | MBRF | MBRB | UNIT                 |
| Maximum thermal resistance per diode                                                 | $R_{\theta JA}$ | -    | 60   | $^{\circ}\text{C/W}$ |
|                                                                                      | $R_{\theta JC}$ | 5.0  | 3.0  |                      |

| ORDERING INFORMATION (Example) |                                  |                 |              |               |               |
|--------------------------------|----------------------------------|-----------------|--------------|---------------|---------------|
| PACKAGE                        | PREFERRED P/N                    | UNIT WEIGHT (g) | PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| ITO-220AB                      | MBRF1545CT-E3/45                 | 1.99            | 45           | 50/tube       | Tube          |
| TO-263AB                       | MBRB1545CT-E3/45                 | 1.35            | 45           | 50/tube       | Tube          |
| TO-263AB                       | MBRB1545CT-E3/81                 | 1.35            | 81           | 800/reel      | Tape and reel |
| ITO-220AB                      | MBRF1545CTHE3_A/P <sup>(1)</sup> | 1.99            | P            | 50/tube       | Tube          |
| TO-263AB                       | MBRB1545CTHE3_B/P <sup>(1)</sup> | 1.35            | P            | 50/tube       | Tube          |
| TO-263AB                       | MBRB1545CTHE3_B/I <sup>(1)</sup> | 1.35            | I            | 800/reel      | Tape and reel |

**Note**

(1) AEC-Q101 qualified



## RATINGS AND CHARACTERISTICS CURVES ( $T_C = 25\text{ }^{\circ}\text{C}$ unless otherwise noted)




Fig. 1 - Forward Current Derating Curve




Fig. 4 - Typical Reverse Characteristics Per Diode




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current Per Diode




Fig. 5 - Typical Junction Capacitance Per Diode




Fig. 3 - Typical Instantaneous Forward Characteristics Per Diode





Fig. 6 - Typical Transient Thermal Impedance Per Diode




## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)


### ITO-220AB



### D<sup>2</sup>PAK (TO-263AB)



### Mounting Pad Layout





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9