




# Flyback Transformers

For 3 Watt, 7 Watt and 13 Watt  
PoE Applications



- Flyback transformers for PoE applications
- Designed to operate in continuous mode at 250 kHz with an input of 36–72 Vdc
- 1500 Vrms, one minute isolation from primary and bias to secondary

**Designer's Kit** C395 contains two of each part shown in bold

**Core material** Ferrite

**Terminations** RoHS tin-silver over tin over nickel over phos bronze. Other terminations available at additional cost.

**Weight** POE13P: 6.15 g; POE70P: 3.85 g; POE30P: 2.05 g

**Ambient temperature** –40°C to +85°C

**Storage temperature** Component: –40°C to +85°C.

Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Failures in Time (FIT) / Mean Time Between Failures (MTBF)**

38 per billion hours / 26,315,789 hours, calculated per Telcordia SR-332

**PCB washing** Tested with pure water or alcohol only. For other solvents, see Doc787\_PCB\_Washing.pdf.

| Part number <sup>1</sup> | Power (W) | Inductance at 0 A <sup>2</sup> ±10% (μH) | Inductance at I <sub>pk</sub> <sup>3</sup> min (μH) | DCR max (Ohms) <sup>4</sup> |       |       | Leakage inductance max (μH) <sup>5</sup> | Turns ratio <sup>6</sup> |            | I <sub>pk</sub> <sup>3</sup> (A) | Output <sup>7</sup> |
|--------------------------|-----------|------------------------------------------|-----------------------------------------------------|-----------------------------|-------|-------|------------------------------------------|--------------------------|------------|----------------------------------|---------------------|
|                          |           |                                          |                                                     | pri                         | bias  | sec   |                                          | pri : sec                | pri : bias |                                  |                     |
| <b>POE30P-33L</b>        | 3         | 310                                      | 279.0                                               | 1.02                        | 2.01  | 0.066 | 4.75                                     | 1 : 0.19                 | 1 : 0.70   | 0.3                              | 3.3 V, 0.91 A       |
| <b>POE30P-50L</b>        | 3         | 310                                      | 279.0                                               | 1.02                        | 2.01  | 0.118 | 4.50                                     | 1 : 0.28                 | 1 : 0.70   | 0.3                              | 5.0 V, 0.6 A        |
| <b>POE30P-12L</b>        | 3         | 310                                      | 279.0                                               | 1.04                        | 2.01  | 0.700 | 4.25                                     | 1 : 0.70                 | 1 : 0.70   | 0.3                              | 12 V, 0.25 A        |
| <b>POE70P-33L</b>        | 7         | 155                                      | 139.5                                               | 0.414                       | 0.822 | 0.036 | 4.00                                     | 1 : 0.19                 | 1 : 0.667  | 0.65                             | 3.3 V, 2.12 A       |
| <b>POE70P-50L</b>        | 7         | 155                                      | 139.5                                               | 0.414                       | 0.822 | 0.060 | 3.60                                     | 1 : 0.262                | 1 : 0.667  | 0.65                             | 5.0 V, 1.4 A        |
| <b>POE70P-12L</b>        | 7         | 155                                      | 139.5                                               | 0.414                       | 0.822 | 0.343 | 3.25                                     | 1 : 0.667                | 1 : 0.667  | 0.65                             | 12 V, 0.6 A         |
| <b>POE13P-33L</b>        | 13        | 127                                      | 114.3                                               | 0.255                       | 0.310 | 0.024 | 1.25                                     | 1 : 0.166                | 1 : 0.50   | 1.0                              | 3.3 V, 4.0 A        |
| <b>POE13P-50L</b>        | 13        | 127                                      | 114.3                                               | 0.222                       | 0.348 | 0.039 | 0.950                                    | 1 : 0.25                 | 1 : 0.50   | 1.0                              | 5.0 V, 2.6 A        |
| <b>POE13P-12L</b>        | 13        | 127                                      | 114.3                                               | 0.199                       | 0.308 | 0.065 | 0.650                                    | 1 : 0.50                 | 1 : 0.50   | 1.0                              | 12 V, 1.08 A        |
| POE13P-19L               | 13        | 127                                      | 114.3                                               | 0.290                       | 0.355 | 0.066 | 0.800                                    | 1 : 0.567                | 1 : 0.50   | 1.0                              | 19.5 V, 0.67 A      |
| POE13P-24L               | 13        | 127                                      | 114.3                                               | 0.255                       | 0.315 | 0.067 | 0.600                                    | 1 : 0.667                | 1 : 0.50   | 1.0                              | 24 V, 0.54 A        |

1. When ordering, please specify **packaging** code:

**POE30P-12LD**

**Packaging:** D = 13" machine-ready reel. EIA-481 embossed plastic tape.

B = Less than full reel. In tape, but not machine ready. To have a leader and trailer added (\$25 charge), use code letter D instead.

2. Inductance is for the primary, measured at 250 kHz, 0.1 Vrms, 0 Adc.

3. I<sub>pk</sub> is peak primary current drawn at minimum input voltage.

4. DCR for the secondary is per winding.

5. Leakage inductance measured between pins 3 and 4 with all other pins shorted.

6. Turns ratio is with the secondary windings connected in parallel.


7. Output of the secondary is with the windings connected in parallel. Bias winding output is 12 V, 20 mA.

8. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.


## Schematics

### POE13P



Secondary windings to be connected in parallel on PC board

### POE70P, POE30P



Secondary windings to be connected in parallel on PC board



www.coilcraft.com

US +1-847-639-6400 sales@coilcraft.com  
 UK +44-1236-730595 sales@coilcraft-europe.com  
 Taiwan +886-2-2264 3646 sales@coilcraft.com.tw  
 China +86-21-6218 8074 sales@coilcraft.com.cn  
 Singapore +65-6484 8412 sales@coilcraft.com.sg

Document 460-1 Revised 05/04/12



© Coilcraft Inc. 2013

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.





# Flyback Transformers for PoE

## POE13P





**Packaging** 175 per 13" reel  
Plastic tape: 32 mm wide, 0.5 mm thick,  
28 mm pocket spacing, 12.93 mm pocket depth



Parts manufactured prior to  
April, 2012 may be marked  
differently.





## POE70P





**Packaging** 200 per 13" reel  
Plastic tape: 32 mm wide, 0.5 mm thick,  
24 mm pocket spacing, 11.2 mm pocket depth



## POE30P



**Packaging** 350 per 13" reel  
Plastic tape: 32 mm wide, 0.42 mm thick, 20 mm  
pocket spacing, 9.16 mm pocket depth



Dimensions are in  $\frac{\text{inches}}{\text{mm}}$



www.coilcraft.com

**US** +1-847-639-6400 sales@coilcraft.com  
**UK** +44-1236-730595 sales@coilcraft-europe.com  
**Taiwan** +886-2-2264 3646 sales@coilcraft.com.tw  
**China** +86-21-6218 8074 sales@coilcraft.com.cn  
**Singapore** + 65-6484 8412 sales@coilcraft.com.sg

Document 460-2 Revised 05/04/12

© Coilcraft Inc. 2013

This product may not be used in medical or high  
risk applications without prior Coilcraft approval.  
Specification subject to change without notice.  
Please check web site for latest information.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9