

TOSHIBA Diode Silicon Epitaxial Planar Type

015AZ2.0~015AZ12

Constant Voltage Regulation Applications

- Small package
- Nominal voltage tolerance about  $\pm 2.5\%$   
(2.0V~12V)


Maximum Ratings (Ta = 25°C)

| Characteristics           | Symbol | Rating  | Unit |
|---------------------------|--------|---------|------|
| Power dissipation         | P*     | 150     | mW   |
| Junction temperature      | Tj     | 125     | °C   |
| Storage temperature range | Tstg   | -55~125 | °C   |

\* Mounted on a glass epoxy circuit board of 20 × 20mm,  
Pad dimension of 4 × 4mm.

Electrical Characteristics



(See Page 2~3)




Marking

Example 1: 015AZ12- $\times$

Example 2: 015AZ12- $\times$



Pin Assignment (top view)



## Electrical Characteristics (Ta = 25°C)

| Type No.    |   | Zener Voltage        |      |                     | Dynamic Impedance  |                     | Knee Dynamic Impedance |                     | Reverse Current     |                    |
|-------------|---|----------------------|------|---------------------|--------------------|---------------------|------------------------|---------------------|---------------------|--------------------|
|             |   | * V <sub>Z</sub> (V) |      | I <sub>Z</sub> (mA) | Z <sub>Z</sub> (Ω) | I <sub>Z</sub> (mA) | Z <sub>ZK</sub> (Ω)    | I <sub>Z</sub> (mA) | I <sub>R</sub> (μA) | V <sub>R</sub> (V) |
|             |   | Min                  | Max  |                     | Max                |                     | Max                    |                     | Max                 |                    |
| 015AZ2.0 ** | X | 1.85                 | 2.05 | 5                   | 100                | 5                   | 1000                   | 0.5                 | 120                 | 0.5                |
|             | Z | 1.95                 | 2.15 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ2.2 ** | X | 2.05                 | 2.26 | 5                   | 100                | 5                   | 1000                   | 0.5                 | 120                 | 1.0                |
|             | Z | 2.16                 | 2.38 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ2.4    | X | 2.28                 | 2.50 | 5                   | 100                | 5                   | 1000                   | 0.5                 | 120                 | 1.0                |
|             | Z | 2.40                 | 2.60 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ2.7    | X | 2.50                 | 2.75 | 5                   | 110                | 5                   | 1000                   | 0.5                 | 120                 | 1.0                |
|             | Z | 2.65                 | 2.90 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ3.0    | X | 2.80                 | 3.05 | 5                   | 120                | 5                   | 1000                   | 0.5                 | 50                  | 1.0                |
|             | Z | 2.95                 | 3.20 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ3.3    | X | 3.10                 | 3.35 | 5                   | 130                | 5                   | 1000                   | 0.5                 | 20                  | 1.0                |
|             | Z | 3.25                 | 3.50 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ3.6    | X | 3.40                 | 3.65 | 5                   | 130                | 5                   | 1000                   | 0.5                 | 10                  | 1.0                |
|             | Z | 3.55                 | 3.80 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ3.9    | X | 3.70                 | 3.97 | 5                   | 130                | 5                   | 1000                   | 0.5                 | 10                  | 1.0                |
|             | Z | 3.87                 | 4.10 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ4.3    | X | 4.00                 | 4.23 | 5                   | 130                | 5                   | 1000                   | 0.5                 | 5                   | 1.0                |
|             | Y | 4.13                 | 4.35 |                     |                    |                     |                        |                     |                     |                    |
|             | Z | 4.25                 | 4.50 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ4.7    | X | 4.40                 | 4.63 | 5                   | 120                | 5                   | 1000                   | 0.5                 | 5                   | 1.0                |
|             | Y | 4.53                 | 4.76 |                     |                    |                     |                        |                     |                     |                    |
|             | Z | 4.66                 | 4.90 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ5.1    | X | 4.80                 | 5.07 | 5                   | 70                 | 5                   | 1000                   | 0.5                 | 1                   | 1.5                |
|             | Y | 4.97                 | 5.24 |                     |                    |                     |                        |                     |                     |                    |
|             | Z | 5.14                 | 5.40 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ5.6    | X | 5.30                 | 5.63 | 5                   | 40                 | 5                   | 900                    | 0.5                 | 1                   | 2.5                |
|             | Y | 5.43                 | 5.81 |                     |                    |                     |                        |                     |                     |                    |
|             | Z | 5.61                 | 6.00 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ6.2    | X | 5.80                 | 6.20 | 5                   | 30                 | 5                   | 500                    | 0.5                 | 1                   | 3.0                |
|             | Y | 6.00                 | 6.39 |                     |                    |                     |                        |                     |                     |                    |
|             | Z | 6.19                 | 6.60 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ6.8    | X | 6.40                 | 6.80 | 5                   | 25                 | 5                   | 150                    | 0.5                 | 0.5                 | 5.0                |
|             | Y | 6.60                 | 7.02 |                     |                    |                     |                        |                     |                     |                    |
|             | Z | 6.82                 | 7.20 |                     |                    |                     |                        |                     |                     |                    |







\* : Test time: t = 30ms



\*\* : Product by order.

**Electrical Characteristics (Ta = 25°C)**

| Type No. |   | Zener Voltage        |       | I <sub>Z</sub> (mA) | Dynamic Impedance  |                     | Knee Dynamic Impedance |                     | Reverse Current     |                    |
|----------|---|----------------------|-------|---------------------|--------------------|---------------------|------------------------|---------------------|---------------------|--------------------|
|          |   | * V <sub>Z</sub> (V) |       |                     | Z <sub>Z</sub> (Ω) | I <sub>Z</sub> (mA) | Z <sub>ZK</sub> (Ω)    | I <sub>Z</sub> (mA) | I <sub>R</sub> (μA) | V <sub>R</sub> (V) |
|          |   | Min                  | Max   |                     | Max                |                     | Max                    |                     | Max                 |                    |
| 015AZ7.5 | X | 7.00                 | 7.43  | 5                   | 23                 | 5                   | 120                    | 0.5                 | 0.5                 | 6.0                |
|          | Y | 7.23                 | 7.66  |                     |                    |                     |                        |                     |                     |                    |
|          | Z | 7.46                 | 7.90  |                     |                    |                     |                        |                     |                     |                    |
| 015AZ8.2 | X | 7.70                 | 8.16  | 5                   | 20                 | 5                   | 120                    | 0.5                 | 0.5                 | 6.5                |
|          | Y | 7.96                 | 8.43  |                     |                    |                     |                        |                     |                     |                    |
|          | Z | 8.23                 | 8.70  |                     |                    |                     |                        |                     |                     |                    |
| 015AZ9.1 | X | 8.50                 | 9.00  | 5                   | 18                 | 5                   | 120                    | 0.5                 | 0.5                 | 7.0                |
|          | Y | 8.80                 | 9.30  |                     |                    |                     |                        |                     |                     |                    |
|          | Z | 9.10                 | 9.60  |                     |                    |                     |                        |                     |                     |                    |
| 015AZ10  | X | 9.40                 | 9.93  | 5                   | 15                 | 5                   | 120                    | 0.5                 | 0.5                 | 8.0                |
|          | Y | 9.73                 | 10.26 |                     |                    |                     |                        |                     |                     |                    |
|          | Z | 10.06                | 10.60 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ11  | X | 10.40                | 10.98 | 5                   | 15                 | 5                   | 120                    | 0.5                 | 0.5                 | 8.5                |
|          | Y | 10.73                | 11.26 |                     |                    |                     |                        |                     |                     |                    |
|          | Z | 11.06                | 11.60 |                     |                    |                     |                        |                     |                     |                    |
| 015AZ12  | X | 11.40                | 11.93 | 5                   | 15                 | 5                   | 110                    | 0.5                 | 0.5                 | 9.0                |
|          | Y | 11.73                | 12.26 |                     |                    |                     |                        |                     |                     |                    |
|          | Z | 12.06                | 12.60 |                     |                    |                     |                        |                     |                     |                    |

\* : Test time: t = 30ms





**RESTRICTIONS ON PRODUCT USE**

000707EAA

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.  
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9