



N=Number of contacts  
 Dim.B = (N-1)x5.08  
 Dim.A = Nx5.08

Poles	3x2P-3x7P	3x8P-3x12P	3x13P-3x18P	3x19P-3x24P
Dim.B	±0.15	±0.20	±0.25	±0.30
Dim.A	±0.20	±0.25	±0.30	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	2/24'09	The dimension changed from 28.0 to 28.1	Kind
△	2/24'09	The dimension changed from 4.3 to 4.0	Kind
△	2/24'09	The dimension changed from 10.0 to 10.16	Kind
△	2/24'09	Add cULus	Kind
△	2/24'09	The screw type changed from M2.5 to M3.0	Kind

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

**Material**

Terminal body

- Item 1 (metal housing): Brass(CuZn): Ni plated
- Item 2 Terminal screw: Steel Zinc plating "-" slot type
- Item 3 Solder pin : Brass , Tin plated (Short)
- Item 4 Solder pin : Brass , Tin plated (Middle)
- Item 5 Solder pin : Brass , Tin plated (Long)
- Item 6 Insulator (housing): Thermoplastic (UL94V-0) Electrical cULus

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
  - Solid wire(AWG): 14-24
  - Stranded wire(AWG): 14-24
  - Torque(Lb-In): 3.5
- Screw: M3.0
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec

△ Safety Approval: cULus

YB xx 21 x 0 xxxx G

- RoHS  
Pb<40,000ppm
- |                  |         |                                       |
|------------------|---------|---------------------------------------|
| 06 3x2P CONTACTS | 0 Black | 0000:"@Logo (Standard)                |
| 09 3x3P CONTACTS | 5 Green | 000A:"ANYTEK"Logo                     |
| ... ..           | 6 Blue  | Any special item by customer request, |
| 72 3x24 CONTACTS | 8 Grey  | please contact sales department.      |

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YB-5.08mm Series		DWG NO.		8YB0001	
PART NO.		YBxx21x0xxxxG		APPROVED		Tolerance	
CHECKED		DESIGNED		DRAWN		UNIT: mm	
Aaron		Aaron		Aaron		X. ±0.50	
2009.08.22		2009.08.22		2009.08.22		X.X ±0.30	
SHEET: 01/01		SCALE: NONE		REV.: E		X.XX ±0.10	
						X° ±1°	

## Данный компонент на территории Российской Федерации

### Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9