

PRODUCT NO.
73725

PRODUCT NUMBER CODE

73725-X X X X LF

HOUSING COLOR OPTION
0-WHITE
1-BLACK


SENSOR CONTACT OPTION
0-WITH SENSOR CONTACT
1-WITHOUT SENSOR CONTACT

SHIELD PLATING OPTION
1- 1.25μm MINIMUM NICKEL UNDERPLATE & 2.5μm MINIMUM BRIGHT TIN OVER ALL AREA. (HOLD DOWN STYLE "A")
2- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY.(HOLD DOWN STYLE "B")
3- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY.(HOLD DOWN STYLE "A")
4- 1.25μm MINIMUM NICKEL UNDERPLATED & 2.5μm MINIMUM BRIGHT TIN OVER ALL AREA. (HOLD DOWN STYLE "B")
5- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "C")
6- 1.25μm MINIMUM NICKEL ONLY. (HOLD DOWN STYLE "A")
7- 1.25μm MINIMUM NICKEL UNDERPLATED & 2.5 μm MINIMUM MATTE TIN PLATED OVER ALL. (HOLD DOWN STYLE "A")
8- 1.25μm MINIMUM NICKEL UNDERPLATED & 2.5 μm MINIMUM MATTE TIN PLATED ALL AREA. (HOLD DOWN STYLE "B")
9- 1.25μm MINIMUM NICKEL UNDERPLATED OVER ALL; 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "D")
S- 1.25μm MINIMUM NICKEL ONLY.(HOLD DOWN STYLE "A"). HIGH PERFORMANCE MATERIAL FOR 12,000 DURABILITY CYCLES
A- 1.25μm MINIMUM NICKEL PLATED OVER ALL 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "F")
B- 1.25μm MINIMUM NICKEL PLATED OVER ALL 2.5 μm MINIMUM MATTE TIN PLATED ON HOLD DOWN AREA ONLY (HOLD DOWN STYLE "F")


TERMINAL OPTION
50u" NI UNDERPLATE; 30u" GXT CONTACT AREA,100u" TIN TAIL AREA;
0- DIM "A": 2.29 (TERMINAL TAIL LENGTH);
1- DIM "A": 3.71 (TERMINAL TAIL LENGTH);

LEAD FREE OPTION
SEE NOTE 9


PACKAGING OPTION
B - TUBE
R - TAPE&REEL



SENSOR CONTACT




WITH SENSOR CONTACT



FRONT OF CONNECTOR

PC BOARD MOUNTING DIMENSIONS FOR 5 PIN



FOR 73725-X0X0B
HOLD DOWN STYLE "A"

NOTES:

- MATERIAL:
CONTACTS: COPPER ALLOY
SHIELD: COPPER ALLOY
HOUSING: UL 94V-0 THERMOPLASTIC, COLOR: SEE PRODUCT CODE
- PLATING:
CONTACTS: GOLD FLASH OVER PALLADIUM NICKEL (0.76μm MINIMUM) IN CONTACT AREA; 2.5 μm TIN MINIMUM IN SOLDER TAIL AREA.
SHIELD: 1.27 μm MINIMUM NICKEL UNDERPLATE OVER ALL SURFACES.
(THE PLATING MEASURE POINT ON THE SHIELD HOLD DOWN AREA ONLY).
- DATUMS & BASIC DIMENSIONS TO BE DETERMINED BY CUSTOMER
- RECOMMENDED PCB BOARD THICKNESS IS 1.00 ~ 1.60mm EXCEPT 73725-1191BLF; 73725-1191BLF CAN BE USED FOR THE PCB BOARD THICKNESS 2.30 ~ 2.65mm.
- MAXIMUM PANEL THICKNESS TO BE 2.67mm IF MOUNTED BEHIND PANEL
- METAL SHELL SLIVER 0.20 MAX.
- NI PLATING DOES NOT COMPLY WITH THE USB STANDARDS (TO BE CONTINUED)

mat'l. code				surface123/tolerance			projection	product family		
				ISO 1302	ISO 406	ISO 1101		HPL 511 USB 2.0		
ltr	ecn no	dr	date	tolerances unless otherwise specified				title		
AJ	ELX-N-27708	LZ	2017/08/15	angles	linear		mm	USB UP-RIGHT RECEPT		
AD	ELX-N-012006	A.ZH	06/25/2012	0±2°			scale 1:1			
AE	ELX-N-13463	A.ZH	11/14/2012	dr	PAMP	5/20/97		dwg no		
AF	ELX-N-14592	J.HAN	06/10/2013	engr	R Y LIU	5/20/97		sheet 1 of 4		
AG	ELX-N-21594	LQ	08/04/2015	chr	R Y LIU	5/20/97		73725		
AH	ELX-N-21919	LQ	08/04/2015	appd	JENN TSAO	5/20/97		A3		
sheet	revision							type Product Customer Drawing		
index	sheet									

PRODUCT NO.
73725

(CONTINUED)

8. P/N'S WITH SUFFIX "LF" ARE LEAD FREE P/N'S



FOR LEAD FREE P/N, THE PRODUCT MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008

FOR THE PRODUCTS WITH THE METAL SHELL PLATING NICKEL AND MATTE SN CAN WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 40 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW PROCESS; FOR THE PRODUCTS WITH METAL SHELL PLATING BRIGHT SN OR SEMI-BRIGHT SN CAN'T WITHSTAND REFLOW AND JUST CAN WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN WAVE SOLDERING PROCESS.



FOR ALL LEAD FREE P/N'S, WITH SUFFIX LF.

12. THE PRODUCT CAN BE USED FOR PIP PROCESS


13. DATUM OF CUSTOMER'S PCB LAYOUT.



PC BOARD MOUNTING DIMENSIONS FOR 4 PIN



WITHOUT SENSOR CONTACT





FOR 73725-X1X0B
HOLD DOWN STYLE "A"


mat'l. code				surface ¹²³ /tolerance			projection 	product family				
				ISO 1302 ✓ ISO 406 ISO 1101				HPL 511 USB 2.0				
ltr	ecn	no	dr	date			tolerances unless otherwise specified			title		
AJ							mm 			USB UP-RIGHT RECEPT		
							angles linear					
							.0±.30					
							.00±.20					
							0°±2' .000±.10			scale 1: 1		
							dr PAMP 5/20/97			dwg no sheet2 of 4 size		
							eng R Y LIU 5/20/97			73725 A3		
							chr R Y LIU 5/20/97					
							appd JENN TSAO 5/20/97			type Product Customer Drawing		
sheet index		revision sheet										

PRODUCT NO.


73725




WITHOUT SENSOR CONTACT
FOR 73725-X1X0B
HOLD DOWN STYLE "B"




WITHOUT SENSOR CONTACT
FOR 73725-XXA0XLF
73725-XXB0XLF ONLY
HOLD DOWN STYLE "F"



SECTION A-A




WITH SENSOR CONTACT
FOR 73725-X0X0B
HOLD DOWN STYLE "B"





WITHOUT SENSOR CONTACT
FOR 73725-X191XLF
HOLD DOWN STYLE "D"

mat'l. code				surface ¹²³ /tolerance			projection		product family		
				ISO 1302 ✓			ISO 406 ISO 1101		HPL 511 USB 2.0		
ltr		ecn no		dr		date		tolerances unless otherwise specified		title	
AJ								angles		linear	
								.0±.30			
								.00±.20			
								0°±2°		.000±.10	
								mm		scale 1:1	
								dwg no		sheet3 of 4	
								Amphenol		size	
								FCI		A3	
								73725			
								type		Product Customer Drawing	
sheet index		revision sheet									

PRODUCT NO.
73725



PC BOARD MOUNTING DIMENSIONS FOR 4 PIN



WITHOUT SENSOR CONTACT
FOR 73725-X150B
HOLD DOWN STYLE "C"

mat'l. code				surface ¹²³ /tolerance		projection		product family			
ISO 1302 ✓				ISO 406 ISO 1101				HPL 511 USB 2.0			
ltr	ecn no	dr	date	tolerances unless otherwise specified				title			
AJ				angles	.0±.30			USB UP-RIGHT			
				linear	.00±.20			RECEPT			
				0°±2°	.000±.10			scale 1:1			
				dr	PAMP	5/20/97	Amphenol FCI	dwg no		sheet 4 of 4	size
				engr	R Y LIU	5/20/97		73725			A3
				chr	R Y LIU	5/20/97					
				appd	JENN TSAO	5/20/97		type Product Customer Drawing			
sheet index		revision sheet									

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9