

AS3711

Product Brief

High Current Power Management Unit for Portable Devices

1 General Description

The AS3711 is a compact System PMU with integrated battery charger and back light driver.

The device offers advanced power management functions. All necessary ICs and peripherals in a battery powered mobile device are supplied by the AS3711. It features 3 DCDC buck converters (4MHz), one buck controller as well as 8 low noise LDOs. The supply voltages are programmable via the serial control interface.

The three step-up converter generate voltages for e.g. the backlight, classD amplifier, USB host support or LCD display supply. Both constant voltage (for e.g. OLED supply) as well as constant current (white LED backlight) operations with three current sinks are possible. An internal voltage protection is limiting the output voltage in the case of external component failures.

AS3711 contains a linear or switching mode Li-Ion battery charger with constant current and constant voltage. The maximum charging current is 1.5A. An integrated battery switch and an optional external switch are separating the battery during charging or whenever an external power supply is present. With this switch it is also possible to operate with no or deeply discharged batteries. A programmable current limit can be used to control the maximum current used from a USB supply. Additional features are a 30V OV protection and battery temperature supervision.

The single supply voltage may vary from 2.7V to 5.5V.

2 Key Features

Power Management

Voltage Generation

- 4 DCDC step down regulators
 - DVM (0.6V-3.3V; 1x 1.2-1.5A, 2x 0.7-1A)
 - controller mode for 2-3A supplies
 - 50uA quiescent current
 - selectable switching frequency (4, 3 or 2MHz)
 - 2A with combined DCDC 2 & 3
- 2 analog low noise LDOs, 6 digital LDOs
 - 2x 1.2-3.3V, 6x 0.9-3.3V; 150-300mA
 - 30uA quiescent current (low power mode)
- 1 ultra low power always on LDO 2.5V, 10mA
- power supply supervision
- 4sec and 8sec emergency shut-down
- hibernation function

HV Backlight Driver

- 2x step up with external transistor
- voltage control mode and over-voltage protection
- 3 programmable current sinks (max. 40mA)
- e.g. 500mA@5V; 40mA@50V
- possible external PWM dimming input (DLS, CABAC)

Battery Charger

- prog. trickle charging (25-220mA)
- prog. constant current charging (up to 1500mA)
- prog. constant voltage charging (3.9V-4.25V)
- charger time-out and temperature supervision
- selectable current limitation for USB mode
- integrated battery switch & ideal diode (linear mode)
- external battery switch control (switching mode)
- external 30V OV protection

General

Supervisor

- automatic battery monitoring with interrupt generation and selectable warning level
- automatic temperature monitoring with interrupt generation and selectable warning and shutdown levels

Real Time Clock

- ultra low power 32kHz oscillator
- sec and minute counter, auto wake-up
- selectable alarm (seconds or minutes)
- 32kHz clock output to peripheral
- <1uA total power consumption

4 General Purpose IOs

- 10bit general purpose ADC input
- wake-up/sleep and DVM input
- PWM (DLS, CABAC) dimming input
- status output for: charger, low battery, power good and step-up overcurrent
- Q32k clock output
- interrupt output
- PWM output
- step-up feedback input

- programmable regulator default voltages
- programmable start-up sequence

- 10bit resolution
- several internal / external sources
 - VUSB, VSUP, CHGIN, VBAT
 - GPIOx, CURRx
 - XOUT32K, SENSEN_SU1
 - chip temperature

- I2C control lines, including watchdog
- Power-Up input
- bidirectional reset, with selectable delay
- ultra low power standby mode

Packaging

QFN56 7x7mm 0.4mm pitch

Portable Media Players, Portable Navigation Devices, E-Books, Mobile Internet Devices, Tablet PCs

[illegible]

Copyright

Copyright © 2011, austriamicrosystems AG, Schloss Premstaetten, 8141 Unterpremstaetten, Austria-Europe. Trade-marks Registered ®. All rights reserved. The material herein may not be reproduced, adapted, merged, translated, stored, or used without the prior written consent of the copyright owner.

All products and companies mentioned are trademarks or registered trademarks of their respective companies.

Disclaimer

Devices sold by austriamicrosystems AG are covered by the warranty and patent indemnification provisions appearing in its Term of Sale. austriamicrosystems AG makes no warranty, express, statutory, implied, or by description regarding the information set forth herein or regarding the freedom of the described devices from patent infringement. austriamicrosystems AG reserves the right to change specifications and prices at any time and without notice. Therefore, prior to designing this product into a system, it is necessary to check with austriamicrosystems AG for current information. This product is intended for use in normal commercial applications. Applications requiring extended temperature range, unusual environmental requirements, or high reliability applications, such as military, medical life-support or life-sustaining equipment are specifically not recommended without additional processing by austriamicrosystems AG for each application. For shipments of less than 100 parts the manufacturing flow might show deviations from the standard production flow, such as test flow or test location.

The information furnished here by austriamicrosystems AG is believed to be correct and accurate. However, austriamicrosystems AG shall not be liable to recipient or any third party for any damages, including but not limited to personal injury, property damage, loss of profits, loss of use, interruption of business or indirect, special, incidental or consequential damages, of any kind, in connection with or arising out of the furnishing, performance or use of the technical data herein. No obligation or liability to recipient or any third party shall arise or flow out of austriamicrosystems AG rendering of technical or other services.



Contact Information

Headquarters

austriamicrosystems AG
A-8141 Schloss Premstaetten, Austria

Tel: +43 (0) 3136 500 0
Fax: +43 (0) 3136 525 01

For Sales Offices, Distributors and Representatives, please visit:

<http://www.austriamicrosystems.com/contact>

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru

moschip.ru_4

moschip.ru_6

moschip.ru_9