

# MOSFET

## 800V CoolMOS™ P7 Power Transistor

The latest 800V CoolMOS™ P7 series sets a new benchmark in 800V super junction technologies and combines best-in-class performance with state of the art ease-of-use, resulting from Infineon's over 18 years pioneering super junction technology innovation.

### Features

- Best-in-class FOM  $R_{DS(on)} * E_{oss}$ ; reduced  $Q_g$ ,  $C_{iss}$ , and  $C_{oss}$
- Best-in-class DPAK  $R_{DS(on)}$
- Best-in-class  $V_{(GS)th}$  of 3V and smallest  $V_{(GS)th}$  variation of  $\pm 0.5V$
- Integrated Zener Diode ESD protection
- Fully qualified acc. JEDEC for Industrial Applications
- Fully optimized portfolio

### Benefits

- Best-in-class performance
- Enabling higher power density designs, BOM savings and lower assembly costs
- Easy to drive and to parallel
- Better production yield by reducing ESD related failures
- Less production issues and reduced field returns
- Easy to select right parts for fine tuning of designs

### Potential applications

Recommended for hard and soft switching flyback topologies for LED Lighting, low power Chargers and Adapters, Audio, AUX power and Industrial power. Also suitable for PFC stage in Consumer applications and Solar.

*Please note: For MOSFET paralleling the use of ferrite beads on the gate or separate totem poles is generally recommended.*



**Table 1 Key Performance Parameters**

| Parameter                  | Value | Unit     |
|----------------------------|-------|----------|
| $V_{DS} @ T_J=25^{\circ}C$ | 800   | V        |
| $R_{DS(on),max}$           | 0.45  | $\Omega$ |
| $Q_{g,typ}$                | 24    | nC       |
| $I_D$                      | 11    | A        |
| $E_{oss} @ 500V$           | 2.7   | $\mu J$  |
| $V_{GS(th),typ}$           | 3     | V        |
| ESD class (HBM)            | 2     | -        |

| Type / Ordering Code | Package           | Marking  | Related Links  |
|----------------------|-------------------|----------|----------------|
| IPA80R450P7          | PG-TO 220 FullPAK | 80R450P7 | see Appendix A |

**Table of Contents**

Description ..... 1

Maximum ratings ..... 3

Thermal characteristics ..... 3

Electrical characteristics ..... 4

Electrical characteristics diagrams ..... 6

Test Circuits ..... 10

Package Outlines ..... 11

Appendix A ..... 12

Revision History ..... 13

Trademarks ..... 13

Disclaimer ..... 13

## 1 Maximum ratings

at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

**Table 2 Maximum ratings**

| Parameter                                     | Symbol         | Values     |      |           | Unit             | Note / Test Condition                                                  |
|-----------------------------------------------|----------------|------------|------|-----------|------------------|------------------------------------------------------------------------|
|                                               |                | Min.       | Typ. | Max.      |                  |                                                                        |
| Continuous drain current <sup>1)</sup>        | $I_D$          | -          | -    | 11<br>7.1 | A                | $T_C=25^\circ\text{C}$<br>$T_C=100^\circ\text{C}$                      |
| Pulsed drain current <sup>2)</sup>            | $I_{D,pulse}$  | -          | -    | 29        | A                | $T_C=25^\circ\text{C}$                                                 |
| Avalanche energy, single pulse                | $E_{AS}$       | -          | -    | 29        | mJ               | $I_D=1.8\text{A}$ ; $V_{DD}=50\text{V}$                                |
| Avalanche energy, repetitive                  | $E_{AR}$       | -          | -    | 0.22      | mJ               | $I_D=1.8\text{A}$ ; $V_{DD}=50\text{V}$                                |
| Avalanche current, repetitive                 | $I_{AR}$       | -          | -    | 1.8       | A                | -                                                                      |
| MOSFET dv/dt ruggedness                       | dv/dt          | -          | -    | 100       | V/ns             | $V_{DS}=0$ to 400V                                                     |
| Gate source voltage                           | $V_{GS}$       | -20<br>-30 | -    | 20<br>30  | V                | static;<br>AC ( $f > 1\text{ Hz}$ )                                    |
| Power dissipation                             | $P_{tot}$      | -          | -    | 29        | W                | $T_C=25^\circ\text{C}$                                                 |
| Operating and storage temperature             | $T_j, T_{stg}$ | -55        | -    | 150       | $^\circ\text{C}$ | -                                                                      |
| Mounting torque                               | -              | -          | -    | 50        | Ncm              | M2.5 screw                                                             |
| Continuous diode forward current              | $I_S$          | -          | -    | 5         | A                | $T_C=25^\circ\text{C}$                                                 |
| Diode pulse current <sup>2)</sup>             | $I_{S,pulse}$  | -          | -    | 29        | A                | $T_C=25^\circ\text{C}$                                                 |
| Reverse diode dv/dt <sup>3)</sup>             | dv/dt          | -          | -    | 1         | V/ns             | $V_{DS}=0$ to 400V, $I_{SD} \leq 2.2\text{A}$ , $T_j=25^\circ\text{C}$ |
| Maximum diode commutation speed <sup>3)</sup> | di/dt          | -          | -    | 50        | A/ $\mu\text{s}$ | $V_{DS}=0$ to 400V, $I_{SD} \leq 2.2\text{A}$ , $T_j=25^\circ\text{C}$ |
| Insulation withstand voltage                  | $V_{ISO}$      | -          | -    | 2500      | V                | $V_{rms}$ , $T_C=25^\circ\text{C}$ , $t=1\text{min}$                   |

## 2 Thermal characteristics

**Table 3 Thermal characteristics**

| Parameter                                                  | Symbol     | Values |      |      | Unit               | Note / Test Condition                |
|------------------------------------------------------------|------------|--------|------|------|--------------------|--------------------------------------|
|                                                            |            | Min.   | Typ. | Max. |                    |                                      |
| Thermal resistance, junction - case                        | $R_{thJC}$ | -      | -    | 4.4  | $^\circ\text{C/W}$ | -                                    |
| Thermal resistance, junction - ambient                     | $R_{thJA}$ | -      | -    | 80   | $^\circ\text{C/W}$ | lead                                 |
| Thermal resistance, junction - ambient for SMD version     | $R_{thJA}$ | -      | -    | -    | $^\circ\text{C/W}$ | n.a.                                 |
| Soldering temperature, wavesoldering only allowed at leads | $T_{sld}$  | -      | -    | 260  | $^\circ\text{C}$   | 1.6 mm (0.063 in.) from case for 10s |

<sup>1)</sup> TO220 equivalent. Limited by  $T_{j,max}$ . Maximum duty cycle  $D=0.5$

<sup>2)</sup> Pulse width  $t_p$  limited by  $T_{j,max}$

<sup>3)</sup>  $V_{DClk}=400\text{V}$ ;  $V_{DS,peak} < V_{(BR)DSS}$ ; identical low side and high side switch with identical  $R_G$ ;  $t_{cond} < 2\mu\text{s}$

### 3 Electrical characteristics

at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

**Table 4 Static characteristics**

| Parameter                                     | Symbol        | Values |              |           | Unit     | Note / Test Condition                                                                                         |
|-----------------------------------------------|---------------|--------|--------------|-----------|----------|---------------------------------------------------------------------------------------------------------------|
|                                               |               | Min.   | Typ.         | Max.      |          |                                                                                                               |
| Drain-source breakdown voltage                | $V_{(BR)DSS}$ | 800    | -            | -         | V        | $V_{GS}=0V$ , $I_D=1mA$                                                                                       |
| Gate threshold voltage                        | $V_{GS(th)}$  | 2.5    | 3            | 3.5       | V        | $V_{DS}=V_{GS}$ , $I_D=0.22mA$                                                                                |
| Zero gate voltage drain current               | $I_{DSS}$     | -      | -            | 1         | $\mu A$  | $V_{DS}=800V$ , $V_{GS}=0V$ , $T_j=25^\circ\text{C}$<br>$V_{DS}=800V$ , $V_{GS}=0V$ , $T_j=150^\circ\text{C}$ |
| Gate-source leakage current incl. zener diode | $I_{GSS}$     | -      | -            | 1         | $\mu A$  | $V_{GS}=20V$ , $V_{DS}=0V$                                                                                    |
| Drain-source on-state resistance              | $R_{DS(on)}$  | -      | 0.38<br>0.99 | 0.45<br>- | $\Omega$ | $V_{GS}=10V$ , $I_D=4.5A$ , $T_j=25^\circ\text{C}$<br>$V_{GS}=10V$ , $I_D=4.5A$ , $T_j=150^\circ\text{C}$     |
| Gate resistance                               | $R_G$         | -      | 1            | -         | $\Omega$ | $f=250kHz$ , open drain                                                                                       |

**Table 5 Dynamic characteristics**

| Parameter                                                  | Symbol       | Values |      |      | Unit | Note / Test Condition                                          |
|------------------------------------------------------------|--------------|--------|------|------|------|----------------------------------------------------------------|
|                                                            |              | Min.   | Typ. | Max. |      |                                                                |
| Input capacitance                                          | $C_{iss}$    | -      | 770  | -    | pF   | $V_{GS}=0V$ , $V_{DS}=500V$ , $f=250kHz$                       |
| Output capacitance                                         | $C_{oss}$    | -      | 14   | -    | pF   | $V_{GS}=0V$ , $V_{DS}=500V$ , $f=250kHz$                       |
| Effective output capacitance, energy related <sup>1)</sup> | $C_{o(er)}$  | -      | 24   | -    | pF   | $V_{GS}=0V$ , $V_{DS}=0$ to $500V$                             |
| Effective output capacitance, time related <sup>2)</sup>   | $C_{o(tr)}$  | -      | 305  | -    | pF   | $I_D=\text{constant}$ , $V_{GS}=0V$ , $V_{DS}=0$ to $500V$     |
| Turn-on delay time                                         | $t_{d(on)}$  | -      | 10   | -    | ns   | $V_{DD}=400V$ , $V_{GS}=13V$ , $I_D=4.5A$ ,<br>$R_G=7.5\Omega$ |
| Rise time                                                  | $t_r$        | -      | 6    | -    | ns   | $V_{DD}=400V$ , $V_{GS}=13V$ , $I_D=4.5A$ ,<br>$R_G=7.5\Omega$ |
| Turn-off delay time                                        | $t_{d(off)}$ | -      | 40   | -    | ns   | $V_{DD}=400V$ , $V_{GS}=13V$ , $I_D=4.5A$ ,<br>$R_G=7.5\Omega$ |
| Fall time                                                  | $t_f$        | -      | 10   | -    | ns   | $V_{DD}=400V$ , $V_{GS}=13V$ , $I_D=4.5A$ ,<br>$R_G=7.5\Omega$ |

**Table 6 Gate charge characteristics**

| Parameter             | Symbol        | Values |      |      | Unit | Note / Test Condition                            |
|-----------------------|---------------|--------|------|------|------|--------------------------------------------------|
|                       |               | Min.   | Typ. | Max. |      |                                                  |
| Gate to source charge | $Q_{gs}$      | -      | 4    | -    | nC   | $V_{DD}=640V$ , $I_D=4.5A$ , $V_{GS}=0$ to $10V$ |
| Gate to drain charge  | $Q_{gd}$      | -      | 9    | -    | nC   | $V_{DD}=640V$ , $I_D=4.5A$ , $V_{GS}=0$ to $10V$ |
| Gate charge total     | $Q_g$         | -      | 24   | -    | nC   | $V_{DD}=640V$ , $I_D=4.5A$ , $V_{GS}=0$ to $10V$ |
| Gate plateau voltage  | $V_{plateau}$ | -      | 4.5  | -    | V    | $V_{DD}=640V$ , $I_D=4.5A$ , $V_{GS}=0$ to $10V$ |

<sup>1)</sup>  $C_{o(er)}$  is a fixed capacitance that gives the same stored energy as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 500V

<sup>2)</sup>  $C_{o(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{oss}$  while  $V_{DS}$  is rising from 0 to 500V

**Table 7 Reverse diode characteristics**

| Parameter                     | Symbol    | Values |      |      | Unit    | Note / Test Condition                   |
|-------------------------------|-----------|--------|------|------|---------|-----------------------------------------|
|                               |           | Min.   | Typ. | Max. |         |                                         |
| Diode forward voltage         | $V_{SD}$  | -      | 0.9  | -    | V       | $V_{GS}=0V, I_F=4.5A, T_f=25^{\circ}C$  |
| Reverse recovery time         | $t_{rr}$  | -      | 1000 | -    | ns      | $V_R=400V, I_F=2.2A, di_F/dt=50A/\mu s$ |
| Reverse recovery charge       | $Q_{rr}$  | -      | 11   | -    | $\mu C$ | $V_R=400V, I_F=2.2A, di_F/dt=50A/\mu s$ |
| Peak reverse recovery current | $I_{rrm}$ | -      | 17   | -    | A       | $V_R=400V, I_F=2.2A, di_F/dt=50A/\mu s$ |

## 4 Electrical characteristics diagrams







Diagram 5: Typ. output characteristics




$I_D = f(V_{DS})$ ;  $T_j = 25^\circ\text{C}$ ; parameter:  $V_{GS}$

Diagram 6: Typ. output characteristics




$I_D = f(V_{DS})$ ;  $T_j = 125^\circ\text{C}$ ; parameter:  $V_{GS}$

Diagram 7: Typ. drain-source on-state resistance




$R_{DS(on)} = f(I_D)$ ;  $T_j = 125^\circ\text{C}$ ; parameter:  $V_{GS}$

Diagram 8: Drain-source on-state resistance




$R_{DS(on)} = f(T_j)$ ;  $I_D = 4.5\text{ A}$ ;  $V_{GS} = 10\text{ V}$

Diagram 9: Typ. transfer characteristics




$I_D = f(V_{GS})$ ;  $V_{DS} = 20V$ ; parameter:  $T_j$

Diagram 10: Typ. gate charge




$V_{GS} = f(Q_{gate})$ ;  $I_D = 4.5$  A pulsed; parameter:  $V_{DD}$

Diagram 11: Forward characteristics of reverse diode




$I_F = f(V_{SD})$ ; parameter:  $T_j$

Diagram 12: Avalanche energy




$E_{AS} = f(T_j)$ ;  $I_D = 1.8$  A;  $V_{DD} = 50$  V

Diagram 13: Drain-source breakdown voltage




$V_{BR(DSS)} = f(T_J); I_D = 1 \text{ mA}$

Diagram 14: Typ. capacitances



$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 250 \text{ kHz}$

Diagram 15: Typ.  $C_{oss}$  stored energy



$E_{oss} = f(V_{DS})$

## 5 Test Circuits

**Table 8 Diode characteristics**

| Test circuit for diode characteristics                                                                                | Diode recovery waveform                                                            |
|-----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
|  <p><math>R_{g1} = R_{g2}</math></p> |  |


**Table 9 Switching times**

| Switching times test circuit for inductive load                                    | Switching times waveform                                                            |
|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |

**Table 10 Unclamped inductive load**

| Unclamped inductive load test circuit                                               | Unclamped inductive waveform                                                         |
|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
|  |  |

## 6 Package Outlines



NOTES:  
DIMENSIONS DO NOT INCLUDE MOLD FLASH, PRO-  
TRUSIONS OR GATE BURRS  
GATE BURRS ARE LESS THAN 0.5 mm

| DIMENSIONS | MILLIMETERS |       |
|------------|-------------|-------|
|            | MIN.        | MAX.  |
| A          | 4.50        | 4.90  |
| A1         | 2.34        | 2.85  |
| A2         | 2.42        | 2.86  |
| b          | 0.65        | 0.90  |
| b1         | 0.95        | 1.38  |
| b2         | 0.95        | 1.51  |
| b3         | 0.65        | 1.38  |
| b4         | 0.65        | 1.51  |
| c          | 0.40        | 0.63  |
| D          | 15.67       | 16.15 |
| D1         | 8.97        | 9.83  |
| E          | 10.00       | 10.65 |
| e          | 2.54        |       |
| H          | 28.70       | 29.75 |
| L          | 12.78       | 13.75 |
| L1         | 2.83        | 3.45  |
| øP         | 3.00        | 3.30  |
| Q          | 3.15        | 3.50  |

|                             |
|-----------------------------|
| DOCUMENT NO.<br>Z8B00003319 |
| REVISION<br>09              |
| ISSUE DATE<br>23.07.2018    |
| SCALE 5:1<br>0 1 2 3 4 5mm  |
| EUROPEAN PROJECTION<br>     |

Figure 1 Outline PG-TO 220 FullPAK, dimensions in mm/inches

## **7 Appendix A**

### **Table 11 Related Links**

- **IFX CoolMOS Webpage:** [www.infineon.com](http://www.infineon.com)
- **IFX Design tools:** [www.infineon.com](http://www.infineon.com)

## Revision History

IPA80R450P7

**Revision: 2018-07-24, Rev. 2.2**

Previous Revision

| Revision | Date       | Subjects (major changes since last revision) |
|----------|------------|----------------------------------------------|
| 2.0      | 2016-07-05 | Release of final version                     |
| 2.1      | 2018-02-07 | Corrected front page text                    |
| 2.2      | 2018-07-24 | Corrected package text                       |

### Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

### We Listen to Your Comments

Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to:

**erratum@infineon.com**

### Published by

**Infineon Technologies AG**

**81726 München, Germany**

**© 2018 Infineon Technologies AG**

**All Rights Reserved.**

### Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

### Information

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

### Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

The Infineon Technologies component described in this Data Sheet may be used in life-support devices or systems and/or automotive, aviation and aerospace applications or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support, automotive, aviation and aerospace device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9