

Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ NCU15XH103E6SRC \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

https://www.murata.com/en-us/products/productdetail?partno=NCU15XH103E6SRC

NCU15XH103E6SRC














Appearance & Shape







- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).



Limited Usage	Automotive Grade
Other Usage	1. Variousengine control units 2. ABS control unit 3. High power devices (IGBT) 4. Temperature compensation for various circuits required high temperature.



Packaging Information

Packaging	Specifications	Minimum Order Quantity
RC	180mm Paper Tape	10000

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/09/14



Note: This datasheet may be out of date

 $\underline{ Please \ download \ the \ latest \ data sheet \ of \ NCU15XH103E6SRC \ from \ the \ official \ website \ of \ Murata \ Manufacturing} }$

Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15XH103E6SRC

NCU15XH103E6SRC



Resistance (25°C)	10kΩ	
Resistance Value Tolerance (at 25°C)	±3%	
B-Constant (25/50°C)	3380K	
B-Constant (25/50°C) Tolerance	±1%	
B-Constant(25/80°C)(Reference Value)	3428K	
B-Constant(25/85°C)(Reference Value)	3434K	
B-Constant(25/100°C)(Reference Value)	3455K	
Max. Voltage	5V	
Maximum Operating Current (25°C)	0.1mA	
Typical Dissipation Constant (25°C)	1mW/℃	
Operating Temperature Range	-40°C to 150°C	
Size Code (in mm)	1.0x0.5mm	
Size Code (in inch)	0.4x0.2inch	
Shape	SMD	
Mass	0.0012g	

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




URL: https://www.murata.com/


Last updated :2019/09/14

 $\underline{ \text{Please download the latest datasheet of NCU15XH103E6SRC from the official website of Murata Manufacturing} \\$ Co., Ltd. https://www.murata.com/en-us/products/productdetail?partno=NCU15XH103E6SRC

NCU15XH103E6SRC







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering. 2.This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering



URL: https://www.murata.com/

Last updated : 2019/09/14

ПОСТАВКА ЭЛЕКТРОННЫХ КОМПОНЕНТОВ

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001 Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г. Москва, ул. Щербаковская д. 3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:

moschip.ru moschip.ru_6 moschip.ru 4 moschip.ru 9