HIGHLY FLEXIBLE, HEAT SHRINKABLE WOVEN FABRIC TUBING

FIT® FABRIC

CHOOSE FIT® FABRIC FOR:

- Superior Abrasion Resistance over a Wide Temperature Range
- Outstanding Flexibility and Durability
- Tight Grip without Additional Fixing
- Ease of Installation
- Resistance to Harsh Environments
- Soft, Safe Handling
- Cuts with Scissors

FIT® FABRIC APPLICATIONS:

- Mechanical Abrasion Protection
- Severe Environment Protection
- Noise and Rattle Protection
- Halogen Free Environment
- Flexing Applications

2 TO 1 SHRINK RATIO

3 TO 1 SHRINK RATIO

New!

CHARACTERISTICS

OPERATING TEMPERATURE:

- –40°C to 125°C

SHRINKAGE RATIO:

- Approximately 2 to 1 or 3 to 1 at 135°C Depending on Size

COLOR DESCRIPTION:

- All Standard Packages: Black

PHYSICAL PROPERTIES:

- Longitudinal Shrinkage:
  Up to 20% @ 2:1 Shrink Ratio
  Up to 25% @ 3:1 Shrink Ratio
- Flammability: Meets MVSS 302 Horizontal Burn Test

CHEMICAL PROPERTIES:

- Corrosive Effect: Non-Corrosive
- Fungus Resistance: No Growth
- Chemical Resistance: Antifreeze (50% Ethylene Glycol), Engine Oil, Mineral Hydraulic Fluid, Detergent (1% Teepol), Brake Fluid (DOT 4), Unleaded Gasoline, Diesel Fuel, Battery Acid

Alpha Part No.	Approx. Shrink Ratio	Minimum Supplied I.D. Inches	Minimum Supplied I.D. mm	Maximum Rec. I.D. Inches	Maximum Rec. I.D. mm	Non-Rec. Wall Thickness Inches	Non-Rec. Wall Thickness mm	Total Ftg.	Std. Spools Total Ftg.
FIT FAB-1	2 to 1	0.47	12,0	0.24	6,0	0.039	0,99	50	200
FIT FAB-2	2 to 1	0.79	20,0	0.39	10,0	0.039	0,99	50	200
FIT FAB-3	2 to 1	1.18	30,0	0.59	15,0	0.039	0,99	50	200
FIT FAB-4	2 to 1	1.57	40,0	0.79	20,0	0.039	0,99	50	200
FIT FAB-5	2 to 1	1.97	50,0	0.98	25,0	0.039	0,99	25	100
FIT FAB-6	2 to 1	2.36	60,0	1.18	30,0	0.039	0,99	25	100
FIT FAB-7	2 to 1	2.76	70,0	1.38	35,0	0.039	0,99	25	100
FIT FAB-8	3 to 1	0.71	18,0	0.24	6,0	0.039	0,99	50	200
FIT FAB-9	3 to 1	1.18	30,0	0.39	10,0	0.039	0,99	50	200
FIT FAB-10	3 to 1	2.36	60,0	0.79	20,0	0.039	0,99	25	100



SPECIFICATIONS

- MVSS 302 Horizontal Burn Test

Recognized Component
Underwriters Laboratories Inc.

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9