

# PMEG2010AEH; PMEG2010AET

1 A very low  $V_F$  MEGA Schottky barrier rectifiers

Rev. 03 — 28 March 2007

Product data sheet

## 1. Product profile

### 1.1 General description

Planar Maximum Efficiency General Application (MEGA) Schottky barrier rectifiers with an integrated guard ring for stress protection, encapsulated in small Surface-Mounted Device (SMD) plastic packages.

Table 1. Product overview

| Type number | Package  |       | Configuration |
|-------------|----------|-------|---------------|
|             | Nexperia | JEITA |               |
| PMEG2010AEH | SOD123F  | -     | single        |
| PMEG2010AET | SOT23    | -     | single        |

### 1.2 Features

- Forward current:  $I_F \leq 1$  A
- Reverse voltage:  $V_R \leq 20$  V
- Very low forward voltage
- Small SMD plastic packages

### 1.3 Applications

- Low voltage rectification
- High efficiency DC-to-DC conversion
- Switch mode power supply
- Reverse polarity protection
- Low power consumption applications

### 1.4 Quick reference data



Table 2. Quick reference data

| Symbol | Parameter       | Conditions          | Min              | Typ | Max | Unit |
|--------|-----------------|---------------------|------------------|-----|-----|------|
| $I_F$  | forward current | $T_{sp} \leq 55$ °C | -                | -   | 1   | A    |
| $V_R$  | reverse voltage |                     | -                | -   | 20  | V    |
| $V_F$  | forward voltage | $I_F = 1$ A         | <sup>[1]</sup> - | 380 | 430 | mV   |

[1] Pulse test:  $t_p \leq 300$   $\mu$ s;  $\delta \leq 0.02$ .

2. Pinning information

Table 3. Pinning

| Pin     | Description   | Simplified outline                                                                  | Symbol                                                                                                  |
|---------|---------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| SOD123F |               |                                                                                     |                                                                                                         |
| 1       | cathode       |  | <br><i>sym001</i>    |
| 2       | anode         |                                                                                     |                                                                                                         |
| SOT23   |               |                                                                                     |                                                                                                         |
| 1       | anode         |  | <br><i>006aaa436</i> |
| 2       | not connected |                                                                                     |                                                                                                         |
| 3       | cathode       |                                                                                     |                                                                                                         |

[1] The marking bar indicates the cathode.

3. Ordering information

Table 4. Ordering information

| Type number | Package |                                          |         |
|-------------|---------|------------------------------------------|---------|
|             | Name    | Description                              | Version |
| PMEG2010AEH | -       | plastic surface-mounted package; 2 leads | SOD123F |
| PMEG2010AET | -       | plastic surface-mounted package; 3 leads | SOT23   |

4. Marking

Table 5. Marking codes

| Type number | Marking code <sup>[1]</sup> |
|-------------|-----------------------------|
| PMEG2010AEH | AF                          |
| PMEG2010AET | *AX                         |

[1] \* = -: made in Hong Kong  
\* = p: made in Hong Kong  
\* = t: made in Malaysia  
\* = W: made in China

## 5. Limiting values

**Table 6. Limiting values**

*In accordance with the Absolute Maximum Rating System (IEC 60134).*

| Symbol    | Parameter                           | Conditions                                    | Min   | Max  | Unit |
|-----------|-------------------------------------|-----------------------------------------------|-------|------|------|
| $V_R$     | reverse voltage                     |                                               | -     | 20   | V    |
| $I_F$     | forward current                     | $T_{sp} \leq 55\text{ °C}$                    | -     | 1    | A    |
| $I_{FRM}$ | repetitive peak forward current     | $t_p \leq 1\text{ ms};$<br>$\delta \leq 0.25$ |       |      |      |
|           | PMEG2010AEH                         |                                               | -     | 7    | A    |
|           | PMEG2010AET                         |                                               | -     | 6    | A    |
| $I_{FSM}$ | non-repetitive peak forward current | square wave;<br>$t_p = 8\text{ ms}$           | -     | 9    | A    |
| $P_{tot}$ | total power dissipation             | $T_{amb} \leq 25\text{ °C}$                   |       |      |      |
|           | PMEG2010AEH                         |                                               | [1] - | 375  | mW   |
|           |                                     |                                               | [2] - | 830  | mW   |
|           | PMEG2010AET                         |                                               | [1] - | 280  | mW   |
|           |                                     |                                               | [2] - | 420  | mW   |
| $T_j$     | junction temperature                |                                               | -     | 150  | °C   |
| $T_{amb}$ | ambient temperature                 |                                               | -65   | +150 | °C   |
| $T_{stg}$ | storage temperature                 |                                               | -65   | +150 | °C   |

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and standard footprint.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for cathode 1 cm<sup>2</sup>.

## 6. Thermal characteristics

**Table 7. Thermal characteristics**

| Symbol         | Parameter                                        | Conditions  | Min   | Typ | Max | Unit |
|----------------|--------------------------------------------------|-------------|-------|-----|-----|------|
| $R_{th(j-a)}$  | thermal resistance from junction to ambient      | in free air | [1]   |     |     |      |
|                | PMEG2010AEH                                      |             | [2] - | -   | 330 | K/W  |
|                |                                                  |             | [3] - | -   | 150 | K/W  |
|                | PMEG2010AET                                      |             | [2] - | -   | 440 | K/W  |
|                |                                                  |             | [3] - | -   | 300 | K/W  |
| $R_{th(j-sp)}$ | thermal resistance from junction to solder point |             | [4]   |     |     |      |
|                | PMEG2010AEH                                      |             | -     | -   | 60  | K/W  |
|                | PMEG2010AET                                      |             | -     | -   | 120 | K/W  |

[1] For Schottky barrier diodes thermal runaway has to be considered, as in some applications the reverse power losses  $P_R$  are a significant part of the total power losses.

[2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and standard footprint.

[3] Device mounted on an FR4 PCB, single-sided copper, tin-plated, mounting pad for cathode 1 cm<sup>2</sup>.


[4] Soldering point of cathode tab.

## 7. Characteristics

**Table 8. Characteristics***T<sub>amb</sub> = 25 °C unless otherwise specified.*


| Symbol | Parameter         | Conditions                             | Min | Typ | Max | Unit          |
|--------|-------------------|----------------------------------------|-----|-----|-----|---------------|
| $V_F$  | forward voltage   |                                        | [1] |     |     |               |
|        |                   | $I_F = 10 \text{ mA}$                  | -   | 200 | 220 | mV            |
|        |                   | $I_F = 100 \text{ mA}$                 | -   | 265 | 290 | mV            |
|        |                   | $I_F = 1 \text{ A}$                    | -   | 380 | 430 | mV            |
| $I_R$  | reverse current   | $V_R = 5 \text{ V}$                    | -   | 15  | 50  | $\mu\text{A}$ |
|        |                   | $V_R = 10 \text{ V}$                   | -   | 20  | 80  | $\mu\text{A}$ |
|        |                   | $V_R = 20 \text{ V}$                   | -   | 50  | 200 | $\mu\text{A}$ |
| $C_d$  | diode capacitance | $V_R = 5 \text{ V}; f = 1 \text{ MHz}$ | -   | 55  | 70  | pF            |

[1] Pulse test:  $t_p \leq 300 \mu\text{s}$ ;  $\delta \leq 0.02$ .




- (1)  $T_{amb} = 125\text{ °C}$
- (2)  $T_{amb} = 85\text{ °C}$
- (3)  $T_{amb} = 25\text{ °C}$
- (4)  $T_{amb} = -40\text{ °C}$

Fig 1. Forward current as a function of forward voltage; typical values



- (1)  $T_{amb} = 125\text{ °C}$
- (2)  $T_{amb} = 85\text{ °C}$
- (3)  $T_{amb} = 25\text{ °C}$
- (4)  $T_{amb} = -40\text{ °C}$


Fig 2. Reverse current as a function of reverse voltage; typical values




$f = 1\text{ MHz}$ ;  $T_{amb} = 25\text{ °C}$

Fig 3. Diode capacitance as a function of reverse voltage; typical values

8. Test information



9. Package outline




10. Packing information

**Table 9. Packing methods**  
The indicated -xxx are the last three digits of the 12NC ordering code.[\[1\]](#)

| Type number | Package | Description                    | Packing quantity |       |
|-------------|---------|--------------------------------|------------------|-------|
|             |         |                                | 3000             | 10000 |
| PMEG2010AEH | SOD123F | 4 mm pitch, 8 mm tape and reel | -115             | -135  |
| PMEG2010AET | SOT23   | 4 mm pitch, 8 mm tape and reel | -215             | -235  |

[1] For further information and the availability of packing methods, see [Section 14](#).

## 11. Soldering






Fig 8. Reflow soldering footprint SOT23 (TO-236AB)




Fig 9. Wave soldering footprint SOT23 (TO-236AB)

## 12. Revision history

Table 10. Revision history

| Document ID                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Release date | Data sheet status  | Change notice | Supersedes    |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------------|---------------|---------------|
| PMEG2010AEH_PMEG2010AET_3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 20070328     | Product data sheet | -             | PMEG2010AEH_2 |
| Modifications:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |              |                    |               |               |
| <ul style="list-style-type: none"><li>• The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.</li><li>• Legal texts have been adapted to the new company name where appropriate.</li><li>• Type number PMEG2010AET added</li><li>• <a href="#">Section 1.1 "General description"</a>: amended</li><li>• <a href="#">Table 1 "Product overview"</a>: added</li><li>• <a href="#">Table 7 "Thermal characteristics"</a>: <a href="#">Table note 1</a> amended</li><li>• <a href="#">Table 7 "Thermal characteristics"</a>: <a href="#">Table note 4</a> added</li><li>• <a href="#">Table 8 "Characteristics"</a>: <math>C_d</math> diode capacitance conditions adapted</li><li>• <a href="#">Figure 2</a>: amended</li><li>• <a href="#">Section 8 "Test information"</a>: added</li><li>• <a href="#">Section 13 "Legal information"</a>: updated</li></ul> |              |                    |               |               |
| PMEG2010AEH_2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 20050526     | Product data sheet | -             | PMEG2010AEH_1 |
| PMEG2010AEH_1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 20050406     | Product data sheet | -             | -             |

## 13. Legal information

### 13.1 Data sheet status

| Document status <sup>[1][2]</sup> | Product status <sup>[3]</sup> | Definition                                                                            |
|-----------------------------------|-------------------------------|---------------------------------------------------------------------------------------|
| Objective [short] data sheet      | Development                   | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet    | Qualification                 | This document contains data from the preliminary specification.                       |
| Product [short] data sheet        | Production                    | This document contains the product specification.                                     |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

### 13.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

### 13.3 Disclaimers

**General** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Nexperia products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or

malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by Nexperia. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

### 13.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

## 14. Contact information

For additional information, please visit: <http://www.nexperia.com>

For sales office addresses, send an email to: [salesaddresses@nexperia.com](mailto:salesaddresses@nexperia.com)

## 15. Contents

---

|           |                                          |           |
|-----------|------------------------------------------|-----------|
| <b>1</b>  | <b>Product profile</b> . . . . .         | <b>1</b>  |
| 1.1       | General description. . . . .             | 1         |
| 1.2       | Features . . . . .                       | 1         |
| 1.3       | Applications . . . . .                   | 1         |
| 1.4       | Quick reference data. . . . .            | 1         |
| <b>2</b>  | <b>Pinning information</b> . . . . .     | <b>2</b>  |
| <b>3</b>  | <b>Ordering information</b> . . . . .    | <b>2</b>  |
| <b>4</b>  | <b>Marking</b> . . . . .                 | <b>2</b>  |
| <b>5</b>  | <b>Limiting values</b> . . . . .         | <b>3</b>  |
| <b>6</b>  | <b>Thermal characteristics</b> . . . . . | <b>3</b>  |
| <b>7</b>  | <b>Characteristics</b> . . . . .         | <b>4</b>  |
| <b>8</b>  | <b>Test information</b> . . . . .        | <b>6</b>  |
| <b>9</b>  | <b>Package outline</b> . . . . .         | <b>6</b>  |
| <b>10</b> | <b>Packing information</b> . . . . .     | <b>6</b>  |
| <b>11</b> | <b>Soldering</b> . . . . .               | <b>7</b>  |
| <b>12</b> | <b>Revision history</b> . . . . .        | <b>9</b>  |
| <b>13</b> | <b>Legal information</b> . . . . .       | <b>10</b> |
| 13.1      | Data sheet status . . . . .              | 10        |
| 13.2      | Definitions. . . . .                     | 10        |
| 13.3      | Disclaimers . . . . .                    | 10        |
| 13.4      | Trademarks. . . . .                      | 10        |
| <b>14</b> | <b>Contact information</b> . . . . .     | <b>10</b> |
| <b>15</b> | <b>Contents</b> . . . . .                | <b>11</b> |

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9