


## Wirewound Resistors, Commercial Power, Axial Lead



### FEATURES

- High performance for low cost
- Auto insertable
- CA0001, CA0002 and CA5000 models are supplied with a high temperature silicone coating for additional environmental protection
- Lead forming available



### APPLICATIONS

Kitchen appliances: Percolators, blenders, mixers, ranges, toasters, deep fryers. Automotive devices: Horns, ignitions, windshield wipers, voltage regulators, instrument gauges. Entertainment devices: Radios, televisions, computers and power supplies.

RoHS\*  
COMPLIANT

### STANDARD ELECTRICAL SPECIFICATIONS

| GLOBAL <sup>(1)</sup><br>MODEL | HISTORICAL <sup>(1)</sup><br>MODEL | POWER RATING<br>$P_{25^{\circ}\text{C}}$ W | RESISTANCE RANGE $\Omega$<br>$\pm 10\%$ Standard, $\pm 5\%$ Available | WEIGHT<br>(Typical) g |
|--------------------------------|------------------------------------|--------------------------------------------|-----------------------------------------------------------------------|-----------------------|
| CA0001                         | CA-1                               | 1.0                                        | 0.1 - 1K                                                              | 0.65                  |
| CA0002                         | CA-2                               | 2.0                                        | 0.1 - 2.4K                                                            | 0.80                  |
| CA4050/CA5050                  | CA-4050/CA-5050                    | 2.0/2.5                                    | 0.1 - 170/0.1 - 2.7K                                                  | 0.64/0.78             |
| CA4055/CA5055                  | CA-4055/CA-5055                    | 2.2/2.75                                   | 0.1 - 195/0.1 - 3.1K                                                  | 0.65/0.80             |
| CA4060/CA5060                  | CA-4060/CA-5060                    | 2.4/3.0                                    | 0.1 - 220/0.1 - 3.5K                                                  | 0.66/0.82             |
| CA4070/CA5070                  | CA-4070/CA-5070                    | 2.8/3.5                                    | 0.1 - 270/0.1 - 4.3K                                                  | 0.68/0.86             |
| CA4080/CA5080                  | CA-4080/CA-5080                    | 3.2/4.0                                    | 0.1 - 320/0.1 - 5.1K                                                  | 0.70/0.90             |
| CA4090/CA5090                  | CA-4090/CA-5090                    | 3.6/4.5                                    | 0.1 - 370/0.1 - 5.9K                                                  | 0.72/0.94             |
| CA4100/CA5100                  | CA-4100/CA-5100                    | 4.0/5.0                                    | 0.15 - 420/0.15 - 6.7K                                                | 0.74/0.98             |
| CA4150/CA5150                  | CA-4150/CA-5150                    | 6.0/7.5                                    | 0.2 - 630/0.2 - 7K                                                    | 0.84/1.19             |
| CA4200/CA5200                  | CA-4200/CA-5200                    | 8.0/10.0                                   | 0.2 - 920/0.2 - 7K                                                    | 0.94/1.40             |
| CA4220/CA5220                  | CA-4220/CA-5220                    | 8.8/11.0                                   | 0.2 - 1.02K/0.2 - 7K                                                  | 0.98/1.48             |

#### Note

<sup>(1)</sup> CA4000 and CA5000 model numbers are calculated from the CA4000 power rating of 4 W per inch and CA5000 power rating of 5 W per inch. The last three digits of the model number are the body length of the resistor in inches (decimal is between the first and second digit). Example: CA5150 = 1.50 inches x 5 W per inch = 7.5 W.

### TECHNICAL SPECIFICATIONS

| PARAMETER                       | UNIT                    | CA0001                                                      | CA0002     | CA4000     | CA5000     |
|---------------------------------|-------------------------|-------------------------------------------------------------|------------|------------|------------|
| Temperature Coefficient         | ppm/ $^{\circ}\text{C}$ | $\pm 600$ below 1 $\Omega$ , $\pm 300$ 1 $\Omega$ and above |            |            |            |
| Power Rating                    | W                       | 1                                                           | 2          | 4 per inch | 5 per inch |
| Short Time Overload             | -                       | 5 x rated power for 5 s                                     |            |            |            |
| Maximum Working Voltage         | V                       | $(P \times R)^{1/2}$                                        |            |            |            |
| Dielectric Withstanding Voltage | $V_{AC}$                | 1000                                                        | 1000       | 1000       | 1000       |
| Operating Temperature Range     | $^{\circ}\text{C}$      | - 65/+ 275                                                  | - 65/+ 275 | - 65/+ 275 | - 65/+ 275 |
| Terminal Strength (minimum)     | lb                      | 10                                                          | 10         | 10         | 10         |

#### Note

- Wirewound CA resistors can reliably function as a fuse and as a resistor. Such components involve compromise between fusing and resistive functions; therefore, each design should be tailored to the application to ensure optimum performance. Contact factory by using the e-mail address at the bottom of this page for design assistance.

### GLOBAL PART NUMBER INFORMATION

New Global Part Numbering: CA000150R00JR05 (preferred part number format)

C A 0 0 0 1 5 0 R 0 0 J R 0 5



| GLOBAL MODEL                                                             | VALUE                                                                         | TOLERANCE                                              | PACKAGING                                                                                                                  | SPECIAL                                                      |
|--------------------------------------------------------------------------|-------------------------------------------------------------------------------|--------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| (See Standard Electrical Specifications Global Model column for options) | R = Decimal<br>K = Thousand<br>R1500 = 0.15 $\Omega$<br>1K500 = 1500 $\Omega$ | H = $\pm 3.0\%$<br>J = $\pm 5.0\%$<br>K = $\pm 10.0\%$ | E14 = Lead (Pb)-free bulk<br>E05 = Lead (Pb)-free tape and reel<br><br>B14 = Tin/lead bulk<br>R05 = Tin/lead tape and reel | (Dash Number) (up to 3 digits)<br>From 1 - 999 as applicable |

Historical Part Number example: CA-1 50  $\Omega$  5 % R05 (will continue to be accepted for tin/lead product only)

|                  |                  |                |           |
|------------------|------------------|----------------|-----------|
| CA-1             | 50 $\Omega$      | 5 %            | R05       |
| HISTORICAL MODEL | RESISTANCE VALUE | TOLERANCE CODE | PACKAGING |

\* Pb containing terminations are not RoHS compliant, exemptions may apply

## DIMENSIONS in inches [millimeters]



### Note

(1) On some standard reel pack methods, the leads may be trimmed to a shorter length than shown.

| GLOBAL MODEL | DIMENSIONS in inches [millimeters] |               |                   |                              | FIGURE |
|--------------|------------------------------------|---------------|-------------------|------------------------------|--------|
|              | A ± 0.031 [0.794]                  | A' (Maximum)  | B ± 0.001 [0.025] | C                            |        |
| CA0001       | 0.400 [10.16]                      | 0.460 [11.68] | 0.032 [0.813]     | 0.170 maximum [4.32 maximum] | 2      |
| CA0002       | 0.570 [14.48]                      | 0.630 [16.00] | 0.032 [0.813]     | 0.170 maximum [4.32 maximum] | 2      |
| CA4050       | 0.500 [12.70]                      | 0.594 [15.09] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4055       | 0.550 [13.97]                      | 0.644 [16.36] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4060       | 0.600 [15.24]                      | 0.694 [17.63] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4070       | 0.700 [17.78]                      | 0.794 [20.17] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4080       | 0.800 [20.32]                      | 0.894 [22.71] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4090       | 0.900 [22.86]                      | 0.994 [25.25] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4100       | 1.00 [25.40]                       | 1.094 [27.79] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4150       | 1.50 [38.10]                       | 1.594 [40.49] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4200       | 2.00 [50.80]                       | 2.094 [53.19] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA4220       | 2.20 [55.88]                       | 2.294 [58.27] | 0.032 [0.813]     | 0.140 ± 0.031 [3.56 ± 0.794] | 1      |
| CA5050       | 0.500 [12.70]                      | 0.625 [15.88] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5055       | 0.550 [13.97]                      | 0.675 [17.15] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5060       | 0.600 [15.24]                      | 0.725 [18.42] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5070       | 0.700 [17.78]                      | 0.825 [20.96] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5080       | 0.800 [20.32]                      | 0.925 [23.50] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5090       | 0.900 [22.86]                      | 1.025 [26.04] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5100       | 1.00 [25.40]                       | 1.125 [28.58] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5150       | 1.50 [38.10]                       | 1.625 [41.28] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5200       | 2.00 [50.80]                       | 2.125 [53.98] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |
| CA5220       | 2.20 [55.88]                       | 2.325 [59.06] | 0.036 [0.914]     | 0.170 ± 0.031 [4.32 ± 0.794] | 2      |

## MATERIAL SPECIFICATIONS

**Element:** Copper-nickel alloy or nickel-chrome alloy, depending on resistance value


**Core:** Woven fiberglass

**Coating:** Special high temperature silicone (CA4000 series is not coated)

**Terminals:** Tin/lead electroplated copper (Lead (Pb)-free will be 100 % tin)

**End Caps:** Tin plated steel

**Part Marking:** DALE, model, wattage, value, tolerance, date code



Derating

| PERFORMANCE                     |                                                                     |                          |
|---------------------------------|---------------------------------------------------------------------|--------------------------|
| TEST                            | CONDITIONS OF TEST                                                  | TEST LIMITS (EIA RS-344) |
| Thermal Shock                   | - 55 °C to + 275 °C, 5 cycles, 30 min dwell time                    | ± (5.0 % + 0.05 Ω) ΔR    |
| Short Time Overload             | 5 x rated power for 5 s                                             | ± (4.0 % + 0.05 Ω) ΔR    |
| Dielectric Withstanding Voltage | 600 V <sub>AC</sub> , (CA0001, CA0002) for 1 min                    | ± (2.0 % + 0.05 Ω) ΔR    |
| Low Temperature Storage         | - 65 °C, full rated working voltage for 45 min                      | ± (3.0 % + 0.05 Ω) ΔR    |
| Humidity                        | 75 °C, 90 % - 100 % RH, 240 h                                       | ± (5.0 % + 0.05 Ω) ΔR    |
| Load Life                       | 1000 h at rated power, + 25 °C, 1.5 h "ON", 0.5 h "OFF"             | ± (10.0 % + 0.05 Ω) ΔR   |
| Terminal Strength               | 10 pounds for 30 s; body twisted about axis, 3 360° rotations       | ± (2.0 % + 0.05 Ω) ΔR    |
| Resistance to Solder Heat       | Terminal immersed 3.5 s in molten solder at 1/8" to 3/16" from body | ± (4.0 % + 0.05 Ω) ΔR    |



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

## Данный компонент на территории Российской Федерации

**Вы можете приобрести в компании MosChip.**

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

<http://moschip.ru/get-element>

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

### Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: [info@moschip.ru](mailto:info@moschip.ru)

Skype отдела продаж:

moschip.ru

moschip.ru\_4

moschip.ru\_6

moschip.ru\_9