PowerStor®

Supercapacitors

PM Series

Description


Cooper Bussmann PowerStor supercapacitors are unique, ultra-high capacitance devices utilizing electrochemical double layer capacitor (EDLC) construction combined with new, high performance materials. This combination of advanced technologies allows Cooper Bussmann to offer a wide variety of capacitor solutions tailored to specific applications that range from a few micro-amps for several days to several amps for milliseconds.

Features & Benefits

- Low ESR with high energy density
- 5.0 Volts
- High capacitance
- Long cycle life
- Low leakage currents
- UL Recognized

Applications

- Pulse power
- Bridge or hold-up power



Cylindrical Device

Specifications	
Working Voltage	5.0V
Surge Voltage	5.5V
Nominal Capacitance	0.47F to 3.0F
Capacitance Tolerance	-20% to +80% (20°C)
Operating Temperature Range	-40°C to 60°C
Extended Operating Temperature Range	-40°C to 85°C (Max. working voltage: 3.9V)

Standard Product

Nominal Capacitance (F)	Part Number		Nominal ESR (Ω) (Equivalent Series Resistance) Measured @		Nominal Leakage Current (μA) After 100 Hrs. @ 5V, 20°C	Nominal Dimensions (mm)	Typical Mass (grams/piece)
	Vertical	Horizontal	1kHz	100Hz			
0.47	PM-5R0V474-R	PM-5R0H474-R	0.42	0.50	8	8.5 x 16.8 x 14.0	2.4
1.0	PM-5R0V105-R	PM-5R0H105-R	0.15	0.20	10	8.5 x 16.8 x 21.5	3.5
1.5	PM-5R0V155-R	PM-5R0H155-R	0.07	0.10	15	10.5 x 20.8 x 22.5	5.4
3.0	PM-5R0V305-R	PM-5R0H305-R	0.05	0.07	20	10.5 x 20.8 x 32	7.8


Performance

Parameter	Capacitance Change (% of specified value)	ESR (% of specified value)
Life (1000 hrs @ 60°C @ 5Vdc)	≤ 30 %	≤ 200 %
Storage - Low and High Temperature (1000 hrs @ -40°C and 60°C)	≤ 30 %	≤ 200 %

COOPER Bussmann

Dimensions (mm)											
Vertical Part#	Horizontal Part#	A	B	C	d'	D	D'	E	E'	F	P
PM-5R0V474-R	PM-5R0H474-R	9.0	17.3	14.5	0.5	20	15	25	20	2.0	11.8
PM-5R0V105-R	PM-5R0H105-R	9.0	17.3	22.0	0.5	20	15	25	20	2.0	11.8
PM-5R0V155-R	PM-5R0H155-R	11.0	21.3	23.0	0.6	20	15	25	20	2.0	5.3
PM-5R0V305-R	PM-5R0H305-R	11.0	21.3	32.5	0.6	20	15	25	20	2.0	5.3
Tolerances		Maximum			± 0.02	Minimum				± 0.5	

Note: Longer lead is positive.



Part Numbering System											
P	**M**	**-**	**5**	**R**	**0**	□	□	□	□	**-**	**R**
Series Code	**Version**		**Voltage (V) R = Decimal**			**Configuration**	**Capacitance (μF)**				
							Value	Multiplier			
P = Pack			5R0 = 5.0V			V = Vertical H = Horizontal	Example: 474 = 47 x 10^4μF or 0.47F				RoHS Compliant

Packaging Information

Standard packaging: Bulk, 100 units per package.

Large, bulk packaging available upon request.

Part Marking

Manufacturer
Capacitance (F)
Max. Operating Voltage (V)
Series Code (or part number)
Polarity

North America
Cooper Bussmann
1225 Broken Sound Parkway NW
Suite F
Boca Raton, FL 33487-3533
Tel: 1-561-998-4100
Fax: 1-561-241-6640
Toll Free: 1-888-414-2645

Cooper Bussmann
P.O. Box 14460
St. Louis, MO 63178-4460
Tel: 1-636-394-2877
Fax: 1-636-527-1607

Europe
Cooper Bussmann
Cooper (UK) Limited
Burton-on-the-Wolds
Leicestershire • LE12 5TH UK
Tel: +44 (0) 1509 882 737
Fax: +44 (0) 1509 882 786

Cooper Bussmann
Avda. Santa Eulalia, 290
08223
Terrassa, (Barcelona), Spain
Tel: +34 937 362 812
+34 937 362 813
Fax: +34 937 362 719

Asia Pacific
Cooper Bussmann
1 Jalan Kilang Timor
#06-01 Pacific Tech Centre
Singapore 159303
Tel: +65 278 6151
Fax: +65 270 4160

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Life Support Policy: Cooper Bussmann does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

© 2011 Cooper Bussmann
www.cooperbussmann.com

COILTRONICS® COOPER Bussmann® PowerStor®

Общество с ограниченной ответственностью «МосЧип» ИНН 7719860671 / КПП 771901001
Адрес: 105318, г.Москва, ул.Щербаковская д.3, офис 1107

Данный компонент на территории Российской Федерации

Вы можете приобрести в компании MosChip.

Для оперативного оформления запроса Вам необходимо перейти по данной ссылке:

http://moschip.ru/get-element

Вы можете разместить у нас заказ для любого Вашего проекта, будь то серийное производство или разработка единичного прибора.

В нашем ассортименте представлены ведущие мировые производители активных и пассивных электронных компонентов.

Нашей специализацией является поставка электронной компонентной базы двойного назначения, продукции таких производителей как XILINX, Intel (ex.ALTERA), Vicor, Microchip, Texas Instruments, Analog Devices, Mini-Circuits, Amphenol, Glenair.

Сотрудничество с глобальными дистрибьюторами электронных компонентов, предоставляет возможность заказывать и получать с международных складов практически любой перечень компонентов в оптимальные для Вас сроки.

На всех этапах разработки и производства наши партнеры могут получить квалифицированную поддержку опытных инженеров.

Система менеджмента качества компании отвечает требованиям в соответствии с ГОСТ Р ИСО 9001, ГОСТ РВ 0015-002 и ЭС РД 009

Офис по работе с юридическими лицами:

105318, г.Москва, ул.Щербаковская д.3, офис 1107, 1118, ДЦ «Щербаковский»

Телефон: +7 495 668-12-70 (многоканальный)

Факс: +7 495 668-12-70 (доб.304)

E-mail: info@moschip.ru

Skype отдела продаж:
moschip.ru
moschip.ru_4
moschip.ru_6
moschip.ru_9